



Station Description

16 Jan 2022

www.aj4co.org

Dave Typinski

C O N T E N T S

Observatory Outline	1
TFD Array Schematic	4
TFD Array Feed Losses	5
TFD Array Element S_{11} and Pattern	6
Antenna Test Range Feed Schematic	7
RF Surge Suppressors	8
Antenna Feed Control	9
Receivers	10
Calibration Temperatures	11
Power Distribution	13
Ethernet Diagram	14
TFD Array Beam Steering	15
Terrestrial Beam Heading Map	21
Magnetic Declination	22
Facility Layout	23
Location Within North America	24



26211 W US Hwy 27
PO Box 2423
High Springs, FL 32655

Contact: Dave Typinski
davetyp@typnet.net
(386)344-3166

OBSERVATORY OUTLINE

Location

29° 50' 13" N 29.8369° N EL89qu
82° 37' 17" W 82.6214° W
53 ft (16 m) MSL

Antennas

TFD Array

Two square arrays on a NS line, eight 30-foot TFD elements, beam steering in 5° increments NS and 15° increments EW.

16 MHz HPBW at zenith: 18° NS x 40° EW
20 MHz HPBW at zenith: 15° NS x 35° EW, D ≈ 14 dBic
24 MHz HPBW at zenith: 12° NS x 30° EW
32 MHz HPBW at zenith: 8° NS x 20° EW
For more about the TFD Array, see: [The DPS and TFD Array](#)

Antenna Test Range

Presently conducting galactic background measurement series with $\frac{1}{2}\lambda$ dipoles.

Receivers

Dual Polarization Spectrograph (DPS)

24 x 7 x 365 unattended operation
16–32 MHz, simultaneous (correlated) RCP and LCP
300 channels per polarization (600 total)
Swept frequency, selectable 7.5, 15, 30, 60 kHz pre-detection BW
~ 6.7 sweeps/sec, integration time = 500 μ s per sample
Frequency resolution = 53 kHz, Δt = 150 ms
For more about the DPS, see: [The DPS and TFD Array](#)

Receivers (cont'd)

Radio Jove Receivers

24 x 7 x 365 unattended operation
~ 20.1 MHz, uncorrelated RCP and LCP
7 kHz RF BW folded via direct conversion into a baseband
3.5 kHz pre-detection audio BW
Integration time = 100 ms per sample
For more about the Jove Receivers, See: [Radio Jove Receiver Manual](#)

Icom R8500 + 10.7 MHz Jove Receiver

7 kHz RF BW folded via direct conversion into a baseband
3.5 kHz pre-detection BW
Integration time = 100 ms per sample

Tunable Wideband Receiver (TWB) Mark III

Attended operation only
Tunable from 16 to 32 MHz, RCP or LCP
2 MHz IF BW direct to high speed digitizer
FFT post-processing, RBW = 4.88 kHz, $\Delta t = 205 \mu s$
For more about the TWB, see: [The TWB](#)

Icom R75 Receivers 1 & 2

Used for live audio stream and as required for antenna test range operations.

Sensitivity

Formal sensitivity calculations and measurements have not been made. A rough estimate considering only the number of dipoles is a 20 MHz on-axis and at zenith 3σ sensitivity on the order of 100 kJy. All receivers presently in use have noise figures between 6 and 8 dB, making their internal noise of little concern given the modest losses between the TFD array and the receivers and the fact that in the upper HF band, system noise is dominated by the galactic background emission.

Timing

All radio telescope data collection systems use a PC's internal clock to apply timestamps to the data. Each PC runs a Network Time Protocol (NTP) daemon to keep its system clock within a few milliseconds of UTC. The NTP server is a GPS-ntp-pi stand-alone unit using multiple GNSS signals to provide the correct time on the local network.

For more information, see: [GPS-NTP Pi](#)

For more information, see: [Meinberg NTP Server](#) and [Meinberg NTP Server Monitor](#)

Calibration

All radio telescope systems are calibrated in terms of antenna temperature using a noise source calibrated against a 5722 noise diode. An automatic calibrator runs a step calibration on all receivers, usually twice per day at ± 3 hours from Jupiter transit. The step cal runs 17 steps each separated by 3 dB. Calibration timing, step duration, and noise temperature varies as required by telescope and test range operations. For more information see: [AJ4CO Automatic Calibrator](#)

Computers

Three identical PCs are used to record data from the receivers. Each has a 2.4 GHz AMD Opteron dual-core processor, 4 GB RAM, and a 1 TB hard drive. All run Windows XP SP3. All are connected to the observatory LAN.

Internet

The observatory has internet access via a 6 Mbps DSL connection. This connection allows the Radio Sky Pipe (RSS) and Radio Sky Spectrograph (RSS) software to serve data to interested remote observers.


Power

The receivers, computers, and network hardware are fed by six 1.5 kVA battery backup units providing at least 15 minutes of power if the AC mains fail.

Operations

Several radio telescopes operate all day, every day (see “Receivers” above). Useful Jupiter observations are made any time Jupiter is within 3 hours of transit, but this is extended to around 4.5 hours when Jupiter’s transit elevation is greater than 70° and Jupiter is near opposition.

North



TFD Array - Electrical

TFD Array - Electrical					
SIZE A		DATE 02 FEB 2020	PART NUMBER N/A		REV B
SCALE	None	DRAWN BY DAVE TYPINSKI	SHEET	1 OF 1	
AJ4C0 OBSERVATORY					

30' terminated folded dipoles, top wire 9'2" height,
8" wire spacing, 32' element Spacing,
800 Ω termination resistors, 16:1 baluns.

TFD Array Feed System Losses

Device sweeps performed 11 Aug 2013





Feed line loss sweeps performed 28 Mar 2015

TFE Element Efficiency Measured Jan 2020




C	TRA AN-TFD-30 Element Efficiency	Element Balun to Outer J-box	Mini-Circuits ZSC-2-1W+ Combiners	Outer J-box to center J-box RG-58 (two)	ZSC-2-1W+ Combiners	Center J-box to gray point of entry box	Rack panel to gray point of entry box	Center J-box LMR-240	Rack panel LMR-400	Loss (dB)	Loss (dB)	Loss (dB)	Loss (dB)
C	Freq (MHz)	Loss (dB)	Loss (dB)	Loss (dB)	Loss (dB)	Loss (dB)	Loss (dB)	Loss (dB)	Loss (dB)	Loss (dB)	Loss (dB)	Loss (dB)	Loss (dB)
	16	-6.8	-0.33	-0.20	-0.75	-0.20	-0.94	-0.99	-0.99	-10.2			
	18	-5.2	-0.35	-0.21	-0.79	-0.21	-0.99	-0.99	-0.99	-8.8			
20	-4.8	-0.37	-0.21	-0.84	-0.21	-0.21	-1.03	-1.09	-8.6				
	22	-5.0	-0.39	-0.22	-0.89	-0.22	-1.07	-1.15	-1.15	-8.9			
	24	-5.2	-0.40	-0.22	-0.93	-0.22	-1.11	-1.20	-1.20	-9.3			
	26	-5.1	-0.42	-0.23	-0.97	-0.23	-1.16	-1.24	-1.24	-9.3			
	28	-4.9	-0.45	-0.24	-1.00	-0.24	-1.20	-1.28	-1.28	-9.3			
	30	-4.7	-0.46	-0.24	-1.04	-0.24	-1.23	-1.32	-1.32	-9.2			
	32	-5.2	-0.46	-0.25	-1.09	-0.25	-1.27	-1.36	-1.36	-9.9			

A.J4C OBSERVATORY		TFD Array Feed System Losses		REV B	
SIZE A	DATE 02 FEB 2020	SCALE NONE	DRAWN BY DAVE TYPINSKI	PART NUMBER N/A	SHEET 1 OF 1
4	3	2	1		


30' TFD Element Feed Point (Balun Output) Characteristics Plots
 Measured above natural ground (no ground screen).



30' TFD 20.1 MHz EZNEC predicted element beam pattern
 Modeled above poor ground. Azimuth pattern at 45° elevation.





9.6 MHz Dipole
for HAARP lunar
radar experiment



Antenna Test Range - Electrical



SIZE	DATE	PART NUMBER
A	14 JAN 2022	N/A
SCALE	NONE	DRAWN BY DAVE TYPINSKI
		SHEET 1 OF 1





RF Surge Suppressors



SIZE	DATE	PART NUMBER	REV
A	30 JAN 2020	N/A	A
SCALE	NONE	DRAWN BY DAVE TYPINISKI	SHEET 1 OF 1


A





AJ4C OBSERVATORY		SIZE	DATE	PART NUMBER	REV
A	16 JAN 2022	N/A	J		
SCALE	NONE	DRAWN BY	DAVE TYPINSKI	SHEET	1 OF 1
2	3				1

The AJ4CO automatic calibrator is presently modified by the addition of a HAT-4 and a HAT-3 in series at the internal noise generator's output connector. Plots below show the noise temperature and variation at the automatic calibrator front panel connectors (the calibration plane) during the calibrator's 0 dB attenuation step. The internal noise generator was measured at $430 \text{ MK} \pm 0.1 \text{ dB}$ on 05 Jan 2020.



Automatic Calibrator Calibration Plane Noise Temperatures at 20 MHz
Internal Noise Generator Calibrated Against 5722 on 05 Jan 2020

T_o (K)

290

Noise Source 20 MHz Temperature (MK)

430

Splitter 20 MHz Loss (dB)

13.4 (6.35 splitter + HAT-4 + HAT-3)

Calibration Plane: CAL relays between Antenna Feeds Entrance and Hybrid Ring Inputs.



Nominal Attn. (dB)	Measured Attn. @ 20 MHz (dB)	Cal Plane Tnoise (K)	Cal Plane Step	Auto Cal Step	Nominal Attn. (dB)	Measured Attn. @ 20 MHz (dB)	Cal Plane Tnoise (K)
0	0.56	17.5 MK	1	0	0.56	17.5 MK	C
1	1.52	14.0 MK	2	3	3.43	9.03 MK	
2	2.56	11.0 MK	3	6	6.47	4.48 MK	
4	4.57	6.94 MK	4	9	9.45	2.26 MK	
8	8.55	2.78 MK	5	12	12.58	1.10 MK	
16	16.58	437 KK	6	15	15.48	563 KK	
32	32.50	11.5 KK	7	18	18.55	278 KK	
64	64.65	297 K	8	21	21.50	141 KK	
			9	24	24.55	70.0 KK	
			10	27	27.51	35.6 KK	
			11	30	30.58	17.7 KK	
			12	33	33.49	9.19 KK	
			13	36	36.54	4.70 KK	
			14	39	39.55	2.50 KK	
			15	42	42.55	1.40 KK	
			16	45	45.59	839 K	
			17	48	48.55	568 K	

Calibration Temperatures



SIZE	DATE	PART NUMBER	REV
A	02 FEB 2020	N/A	E
SCALE	NONE	DRAWN BY DAVE TYPLINSKI	SHEET 1 OF 1

SIZE	DATE	PART NUMBER	REV
A	02 FEB 2020	N/A	E
SCALE	NONE	DRAWN BY DAVE TYPLINSKI	SHEET 1 OF 1




Power Distribution

AJ4C
OBSERVATORY

SIZE A	DATE 29 NOV 2019	PART NUMBER N/A	REV D
SCALE NONE	DRAWN BY DAVE TYPINSKI	SHEET 1 OF 1	

Ethernet Diagram



A

AJ4C OBSERVATORY		SIZE A	DATE 20 AUG 2019	PART NUMBER N/A	REV A
SCALE NONE	DRAWN BY DAVE TYPINSKI	SHEET 1 OF 1			

TFD Array Beam Steering

Time Delay Cable VoP: 66%

ray elements N-S baseline spacing (feet): 32
Array elements E-W baseline spacing (feet): 32

		Delay Cable Lengths (feet & inches)						AZ (degrees)		EL (degrees)	
D	N-S Offset (degrees)	E-W Offset (degrees)	A (S) / B (N)	C (S) / D (N)	E	F (W) / G (E)	H				
C	20 N	60 E	7' 2-3/4"	14' 5-1/4"	3' 7-1/4"	18' 3-1/2"	9' 1-3/4"	78	29		
	20 N	45 E	7' 2-3/4"	14' 5-1/4"	3' 7-1/4"	14' 11-1/4"	7' 5-1/2"	70	43		
	20 N	30 E	7' 2-3/4"	14' 5-1/4"	3' 7-1/4"	10' 6-3/4"	5' 3-1/4"	58	56		
	20 N	15 E	7' 2-3/4"	14' 5-1/4"	3' 7-1/4"	5' 5-1/2"	2' 8-3/4"	36	66		
	20 N	0	7' 2-3/4"	14' 5-1/4"	3' 7-1/4"	0"	0"	0	70		
	20 N	15 W	7' 2-3/4"	14' 5-1/4"	3' 7-1/4"	5' 5-1/2"	2' 8-3/4"	324	66		
	20 N	30 W	7' 2-3/4"	14' 5-1/4"	3' 7-1/4"	10' 6-3/4"	5' 3-1/4"	302	56		
	20 N	45 W	7' 2-3/4"	14' 5-1/4"	3' 7-1/4"	14' 11-1/4"	7' 5-1/2"	290	43		
	20 N	60 W	7' 2-3/4"	14' 5-1/4"	3' 7-1/4"	18' 3-1/2"	9' 1-3/4"	282	29		
	15 N	60 E	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	18' 3-1/2"	9' 1-3/4"	81	30		
B	15 N	45 E	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	14' 11-1/4"	7' 5-1/2"	75	44		
	15 N	30 E	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	10' 6-3/4"	5' 3-1/4"	65	58		
	15 N	15 E	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	5' 5-1/2"	2' 8-3/4"	45	69		
	15 N	0	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	0"	0"	360	75		
	15 N	15 W	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	5' 5-1/2"	2' 8-3/4"	315	69		
	15 N	30 W	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	10' 6-3/4"	5' 3-1/4"	295	58		
	15 N	45 W	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	14' 11-1/4"	7' 5-1/2"	285	44		
	15 N	60 W	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	18' 3-1/2"	9' 1-3/4"	279	30		
	10 N	60 E	3' 8"	7' 4"	1' 10"	18' 3-1/2"	9' 1-3/4"	84	30		
	10 N	45 E	3' 8"	7' 4"	1' 10"	14' 11-1/4"	7' 5-1/2"	80	45		
A	10 N	30 E	3' 8"	7' 4"	1' 10"	10' 6-3/4"	5' 3-1/4"	73	59		
	10 N	15 E	3' 8"	7' 4"	1' 10"	5' 5-1/2"	2' 8-3/4"	57	72		
	10 N	0	3' 8"	7' 4"	1' 10"	0"	0"	360	80		
	10 N	15 W	3' 8"	7' 4"	1' 10"	5' 5-1/2"	2' 8-3/4"	303	72		
	10 N	30 W	3' 8"	7' 4"	1' 10"	10' 6-3/4"	5' 3-1/4"	287	59		
	10 N	45 W	3' 8"	7' 4"	1' 10"	14' 11-1/4"	7' 5-1/2"	280	45		
	10 N	60 W	3' 8"	7' 4"	1' 10"	18' 3-1/2"	9' 1-3/4"	276	30		
	4	3	2	1							

TFD Array Beam Steering



TFD
OBSERVATORY

SIZE A DATE 01 OCT 2014 DRAWN BY DAVE TYPINSKI

SCALE NONE

PART NUMBER N/A

REV A

SHEET 1 OF 6

1

TFD Array Beam Steering

Time Delay Cable VoP: **66%**

Array elements N-S baseline spacing (feet): **32**
Array elements E-W baseline spacing (feet): **32**

		Delay Cable Lengths (feet & inches)						AZ (degrees)	EL (degrees)	D
D	N-S Offset (degrees)	E-W Offset (degrees)	A (S) / B (N)	C (S) / D (N)	E	F (W) / G (E)	H			C
5 N	60 E	1' 10"	3' 8-1/4"	11"	18' 3-1/2"	9' 1-3/4"		87	30	B
	45 E	1' 10"	3' 8-1/4"	11"	14' 11-1/4"	7' 5-1/2"		85	45	
	30 E	1' 10"	3' 8-1/4"	11"	10' 6-3/4"	5' 3-1/4"		81	60	
	15 E	1' 10"	3' 8-1/4"	11"	5' 5-1/2"	2' 8-3/4"		72	74	
	0	1' 10"	3' 8-1/4"	11"	0"	0"		360	85	
	15 W	1' 10"	3' 8-1/4"	11"	5' 5-1/2"	2' 8-3/4"		288	74	
	30 W	1' 10"	3' 8-1/4"	11"	10' 6-3/4"	5' 3-1/4"		279	60	
	45 W	1' 10"	3' 8-1/4"	11"	14' 11-1/4"	7' 5-1/2"		275	45	
	60 W	1' 10"	3' 8-1/4"	11"	18' 3-1/2"	9' 1-3/4"		273	30	
C	0	60 E	0"	0"	18' 3-1/2"	9' 1-3/4"		90	30	A
	0	45 E	0"	0"	14' 11-1/4"	7' 5-1/2"		90	45	
	0	30 E	0"	0"	10' 6-3/4"	5' 3-1/4"		90	60	
	0	15 E	0"	0"	5' 5-1/2"	2' 8-3/4"		90	75	
	0	0	0"	0"	0"	0"		180	90	
	0	15 W	0"	0"	5' 5-1/2"	2' 8-3/4"		270	75	
	0	30 W	0"	0"	10' 6-3/4"	5' 3-1/4"		270	60	
	0	45 W	0"	0"	14' 11-1/4"	7' 5-1/2"		270	45	
	0	60 W	0"	0"	18' 3-1/2"	9' 1-3/4"		270	30	

TFD Array Beam Steering



REV A

N/A

PART NUMBER

SHEET 2 OF 6

1

TFD Array Beam Steering

Time Delay Cable VoP: 66%

Array elements N-S baseline spacing (feet): 32
Array elements E-W baseline spacing (feet): 32

		Delay Cable Lengths (feet & inches)						EL	
D	N-S Offset (degrees)	E-W Offset (degrees)	A (S) / B (N)	C (S) / D (N)	E	F (W) / G (E)	H	(degrees)	(degrees)
C	10 S	60 E	3' 8"	7' 4"	1' 10"	18' 3-1/2"	9' 1-3/4"	96	30
	10 S	45 E	3' 8"	7' 4"	1' 10"	14' 11-1/4"	7' 5-1/2"	100	45
	10 S	30 E	3' 8"	7' 4"	1' 10"	10' 6-3/4"	5' 3-1/4"	107	59
	10 S	15 E	3' 8"	7' 4"	1' 10"	5' 5-1/2"	2' 8-3/4"	123	72
	10 S	0	3' 8"	7' 4"	1' 10"	0"	0"	180	80
	10 S	15 W	3' 8"	7' 4"	1' 10"	5' 5-1/2"	2' 8-3/4"	237	72
	10 S	30 W	3' 8"	7' 4"	1' 10"	10' 6-3/4"	5' 3-1/4"	253	59
	10 S	45 W	3' 8"	7' 4"	1' 10"	14' 11-1/4"	7' 5-1/2"	260	45
	10 S	60 W	3' 8"	7' 4"	1' 10"	18' 3-1/2"	9' 1-3/4"	264	30
B	15 S	60 E	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	18' 3-1/2"	9' 1-3/4"	99	30
	15 S	45 E	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	14' 11-1/4"	7' 5-1/2"	105	44
	15 S	30 E	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	10' 6-3/4"	5' 3-1/4"	115	58
	15 S	15 E	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	5' 5-1/2"	2' 8-3/4"	135	69
	15 S	0	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	0"	0"	180	75
	15 S	15 W	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	5' 5-1/2"	2' 8-3/4"	225	69
	15 S	30 W	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	10' 6-3/4"	5' 3-1/4"	245	58
	15 S	45 W	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	14' 11-1/4"	7' 5-1/2"	255	44
	15 S	60 W	5' 5-1/2"	10' 11-1/4"	2' 8-3/4"	18' 3-1/2"	9' 1-3/4"	261	30

TFD Array Beam Steering



OBSERVATORY

SIZE A DATE 01 OCT 2014

SCALE NONE DRAWN BY DAVE TYPINSKI

PART NUMBER N/A

REV A

SHEET 3 OF 6

1

TFD Array Beam Steering

Time Delay Cable VoP: 66%

Array elements N-S baseline spacing (feet): 32
Array elements E-W baseline spacing (feet): 32

		Delay Cable Lengths (feet & inches)						AZ	EL
D	N-S Offset (degrees)	E-W Offset (degrees)	A (S) / B (N)	C (S) / D (N)	E	F (W) / G (E)	H	(degrees)	(degrees)
C	25 S	60 E	8' 11"	17' 10-1/4"	4' 5-1/2"	18' 3-1/2"	9' 1-3/4"	105	29
	25 S	45 E	8' 11"	17' 10-1/4"	4' 5-1/2"	14' 11-1/4"	7' 5-1/2"	115	42
	25 S	30 E	8' 11"	17' 10-1/4"	4' 5-1/2"	10' 6-3/4"	5' 3-1/4"	129	53
	25 S	15 E	8' 11"	17' 10-1/4"	4' 5-1/2"	5' 5-1/2"	2' 8-3/4"	150	62
	25 S	0	8' 11"	17' 10-1/4"	4' 5-1/2"	0"	0"	180	65
	25 S	15 W	8' 11"	17' 10-1/4"	4' 5-1/2"	5' 5-1/2"	2' 8-3/4"	210	62
	25 S	30 W	8' 11"	17' 10-1/4"	4' 5-1/2"	10' 6-3/4"	5' 3-1/4"	231	53
	25 S	45 W	8' 11"	17' 10-1/4"	4' 5-1/2"	14' 11-1/4"	7' 5-1/2"	245	42
	25 S	60 W	8' 11"	17' 10-1/4"	4' 5-1/2"	18' 3-1/2"	9' 1-3/4"	255	29
B	30 S	60 E	10' 6-3/4"	21' 1-1/2"	5' 3-1/4"	18' 3-1/2"	9' 1-3/4"	108	29
	30 S	45 E	10' 6-3/4"	21' 1-1/2"	5' 3-1/4"	14' 11-1/4"	7' 5-1/2"	120	41
	30 S	30 E	10' 6-3/4"	21' 1-1/2"	5' 3-1/4"	10' 6-3/4"	5' 3-1/4"	135	51
	30 S	15 E	10' 6-3/4"	21' 1-1/2"	5' 3-1/4"	5' 5-1/2"	2' 8-3/4"	155	58
	30 S	0	10' 6-3/4"	21' 1-1/2"	5' 3-1/4"	0"	0"	180	60
	30 S	15 W	10' 6-3/4"	21' 1-1/2"	5' 3-1/4"	5' 5-1/2"	2' 8-3/4"	205	58
	30 S	30 W	10' 6-3/4"	21' 1-1/2"	5' 3-1/4"	10' 6-3/4"	5' 3-1/4"	225	51
	30 S	45 W	10' 6-3/4"	21' 1-1/2"	5' 3-1/4"	14' 11-1/4"	7' 5-1/2"	240	41
	30 S	60 W	10' 6-3/4"	21' 1-1/2"	5' 3-1/4"	18' 3-1/2"	9' 1-3/4"	252	29
A	35 S	60 E	12' 1-1/4"	24' 2-3/4"	6' 0-3/4"	18' 3-1/2"	9' 1-3/4"	112	28
	35 S	45 E	12' 1-1/4"	24' 2-3/4"	6' 0-3/4"	14' 11-1/4"	7' 5-1/2"	125	39
	35 S	30 E	12' 1-1/4"	24' 2-3/4"	6' 0-3/4"	10' 6-3/4"	5' 3-1/4"	140	48
	35 S	15 E	12' 1-1/4"	24' 2-3/4"	6' 0-3/4"	5' 5-1/2"	2' 8-3/4"	159	53
	35 S	0	12' 1-1/4"	24' 2-3/4"	6' 0-3/4"	0"	0"	180	55
	35 S	15 W	12' 1-1/4"	24' 2-3/4"	6' 0-3/4"	5' 5-1/2"	2' 8-3/4"	201	53
	35 S	30 W	12' 1-1/4"	24' 2-3/4"	6' 0-3/4"	10' 6-3/4"	5' 3-1/4"	220	48
	35 S	45 W	12' 1-1/4"	24' 2-3/4"	6' 0-3/4"	14' 11-1/4"	7' 5-1/2"	235	39
	35 S	60 W	12' 1-1/4"	24' 2-3/4"	6' 0-3/4"	18' 3-1/2"	9' 1-3/4"	248	28

TFD Array Beam Steering



SIZE	DATE	PART NUMBER	REV
A	01 OCT 2014	N/A	A
SCALE	NONE	DRAWN BY DAVE TYPINSKI	SHEET 4 OF 6

TFD Array Beam Steering

Time Delay Cable VoP: **66%**

Array elements N-S baseline spacing (feet): **32**
 Array elements E-W baseline spacing (feet): **32**

		Delay Cable Lengths (feet & inches)								
D	N-S Offset (degrees)	E-W Offset (degrees)	A (S) / B (N)	C (S) / D (N)	E	F (W) / G (E)	H	AZ (degrees)	EL (degrees)	
D	40 S	60 E	13' 7"	27' 1-3/4"	6' 9-1/2"	18' 3-1/2"	9' 1-3/4"	116	27	
	40 S	45 E	13' 7"	27' 1-3/4"	6' 9-1/2"	14' 11-1/4"	7' 5-1/2"	130	37	
	40 S	30 E	13' 7"	27' 1-3/4"	6' 9-1/2"	10' 6-3/4"	5' 3-1/4"	145	44	
	40 S	15 E	13' 7"	27' 1-3/4"	6' 9-1/2"	5' 5-1/2"	2' 8-3/4"	162	49	
	40 S	0	13' 7"	27' 1-3/4"	6' 9-1/2"	0"	0"	180	50	
	40 S	15 W	13' 7"	27' 1-3/4"	6' 9-1/2"	5' 5-1/2"	2' 8-3/4"	198	49	
	40 S	30 W	13' 7"	27' 1-3/4"	6' 9-1/2"	10' 6-3/4"	5' 3-1/4"	215	44	
	40 S	45 W	13' 7"	27' 1-3/4"	6' 9-1/2"	14' 11-1/4"	7' 5-1/2"	230	37	
	40 S	60 W	13' 7"	27' 1-3/4"	6' 9-1/2"	18' 3-1/2"	9' 1-3/4"	244	27	
	C	45 S	60 E	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	18' 3-1/2"	9' 1-3/4"	120	27
C	45 S	45 E	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	14' 11-1/4"	7' 5-1/2"	135	35	
	45 S	30 E	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	10' 6-3/4"	5' 3-1/4"	150	41	
	45 S	15 E	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	5' 5-1/2"	2' 8-3/4"	165	44	
	45 S	0	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	0"	0"	180	45	
	45 S	15 W	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	5' 5-1/2"	2' 8-3/4"	195	44	
	45 S	30 W	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	10' 6-3/4"	5' 3-1/4"	210	41	
	45 S	45 W	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	14' 11-1/4"	7' 5-1/2"	225	35	
	45 S	60 W	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	18' 3-1/2"	9' 1-3/4"	240	27	
	B	50 S	60 E	16' 2-1/4"	32' 4-1/4"	8' 1"	18' 3-1/2"	9' 1-3/4"	125	25
	50 S	45 E	16' 2-1/4"	32' 4-1/4"	8' 1"	14' 11-1/4"	7' 5-1/2"	140	33	
B	50 S	30 E	16' 2-1/4"	32' 4-1/4"	8' 1"	10' 6-3/4"	5' 3-1/4"	154	37	
	50 S	15 E	16' 2-1/4"	32' 4-1/4"	8' 1"	5' 5-1/2"	2' 8-3/4"	167	39	
	50 S	0	16' 2-1/4"	32' 4-1/4"	8' 1"	0"	0"	180	40	
	50 S	15 W	16' 2-1/4"	32' 4-1/4"	8' 1"	5' 5-1/2"	2' 8-3/4"	193	39	
	50 S	30 W	16' 2-1/4"	32' 4-1/4"	8' 1"	10' 6-3/4"	5' 3-1/4"	206	37	
	50 S	45 W	16' 2-1/4"	32' 4-1/4"	8' 1"	14' 11-1/4"	7' 5-1/2"	220	33	
	50 S	60 W	16' 2-1/4"	32' 4-1/4"	8' 1"	18' 3-1/2"	9' 1-3/4"	235	25	
	C	45 S	60 E	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	18' 3-1/2"	9' 1-3/4"	120	27
	45 S	45 E	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	14' 11-1/4"	7' 5-1/2"	135	35	
	45 S	30 E	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	10' 6-3/4"	5' 3-1/4"	150	41	
	45 S	15 E	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	5' 5-1/2"	2' 8-3/4"	165	44	
	45 S	0	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	0"	0"	180	45	
	45 S	15 W	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	5' 5-1/2"	2' 8-3/4"	195	44	
	45 S	30 W	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	10' 6-3/4"	5' 3-1/4"	210	41	
	45 S	45 W	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	14' 11-1/4"	7' 5-1/2"	225	35	
	45 S	60 W	14' 11-1/4"	29' 10-1/2"	7' 5-1/2"	18' 3-1/2"	9' 1-3/4"	240	27	

AJ4C OBSERVATORY	SIZE A	DATE 01 OCT 2014	PART NUMBER N/A	REV A
	SCALE NONE		DRAWN BY DAVE TYPINSKI	SHEET 5 OF 6
A	2	3	4	1

TFD Array Beam Steering

TFD Array Beam Steering

Time Delay Cable VoP:

66% **Array elements N-S baseline spacing (feet):** **32**
Array elements E-W baseline spacing (feet): **32**

D	N-S Offset (degrees)	E-W Offset (degrees)	A (S) / B (N) C (S) / D (N)	Delay Cable Lengths (feet & inches)			AZ (degrees)	EL (degrees)	
				E	F (W) / G (E)	H			
55 S	60 E	17' 3-1/2"	34' 7-1/4"	8' 7-3/4"	18' 3-1/2"	9' 1-3/4"	130	24	
55 S	45 E	17' 3-1/2"	34' 7-1/4"	8' 7-3/4"	14' 11-1/4"	7' 5-1/2"	145	30	
55 S	30 E	17' 3-1/2"	34' 7-1/4"	8' 7-3/4"	10' 6-3/4"	5' 3-1/4"	158	33	
55 S	15 E	17' 3-1/2"	34' 7-1/4"	8' 7-3/4"	5' 5-1/2"	2' 8-3/4"	169	35	
55 S	0	17' 3-1/2"	34' 7-1/4"	8' 7-3/4"	0"	0"	180	35	
55 S	15 W	17' 3-1/2"	34' 7-1/4"	8' 7-3/4"	5' 5-1/2"	2' 8-3/4"	191	35	
55 S	30 W	17' 3-1/2"	34' 7-1/4"	8' 7-3/4"	10' 6-3/4"	5' 3-1/4"	202	33	
55 S	45 W	17' 3-1/2"	34' 7-1/4"	8' 7-3/4"	14' 11-1/4"	7' 5-1/2"	215	30	
55 S	60 W	17' 3-1/2"	34' 7-1/4"	8' 7-3/4"	18' 3-1/2"	9' 1-3/4"	230	24	
C	60 S	60 E	18' 3-1/2"	36' 7"	9' 1-3/4"	18' 3-1/2"	9' 1-3/4"	135	22
60 S	45 E	18' 3-1/2"	36' 7"	9' 1-3/4"	14' 11-1/4"	7' 5-1/2"	150	27	
60 S	30 E	18' 3-1/2"	36' 7"	9' 1-3/4"	10' 6-3/4"	5' 3-1/4"	162	29	
60 S	15 E	18' 3-1/2"	36' 7"	9' 1-3/4"	5' 5-1/2"	2' 8-3/4"	171	30	
60 S	0	18' 3-1/2"	36' 7"	9' 1-3/4"	0"	0"	180	30	
60 S	15 W	18' 3-1/2"	36' 7"	9' 1-3/4"	5' 5-1/2"	2' 8-3/4"	189	30	
60 S	30 W	18' 3-1/2"	36' 7"	9' 1-3/4"	10' 6-3/4"	5' 3-1/4"	198	29	
60 S	45 W	18' 3-1/2"	36' 7"	9' 1-3/4"	14' 11-1/4"	7' 5-1/2"	210	27	
60 S	60 W	18' 3-1/2"	36' 7"	9' 1-3/4"	18' 3-1/2"	9' 1-3/4"	225	22	

B

B


A

B

TFD Array Beam Steering

SIZE	DATE	PART NUMBER		REV
		SCALE	DRAWN BY	
A	01 OCT 2014	N/A	DAVE TYPINSKI	A
			SHEET	6 OF 6
		2		1





Find your location

City

Enter your city...


Country

USA

State




[Search map](#)[Browse countries](#)

Find the magnetic declination at your location


[Share](#)

Copyright ©2020 Magnetic-Declination.com

Magnetic declination is calculated using the World Magnetic Model WMM2020.

Questions? webmaster@magnetic-declination.com...If the compass at your place is pointing **clockwise** with respect to the True North, declination is **positive** or **EAST**If the compass at your place is pointing **counter-clockwise** with respect to the True North, declination is **negative** or **WEST**


Negative declination (WEST)



Positive declination (EAST)

Sites of Interest

[Cosmos Plus!](#)[Live Meteors](#)[Satellite tracking](#)[Radio Astronomy](#)



DATE: 18 JUN 2017

SCALE: 1" = 20' 2"

AJ4CO
OBSERVATORY

UFRO

AJ4CO
OBSERVATORY

LGM

