

#364

PIONEER 11
ENCOUNTER DATA SUMMARY, BINARY REDUCTION
AND INTERPLANETARY DATA SUMMARY
73-019A-05A, 05B + 05C

PIONEER 11

ENCOUNTER DATA SUMMARY

73-019A-05A

PSFP-00010

This data set has been restored. There were originally 4 Binary 7-Track, 556 BPI tapes. There is one restored tape. The DR tape is a 3480 cartridge and the DS tape is 9-track, 6250 BPI. The tapes were created on a CDC 3600 computer. The DR and DS numbers along with the corresponding D numbers and the time spans are as follows:

DR#	DS#	D#	FILES	TIME SPAN
DR00843	DS00843	D25186	1	11/25/74 - 11/29/74
		D25187	2	11/29/74 - 12/03/74
		D25188	3	12/03/74 - 12/07/74
		D25189	4	12/07/74 - 12/09/74

Refer to 73-019A-05B

PIONEER 11

ENCOUNTER BINARY REDUCTION

73-019A-05B

PSFP-00078

This data set has been restored. There was originally 1 Binary 7-Track, 556 BPI tape. There is one restored tape. The DR tape is a 3480 cartridge and the DS tape is 9-track, 6250 BPI. The tapes were created on a CDC 3600 computer. The DR and DS numbers along with the corresponding D number and the time spans are as follows:

DR#	DS#	D#	FILES	TIME SPAN
DR00844	DS00844	D25185	1	12/02/74 - 12/03/74

PIONEER 11

INTERPLANETARY DATA SUMMARY

73-019A-05C

SPHE-00223

This data set has been restored. There were originally 2 Binary 7-track, 556 BPI tapes. There is one restored tape. The DR tape is a 3480 cartridge and the DS tape is 9-track, 6250 BPI. The tapes were created on a CDC 3600 computer. The DR and DS numbers along with the corresponding D numbers and the time spans are as follows:

DR#	DS#	D#	FILES	TIME SPAN
DR00846	DS00846	D31856	1	04/16/73 - 12/02/74
		D31857	2	12/03/74 - 05/31/77

Refer to 73-019A-05B

REQ. AGENT

CAW
VJP

RAND NO.

RC6736
RD1609

ACQ. AGENT

LRD
RWV

PIONEER 11

ENCOUNTER DATA SUMMARY, BINARY REDUCTION

AND INTERPLANETARY DATA SUMMARY

73-019A-05A, 05B + 05C

This data set consists of 4 Pioneer 11 05A, 1 Pioneer 11 05B and 2 Pioneer 11 05C data tapes. These tapes were created on the CDC 3600 computer. The tapes are 7 track, Binary, 556 BPI and have 1 file of data. The following tapes are listed below with their 'D' and 'C' numbers and time span.

73-019A-05A

<u>D#</u>	<u>C#</u>	<u>TIME SPAN</u>
D-25186	C-18552	11/25/74 - 11/29/74
D-25187	C-18553	11/29/74 - 12/03/74
D-25188	C-18554	12/03/74 - 12/07/74
D-25189	C-18555	12/07/74 - 12/09/74

73-019A-05B

D-25185	C-18556	12/02/74 - 12/03/74
---------	---------	---------------------

73-019A-05C

D-31856	C-20349	4/16/73 - 12/02/74
D-31857	C-20350	12/03/74 - 5/31/77

4.0 UCSD/TRD DATA TAPES

The raw data tapes received at the laboratory are the EDR and EPH tapes, which are processed by our reduction program. The reduction program produces SUMMARY tapes which are described below, and BINARY REDUCTION tapes which contain each reading. The data are also fitted to a function of time and angle and the coefficients of this fit are given in the ANALYSIS tapes.

4.1 SUMMARY TAPES

4.1.1 Pioneer 10 Encounter Tape Contents

1 summary every computation cycle (108 sec.)

TAPE	DATES	NO. of RECORDS
M44900	11-26-73	807
	11-27-73	+ 809 = 1616
	11-28-73	+ 807 = 2423
	11-29-73	+ 825 = 3248
M44901	11-30-73	814
	12-01-73	+ 828 = 1642
	12-02-73	+ 736 = 2378
	12-03-73	+ 806 = 3184
M44902	12-04-73	786
	12-05-73	+ 813 = 1599
	12-06-73	+ 866 = 2465
	12-07-73	+ 839 = 3304
M44903	12-08-73	814
	12-09-73	+ 809 = 1623
	12-10-73	+ 822 = 2445
	12-11-73	+ 815 = 3260
M44904	12-12-73	823
	12-13-73	+ 864 = 1687
	12-14-73	+ 831 = 2518
	12-15-73	+ 886 = 3404
M44905	12-16-73	858
	12-17-73	+ 834 = 1692
	12-18-73	+ 854 = 2546
	12-19-73	+ 813 = 3359

4.1.2 UCSD/TRD Pioneer Summary Tape Format

Pioneer summary tapes are single-file, multi-record tapes, written in odd parity on the CDC 3600. Each 300 word record contains one complete data summary, along with associated information. All numbers are written on the tape as positive binary integers. The tape format is as follows:

(tapes are 7-track, 556 bpi, 48 bit words)

Word Number	Name	Definition	Bias, Value or Units
1	SAT	Satellite Number	10 or 11
2	NFMOD	Mode of reduction: Earth traversal, Cruise or Jupiter Encounter	1-3
3	ISTART	Start time of summary	Cole time (ms) = 43,200,000 for Jan 1, 1972, 1200
4	ISTOP	Stop time of summary	Cole time (ms)
5	IDAY	Day of year	
6	IYR	4 digit year	
7	IDRTAP	5 digit name of EDR tape which produced the summary	
8	BRTAP	5 digit name of binary reduction tape associated with the summary	
9	IFF	1 digit code for data format, 1 = A, 2 = A/D, 3 = B, 4 = B/D	
10	IB	1 digit code for bit rate	1-8 $[2^4, 2^5, \dots, 2^{11}]$ (bits/sec)
11	IBR(IB)	Bit rate as defined by IB	16-2048
12	<u>RFLT</u>	Round trip Light Time (for ISTART)	milliseconds
13	ICOMAL	Number of commutate alarms; currently unused (-2)	
14-16	PMIN(I), I=1,3	Minimum Pulse Temp., High Voltage Regulator current & Detector C Temp., respectively	PMIN(I)*1.E6+1.E8
17-19	PMAx(I), I=1,3	Maximum values of the above parameters	PMAx(I)*1.E6+1.E8
20-22	PAVE(I), I=1,3	Average values of the above I=2 not currently used.	PAVE(I)*1.E6+1.E8

PULSE DATA

Each parameter for pulse data can be sorted into one of 21 bins, depending on detector ID and high voltage status. Bins are labeled as follows:

I	Detector	I	Detector
1	C1	12	E3U
2	C2	13	M1H
3	C3	14	M2H
4	E1H	15	M3H
5	E2H	16	M1L
6	E3H	17	M2L
7	E1L	18	M3L
8	E2L	19	M1U
9	E3L	20	M2U
10	E1U	21	M3U
11	E2U		

Word Number	Name	Definition*	Bias
23-43	AVG(I)	Average number of counts/ reading	AVG(I)*1.E6
44-64	RMS(I)	RMS Deviation	RMS(I)*1.E6
65-85	RESMAX(I)	Maximum Residue	RESMAX(I)*1.E6+1.E8
86-106	RESMIN(I)	Minimum Residue	RESMIN(I)*1.E6+1.E8
107-127	NREAD(I)	Number of readings	None
128-148	NCOUNT(I)	Total counts	None
149-169	TOTIME(I)	Total time, in seconds	TOTIME*1.E6
170-190	AVGCR(I)	Average number of counts/ second	AVGCR(I)*1.E6
191-211	PROBER(I)	Probable Error (Counts/Second)	PROBER(I)*1.E10

* More extensive definitions are given at the end

47

ELECTROMETER DATA

Each parameter for electrometer data can be sorted into one of 6 bins, depending on detector ID. Bins are labeled as follows:

I	Detector
1	CDC
2	SEDC
3	SPDC
4	CAL1
5	CAL2
6	CAL3

Word Number	Name	Definition	Bias
212-217	AVG(I)	Average reading	AVG(I)*1.E6
218-223	RMS(I)	RMS Deviation(current)	RMS(I)*1.E18
224-229	RESMAX(I)	Maximum Residue(current)	RESMAX(I)*1.E6+1.E8
230-235	RESMIN(I)	Minimum Residue(current)	RESMIN(I)*1.E6+1.E8
236-241	AVGA(I)	Average Current	AVGA(I)*1.E18
242-247	EMAX(I)	Maximum Current	EMAX(I)*1.E18
248-253	EMIN(I)	Minimum Current	EMIN(I)*1.E18
254-259	MREAD(I)	Number of readings	None

TRAJECTORY DATA
Earth Traversal (NFMOD = 1)

Definitions are given alphabetically at the end

WORD NUMBER		NAME
ISTART	ISTOP	
260	275	ATQCLT
261	276	ATQLONG
262	277	RADPE
263	278	CLTPEE
264	279	ALGPEE
265	280	TLCPEE
265-270 and 281-300		_____ (SPARE)

49

TRAJECTORY DATA
Cruise (NFMOD - 2)

WORD NUMBER		NAME
ISTART	ISTOP	
260	275	ATCCLT
261	276	ATCLONG
262	277	RADPS
263	278	CLTPSC
264	279	ALGPSC
265	280	RADES
266	281	CLTESC
267	282	ALGESC
268	283	RADJS
269	284	CLTJSC
270	285	ALGJSC
286 - 300		_____ (SPARE)

TRAJECTORY DATA
Jupiter Encounter (NFMOD = 3)

WORD NUMBER		NAME
ISTART	ISTOP	
260	275	ATCCLT
261	276	ATCLONG
262	277	RADPJ
263	278	CLTPJJ
264	279	ALGPJJ1R
265	280	TLCPJJ
266	281	RADPJM
267	282	CLTPJM
268	283	TLC PJM
269	284	B
270	285	EL
286	287	ALGPJJ3L
288-300		(SPARE)

Word 274 is RTLT corresponding to ISTOP

RESTART DATA

This information is written on the summary tape in order to provide the information necessary to restart the Pioneer data reduction program following any summary.

271	IREC	Physical record number in File 4 of EDR tape at ISTOP
272	NREC	Logical record number on binary reduction tape at ISTOP
273	ISREC	Physical record number on summary tape
274-300	---	Spare

OUTPUT FUNCTION DEFINITIONS

FUNCTION NAME	SYMBOL OR EQUATION	PRINTOUT ACCURACY	PRINTOUT RANGE
Average Count	\bar{j}^C	0.1%	10^{-4} to 10^{+9}
RMS Deviation	$j^\sigma = \sqrt{j^C{}^2 - (\bar{j}^C)^2}$	0.1%	10^{-3} to 10^{+5}
Maximum Residue	$\frac{j^C \text{ max} - \bar{j}^C}{j^\sigma}$	1.0%	-99 to +99
Minimum Residue	$\frac{j^C \text{ min} - \bar{j}^C}{j^\sigma}$	1.0%	-99 to +99
Number of Readings	j^N	Exact integer	0 to 99999
Total Counts	$\sum_{i=1}^{j^N} j^C{}_i$	0.1%	0 to 10^9
Total Time, Sec.	$\sum_{i=1}^{j^N} j^t{}_i$	$\frac{1}{2}$ sec.	0 to 99999.9
Average Count Rate, c/s	$\frac{\bar{CR}}{j}$	0.1%	10^{-4} to 10^{+7}
Probable Error, c/s	$\pm .6745 \sqrt{\Sigma j^C} / \Sigma t_i$	0.1%	10^{-4} to 10^{+4}

OTHER DEFINITIONS

PARAMETER NAME	MODE	PARAMETER	BODY	REF.POINT	REF.PLANE	UNITS
ALGESC	Traversal	Longitude	Earth	Sun	Ecliptic	-
ALGJSC	Cruise	"	Jupiter	Sun	"	Micro-radians
ALGPEE	Traversal	"	Pioneer S/C	Earth	Equator	"
ALGPJJ1R	Encounter	"	"	Jupiter	"	"
ALGPJJ3L	"	"	"	"	"	"
ALGPSC	Cruise	"	"	Sun	Ecliptic	"
ATCCLT	"	Colatitude	Spin Axis	Pioneer S/C	"	"
ATCCLT	Encounter	"	"	"	"	"
ATCLONG	Cruise	Longitude	"	"	"	"
ATCLONG	Encounter	"	"	"	"	"
ATQCLT	Traversal	Colatitude	"	"	E.Equator	"
ATQLONG	"	Longitude	"	"	"	"
B	Encounter	Magnetic Field	D2 Model (JGR 79, 3501, 1974)			Micro-gauss
CLTESC	Cruise	Colatitude	Earth	Sun	Ecliptic	Micro-radians
CLTJSC	"	"	Jupiter	Sun	"	"
CLTPEE	Traversal	"	Pioneer S/C	Earth	Equator	"
CLTPJJ	Encounter	"	"	Jupiter	"	"
CLTPJM	"	"	"	"	Mag.Equator	"
CLTPSC	Cruise	"	"	Sun	Ecliptic	"
EL	Encounter	L value -	D2 Model (JGR 79, 3501, 1974)			Micro-radial
RADES	Cruise	Radius	Earth	Sun		Micro-AU
RADJS	"	"	Jupiter	Sun		"
RADPE	Traversal	"	Pioneer S/C	Earth		Micro-RE
RADPJ	Encounter	"	"	Jupiter		Micro-RJ
RADPJM	"	"	"	"	Mag.Equator	"
RADPS	Cruise	"	"	Sun		"
TLCPEE	Traversal	Local Time	"	Earth	Equator	Micro-hour
TLCPJJ	Encounter	"	"	Jupiter	"	"
TLCPJM	"	"	"	"	Mag.Equator	"

4.2 UCSD/TRD PIONEER 10 ANALYSIS TAPES

4.2.1 Analysis Tape Format

7 Tracks-even parity, 556 bpi

120 BCD characters per record (standard output tape)

CHARACTER	CORRESPONDING DATA	FORMAT	INTERPRETATION
1	----	IX	Blank space
2 - 3	IDA	I2	Detector Identification ¹
4 - 13	T(JC)	F10.5	Time in days + fraction 12:00 Jan. 1, 1972 = Day 1.5
14 - 23	CA(1) ²	E10.3	Average counting rate D.C. Term ²
24 - 33	CA(2) ²	E10.3	Coefficient of SIN term of first harmonic ²
34 - 43	CA(3) ²	E10.3	Coefficient of COS term of first harmonic ²
44 - 53	CA(4) ²	E10.3	Coefficient of SIN term of second harmonic ²
54 - 63	CA(5) ²	E10.3	Coefficient of COS term of second harmonic ²
64 - 73	CA(6) ²	E10.3	Coefficient of SIN term of fourth harmonic ²
74 - 83	CA(7) ²	E10.3	Coefficient of COS term of fourth harmonic ²
84 - 92	CA(8) ²	E9.2	Coefficient of TIME term ²
93 - 101	CA(9) ²	E9.2	Coefficient of TIME squared term ²
102 - 107	ERA	2PF6.1	RMS error ³
108 - 110	NDAT	OPF3	Number of data points per fit ⁽⁴⁾
111 - 113	NCOMCY	I3	Number of commutation cycles per fit
114 - 119	TW	5PF6	Full width of triangular weight function in days
120	"3"	1H3	Third generation of program

4.2.2 Analysis Tape Notes

1. The twelve files are in the following order:

FILE NUMBER	TRD CHANNEL	DETECTOR IDENTIFICATION	TIME INTERVAL IN COLE DAYS + FRACTION
1	M1	1	703.716-704.532
2	M2	2	703.810-704.466
3	M3	3	703.856-704.370
4	E1 (5)	4	702.774-705.950
5	E2	5	702.774-704.608
6	E3	6	702.773-704.600
7	C1	7	702.774-704.615
8	C2	8	702.774-704.590
9	C3	9	703.348-704.533
10	E1 - 2.6M1	4	703.716-704.532
11	E2 - 2.12M1	5	703.716-704.532
12	E3 - 1.12M1	6	703.716-704.532

2. The coefficients are connected to the data as follows:

$$\begin{aligned} \text{Dead time corrected counting rate at time (T)} = & CA(1) + CA(2) \sin \theta + CA(3) \cos \theta \\ & + CA(4) \sin 2\theta + CA(5) \cos 2\theta + CA(6) \sin 4\theta + CA(7) \cos 4\theta \\ & + CA(8)(T-CT) + CA(9)(T-CT)^2 + \text{error} \end{aligned}$$

Where θ = azimuthal angle with respect to the closest approach to the direction of B.

And T = time in days + fraction, C T = time at which coefficients were calculated in cole days + fraction.

Day 703 on the Cole Calendar is December 3, 1973.

3. RMS error of square fit function with respect to data points.
4. Where data gaps exist, the number of data points per fit is reduced, resulting in a larger RMS error.
5. 2660 counts subtracted inbound, 3090 outbound, from channel E1 to account for power supply noise.

4.3 UCSD/TRD BINARY REDUCTION TAPES

The Binary Reduction Tapes (BRT's) are written in 7 track tape at 556 bits per inch by a CDC 3600 computer. All data are written as positive binary integers to facilitate decoding by different machines. (Padding and missing data are given negative values). The record length is 342 48-bit words, which is equivalent to 2736 six-bit characters.

4.3.1 BINARY TAPE FORMAT

Earth Traversal (Launch)		Cruise		Encounter	
1	TCOLE	1	TCOLE	1	TCOLE
2	IDV	2	IDV	2	IDV
3	CR	3	CR	3	CR
4	CRANCE	4	CRANCE	4	CRANCE
5	FLACES	5	FLACES	5	FLACES
6	PP123	6	ANGSWP	6	PP123
7	PP456	7	ANGLS	7	PP456
8	ANGSWP	8	ANGLEC	8	ANGSWP
9	ANGLS	9	HCSXEC	9	ANGLS
10	HCSXEQ	10	HCSYEC	10	HCSXEC
11	HCSYEQ	11	HCSZEC	11	HCSYEC
12	HCSZEQ	12	ANGECLE	12	HCSZEC
13	ANGLOOK	.	.	13	BLOODEC (alias ANGLOOK)
14	ATQCLT	.	.	14	A.CCLT
15	ATCLONG	.	.	15	ATCLONG
16	SPAPD	289	TCOLE	16	SPAPD
17	A.FLACS	290	RADPS	17	A.FLACS
18	RADPE	291	CLTPSC	18	RADPJ
19	CLTPEE	292	ALGPSC	19	CLTPJJ
20	ALPEE	293	RADES	20	ALGPJJH (alias ALGPJJ)
21	TLCPEE	294	CLPESC	21	TLCPEJ
22	CLPEE	295	ALPESC	22	CLTPJC
23	ALPEE	296	RADJS	23	ALGPJC
24	ALGSEC	297	CLPESC	24	ALGSJC
25	ANGDISCE	298	ALGJSC	25	ANGDISCJ
26	ANGSJP	299	ANGESP	26	ANGSJP
27	RADOOE	300	R/LI	27	RADPJH
28	CDCOOEE	301	ATCCLT	28	CLTPJH
29	RASOOEE	302	A.CLONG	29	TLCPEH
30	CLTON-EC	303	SPAPD	30	ALGPJJ3L
31	ATBODDEE	304	ATFLACS	31	ALGQGC
32	B	305	-2	32	B
33	L	306	-2	33	EL (alias L)
34	PHINV	.	.	34	PHINV

3/15/76

<u>TRAVERSAL</u>		<u>CRUISE</u>		<u>ENCOUNTER</u>	
35	RTLT			35	RTLT
36	FORM			36	FORM
37	BITR	336	PF123	37	ELR
38	SCNO	337	PF456	38	SCNO
39	SINO	338	FORM	39	SINO
40	ANGECLN	339	BITR	40	ANGECLN
41	-2	340	SCNO	41	-2
42	-2	341	SINO	42	-2
.		342	NFMOD	.	
337	-2			337	-2
338	-2	12 words describe 1 data point.		338	-2
339	-2	24 data points per record.		339	-2
340	-2	Words 1-12 are repeated 24 times.		340	-2
341	-2			341	-2
342	NFMOD	18 words describe spacecraft position. Words 289-306 give the position for first data point in record. Words 307-324 give the position for last data point in record.		342	NFMOD
42 words describe 1 data point 8 data points per record. Words 1-42 are repeated 8 times.		Words 336 and 337 are averages over all data points in record.		42 words describe 1 data point. 8 data points per record. Words 1-42 are repeated 8 times.	

4.3.2 BINARY TAPE PARAMETER LIST

3/15/74

PARAMETER NAME	MODE	BINOUT POSITION	PARAMETER	BODY	REF. POINT	REF. PLANE	BINOUT UNITS	SOURCE	SOURCE UNITS	SOURCE LOCAL. OF
ALCESC	* Traversal	Ref.	Longitude	Earth	Sun	Ecliptic	-	CELLNE or CELLNE + 360	Degrees	INTERP 7)
ALCESC	* Cruise	295	"	Earth	Sun	Ecliptic	Micro-radians	CELLNE	Degrees	INTERP 8)
ALCISC	** Cruise	298	"	Jupiter	Sun	Ecliptic	"	ALCISC + 180°	-	-
ALFOIC	Encounter	31	"	Io	Jupiter	Ecliptic	"	TBS	-	-
ALMOEC	Traversal	31	"	Moon	Earth	Ecliptic	"	① DECOOE, RASOOE	-	-
ALPEC	Traversal	23	"	Pioneer S/C	Earth	Ecliptic	"	② XCIPEC, YCIPEC, ZCIPEC	-	-
ALPEE	Traversal	20	"	Pioneer S/C	Earth	Equator	"	EALONP	Degrees	INTERP 11)
ALPJC	Encounter	23	"	Pioneer S/C	Jupiter	Ecliptic	"	③ XCIJIC, YCIJIC, ZCIJIC	-	-
ALPJJR	Encounter	20	"	Pioneer S/C	Jupiter	Equator	"	BILONP	Degrees	INTERP 3)
ALPJSB	Encounter	30	"	Pioneer S/C	Jupiter	Equator	"			
ALPSC	Cruise	292	"	Pioneer S/C	Sun	Ecliptic	"	CELLNP	Degrees	INTERP 5)
ALSEC	Traversal	24	"	Sun	Earth	Ecliptic	"	ALCESC - 180°	-	-
ALSSC	* Cruise	Ref.	"	Sun	Jupiter	Ecliptic	-	RASI	-	-
ALSSC	* Encounter	24	"	Sun	Jupiter	Ecliptic	Micro-radians	RASI	-	-
ALTEC	Cruise	Ref.	Latitude	Earth	Sun	Ecliptic	-	CELLTE	Degrees	INTERP(5)
ALTEC	Cruise	Ref.	"	Jupiter	Sun	Ecliptic	-	-ALTSJC	-	-
ALFOIC	Encounter	Ref.	"	Io	Jupiter	Ecliptic	-	TBS	-	-
ALTOJ	Encounter	Ref.	"	Io	Jupiter	Equator	-	TBS	-	-
ALPPE	Traversal	Ref.	"	Pioneer S/C	Earth	Equator	-	EALATP	Degrees	INTERP(10)
ALPJJ	Encounter	Ref.	"	Pioneer S/C	Jupiter	Equator	-	BILATP	Degrees	INTERP(4)
ALPSC	Cruise	Ref.	"	Pioneer S/C	Sun	Ecliptic	-	CELLTP	Degrees	INTERP(3)
ALTSJC	Cruise	Ref.	"	Sun	Jupiter	Ecliptic	-	DECS1	-	-
ALCBAOK	* Traversal	13	Angle between look vector and magnetic field				Micro-radians	TBS	-	-
ANGDISCE	Traversal	25	Ang. Semi diameter	Earth	Pioneer S/C		"	EASD	Degrees	INTERP(9)
ANGDISCJ	Encounter	29	Ang. Semi diameter	Jupiter	Pioneer S/C		"	ASASD	Degrees	INTERP(5)
ANGESP	Cruise	259	Earth/Sun/Spacecraft angle				"	ESPA'G	Degrees	INTERP 11)
ANGLEC	Cruise	8	Angle between look vector and ecliptic plane				"	90° - ALEC	Radians	READ 2)

BINARY TAPE PARAMETERS LIST

3/15/74

PARAMETER NAME	MODE	BINOUT POSITION	PARAMETER	BODY	REF.POINT	REF.PLANE	BINOUT UNITS	SOURCE	SOURCE UNITS	SOURCE LOCAL. CN
ANGLS	* Traversal	9	Angle between look vector and sun vector				Micro-radians	ALS	Radians	READING(5)
ANGLS	* Cruise	7	Angle between look vector and sun vector				"	ALS	Radians	READING(5)
ANGLS	* Encounter	9	Angle between look vector and sun vector				"	ALS	Radians	READING(9)
ANGSJP	* Traversal	26	Sun/Jupiter/Spacecraft angle				"	SSP	Degrees	INTERP(17)
ANGSJP	* Encounter	26	Sun/Jupiter/Spacecraft angle				"	SSP	Degrees	INTERP(17)
AXECLN	* Trav/Enc	40	Angle between look vector and ecliptic nadir of look vector (e.g: at asc node, = 90°)				"	SWPA	Radians	/SWPA/
AXECLN	* Cruise	12	Angle between look vector and ecliptic nadir of look vector				"	SWPA	Radians	/SWPA/
ANGSWP	* Trav/Enc	8	Angular scan of look vector during data sample				"	ASW	Radians	READING(8)
ANGSWP	* Cruise	6	Angular scan of look vector during data sample				"	ASW	Radians	READING(6)
ATCLAT	* Cruise	301	Colatitude	Spin Axis	Pioneer S/C	Ecliptic	"	90° - ATCLAT	-	-
ATCLAT	* Encounter	14	Colatitude	Spin Axis	Pioneer S/C	Ecliptic	"	90° - ATCLAT	-	-
ATCLAT	* Cruise	Ref.	Latitude	Spin Axis	Pioneer S/C	Ecliptic	"	ATCLAT	Radians	/BROOM/
ATCLAT	* Encounter	Ref.	Latitude	Spin Axis	Pioneer S/C	Ecliptic	"	ATCLAT	Radians	/BROOM/
ATCLONG	* Cruise	302	Longitude	Spin Axis	Pioneer S/C	Ecliptic	"	ATCLNG	Radians	/BROOM/
ATCLONG	* Encounter	15	Longitude	Spin Axis	Pioneer S/C	Ecliptic	"	ATCLNG	Radians	/BROOM/
ATFLACS	* Traversal	17	Attitude flags				Ⓐ	④ ISEC(1),AREF(KPOINT)	-	/EDR/,/ANGEL/
ATFLACS	* Cruise	304	Attitude flags				Ⓐ	④ ISEC(1),AREF(KPOINT)	-	/EDR/,/ANGEL/
ATFLACS	* Encounter	17	Attitude flags				Ⓐ	④ ISEC(1),AREF(KPOINT)	-	/EDR/,/ANGEL/
ATQCLT	Traversal	16	Colatitude	Spin Axis	Pioneer S/C	E,Equator	Micro-radians	90° - ATQCLT	-	-
ATQCLT	Traversal	Ref.	Latitude	Spin Axis	Pioneer S/C	E,Equator	"	ATQDEC	Radians	/BROOM/
ATQLONG	Traversal	15	Longitude	Spin Axis	Pioneer S/C	E,Equator	"	ATQRASC	Radians	/BROOM/
B	* Traversal	32	Magnetic field				Micro-gauss	TBS	-	-
B	* Encounter	32	Magnetic field				Micro-gauss	TBS	-	-
BITR	* Traversal	37	Bit Rate				①	BR	Seconds ⁻¹	IFIRST(7)
BITR	* Cruise	339	Bit Rate				①	BR	Seconds ⁻¹	IFIRST(7)
BITR	* Encounter	37	Bit Rate				①	BR	Seconds ⁻¹	IFIRST(7)
BLOVDEC	* Encounter	13	Angle between look vector and magnetic field				Micro-radians	TBS	-	-

BINARY TAPE PARAMETERS LIST

3/15/74

PARAMETER NAME	MODE	BINOUT POSITION	PARAMETER	BODY	REF.POINT	REF.PLANE	BINOUT UNITS	SOURCE	SOURCE UNITS	SOURCE LOCATION
DCOOEE	Traversal	28	Codeclination	Moon	Earth	Equator	Micro-Radians	90° - DECOEE	-	-
CLIESC	Cruise	294	Colatitude	Earth	Sun	Ecliptic	"	90° - ALIESC	-	-
CLIJSC	** Cruise	297	Colatitude	Jupiter	Sun	Ecliptic	"	90° - ALIJSC	-	-
CLMOEC	Traversal	30	Colatitude	Moon	Earth	Ecliptic	"	⊙ DECOEE, RASOOE	-	-
CLTPEC	Traversal	22	Colatitude	Pioneer S/C	Earth	Ecliptic	"	⊙ XCTPEC, YCTPEC, ZCTPEC	-	-
CLPEE	Traversal	19	Colatitude	Pioneer S/C	Earth	Equator	"	90° - ALPEE	-	-
CLTPJC	Encounter	22	Colatitude	Pioneer S/C	Jupiter	Ecliptic	"	⊙ XCTPJC, YCTPJC, ZCTPJC	-	-
CLTPJJ	Encounter	19	Colatitude	Pioneer S/C	Jupiter	Equator	"	90° - ALTPJJ	-	-
CLTPJH	Encounter	28	Colatitude	Pioneer S/C	Jupiter	Mag. Equator	"			
CLPSC	Cruise	291	Colatitude	Pioneer S/C	Sun	Ecliptic	"	90° - ALPSC	-	-
CSXEC	* Cruise	Ref.	X-direction cos.	Look Vector	Pioneer S/C	Ecliptic	±1	CSXEC	+1	/EROOM/
CSXEC	* Encounter	Ref.	X-direction cos.	Look Vector	Pioneer S/C	Ecliptic	"	CSXEC	"	/EROOM/
CSXEQ	Traversal	Ref.	X-direction cos.	Look Vector	Pioneer S/C	E. Equator	"	CSXEC	"	/EROOM/
COS1EC	* Cruise	Ref.	Y-direction cos.	Look Vector	Pioneer S/C	Ecliptic	"	CS1EC	"	/EROOM/
COS1EC	* Encounter	Ref.	Y-direction cos.	Look Vector	Pioneer S/C	Ecliptic	"	CS1EC	"	/EROOM/
COS1EQ	Traversal	Ref.	Y-direction cos.	Look Vector	Pioneer S/C	E. Equator	"	CS1EQ	"	/EROOM/
COS2EC	* Cruise	Ref.	Z-direction cos.	Look Vector	Pioneer S/C	Ecliptic	"	CS2EC	"	/EROOM/
COS2EC	* Encounter	Ref.	Z-direction cos.	Look Vector	Pioneer S/C	Ecliptic	"	CS2EC	"	/EROOM/
COS2EQ	Traversal	Ref.	Z-direction cos.	Look Vector	Pioneer S/C	E. Equator	-	CS2EQ	±	/EROOM/
CR	* Traversal	3	Count rate/Electrometer count				ⓐ	COUNTS	Seconds ⁻¹	READ(3)
CR	* Cruise	3	Count rate/Electrometer count				ⓑ	COUNTS	Seconds ⁻¹	READ(3)
CR	* Encounter	3	Count rate/Electrometer count				ⓒ	COUNTS	Seconds ⁻¹	READ(3)
CRANGE	* Traversal	4	Encoder overflow/Electrometer range				ⓓ	RANG	0-1	IREAD(3)
CRANGE	* Cruise	4	Encoder overflow/Electrometer range				ⓔ	RANG	0-1	IREAD(4)
CRANGE	* Encounter	4	Encoder overflow/Electrometer range				ⓕ	RANG	0-1	IREAD(4)
DECOEE	Traversal	Ref.	Declination	Moon	Earth	Equator	-	DECHOO	Degrees	TORP(S)
DECS1	Cruise	Ref.	Latitude	Sun	Jupiter	Ecliptic	-	-DECS	-	-

BINARY TAPE PARAMETERS LIST

3/15/74

PARAMETER NAME	MODE	BINOUT POSITION	PARAMETER	BODY	REF. POINT	REF. PLANE	BINOUT UNITS	SOURCE	SOURCE UNITS	SOURCE LOCATION
EL	* Traversal	33	L value				Micro-radii	TBS	-	-
EL	* Encounter	33	L value				Micro-radii	TBS	-	-
FLACS	* Traversal	5	Data flags				Ⓒ	FLAG	0-7777 ₈	I(READ 1)
FLACS	* Cruise	5	Data flags				Ⓒ	FLAG	0-7777 ₈	I(READ 1)
FLACS	* Encounter	5	Data flags				Ⓒ	FLAG	0-7777 ₈	I(READ 1)
FORM	* Traversal	36	Telemetry format				Ⓓ	FMT	A,A/D,B,B/D	IFIRST(9)
FORM	* Cruise	338	Telemetry format				Ⓓ	FMT	A,A/D,B,B/D	IFIRST(9)
FORM	* Encounter	36	Telemetry format				Ⓓ	FMT	A,A/D,B,B/D	IFIRST(9)
HDECS	Cruise	Ref.	Latitude	Jupiter	Sun	Ecliptic	-	HDECS	Degrees	I(ERP 7)
HRS	Cruise	Ref.	Radius	Jupiter	Sun	Ecliptic	-	HRS	Kilometers	I(ERP 7)
HRA5	* Cruise	Ref.	Longitude	Jupiter	Sun	Ecliptic	-	HRA5	Degrees	I(ERP 9)
HRA5	* Encounter	Ref.	Longitude	Jupiter	Sun	Ecliptic	-	HRA5	Degrees	I(ERP 9)
HCSXEC	* Cruise	9	X-direction h.cos.	Look vector	Pioneer S/C	Ecliptic	(0-2)·10 ⁶	1.-COSXEC	-	-
HCSXEC	* Encounter	10	X-direction h.cos.	Look vector	Pioneer S/C	Ecliptic	(0-2)·10 ⁶	1.-COSXEC	-	-
HCSXEQ	Traversal	10	X-direction h.cos.	Look vector	Pioneer S/C	E.Equator	(0-2)·10 ⁶	1.-COSXEQ	-	-
HCSYEC	* Cruise	10	Y-direction h.cos.	Look vector	Pioneer S/C	Ecliptic	(0-2)·10 ⁶	1.-COSYEC	-	-
HCSYEC	* Encounter	11	Y-direction h.cos.	Look vector	Pioneer S/C	Ecliptic	(0-2)·10 ⁶	1.-COSYEC	-	-
HCSYEQ	Traversal	11	Y-direction h.cos.	Look vector	Pioneer S/C	E.Equator	(0-2)·10 ⁶	1.-COSYEQ	-	-
HCSZEC	* Cruise	11	Z-direction h.cos.	Look vector	Pioneer S/C	Ecliptic	(0-2)·10 ⁶	1.-COSZEC	-	-
HCSZEC	* Encounter	12	Z-direction h.cos.	Look vector	Pioneer S/C	Ecliptic	(0-2)·10 ⁶	1.-COSZEC	-	-
HCSZEQ	Traversal	12	Z-direction h.cos.	Look vector	Pioneer S/C	E. Equator	(0-2)·10 ⁶	1.-COSZEQ	-	-
IDV	* Traversal	2	Detector ID/IV status				Ⓔ	Ⓔ IPP(13), IREAD(2)	0-1,1-16	/PP/,/READING/
IDV	* Cruise	2	Detector ID/IV status				Ⓔ	Ⓔ IPP(13), IREAD(2)	0-1,1-16	/PP/,/READING/
IDV	* Encounter	2	Detector ID/IV status				Ⓔ	Ⓔ IPP(13), IREAD(2)	0-1,1-16	/PP/,/READING/
IFMOD	* Traversal	342	Binary reduction tape format				Ⓕ	IFMOD	1-3	/CTRL/
IFMOD	* Cruise	342	Binary reduction tape format				Ⓕ	IFMOD	1-3	/CTRL/
IFMOD	* Encounter	342	Binary reduction tape format				Ⓕ	IFMOD	1-3	/CTRL/

BINARY TAPE PARAMETERS LIST

3/15/74

PARAMETER NAME	MODE	BINOLT POSITION	PARAMETER	BODY	REF. POINT	REF. POINT	BINOLT UNITS	SOURCE	SOURCE UNITS	SOURCE LOCATION
RAS1	* Cruise	Ref.	Longitude	Sun	Jupiter	Ecliptic	-	HRA5-180°	-	-
RAS1	* Encounter	Ref.	Longitude	Sun	Jupiter	Ecliptic	-	HRA5-180°	-	-
RASGOE2	Traversal	29	Right Asc.	Moon	Earth	Equator	Micro-radians	RTASCH	Degrees	IN.ERP (5)
RASPEE	Traversal	Ref.	Right Asc.	Pioneer S/C	Earth	Equator	-	RTASCP	Degrees	IN.ERP (5)
RASSEE	Traversal	Ref.	Right Asc.	Sun	Earth	Equator	-	RTASCS	Degrees	IN.ERP (5)
RS1	Cruise	Ref.	Distance to the Sun				-	HRS	-	-
RTLT	* Traversal	35	Round trip light time				Milli-seconds	RTLT	Milli-seconds	IFIRST (10)
RILT	* Cruise	300	Round trip light time				"	RILT	Milli-seconds	IFIRST (10)
R. LT	* Encounter	35	Round trip light time				"	RILT	Milli-seconds	IFIRST (10)
SC:O	* Traversal	38	Spacecraft number				(G)	SAT	F or G	EDR File 1
SC:O	* Cruise	340	Spacecraft number				(G)	SAT	F or G	EDR File 1
SC:O	* Encounter	39	Spacecraft number				(G)	SAT	F or G	EDR File 1
SP:PD	* Traversal	16	Spin period				Micro-seconds	ASP	Seconds	Second (3)
SP:PD	* Cruise	303	Spin Period				"	ASP	Seconds	Second (3)
SP:PD	* Encounter	16	Spin Period				"	ASP	Seconds	Second (3)
ST:O	* Traversal	39	Receiving station number				(H)	DSS	XXX ₃	IFIRST (6)
ST:O	* Cruise	341	Receiving station number				(H)	DSS	"	IFIRST (6)
ST:O	* Encounter	39	Receiving station number				(H)	DSS	"	IFIRST (6)
TCOL	* Traversal	1	Cole Time				Milli-seconds	MSDATA	Milli-seconds	/C/TIME/
TCOL	* Cruise	1	Cole Time				"	MSDATA	Milli-seconds	/C/TIME/
TCOL	* Encounter	1	Cole Time				"	MSDATA	Milli-seconds	/C/TIME/
TLCPEE	Traversal	21	Local Time	Pioneer S/C	Earth	Equator	Micro-hour	(13) RASPEE, RASSEE	-	-
TLCPIJ	Encounter	21	Local Time	Pioneer S/C	Jupiter	Equator	"	TES	-	-
TLCPIJ	Encounter	29	Local Time	Pioneer S/C	Jupiter	Mag. Equator	"		-	-
XCTPEC	Traversal	Ref.	Cartesian X	Pioneer S/C	Earth	Ecliptic	-	XPGSFF	Km.	INTERP (13)
XCPIC	Encounter	Ref.	Cartesian X	Pioneer S/C	Jupiter	Ecliptic	-	XPISFF	Km.	IN.ERP (5)
YC.PEC	Traversal	Ref.	Cartesian Y	Pioneer S/C	Earth	Ecliptic	-	YPSFF	Km.	IN.ERP (13)

BINARY TAP PARAMETERS LIST

3/15/74

PARAMETER NAME	MODE	BINOUT POSITION	PARAMETER	BODY	REF. POINT	REF. PLANE	BINOUT UNITS	SOURCE	SOURCE UNITS	SOURCE LOCATION
PHINV	* Traversal	34	Adiabatic invariant for azimuth				TBS	TBS	-	-
PHINV	* Encounter	34	Adiabatic invariant for azimuth				TBS	TBS	-	-
PP123	* Traversal	6	Performance Parameters: DC Bus voltage				Milli-volts	(9) PP(1)	Volts	/PP/
			DC Bus current				Milli-amps	(9) PP(3)	Amps	/PP/
			Platform Temperature				Deci-degrees	(9) PP(5)	Degrees C	/PP/
PP123	* Cruise	336	Performance Parameters: DC Bus voltage				Milli-volts	(10) PP(1)	Volts	/PP/
			DC Bus current				Milli-amps	(10) PP(3)	Amps	/PP/
			Platform temperature				Deci-degrees	(10) PP(5)	Degrees C	/PP/
PP123	* Encounter	6	Performance Parameters: DC Bus voltage				Milli-volts	(9) PP(1)	Volts	/PP/
			DC Bus current				Milli-amps	(9) PP(3)	Amps	/PP/
			Platform Temperature				Deci-degrees	(9) PP(5)	Degrees C	/PP/
PP456	* Traversal	7	Performance Parameters: Pulse Temperature				Deci-degrees	(11) PP(7)	Degrees C	/PP/
			H.V.R.C.				10 ⁻⁸ amps	(11) PP(9)	10 ⁻⁶ amps	/PP/
			Det. C Temperature				Deci-degrees	(11) PP(11)	Degrees C	/PP/
PP456	* Cruise	337	Performance Parameters: Pulse Temperature				Deci-degrees	(12) PP(7)	Degrees C	/PP/
			H.V.R.C.				10 ⁻⁸ amps	(12) PP(9)	10 ⁻⁶ amps	/PP/
			Det. C Temperature				Deci-degrees	(12) PP(11)	Degrees C	/PP/
PP456	* Encounter	7	Performance Parameters: Pulse Temperature				Deci-degrees	(11) PP(7)	Degrees C	/PP/
			H.V.R.C.				10 ⁻⁸ amps	(11) PP(9)	10 ⁻⁶ amps	/PP/
			Det. C Temperature				Deci-degrees	(11) PP(11)	Degrees C	/PP/
RAD:ES	+ Cruise	293	Radius	Earth	Sun		Micro-AU	BEARSU	Km.	INTERP 10)
RAD:J	+ Cruise	296	Radius	Jupiter	Sun		Micro-AU	BASI	-	-
RAD:ME	+ Traversal	27	Radius	Moon	Earth		Micro-RE	BEARMO	Km.	INTERP 3)
RAD:PE	+ Traversal	18	Radius	Pioneer S/C	Earth		Micro-RE	BEARPR	Km.	INTERP 3)
RAD:PJ	+ Encounter	18	Radius	Pioneer S/C	Jupiter		Micro-RJ	BIMACR	Km.	INTERP 3)
RAD:PM	Encounter	27	Radius	Pioneer S/C	Jupiter	Mag. Equator	Micro-RJ			
RAD:PS	+ Cruise	290	Radius	Pioneer S/C	Sun		Micro-AU	BEARSP	Km.	INTERP 3)

3/15/74

BINARY TAPE PARAMETERS LIST

PARAMETER NAME	MODE	BINOUT POSITION	PARAMETER	BODY	REF. POINT	REF. PLANE	BINOUT UNITS	SOURCE	SOURCE UNITS	SOURCE LOCATION
YCIPJC	Encounter	Ref.	Cartesian Y	Pioneer S/C	Jupiter	Ecliptic	-	YPLSFF	Km.	INTERP(9)
ZCIPEC	Traversal	Ref.	Cartesian Z	Pioneer S/C	Earth	Ecliptic	-	ZPLSFF	Km.	INTERP(15)
ZCIPJC	Encounter	Ref.	Cartesian Z	Pioneer S/C	Jupiter	Ecliptic	-	ZPLSFF	Km.	INTERP(10)

\leftrightarrow $ALGJSC = ALGSJC + 180^\circ - RAS1 + 180^\circ - (HRAS - 180^\circ) + 180^\circ - HRAS - INTERP(9)$
 $CLTJSC = 90^\circ - ALTJSC - 90^\circ - (-ALTSJC) - 90^\circ - (-DECS1) - 90^\circ - HDECS - 90^\circ - INTERP(8)$

\rightarrow AU = 1.495985×10^{13} cm : Allen, Astrophysical Quantities, 1963.

RE = 6378.166 km. : ATS-E Orbit Tape Listing

RJ = 71372.0 km. :

\star Caution: More than one entry exists under this name. Be sure you have selected the correct mode.

3/15/74

10

PP123

P1 .OR. P2 .OR. P3
P1 = LSHIFT [(PP1/CNT1) + 1000. , 32]
P2 = LSHIFT [(PP2/CNT2) + 1000. , 16]
P3 = (PP3/CNT3) + 10. + 1000.
PP1 = Running sum of good values of PP(1)
PP2 = Running sum of good values of PP(3)
PP3 = Running sum of good values of PP(5)
CNT1 = Counter for good values of PP(1)
CNT2 = Counter for good values of PP(3)
CNT3 = Counter for good values of PP(5)
PP(1) = DC Bus Voltage
PP(3) = DC Bus Current
PP(5) = Platform Temperature

11

PP456

P4 .OR. P5 .OR. P6
P4 = LSHIFT [PP(7) + 10. , 32] and PP(7) = Pulse Temp.
P5 = LSHIFT [PP(9) + 100. , 16] and PP(9) = H.V.R.C.
P6 = PP(11) + 10. and PP(11) = Det. C Temp.

12

PP456

P4 .OR. P5 .OR. P6
P4 = LSHIFT [(PP4/CNT4) + 10. + 1000. , 32]
P5 = LSHIFT [(PP5/CNT5) + 100. , 16]
P6 = (PP6/CNT6) + 10. + 1000.
PP4 = Running sum of good values of PP(7)
PP5 = Running sum of good values of PP(9)
PP6 = Running sum of good values of PP(11)
CNT4 = Counter for good values of PP(7)
CNT5 = Counter for good values of PP(9)
CNT6 = Counter for good values of PP(11)
PP(7) = Pulse Temp.
PP(9) = H.V.R.C.
PP(11) = Det. C Temp.

13

TLCPEE

AMOD [(RASPEE - RASSEE + 540.) , 360.] / 15

3/15/74

- ① ALCOOEC - ATAN2 [CDSR * CW + SD * SW, CD * COS(RAS)] + PI
CDSR = CD + SR
CD = COS (DEC)
SD = SIN (DEC)
SR = SIN (RAS)
DEC = DECOOEE + FACTOR
RAS = RASOOEE + FACTOR
FACTOR = radians/degree = $\pi/180 = 0.1745329$
CW = COS (23°) = 0.917060093
SW = SIN (23°) = 0.398749015
- ② ALGPEC - ACOS [XCTPEC/SQRT [XCTPEC² + YCTPEC²]] + FAC
FAC = 0. or π
- ③ ALGPJC - ACOS [XCTPJC/SQRT [XCTPJC² + YCTPJC²]] + FAC
FAC = 0. or π
- ④ ATFLGS - RSHIFT [ATIFLGS, 18] .OR. LSHIFT [AREF + 2, 6]
ATIFLGS = ISEC(1)
AREF = AREF (KPOINT)
- ⑤ CLTOOEC - $\pi/2 - \text{ASIN} (SD * CW - CDSR * SW)$
See ALCOOEC above
- ⑥ CLTPEC - ACOS [ZCTPEC/SQRT [XCTPEC² + YCTPEC² + ZCTPEC²]]
- ⑦ CLTPJC - ACOS [ZCTPJC/SQRT [XCTPJC² + YCTPJC² + ZCTPJC²]]
- ⑧ IDV - HVSTAT .OR. ID
HVSTAT = LSHIFT [IPP(13), 3]
ID = IREAD(2) + 1
- ⑨ FP123 - F1 .OR. F2 .OR. F3
F1 = LSHIFT [FP(1) * 1000., 32] and FP(1) = DC Bus Voltage
F2 = LSHIFT [FP(3) * 1000., 16] and FP(3) = DC Bus Current
F3 = FP(5) * 10. and FP(5) = Platform Temperature

3/15/74

Ⓐ

ISEC(1) = ATFLGS = ARIFPEC, ASPNDC, RAT, SPF = FLAG4, FLAG3, FLAG2, FLAG1

AREF (KPOINT) = AREF = AREFSELS

ATFLGS = ATFLGS, AREFSELS

ATFLGS:	00 = ok	AREFSELS:	00 = Error
	01 = old value		01 = Star
	10 = value missing		10 = Sun B
	11 = corrected value		11 = Sun A

FLAG4	FLAG3	FLAG2	FLAG1	AREF	Binary ATFLGS	Octal ATFLGS	Decimal ATFLGS
00	00	00	00	00	Any combination of any five binary numbers across the table	0	0
01	01	01	01	01		↓	↓
10	10	10	10	10		03 03 03 03 03	51130563
11	11	11	11	11			

ATFLGS will range thus, without biasing :

0_2 - 000011000011000011000011000011₂

0_8 - 0303030303₈

0_{10} - 51130563₁₀

Ⓑ

CRANCE = 0 : No overflow/low range

= 1 : Overflow/high range

Overflow refers to pulse data

Range refers to electrometer data

3/15/76

Ⓒ

FLAGES :

<u>BITS</u>	<u>ID</u>	<u>MEANING</u>
1 - 2	DQ	Data quality as given on EDR tape. See DQ below.
3	F	Data or padded as given on EDR tape: 0 = data, 1 = fill
4	SCID	Discontinuity in SCID: 1 = yes, 0 = no
5	GNT	Discontinuity in Time: 1 = yes, 0 = no
6	TCF	Time correction flag as given on EDR tape. 1 = suspect, 0 = no correction
7		
8		
9		
10		Average value used
11		Reconstructed by average method
12		Word reconstructed by bit rate

- DQ : 00 = Data is bad, no sync
 01 = At least 2 indicators bad, data is suspect
 10 = At least 1 indicator bad, data is suspect
 11 = Data is good, all indicators good

<u>BITS:</u>	12	11	10	9	8	7	6	5	4	3	2	1
Value	0	0	0	0	0	0	0	0	0	0	0	0
Value	1	1	1	1	1	1	1	1	1	1	1	1

FLAGES will range thus:

$O_2 = 111111111111_2$

$O_8 = 7777_8$

$O_{10} = 4095_{10}$

3/15/74

(D)

FORM:

<u>Format</u>	<u>Value</u>	<u>FORM will thus range:</u>
A	1	$1_{10} - 5_{10}$
A/D	2	
B	3	
B/D	4	
Illegal	5	

(E)

IDV:

<u>Type Data:</u>	<u>Unbiased Value</u>	<u>Biased Value</u>	<u>Type Data:</u>	<u>Unbiased Value</u>	<u>Biased Value</u>
CDC	0	1	MOL	14	15
SEDC	1	2	CAL3	15	16
SPDC	2	3	E1H	16	17
	3	4	E1U	17	18
C1	4	5	M1H	18	19
E1L	5	6	M1U	19	20
M1L	6	7	E2H	20	21
CAL1	7	8	E2U	21	22
C2	8	9	M2H	22	23
E2L	9	10	M2U	23	24
M2L	10	11	E3H	24	25
CAL2	11	12	E3U	25	26
C3	12	13	M3H	26	27
E3L	13	14	M3U	27	28

IDV thus ranges after a +1 bias:

$$1_{10} - 28_{10}$$

$$1_8 - 34_8$$

$$1_2 - 011100_2$$

Bits: 5 4 3 2 1

Value: $\begin{matrix} 0 & 0 & 0 & 0 & 0 \\ 1 & 1 & 1 & 1 & 1 \end{matrix}$

3/15/74

(F) MFMOD - 1 ; Earth Traversal
 2 ; Interplanetary Cruise
 3 ; Jupiter Encounter

(G) SCNO - 10₁₀ - 12₈ ; Pioneer-10 = 10
 - 11₁₀ - 13₈ ; Pioneer-11 = 11

(H) STNO:

Name	Source Code	STNO ₁₀	STNO ₂	STNO ₈
DSS 11	051	11	00001011	13
DSS 12	351	12	00001100	14
DSS 14	031	14	00001110	16
DSS 21	153	21	00010101	25
DSS 27, DSN Simulation Center (SIMCEN)	023	27	00011011	31
DSS 41	211	41	00101001	51
DSS 42	111	42	00101010	52
DSS 51	026	51	00110011	63
DSS 61	326	61	00111101	75
DSS 62	166	62	00111110	76
DSS 70, Cape Building A0	106	70	01000110	106
DSS 71	046	71	01000111	107
DSS 90, Merritt Island MSFN (MIL)	100	90	01011010	132
DSS 91, USNS Vanguard MSFN (VAN)	112	91	01011011	133
DSS 92, Bermuda MSFN (BDA)	114	92	01011100	134
DSS 93, Ascension MSFN (ACN)	117	93	01011101	135
DSS 94, Canary Island MSFN (CYI)	121	94	01011110	136
DSS 99, Boulder, Colorado	200	99	01100011	143
DSS 00, SPOF 1	310	0	00000000	0

3/13/76

②

BTR:	<u>Bits/Second</u>	<u>Value Biased</u>	<u>Value Unbiased</u>
	16	1	0
	32	2	1
	64	3	2
	128	4	3
	256	5	4
	512	6	5
	1024	7	6
	2048	8	7

The binary tape contains the unbiased value.

③ CR: Count Rate = Counts/kilosecond

Electrometer Count = $\times 10^3$

④ Right-handed System I longitude as carried on JPL ephemeris tape.

⑤ Left-handed System III longitude (I.A.U. definition), in Micro-radians.

3/15/74

READING, IREAD

1	FLAG	Int.
2	ID	Int.
3	COUNTS	Real
4	RANG	Int.
5	TIME	Int.
6	ASW	Real
7	ALEC	Real
8	ALS	Real
9	ACEL or AGLO	Real
10	Empty or AGLA	Real

FIRST, IFIRST

1	GMT	Int.
2	DAY	Int.
3	COLE TIME	Int.
4	TCP	Int.
5	SNR	Real
6	DSS	Int.
7	BR	Int.
8	MOD	Int.
9	FMT	Int.
10	RTLE	Int.
11	ESC	Int.
12	ACGT	Real
13	IPFT	Int.
14	NREDUN	Int.
15	NCOM	Int.
16	IADD	Int.

SECOND, ISEC

1	ATTFLCS	Int.
2	RAT	Real
3	ASF	Real
4	SFF	Int.
5	ARIPHC	Real
6	GMT112	Int.
7	C124	Int.
8	GMT124	Int.
9	C431	Int.

COMMON/ANGEL/IFLAG(3), RAT(3), ASF(3), ISFF(3), ARIPHC(3), C112(3), AREF(3), ASTD(3), XPOINT

COMMON/BROOM/ATQDEC, ATQRASC, ATCLAT, ATCLNG, CSXEC, CSYEC, CSZEC, CZVEQ, CSZEQ

COMMON/CNTRL/SAT, TYPE, RSTR1, EDRIAP, EDRSNO, NFMOD, TRJA, TRJB

COMMON/CTIME/MSDATA

COMMON/EDR/FIRST(36), SECOND(18), ARRAY(224), IPOINT, ICHG, NDEC, XREADS, NSCID, JPOINT, JCHG

COMMON/PP/PP(14)

COMMON/READING/READING(128), NTRIES, DTIME

3/15/76

INTERP (TRJDAT)

Traversal:	Position	Source ID	Array TRAJ Origin	PC 262.04 Tape Parameter #
	1	VIGDAT	8	3
	2	REARPR	34	11
	3	REARMO	52	17
	4	RTASCP	40	13
	5	RTASCS	49	16
	6	RTASCH	58	19
	7	CELLNE	79	26
	8	DECMOO	55	18
	9	EASD	460	153
	10	EALATP	181	60
	11	EALONP	184	61
	12	SSP	445	148
	13	XPCSFF	97	32
	14	YPCSFF	100	33
	15	ZPCSFF	103	34
	16	HOURAN	325	108
	17	CELLTP	70	23
	18	CELLNP	73	24

Cruise:	Position	Source ID	Array TRAJ Origin	PC 262.04 Tape Parameter #
	1	VIGDAT	8	3
	2	NRANCP	61	30
	3	CELLTP	70	23
	4	CELLNP	73	24
	5	CELLTE	76	25
	6	CELLNE	79	26
	7	HRS	418	139
	8	HDECS	415	138
	9	HRA5	412	137
	10	REARSU	43	14
	11	ESPANG	256	85

Encounter:	Position	Source ID	Array TRAJ Origin	PC 262.04 Tape Parameter #
	1	VIGDAT	8	3
	2	BIMAGR	169	56
	3	BILONP	199	66
	4	BILATP	196	65
	5	ASASD	469	156
	6	SSP	445	148
	7	HRA5	412	137
	8	XPISFF	133	44
	9	YPISFF	136	45
	10	ZPISFF	139	46

Word in TRAJ = Tape Parameter + 3 + 1 after parameter 4

3/15/74

PP, IFF

1	DC Bus Voltage	Real
2	# in sum PP(1)	Int.
3	DC Bus Current	Real
4	# in sum PP(3)	Int.
5	Platform Temperature	Real
6	# in sum PP(5)	Int.
7	Fulse Temperature	Real
8	# in sum PP(7)	Int.
9	HVRC	Real
10	# in sum PP(9)	Int.
11	Det. C Temperature	Real
12	# in sum PP(11)	Int.
13	HV	Int.
14	# in sum PP(13)	Int.

HL

\$JOB 14:45:58
 \$ASS IN MSS SI TY
 \$EXEC DPOCT7 BS
 INPUT TAPE ON MSS

PIONEER II BRT
 23-019A-05B
 12/02/77 12/03/77

(2-372-373)
 DLPF OF D-25185

DAY 336

1 3 3 1066.977752

DATA INPUT	FILE 1	RECORD 1	LENGTH	2736 BYTES
	(0)	000125665703	3063	000000032000 000017665310
	(48)	000000470400	0000	000000000000 030132720000 000006706772
	(96)	000000001024	2370	000000000000 057234510000 000012460346
	(144)	000000000776	0223	000000000000 017603400000 000035452316
	(192)	000000000035	7702	000000000000 044234560000 000037370315
	(240)	777777777777	7775	000000001026 051000000000 371377450000
	(288)	000000000000	0007	000000000000 000246140000 000057241570
	(336)	000125665703	6016	000000130000 000000000016 000000001637
	(384)	000000470400	0000	000000000000 030132720000 000007302651
	(432)	000000001134	5207	000000000000 057234510000 000012460346
	(480)	000000000776	0240	000000000000 017577030000 000035450213
	(528)	000000000035	7711	000000000000 044235020000 000037367436
	(576)	777777777777	7775	000246160000 000057242447 777777777777
	(624)	000000000000	0007	000000000000 000000130000 000000000016
	(672)	000125665704	0751	000000320000 000017677640 000000000000
	(720)	000000470400	0000	030132720000 000007014044 000000000262
	(768)	000000001010	4562	000000000000 057234510000 000012460346
	(816)	000000000776	0265	000000000000 017572450000 000035455073
	(864)	000000000035	7717	000000000000 044235270000 000037366560
	(912)	777777777777	7775	000246200000 000057243309 777777777777
	(960)	000000000000	0007	000000000000 000000130000 000000000016
	(1008)	000125665704	3705	000000330000 000000000000 000000000000
	(1056)	010534154140	2070	000000000000 030132720000 000006041022
	(1104)	000000000565	7552	000000000000 057234510000 000012460346
	(1152)	000000000776	0306	000000000000 017566100000 000035452770
	(1200)	000000000035	7726	000000000000 044235540000 000037365701
	(1248)	777777777777	7775	000246230000 000057244157 777777777777
	(1296)	000000000000	0007	000000000000 000000130000 000000000016
	(1344)	000125665705	0061	000000300000 000000135600 000000000000
	(1392)	010534154140	2070	000000000000 001471630000 000004610450
	(1440)	000000000267	3320	000000000000 057234510000 000012460346
	(1488)	000000000776	0336	000000000000 017557550000 000035447731
	(1536)	000000000035	7737	000000000000 044236120000 000037364526
	(1584)	777777777777	7775	000246260000 000057245332 777777777777
	(1632)	000000000000	0007	000000000000 000000130000 000000000016
	(1680)	000125665705	3015	000000030000 000000133630 000000000000
	(1728)	010534154140	2070	000000000000 001471630000 000004526337
	(1776)	000000000272	5342	000000000000 057234510000 000012460346
	(1824)	000000000776	0357	000000000000 017553200000 000035454610
	(1872)	000000000035	7746	000000000000 044236370000 000037363647
	(1920)	777777777777	7775	000246300000 000057246163 777777777777
	(1968)	000000000000	0007	000000000000 000000130000 000000000016
	(2016)	000125665705	5752	000000030000 000000135600 000000000000
	(2064)	010534154140	2070	000000000000 001471630000 000005277345
	(2112)	000000000471	4741	000000000000 057234510000 000012460346
	(2160)	000000000776	0400	000000000000 017546620000 000035452504
	(2208)	000000000035	7754	000000000000 044236640000 000037362770
	(2256)	777777777777	7775	000246320000 000057247042 777777777777
	(2304)	000000000000	0007	000000000000 000000130000 000000000016
	(2352)	000125665706	0706	000000000000 000000000016 000000001177
	(2400)	010534154140	2070	000000000000 001471630000 000006331771
	(2448)	000000000720	3136	000000000000 057234510000 000012460346
	(2496)	000000000776	0420	000000000000 017542240000 000035450401
	(2544)	000000000035	7763	000000000000 044237110000 000037362112
	(2592)	777777777777	7775	000246340000 000057247720 777777777777
	(2640)	000000000000	0007	000000000000 000000130000 000000000016
	(2688)	777777777777	7775	00000001500 602277777777 777777777777
FILE 1	RECORD 2	LENGTH	2736 BYTES	

