

All Classes

Packages

gsfc.nssdc.cdf

gsfc.nssdc.cdf.util

All Classes

Attribute

CDF

CDFConstants

CDFData

CDFDelegate

CDFException

CDFNativeLibrary

CDFObject

CDFTools

CDFTT2000

CDFUtils

Entry

Epoch

Epoch16

EpochNative

Variable

Overview

Package

Class

Tree

Deprecated

Index

Help

Prev

Next

Frames

No Frames

Packages

Package

Description

gsfc.nssdc.cdf

gsfc.nssdc.cdf.util

Overview

Package

Class

Tree

Deprecated

Index

Help

Prev

Next

Frames

No Frames

All Classes				
-------------	--	--	--	--

- Attribute
- CDF
- CDFConstants*
- CDFData
- CDFDelegate*
- CDFException
- CDFNativeLibrary
- CDFObject*
- CDFTools
- CDFTT2000
- CDFUtils
- Entry
- Epoch
- Epoch16
- EpochNative
- Variable

Interfaces

- CDFConstants*
- CDFDelegate*
- CDFObject*

Classes

- Attribute
- CDF
- CDFData
- CDFNativeLibrary
- CDFTools
- Entry
- Variable

Exceptions

- CDFException

gsfc.nssdc.cdf.util				
---------------------	--	--	--	--

Classes

- CDFTT2000
- CDFUtils
- Epoch
- Epoch16
- EpochNative

gsfc.nssdc.cdf

Class Attribute

java.lang.Object
gsfc.nssdc.cdf.Attribute

All Implemented Interfaces:

CDFConstants, CDFObject

```
public class Attribute
extends java.lang.Object
implements CDFConstants, CDFObject
```

This class contains the methods that are associated with either global or variable attributes.

Version:

1.0, 2.0 03/18/05 Selection of current CDF and attribute are done as part of operations passed to JNI. JNI call is synchronized so only one process is allowed in a JVM, due to multi-thread safety. The select method will never be called., 3.3 01/31/11 Reset the vector size to match the maximum entry in stead of its expanded capacity in getEntries method.

See Also:

CDF, CDFException, Entry, Variable

Field Summary

Fields inherited from interface gsfc.nssdc.cdf.CDFConstants
AHUFF COMPRESSION, ALPHAOSf1 DECODING, ALPHAOSf1 ENCODING, ALPHAVMSd DECODING, ALPHAVMSd ENCODING, ALPHAVMSG DECODING, ALPHAVMSG ENCODING, ALPHAVMSI DECODING, ALPHAVMSI ENCODING, ARM BIG DECODING, ARM BIG ENCODING, ARM LITTLE DECODING, ARM LITTLE ENCODING, ATTR, ATTR EXISTENCE, ATTR EXISTS, ATTR MAXgENTRY, ATTR MAXrENTRY, ATTR MAXzENTRY, ATTR NAME, ATTR NAME TRUNC, ATTR NUMBER, ATTR NUMgENTRIES, ATTR NUMrENTRIES, ATTR NUMzENTRIES, ATTR SCOPE, BACKWARD, BACKWARDFILEoff, BACKWARDFILEon, BAD ALLOCATE RECS, BAD ARGUMENT, BAD ATTR NAME, BAD ATTR NUM, BAD BLOCKING FACTOR, BAD CACHE SIZE, BAD CDF EXTENSION, BAD CDF ID, BAD CDF NAME, BAD CDFSTATUS, BAD CHECKSUM, BAD COMPRESSION PARM, BAD DATA TYPE, BAD DECODING, BAD DIM COUNT, BAD DIM INDEX, BAD DIM INTERVAL, BAD DIM SIZE, BAD ENCODING, BAD ENTRY NUM, BAD FNC OR ITEM, BAD FORMAT, BAD INITIAL RECS, BAD MAJORITY, BAD MALLOC, BAD NEGtoPOSfp0 MODE, BAD NUM DIMS, BAD NUM ELEMS, BAD NUM STRINGS, BAD NUM VARS, BAD READONLY MODE, BAD REC COUNT, BAD REC INTERVAL, BAD REC NUM, BAD SCOPE, BAD SCRATCH DIR, BAD SPARSEARRAYS PARM, BAD VAR NAME, BAD VAR NUM, BAD zMODE, BADDATE LEAPSECOND UPDATED, BeginUnixTimeEPOCH, BeginUnixTimeEPOCH16, BLOCKINGFACTOR TOO LARGE, BLOCKINGFACTOR TOO SMALL, BLOCKINGFACTOR TOO SMALL2, CANNOT ALLOCATE RECORDS, CANNOT CHANGE, CANNOT COMPRESS, CANNOT CONVERT WIDECCHAR, CANNOT COPY, CANNOT INSERT RECORDS, CANNOT SPARSEARRAYS, CANNOT SPARSERECORDS, CDF, CDF ACCESS, CDF ATTR NAME LEN, CDF ATTR NAME LEN256, CDF BYTE, CDF CACHESIZE, CDF CHAR, CDF CHECKSUM, CDF CLOSE ERROR, CDF COMPRESSION, CDF COPYRIGHT, CDF COPYRIGHT LEN, CDF CREATE ERROR, CDF DECODING, CDF DELETE ERROR, CDF DOUBLE, CDF ENCODING, CDF EPOCH, CDF EPOCH16, CDF EXISTS, CDF FLOAT, CDF FORMAT, CDF INCREMENT, CDF INFO, CDF INT1, CDF INT2, CDF INT4, CDF INT8, CDF INTERNAL ERROR, CDF LEAPSECONDLASTUPDATED, CDF MAJORITY, CDF MAX DIMS, CDF MAX PARMS, CDF MIN DIMS, CDF NAME, CDF NAME TRUNC, CDF NEGtoPOSfp0 MODE, CDF NUMATTRS, CDF NUMgATTRS, CDF NUMrVARS, CDF NUMvATTRS, CDF NUMzVARS, CDF OK, CDF OPEN ERROR, CDF PATHNAME LEN, CDF READ ERROR, CDF READONLY MODE, CDF REAL4, CDF REAL8, CDF RELEASE, CDF SAVE ERROR, CDF SCRATCHDIR, CDF STATUS, CDF STATUSTEXT LEN, CDF TIME TT2000, CDF UCHAR, CDF UINT1, CDF UINT2, CDF UINT4, CDF VAR NAME LEN, CDF VAR NAME LEN256, CDF VERSION, CDF WARN, CDF WRITE ERROR, CDF zMODE, CDFwithSTATS, CHECKSUM, CHECKSUM ERROR, CHECKSUM NOT ALLOWED, CLOSE, COLUMN MAJOR, COMPRESS CACHESIZE, COMPRESSION ERROR, CONFIRM, CORRUPTED V2 CDF, CORRUPTED V3 CDF, CREATE, CURgENTRY EXISTENCE, CURrENTRY EXISTENCE, CURzENTRY EXISTENCE, DATATYPE MISMATCH, DATATYPE SIZE, DECOMPRESSION ERROR, DECSTATION DECODING, DECSTATION ENCODING, DEFAULT BYTE PADVALUE, DEFAULT CHAR PADVALUE, DEFAULT DOUBLE PADVALUE, DEFAULT EPOCH PADVALUE, DEFAULT EPOCH16 PADVALUE, DEFAULT FLOAT PADVALUE, DEFAULT INT1 PADVALUE, DEFAULT INT2 PADVALUE, DEFAULT INT4 PADVALUE, DEFAULT INT8 PADVALUE, DEFAULT REAL4 PADVALUE, DEFAULT REAL8 PADVALUE, DEFAULT TT2000 PADVALUE, DEFAULT UCHAR PADVALUE, DEFAULT UINT1 PADVALUE, DEFAULT UINT2 PADVALUE, DEFAULT UINT4 PADVALUE, DELETE, DID NOT COMPRESS, EMPTY COMPRESSED CDF, END OF VAR, EPOCH STRING LEN, EPOCH STRING LEN EXTEND, EPOCH1 STRING LEN, EPOCH1 STRING LEN EXTEND, EPOCH2 STRING LEN, EPOCH2 STRING LEN EXTEND, EPOCH3 STRING LEN,

EPOCH3 STRING LEN EXTEND, EPOCH4 STRING LEN, EPOCH4 STRING LEN EXTEND, EPOCHx FORMAT MAX, EPOCHx STRING MAX, FILLED TT2000 VALUE, FORCED PARAMETER, FUNCTION NOT SUPPORTED, gENTRY, gENTRY DATA, gENTRY DATASPEC, gENTRY DATATYPE, gENTRY EXISTENCE, gENTRY NUMELEMS, GET, GETCDFCHECKSUM, GETCDFFILEBACKWARD, GETCDFVALIDATE, GETLEAPSECONDSENVVAR, GLOBAL SCOPE, GZIP COMPRESSION, HOST DECODING, HOST ENCODING, HP DECODING, HP ENCODING, HUFF COMPRESSION, IA64VMSd DECODING, IA64VMSd ENCODING, IA64VMSg DECODING, IA64VMSg ENCODING, IA64VMSi DECODING, IA64VMSi ENCODING, IBM PC OVERFLOW, IBMPC DECODING, IBMPC ENCODING, IBMRS DECODING, IBMRS ENCODING, ILLEGAL EPOCH FIELD, ILLEGAL EPOCH VALUE, ILLEGAL FOR SCOPE, ILLEGAL IN zMODE, ILLEGAL ON V1 CDF, ILLEGAL TT2000 VALUE, IS A NETCDF, LIB COPYRIGHT, LIB INCREMENT, LIB RELEASE, LIB subINCREMENT, LIB VERSION, MAC DECODING, MAC ENCODING, MD5 CHECKSUM, MULTI FILE, MULTI FILE FORMAT, NA FOR VARIABLE, NEGATIVE FP ZERO, NEGtoPOSfp0off, NEGtoPOSfp0on, NETWORK DECODING, NETWORK ENCODING, Next DECODING, Next ENCODING, NO ATTR SELECTED, NO CDF SELECTED, NO CHECKSUM, NO COMPRESSION, NO DELETE ACCESS, NO ENTRY SELECTED, NO MORE ACCESS, NO PADVALUE SPECIFIED, NO SPARSEARRAYS, NO SPARSERECORDS, NO STATUS SELECTED, NO SUCH ATTR, NO SUCH CDF, NO SUCH ENTRY, NO SUCH RECORD, NO SUCH VAR, NO VAR SELECTED, NO VARS IN CDF, NO WRITE ACCESS, NONE CHECKSUM, NOT A CDF, NOT A CDF OR NOT SUPPORTED, NOVARY, NULL, OPEN, OPTIMAL ENCODING TREES, OTHER CHECKSUM, PAD SPARSERECORDS, PPC DECODING, PPC ENCODING, PRECEDING RECORDS ALLOCATED, PREV SPARSERECORDS, PUT, READ ONLY DISTRIBUTION, READ_ONLY_MODE, READONLYoff, READONLYon, rENTRY, rENTRY DATA, rENTRY DATASPEC, rENTRY DATATYPE, rENTRY EXISTENCE, rENTRY NAME, rENTRY NUMELEMS, rENTRY NUMSTRINGS, rENTRY STRINGSDATA, RLE COMPRESSION, RLE OF ZEROS, ROW MAJOR, rVAR, rVAR ALLOCATEBLOCK, rVAR ALLOCATEDFROM, rVAR ALLOCATEDTO, rVAR ALLOCATERECS, rVAR BLOCKINGFACTOR, rVAR CACHESIZE, rVAR COMPRESSION, rVAR DATA, rVAR DATASPEC, rVAR DATATYPE, rVAR DIMVARYS, rVAR EXISTENCE, rVAR HYPERDATA, rVAR INITIALRECS, rVAR MAXallocREC, rVAR MAXREC, rVAR NAME, rVAR nINDEXENTRIES, rVAR nINDEXLEVELS, rVAR nINDEXRECORDS, rVAR NUMallocRECS, rVAR NUMBER, rVAR NUMELEMS, rVAR NUMRECS, rVAR PADVALUE, rVAR RECORDS, rVAR RECORDS RENUMBER, rVAR RECVAR, rVAR RESERVEPERCENT, rVAR SEQDATA, rVAR SEQPOS, rVAR SPARSEARRAYS, rVAR SPARSERECORDS, rVARs CACHESIZE, rVARs DIMCOUNTS, rVARs DIMINDICES, rVARs DIMINTERVALS, rVARs DIMSIZES, rVARs MAXREC, rVARs NUMDIMS, rVARs RECCOUNT, rVARs RECDATA, rVARs RECINTERVAL, rVARs RECNUMBER, SAVE, SCRATCH CREATE ERROR, SCRATCH DELETE ERROR, SCRATCH READ ERROR, SCRATCH WRITE ERROR, SELECT, SGI DECODING, SGI ENCODING, SINGLE FILE, SINGLE FILE FORMAT, SOME ALREADY ALLOCATED, STAGE CACHESIZE, STATUS TEXT, STRING NOT UTF8 ENCODING, STRINGDELIMITER, SUN DECODING, SUN ENCODING, TOO MANY PARMS, TOO MANY VARS, TRY TO READ NONSTRING DATA, TT2000 0 STRING LEN, TT2000 1 STRING LEN, TT2000 2 STRING LEN, TT2000 3 STRING LEN, TT2000 4 STRING LEN, TT2000 CDF MAYNEEDUPDATE, TT2000 TIME ERROR, TT2000 USED OUTDATED TABLE, UNABLE TO PROCESS CDF, UNKNOWN COMPRESSION, UNKNOWN SPARSENESS, UNSUPPORTED OPERATION, VALIDATE, VALIDATEFILEoff, VALIDATEFILEon, VAR ALREADY CLOSED, VAR CLOSE ERROR, VAR CREATE ERROR, VAR DELETE ERROR, VAR EXISTS, VAR NAME TRUNC, VAR OPEN ERROR, VAR READ ERROR, VAR SAVE ERROR, VAR WRITE ERROR, VARIABLE SCOPE, VARY, VAX DECODING, VAX ENCODING, VIRTUAL RECORD DATA, zENTRY, zENTRY DATA, zENTRY DATASPEC, zENTRY DATATYPE, zENTRY EXISTENCE, zENTRY NAME, zENTRY NUMELEMS, zENTRY NUMSTRINGS, zENTRY STRINGSDATA, ZLIB COMPRESS ERROR, ZLIB UNCOMPRESS ERROR, zMODEoff, zMODEon1, zMODEon2, zVAR, zVAR ALLOCATEBLOCK, zVAR ALLOCATEDFROM, zVAR ALLOCATEDTO, zVAR ALLOCATERECS, zVAR BLOCKINGFACTOR, zVAR CACHESIZE, zVAR COMPRESSION, zVAR DATA, zVAR DATASPEC, zVAR DATATYPE, zVAR DIMCOUNTS, zVAR DIMINDICES, zVAR DIMINTERVALS, zVAR DIMSIZES, zVAR DIMVARYS, zVAR EXISTENCE, zVAR HYPERDATA, zVAR INITIALRECS, zVAR MAXallocREC, zVAR MAXREC, zVAR NAME, zVAR nINDEXENTRIES, zVAR nINDEXLEVELS, zVAR nINDEXRECORDS, zVAR NUMallocRECS, zVAR NUMBER, zVAR NUMDIMS, zVAR NUMELEMS, zVAR NUMRECS, zVAR PADVALUE, zVAR RECCOUNT, zVAR RECINTERVAL, zVAR RECNUMBER, zVAR RECORDS, zVAR RECORDS RENUMBER, zVAR RECVAR, zVAR RESERVEPERCENT, zVAR SEQDATA, zVAR SEQPOS, zVAR SPARSEARRAYS, zVAR SPARSERECORDS, zVARs CACHESIZE, zVARs MAXREC, zVARs RECDATA, zVARs RECNUMBER

Method Summary

Methods	
Modifier and Type	Method and Description
static Attribute	create (CDF myCDF, java.lang.String name, long scope) Creates a new attribute in the given CDF.
void	delete () Deletes this attribute.
void	deleteEntry (long entryID) Deletes an attribute entry for the given entry number.
void	deleteEntry (Variable var) Deletes the attribute entry for the given variable.
java.util.Vector	getEntries () Gets all the entries defined for this attribute.
Entry	getEntry (long entryID) Gets the attribute entry for the given entry number.
Entry	getEntry (Variable var) Gets the attribute entry for the given variable.
long	getEntryID (Entry entry)

	Gets the entry id for the given entry.
long	<code>getID()</code> Gets the attribute ID of this attribute.
long	<code>getMaxEntryNumber()</code> Gets the largest Entry number for this attribute.
CDF	<code>getMyCDF()</code> Gets the CDF object to which this attribute belongs.
java.lang.String	<code>getName()</code> Gets the name of this attribute.
long	<code>getNumEntries()</code> Gets the number of entries in this attribute.
long	<code>getScope()</code> Gets the scope of this attribute.
void	<code>rename(java.lang.String newName)</code> Renames the current attribute.
java.lang.String	<code>toString()</code> Gets the name of this attribute.

Methods inherited from class java.lang.Object

`equals, getClass, hashCode, notify, notifyAll, wait, wait, wait`

Method Detail

create

```
public static Attribute create(CDF myCDF,
                             java.lang.String name,
                             long scope)
    throws CDFException
```

Creates a new attribute in the given CDF. Attributes and attribute entries are used to describe information about a CDF file and the variables in the file. Any number of attributes may be stored in a CDF file.

The following example creates a global attribute called 'Project' and a variable attribute called 'VALIDMIN':

```
Attribute project, validMin;

project = Attribute.create(cdf, "Project", GLOBAL_SCOPE);
validMin = Attribute.create(cdf, "VALIDMIN", VARIABLE_SCOPE);
```

Parameters:

- `myCDF` - the CDF object to which this attribute belongs
- `name` - the name of the attribute to be created
- `scope` - the attribute's scope - it should be either GLOBAL_SCOPE or VARIABLE_SCOPE

Returns:

Attribute an Attribute object in the CDF.

Throws:

`CDFException` - if a problem occurred in creating an attribute

delete

```
public void delete()
    throws CDFException
```

Deletes this attribute.

Note: When an attribute is deleted all the entries for attribute are deleted as well. Also, all attributes that follow the deleted attribute will be renumbered immediately (their IDs will be decremented by one). This can cause confusion when using a loop to delete attributes. The following is incorrect and will result in every other attribute being deleted:

```
Vector attrs = cdf.getAttributes();
int n = attrs.size();
for (int i = 0; i < n; i++)
    ((Attribute)attrs.elementAt(i)).delete();
```

Two possible workarounds are:

```
Vector attrs = cdf.getAttributes();
int n = attrs.size();
for (int i = n-1; i >= 0; i--)
    ((Attribute)attrs.elementAt(i)).delete();
```

and

```
Vector attrs = cdf.getAttributes();
int n = attrs.size();
for (int i = 0; i < n; i++)
    ((Attribute)attrs.elementAt(0)).delete();
```

Specified by:

`delete` in interface `CDFObject`

Throws:

`CDFException` - if there is a problem deleting the attribute

getEntry

```
public Entry getEntry(long entryID)
    throws CDFException
```

Gets the attribute entry for the given entry number.

The following example retrieves the first entry of the global attribute 'project'. Please note that a global attribute can have multiple entries (whereas, a variable attribute has only one entry for a particular attribute), and attribute id starts at 0, not 1.

```
Entry tEntry = project.getEntry(0L)
```

Parameters:

`entryID` - the entry number from which an attribute entry is retrieved

Returns:

Entry the Entry object

Throws:

`CDFException` - if an error occurred getting an entry (i.e. invalid entryID, no attribute entry for entryID)

getEntry

```
public Entry getEntry(Variable var)
    throws CDFException
```

Gets the attribute entry for the given variable.

The following example retrieves the 'longitude' variable entry associate with the attribute 'validMin':

```
vEntry = validMin.getEntry(longitude);
```

Parameters:

var - the variable from which an attribute entry is retrieved

Returns:

Entry the Entry object

Throws:

CDFException - if an error occurred getting a variable attribute entry (e.g. non-existent variable, no attribute entry for this variable, etc.)

deleteEntry

```
public void deleteEntry(long entryID)
    throws CDFException
```

Deletes an attribute entry for the given entry number.

The following example deletes the first and second entries of the global attribute 'Project':

```
project.deleteEntry(0L);
project.deleteEntry(1L);
```

The following example deletes the 'longitude' variable entry associated with the attribute 'validMin':

```
validMin.deleteEntry(longitude.getID());
```

Parameters:

entryID - the ID of the entry to be deleted

Throws:

CDFException - if there was a porblem deleting the entry

deleteEntry

```
public void deleteEntry(Variable var)
    throws CDFException
```

Deletes the attribute entry for the given variable.

The following example deletes the 'longitude' variable entry associated with the attribute 'validMin':

```
validMin.deleteEntry(longitude);
```

Parameters:

var - the variable from which the attribute entry is deleted

Throws:

`CDFException` - if there was a porblem deleting the entry

getEntries

```
public java.util.Vector getEntries()  
    throws CDFException
```

Gets all the entries defined for this attribute. A global attribute can have multiple entries. Whereas, a variable attribute has only one entry for a particular attribute.

Returns:

all the entries (one or more) defined for a global attribute or all variable entries for this attribute. The number of returned entries vector for a variable attribute may be less than the number of variables, as not all variables have an entry for the attribute.

Throws:

`CDFException` - if there was a porblem getting the entries

getEntryID

```
public long getEntryID(Entry entry)
```

Gets the entry id for the given entry.

Parameters:

`entry` - the entry from which an entry id is retrieved

Returns:

the entry id for the given entry

rename

```
public void rename(java.lang.String newName)  
    throws CDFException
```

Renames the current attribute.

Specified by:

`rename` in interface `CDFObject`

Parameters:

`newName` - the new attribute name

Throws:

`CDFException` - if there was a problem renaming the attribute

getNumEntries

```
public long getNumEntries()
```

Gets the number of entries in this attribute.

Returns:

the number of entries in this attribute

getMaxEntryNumber

```
public long getMaxEntryNumber()

Gets the largest Entry number for this attribute.

Returns:
    the largest Entry number for this attribute
```

getID

```
public long getID()

Gets the attribute ID of this attribute.

Returns:
    the attribute id of this attribute
```

getMyCDF

```
public CDF getMyCDF()

Gets the CDF object to which this attribute belongs.

Returns:
    the CDF object to which this attribute belongs
```

getName

```
public java.lang.String getName()

Gets the name of this attribute.

Specified by:
    getName in interface CDFObject

Returns:
    the name of this attribute
```

toString

```
public java.lang.String toString()

Gets the name of this attribute.

Overrides:
    toString in class java.lang.Object

Returns:
```

the name of this attribute

getScope

```
public long getScope()
```

Gets the scope of this attribute.

Returns:

If the attribute is a global attribute, GLOBAL_SCOPE is returned. If the attribute is a variable attribute, VARIABLE_SCOPE is returned.

Overview

Package

Class

Tree

Deprecated

Index

Help

Prev Class

Next Class

Frames

No Frames

All Classes

Summary: Nested | Field | Constr | Method

Detail: Field | Constr | Method

gsfc.nssdc.cdf

Class CDF

java.lang.Object
gsfc.nssdc.cdf.CDF

All Implemented Interfaces:

CDFConstants, CDFObject

```
public class CDF
extends java.lang.Object
implements CDFObject, CDFConstants
```

The CDF class is the main class used to interact with a CDF file.

Notes:

- All files are placed in zMODE 2 upon opening or creation
- Variable attributes are handled slightly differently from C.
 - Each variable has a java.util.Vector of attributes.
 - This vector contains only those vAttributes that have a z entry for this variable.
 - Therefore, the index for a given variable Attribute may not be the same for another variable.

CDF dataType	Java dataType	Read/Write
CDF_BYTE	java.lang.Byte	Y/Y
CDF_INT1	java.lang.Byte	Y/Y
CDF_UINT1	java.lang.Short	Y/Y
CDF_INT2	java.lang.Short	Y/Y
CDF_UINT2	java.lang.Integer	Y/Y
CDF_INT4	java.lang.Integer	Y/Y
CDF_UINT4	java.lang.Long	Y/Y
CDF_INT8	java.lang.Long	Y/Y
CDF_FLOAT	java.lang.Float	Y/Y
CDF_REAL4	java.lang.Float	Y/Y
CDF_DOUBLE	java.lang.Double	Y/Y
CDF_REAL8	java.lang.Double	Y/Y
CDF_EPOCH	java.lang.Double	Y/Y
CDF_EPOCH16	java.lang.Double[]	Y/Y
CDF_TIME_TT2000	java.lang.Long	Y/Y
CDF_CHAR	java.lang.String	Y/Y
CDF_UCHAR	java.lang.String	Y/Y

Version:

1.0, 2.0 03/18/05 Selection of current attribute is done as part of operations passed to JNI. JNI call is synchronized so only one process is allowed in a JVM, due to multi-thread safety. The select method will never be called. Sync'd the CDF (id) for every JNI calls.

See Also:

Attribute, CDFException, Variable

Field Summary

Fields inherited from interface gsfc.nssdc.cdf.CDFConstants

AHUFF COMPRESSION, ALPHAOSf1 DECODING, ALPHAOSf1 ENCODING, ALPHAVMSd DECODING, ALPHAVMSd ENCODING, ALPHAVMSg DECODING, ALPHAVMSg ENCODING, ALPHAVMSi DECODING, ALPHAVMSi ENCODING, ARM BIG DECODING, ARM BIG ENCODING, ARM LITTLE DECODING, ARM LITTLE ENCODING, ATTR, ATTR EXISTENCE, ATTR EXISTS, ATTR MAXgENTRY, ATTR MAXrENTRY, ATTR MAXZENTRY, ATTR NAME, ATTR NAME TRUNC, ATTR NUMBER, ATTR NUMgENTRIES, ATTR NUMrENTRIES, ATTR NUMzENTRIES, ATTR SCOPE, BACKWARD, BACKWARDFILEoff, BACKWARDFILEon, BAD ALLOCATE RECS, BAD ARGUMENT, BAD ATTR NAME, BAD ATTR NUM, BAD BLOCKING FACTOR, BAD CACHE SIZE, BAD CDF EXTENSION, BAD CDF ID, BAD CDF NAME, BAD CDFSTATUS, BAD CHECKSUM, BAD COMPRESSION PARM, BAD DATA TYPE, BAD DECODING, BAD DIM COUNT, BAD DIM INDEX, BAD DIM INTERVAL, BAD DIM SIZE, BAD ENCODING, BAD ENTRY NUM, BAD FNC OR ITEM, BAD FORMAT, BAD INITIAL RECS, BAD MAJORITY, BAD MALLOC, BAD NEGtoPOSfp0 MODE, BAD NUM DIMS, BAD NUM ELEMS, BAD NUM STRINGS, BAD NUM VARS, BAD READONLY MODE, BAD REC COUNT, BAD REC INTERVAL, BAD REC NUM, BAD SCOPE, BAD SCRATCH DIR, BAD SPARSEARRAYS PARM, BAD VAR NAME, BAD VAR NUM, BAD zMODE, BADDATE LEAPSECOND UPDATED, BeginUnixTimeEPOCH, BeginUnixTimeEPOCH16, BLOCKINGFACTOR TOO LARGE, BLOCKINGFACTOR TOO SMALL, BLOCKINGFACTOR TOO SMALL2, CANNOT ALLOCATE RECORDS, CANNOT CHANGE, CANNOT COMPRESS, CANNOT CONVERT WIDECHAR, CANNOT COPY, CANNOT INSERT RECORDS, CANNOT SPARSEARRAYS, CANNOT SPARSERECORDS, CDF, CDF ACCESS, CDF ATTR NAME LEN, CDF ATTR NAME LEN256, CDF BYTE, CDF CACHESIZE, CDF CHAR, CDF CHECKSUM, CDF CLOSE ERROR, CDF COMPRESSION, CDF COPYRIGHT, CDF COPYRIGHT LEN, CDF CREATE ERROR, CDF DECODING, CDF DELETE ERROR, CDF DOUBLE, CDF ENCODING, CDF EPOCH, CDF EPOCH16, CDF EXISTS, CDF FLOAT, CDF FORMAT, CDF INCREMENT, CDF INFO, CDF INT1, CDF INT2, CDF INT4, CDF INT8, CDF INTERNAL ERROR, CDF LEAPSECONDLASTUPDATED, CDF MAJORITY, CDF MAX DIMS, CDF MAX PARMS, CDF MIN DIMS, CDF NAME, CDF NAME TRUNC, CDF NEGtoPOSfp0 MODE, CDF NUMATTRS, CDF NUMgATTRS, CDF NUMrVARS, CDF NUMvATTRS, CDF NUMzVARS, CDF OK, CDF OPEN ERROR, CDF PATHNAME LEN, CDF READ ERROR, CDF READONLY MODE, CDF REAL4, CDF REAL8, CDF RELEASE, CDF SAVE ERROR, CDF SCRATCHDIR, CDF STATUS, CDF STATUSTEXT LEN, CDF TIME TT2000, CDF UCHAR, CDF UINT1, CDF UINT2, CDF UINT4, CDF VAR NAME LEN, CDF VAR NAME LEN256, CDF VERSION, CDF WARN, CDF WRITE ERROR, CDF zMODE, CDFwithSTATS, CHECKSUM, CHECKSUM ERROR, CHECKSUM NOT ALLOWED, CLOSE, COLUMN MAJOR, COMPRESS CACHESIZE, COMPRESSION ERROR, CONFIRM, CORRUPTED V2 CDF, CORRUPTED V3 CDF, CREATE, CURgENTRY EXISTENCE, CURrENTRY EXISTENCE, CURzENTRY EXISTENCE, DATATYPE MISMATCH, DATATYPE SIZE, DECOMPRESSION ERROR, DECSTATION DECODING, DECSTATION ENCODING, DEFAULT BYTE PADVALUE, DEFAULT CHAR PADVALUE, DEFAULT DOUBLE PADVALUE, DEFAULT EPOCH PADVALUE, DEFAULT EPOCH16 PADVALUE, DEFAULT FLOAT PADVALUE, DEFAULT INT1 PADVALUE, DEFAULT INT2 PADVALUE, DEFAULT INT4 PADVALUE, DEFAULT INT8 PADVALUE, DEFAULT REAL4 PADVALUE, DEFAULT REAL8 PADVALUE, DEFAULT TT2000 PADVALUE, DEFAULT UCHAR PADVALUE, DEFAULT UINT1 PADVALUE, DEFAULT UINT2 PADVALUE, DEFAULT UINT4 PADVALUE, DELETE, DID NOT COMPRESS, EMPTY COMPRESSED CDF, END OF VAR, EPOCH STRING LEN, EPOCH STRING LEN EXTEND, EPOCH1 STRING LEN, EPOCH1 STRING LEN EXTEND, EPOCH2 STRING LEN, EPOCH2 STRING LEN EXTEND, EPOCH3 STRING LEN, EPOCH3 STRING LEN EXTEND, EPOCH4 STRING LEN, EPOCH4 STRING LEN EXTEND, EPOCHx FORMAT MAX, EPOCHx STRING MAX, FILLED TT2000 VALUE, FORCED PARAMETER, FUNCTION NOT SUPPORTED, gENTRY, gENTRY DATA, gENTRY DATASPEC, gENTRY DATATYPE, gENTRY EXISTENCE, gENTRY NUMELEMS, GET, GETCDFCHECKSUM, GETCDFFILEBACKWARD, GETCDFVALIDATE, GETLEAPSECONDSENVVAR, GLOBAL SCOPE, GZIP COMPRESSION, HOST DECODING, HOST ENCODING, HP DECODING, HP ENCODING, HUFF COMPRESSION, IA64VMSd DECODING, IA64VMSd ENCODING, IA64VMSg DECODING, IA64VMSg ENCODING, IA64VMSi DECODING, IA64VMSi ENCODING, IBM PC OVERFLOW, IBMPC DECODING, IBMPC ENCODING, IBMRS DECODING, IBMRS ENCODING, ILLEGAL EPOCH FIELD, ILLEGAL EPOCH VALUE, ILLEGAL FOR SCOPE, ILLEGAL IN zMODE, ILLEGAL ON V1 CDF, ILLEGAL TT2000 VALUE, IS A NETCDF, LIB COPYRIGHT, LIB INCREMENT, LIB RELEASE, LIB subINCREMENT, LIB VERSION, MAC DECODING, MAC ENCODING, MD5 CHECKSUM, MULTI FILE, MULTI FILE FORMAT, NA FOR VARIABLE, NEGATIVE FP ZERO, NEGtoPOSfp0off, NEGtoPOSfp0on, NETWORK DECODING, NETWORK ENCODING, Next DECODING, Next ENCODING, NO ATTR SELECTED, NO CDF SELECTED, NO CHECKSUM, NO COMPRESSION, NO DELETE ACCESS, NO ENTRY SELECTED, NO MORE ACCESS, NO PADVALUE SPECIFIED, NO SPARSEARRAYS, NO SPARSERECORDS, NO STATUS SELECTED, NO SUCH ATTR, NO SUCH CDF, NO SUCH ENTRY, NO SUCH RECORD, NO SUCH VAR, NO VAR SELECTED, NO VARS IN CDF, NO WRITE ACCESS, NONE CHECKSUM, NOT A CDF, NOT A CDF OR NOT SUPPORTED, NOVARY, NULL, OPEN, OPTIMAL ENCODING TREES, OTHER CHECKSUM, PAD SPARSERECORDS, PPC DECODING, PPC ENCODING, PRECEEDING RECORDS ALLOCATED, PREV SPARSERECORDS, PUT, READ ONLY DISTRIBUTION, READ ONLY MODE, READONLYoff, READONLYon, rENTRY, rENTRY DATA, rENTRY DATASPEC, rENTRY DATATYPE, rENTRY EXISTENCE, rENTRY NAME, rENTRY NUMELEMS, rENTRY NUMSTRINGS, rENTRY STRINGSDATA, RLE COMPRESSION, RLE OF ZEROS, ROW MAJOR, rVAR, rVAR ALLOCATEBLOCK, rVAR ALLOCATEDFROM, rVAR ALLOCATEDTO, rVAR ALLOCATERECS, rVAR BLOCKINGFACTOR, rVAR CACHESIZE, rVAR COMPRESSION, rVAR DATA, rVAR DATASPEC, rVAR DATATYPE, rVAR DIMVARYS, rVAR EXISTENCE, rVAR HYPERDATA, rVAR INITIALRECS, rVAR MAXallocREC, rVAR MAXREC, rVAR NAME, rVAR nINDEXENTRIES, rVAR nINDEXLEVELS, rVAR nINDEXRECORDS, rVAR NUMallocRECS, rVAR NUMBER, rVAR NUMELEMS, rVAR NUMRECS, rVAR PADVALUE, rVAR RECORDS, rVAR RECORDS RENUMBER, rVAR RECVAR, rVAR RESERVEPERCENT, rVAR SEQDATA, rVAR SEQOPS, rVAR SPARSEARRAYS, rVAR SPARSERECORDS, rVARs CACHESIZE, rVARs DIMCOUNTS, rVARs DIMINDICES, rVARs DIMINTERVALS, rVARs DIMSIZES, rVARs MAXREC, rVARs NUMDIMS, rVARs RECCOUNT, rVARs RECDATA, rVARs RECINTERVAL, rVARs RECNUMBER, SAVE, SCRATCH CREATE ERROR, SCRATCH DELETE ERROR, SCRATCH READ ERROR, SCRATCH WRITE ERROR, SELECT, SGI DECODING, SGI ENCODING, SINGLE FILE, SINGLE FILE FORMAT, SOME ALREADY ALLOCATED, STAGE CACHESIZE, STATUS TEXT, STRING NOT UTF8 ENCODING, STRINGDELIMITER, SUN DECODING, SUN ENCODING, TOO MANY PARMS, TOO MANY VARS, TRY TO READ NONSTRING DATA, TT2000 0 STRING LEN, TT2000 1 STRING LEN, TT2000 2 STRING LEN, TT2000 3 STRING LEN, TT2000 4 STRING LEN, TT2000 CDF MAYNEEDUPDATE, TT2000 TIME ERROR, TT2000 USED OUTDATED TABLE, UNABLE TO PROCESS CDF, UNKNOWN COMPRESSION, UNKNOWN SPARSENESS, UNSUPPORTED OPERATION, VALIDATE, VALIDATEFILEoff, VALIDATEFILEon, VAR ALREADY CLOSED, VAR CLOSE ERROR, VAR CREATE ERROR, VAR DELETE ERROR, VAR EXISTS, VAR NAME TRUNC, VAR OPEN ERROR, VAR READ ERROR, VAR SAVE ERROR, VAR WRITE ERROR, VARIABLE SCOPE, VARY, VAX DECODING, VAX ENCODING, VIRTUAL RECORD DATA, zENTRY,

```
zENTRY_DATA, zENTRY_DATASPEC, zENTRY_DATATYPE, zENTRY_EXISTENCE, zENTRY_NAME,
zENTRY_NUMELEMS, zENTRY_NUMSTRINGS, zENTRY_STRINGSDATA, ZLIB_COMPRESS_ERROR,
ZLIB_UNCOMPRESS_ERROR, zMODEoff, zMODEon1, zMODEon2, zVAR, zVAR_ALLOCATEBLOCK,
zVAR_ALLOCATEDFROM, zVAR_ALLOCATEDTO, zVAR_ALLOCATERECS, zVAR_BLOCKINGFACTOR, zVAR_CACHESIZE,
zVAR_COMPRESSION, zVAR_DATA, zVAR_DATASPEC, zVAR_DATATYPE, zVAR_DIMCOUNTS, zVAR_DIMINDICES,
zVAR_DIMINTERVALS, zVAR_DIMSIZES, zVAR_DIMVARYS, zVAR_EXISTENCE, zVAR_HYPERDATA,
zVAR_INITIALRECS, zVAR_MAXallocREC, zVAR_MAXREC, zVAR_NAME, zVAR_nINDEXENTRIES,
zVAR_nINDEXLEVELS, zVAR_nINDEXRECORDS, zVAR_NUMallocRECS, zVAR_NUMBER, zVAR_NUMDIMS,
zVAR_NUMELEMS, zVAR_NUMRECS, zVAR_PADVALUE, zVAR_RECCOUNT, zVAR_RECINTERVAL, zVAR_RECNUMBER,
zVAR_RECORDS, zVAR_RECORDS_RENUMBER, zVAR_RECVAR, zVAR_RESERVEPERCENT, zVAR_SEQDATA,
zVAR_SEQPOS, zVAR_SPARSEARRAYS, zVAR_SPARSEREORDS, zVARS_CACHESIZE, zVARS_MAXREC,
zVARS_RECDATA, zVARS_RECNUMBER
```

Method Summary

Methods	
Modifier and Type	Method and Description
void	close() Closes this CDF file.
long	confirmCDFCacheSize() Gets the CDF cache size (the number of 512-byte cache buffers) set for this CDF.
long	confirmCompressCacheSize() Gets the number of 512-byte cache buffers being used for the compression scratch file (for the current CDF).
long	confirmDecoding() Gets the CDF decoding method defined for this CDF.
long	confirmNegtoPosfp0() Gets the -0.0 to 0.0 translation flag set for this CDF.
long	confirmReadOnlyMode() Gets the value of the read-only mode flag set for this CDF file.
long	confirmStageCacheSize() Gets the number of 512-byte cache buffers defined for the staging scratch file.
long	confirmzMode() Gets the zMode set for this CDF.
static CDF	create (java.lang.String path) Creates a CDF file in the current directory.
static CDF	create (java.lang.String path, int flag) Deprecated. <i>Use setFileBackward(long) method to set the file backward flag and create(String) to create file instead.</i>
void	delete() Deletes this CDF file.
void	finalize() Do the necessary cleanup when garbage collector reaps it.
Attribute	getAttribute (long attrNum) Gets the attribute for the given attribute number.
Attribute	getAttribute (java.lang.String attrName) Gets the attribute for the given attribute name.
long	getAttributeID (java.lang.String attrName) Gets the id of the given attribute.
java.util.Vector	getAttributes() Gets all the global and variable attributes defined for this CDF.
long	getChecksum()

	Gets the checksum method, if any, applied to the CDF.
static long	<code>getChecksumEnvVar()</code> Gets the value of the CDF_CHECKSUM environment variable.
java.lang.String	<code>getCompression()</code> Gets the string representation of the compression type and parameters defined for this CDF.
long[]	<code>getCompressionParms()</code> Gets the compression parameters set for this CDF.
long	<code>getCompressionPct()</code> Gets the compression percentage set for this CDF.
long	<code>getCompressionType()</code> Gets the compression type set for this CDF.
java.lang.String	<code>getCopyright()</code> Gets the CDF copyright statement for this CDF.
CDFDelegate	<code>getDelegate()</code> This is a placeholder for future expansions/extensions.
long	<code>getEncoding()</code> Gets the encoding method defined for this CDF.
static boolean	<code>getFileBackward()</code> Gets the file backward flag.
static int	<code>getFileBackwardEnvVar()</code> Gets the value of the CDF_FILEBACKWARD environment variable.
long	<code>getFormat()</code> Gets the CDF format defined for this CDF.
java.util.Vector	<code>getGlobalAttributes()</code> Gets the global attributes defined for this CDF.
long	<code>getID()</code> Gets the id of this CDF file.
long	<code>getLeapSecondLastUpdated()</code> Gets the date that the CDF has the last leap second updated.
static java.lang.String	<code>getLeapSecondsTableEnvVar()</code> Gets the the CDF_LEAPSECONDSTABLE (or CDF\$LEAPSECONDSTABLE on VMS) environment variable.
static java.lang.String	<code>getLibraryCopyright()</code> Retrieve library copyright information associated with the CDF library.
static java.lang.String	<code>getLibraryVersion()</code> Retrieve library version/release/increment/sub_increment information associated with the CDF library.
long	<code>getMajority()</code> Gets the variable majority defined for this CDF.
java.lang.String	<code>getName()</code> Gets the name of this CDF.
long	<code>getNumAttrs()</code> Gets the total number of global and variable attributes in this CDF.
long	<code>getNumGattrs()</code> Gets the number of global attributes in this CDF.
long	<code>getNumRvars()</code> Gets the number of r variables.
long	<code>getNumVars()</code> Gets the number of Z variables defined for this CDF.
long	<code>getNumVattrs()</code> Gets the number of variable attributes in this CDF.

long	getNumZvars () Gets the number of z variables in this CDF file.
java.util.Vector	getOrphanAttributes () Gets the variable attributes defined for this CDF that are not associated with any variables.
java.util.Vector	getRecord (long recNum, long[] varIDs) Retrieves a logical record that consists of single variable record(s) from an arbitrary number of CDF variables.
java.util.Vector	getRecord (long recNum, long[] varIDs, long[] status) Retrieves a logical record that consists of single variable record(s) from an arbitrary number of CDF variables.
java.util.Vector	getRecord (long recNum, java.lang.String[] strVars) Retrieves a logical record that consists of single variable record(s) from an arbitrary number of CDF variables.
java.util.Vector	getRecord (long recNum, java.lang.String[] strVars, long[] status) Retrieves a logical record that consists of single variable record(s) from an arbitrary number of CDF variables.
long	getStatus () Gets the status of the most recent CDF JNI/library function call.
static java.lang.String	getStatusText (long statusCode) Gets the status text of the most recent CDF JNI/library function call.
static boolean	getValidate () Gets the file validation mode.
Variable	getVariable (long varNum) Gets the variable object for the given variable number.
Variable	getVariable (java.lang.String varName) Gets the variable object for the given variable name.
java.util.Vector	getVariableAttributes () Gets the variable attributes defined for this CDF.
long	getVariableID (java.lang.String varName) Gets the ID of the given variable.
java.util.Vector	getVariables () Gets the z variables defined for this CDF.
java.lang.String	getVersion () Gets the CDF library version that was used to create this CDF (e.g. 2.6.7, etc.).
static CDF	open (java.lang.String path) Open a CDF file for read/write, the default mode for opening a CDF.
static CDF	open (java.lang.String path, long readOnly) Open a CDF file.
void	putRecord (long recNum, long[] varIDs, java.util.Vector myData) Writes a logical record that consists of single variable record(s) from an arbitrary number of CDF variables.
void	putRecord (long recNum, long[] varIDs, java.util.Vector myData, long[] status) Writes a logical record that consists of single variable record(s) from an arbitrary number of CDF variables.
void	putRecord (long recNum, java.lang.String[] strVars, java.util.Vector myData) Writes a logical record that consists of single variable record(s) from an arbitrary number of CDF variables.
void	putRecord (long recNum, java.lang.String[] strVars, java.util.Vector myData, long[] status) Writes a logical record that consists of single variable record(s) from an arbitrary number of CDF variables.
java.util.Map	readCDF ()

	Gets the full CDF information.
java.util.Map	readCDF (boolean encoding) Gets the full CDF information.
java.util.Map	readCDF (boolean encoding, boolean basic, boolean globals, boolean varinfo) Gets the specified information from a CDF.
java.util.Map	readCDF (boolean encoding, boolean basic, boolean globals, boolean varinfo, boolean varmeta, boolean vardata) Gets the specified information from a CDF.
java.util.Map	readCDF (boolean encoding, boolean basic, boolean globals, boolean varinfo, boolean varmeta, boolean vardata, boolean noentry) Gets the specified information from a CDF.
java.util.Map	readCDFGlobalAttributes () Gets the global attributes and their entries defined for this CDF.
java.util.Map	readCDFGlobalAttributes (boolean encoding) Gets the global attributes and their entries defined for this CDF.
java.util.Map	readCDFGlobalAttributes (long attrNum) Gets a specified global attribute's entry(ies) defined for this CDF.
java.util.Map	readCDFGlobalAttributes (long[] attrNums) Gets a specified list of global attributes and their entries defined for this CDF.
java.util.Map	readCDFGlobalAttributes (java.lang.Object attrs, boolean encoding) Gets a list of specified global attributes and their entries defined for this CDF.
java.util.Map	readCDFGlobalAttributes (java.lang.String attrName) Gets a specified global attribute's entry(ies) defined for this CDF.
java.util.Map	readCDFGlobalAttributes (java.lang.String[] attrNames) Gets a specified list of global attributes and their entries defined for this CDF.
java.util.Map	readCDFInfo () Gets the basic information about this CDF.
java.util.Map	readCDFNoEntryAttributes () Gets a map of global attributes and variable attributes with no entry data.
java.util.Map	readCDFVariables () Reads all variables' information in the CDF.
java.util.Map	readCDFVariablesData () Reads all variables' data in the CDF.
java.util.Map	readCDFVariablesMetaData () Reads all variables' metadata in the CDF.
java.util.Map	readCDFVariablesSpec () Reads all variables' specifications in the CDF.
void	rename (java.lang.String path) Renames the current CDF.
void	save () Saves this CDF file without closing.
void	selectCDFCacheSize (long cacheSize) Defines the number of 512-byte cache buffers to be used for the dotCDF file (for the current CDF).
void	selectCompressCacheSize (long compressCacheSize) Sets the number of 512-byte cache buffers to be used for the compression scratch file (for the current CDF).
void	selectDecoding (long decoding) Defines the CDF decoding method to be used for this CDF.
void	selectNegtoPosfp0 (long negtoPosfp0) Defines whether to translate -0.0 to 0.0 for reading or writing.
void	selectReadOnlyMode (long readOnly) Sets the desired read-only mode.

void	<code>selectStageCacheSize</code> (long stageCacheSize) Sets the number of 512-byte cache buffers to be used for the staging scratch file (for the current CDF).
void	<code>setChecksum</code> (long checksum) Specifies the checksum option applied to the CDF.
void	<code>setCompression</code> (long cType, long[] cParms) Sets the compression type and parameters for this CDF.
void	<code>setDelegate</code> (CDFDelegate delegate) This is a placeholder for future expansions/extensions.
void	<code>setEncoding</code> (long encoding) Defines the encoding method to be used for this CDF.
static void	<code>setFileBackward</code> (long flag) Sets the file backward flag so that when a new CDF file is created, it will be created in either in the older V2.7 version or the current library version, i.e., V3.*.
void	<code>setFormat</code> (long format) Specifies the format of this CDF.
void	<code>setInfoWarningOff</code> () Sets the informational (status code < 0) or warning messages (status code between -1 and -2000) coming from the CDF JNI/library function off.
void	<code>setInfoWarningOn</code> () Sets the informational (status code < 0) or warning messages (status code between -1 and -2000) coming from the CDF JNI/library function on.
void	<code>setLeapSecondLastUpdated</code> (long lastUpdated) Set the leap second last updated for this CDF.
void	<code>setMajority</code> (long majority) Sets the variable majority for this CDF.
static void	<code>setValidate</code> (long mode) Sets the file validation mode so that when a CDF file is open, it will be validated accordingly.
java.lang.String	<code>toString</code> () Gets the name of this CDF.
long	<code>verifyChecksum</code> () Verifies the data integrity of the CDF file from its checksum.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, wait, wait, wait

Method Detail

create

```
public static CDF create(java.lang.String path)
    throws CDFException
```

Creates a CDF file in the current directory. By default, a single-file CDF is created and it's the preferred format. However, if the user wants to create a multi-file CDF, its file format needs to be changed as following:

```
CDF cdf = null;
cdf = CDF.create("test");
cdf.setFormat(MULTI_FILE);
```

For the single-file format CDF, the above example would have created a single-file CDF called 'test.cdf'. See Chapter 1 of the CDF

User's Guide for more information about the file format options. **Notes:**

The newly created file will be of the same version as the CDF library, as a V3.*. To create a backward file, i.e., V2.7, there are two options that can be used. Use the static method `setFileBackward` to set the backward flag. The following example will create backward file for `test1.cdf` and `test2.cdf`, but a V3.* file for `test3.cdf`.

```
CDF cdf1, cdf2, cdf3;
CDF.setFileBackward(BACKWARDFILEon);
cdf1 = CDF.create("test1");
cdf2 = CDF.create("test2");
CDF.setFileBackward(BACKWARDFILEoff);
cdf3 = CDF.create("test3");
```

Alternatively, use an environment variable to control the backward file creation. The environment variable `CDF_FILEBACKWARD` on Unix or Windows or `CDF$FILEBACKWARD` on Open/VMS is used. When it is set to `TRUE`, a V2.7 file(s) will be created automatically. In the following example, both `test1.cdf` and `test2.cdf` will be V2.7 if environment variable `CDF_FILEBACKWARD` (or `CDF$FILEBACKWARD`) is `TRUE`.

```
CDF cdf1 = CDF.create("test1");
CDF cdf2 = CDF.create("test2");
```

Parameters:

`path` - the full pathname of the CDF file to be created

Returns:

the newly created CDF file/object

Throws:

`CDFException` - if there was a problem creating a CDF file

create

```
public static CDF create(java.lang.String path,
    int flag)
    throws CDFException
```

Deprecated. Use `setFileBackward(long)` method to set the file backward flag and `create(String)` to create file instead.

Creates a CDF file in the current directory. By default, a single-file CDF is created and it's the preferred format. The following example will create a CDF file:

```
CDF cdf = null;
cdf = CDF.create("test", 0);
```

For the single-file format CDF, the above example would have created a single-file CDF called 'test.cdf'. The newly created file will be of the same version as the CDF library, To create a backward file, i.e., V2.7, use a differnt argument for the flag.

```
CDF cdf;
cdf = CDF.create("test", 1);
```

Parameters:

`path` - the full pathname of the CDF file to be created

`flag` - the file backward indicator flag. Passed 0 if a file of current library version is to be created. Not 0 if a backward is to be created.

Returns:

the newly created CDF file/object

Throws:

`CDFException` - if there was a problem creating a CDF file

open

```
public static CDF open(java.lang.String path)
    throws CDFException
```

Open a CDF file for read/write, the default mode for opening a CDF. If the user wants only to read the file, the file must be opened in read-only mode as following:

```
CDF cdf = CDF.open(fileName, READONLYon);
```

Note: Opening a file with read/write mode will cause the checksum signature to be recomputed every time the file is closed. (NEW) Each open CDF file is subjected to a default data validating process (some overheads) that will perform sanity checks. To overwrite it, you can use one of two ways: 1) Use the CDF static method setValidate before calling the open method: CDF.setValidate (VALIDATEFILEoff); 2) Set the environment variable CDF_VALIDATE (CDF\$VALIDATE on VMS) to no

Parameters:

path - the full pathname of the CDF file to be opened

Returns:

the CDF object that represents the CDF file the user requested for opening

Throws:

[CDFException](#) - if there was a major problem opening a file Not always that a CDFException will be thrown. It is good practice to check the status from this open method to see if some others problems, e.g., invalid checksum is being detected, may occur. Use something like the followings

```
if (cdf.getStatus() != CDF_OK)
{
    if (cdf.getStatus() == CHECKSUM_ERROR)
        .....
}
```

where cdf is the returned object from the open method. It is up to each individual to determine whether to continue to use a CDF file with an error like checksum.

open

```
public static CDF open(java.lang.String path,
    long readOnly)
    throws CDFException
```

Open a CDF file. A CDF file can be opened in read-only or read/write mode. If a file is opened in read-only mode, the user can only read values out of the file. Any operation other than reading data will throw a CDFException. If the user wants to modify the contents of a file, the file must be opened in read/write mode as following:

```
CDF cdf = CDF.open(fileName, READONLYoff);
```

Parameters:

path - the full pathname of the CDF file to be opened

readOnly - read-only flag that should be one the following:

- READONLYon - opens the file in read only mode.
- READONLYoff - opens the file in read/write mode

Returns:

the CDF object that represents the CDF file the user requested for opening

Throws:

`CDFException` - if there was a major problem opening a file Not always that a `CDFException` will be thrown. It is good practice to check the status from this open method to see if some others problems, e.g., invalid checksum is being detected, may occur. Use something like the followings

```
if (cdf.getStatus() != CDF_OK)
{
    if (cdf.getStatus() == CHECKSUM_ERROR)
        .....
}
```

where `cdf` is the returned object from the open method. It is up to each individual to determine whether to continue to use a CDF file with an error like checksum.

getLibraryVersion

```
public static java.lang.String getLibraryVersion()
                                throws CDFException
```

Retrieve library version/release/increment/sub_increment information associated with the CDF library.

Returns:

The library version in string

Throws:

`CDFException` - If there was a problem retrieving the information associated with this CDF file

getLibraryCopyright

```
public static java.lang.String getLibraryCopyright()
                                throws CDFException
```

Retrieve library copyright information associated with the CDF library.

Returns:

the string for CDF copy right note

Throws:

`CDFException` - If there was a problem retrieving the information associated with this CDF file

close

```
public void close()
            throws CDFException
```

Closes this CDF file. It is essential that a CDF that has been created or modified by an application be closed before the program exits. If the CDF is not closed, the file will be corrupted and unreadable. This is because the cache buffers maintained by the CDF library will not have been written to the CDF file(s).

The following example closes a CDF file:

```
cdf.close();
```

Throws:

`CDFException` - if there was a problem closing the CDF file

getID

```
public long getID()
```

Gets the id of this CDF file.

Returns:

the id of this CDF file

getEncoding

```
public long getEncoding()
```

Gets the encoding method defined for this CDF.

Returns:

The encoding method defined for this CDF file. One of the encoding methods described in the setEncoding method is returned.

setEncoding

```
public void setEncoding(long encoding)
    throws CDFException
```

Defines the encoding method to be used for this CDF. A CDF's data encoding affects how its attribute entry and variable data values are stored. By default, attribute entry and variable data values passed into the CDF library are always stored using the host machine's native encoding. For example, if a CDF file is created without specifying what encoding method should be used on a IBM PC, the IBMPC_ENCODING method is used. This method becomes useful if someone wants to create a CDF file that will be read on a machine that is different from the machine the CDF file was created. A CDF with any of the supported encodings may be read from and written to any supported computer. See section 2.2.8 of the CDF User's Guide for a detailed description of the encodings listed below.

Parameters:

encoding - the encoding method to be used for this CDF that should be one of the following:

- HOST_ENCODING
- NETWORK_ENCODING
- SUN_ENCODING
- VAX_ENCODING
- DECSTATION_ENCODING
- SGI_ENCODING
- IBMPC_ENCODING
- IBMRS_ENCODING
- PPC_ENCODING
- HP_ENCODING
- NeXT_ENCODING
- ALPHAOSF1_ENCODING
- ALPHAVMSd_ENCODING
- ALPHAVMSg_ENCODING
- ALPHAVMSi_ENCODING

Throws:

CDFException - if there was a problem setting the requested encoding method

selectDecoding

```
public void selectDecoding(long decoding)
    throws CDFException
```

Defines the CDF decoding method to be used for this CDF. A CDF's decoding affects how its attribute entry and variable data values are passed out to a calling application. The decoding for a CDF may be selected any number of times while the CDF is open. Selecting a decoding does not affect how the values are store in the CDF file(s) - only how the values are decoded by the CDF library.

Parameters:

`decoding` - the decoding method to be used for this CDF that should be one of the following:

- HOST_DECODING - this is the default decoding
- NETWORK_DECODING
- SUN_DECODING
- VAX_DECODING
- DECSTATION_DECODING
- SGI_DECODING
- IBMPC_DECODING
- IBMRS_DECODING
- PPC_DECODING
- HP_DECODING
- NeXT_DECODING
- ALPHAOSF1_DECODING
- ALPHAVMSd_DECODING
- ALPHAVMSg_DECODING
- ALPHAVMSi_DECODING

Throws:

`CDFException` - if there was a problem selecting the requested decoding method

confirmDecoding

```
public long confirmDecoding()
    throws CDFException
```

Gets the CDF decoding method defined for this CDF.

Returns:

The decoding method set for this CDF file. One of the decoding methods defined in the `selectDecoding` method is returned.

Throws:

`CDFException` - if there was a problem getting the decoding method set for this CDF file

selectCDFCacheSize

```
public void selectCDFCacheSize(long cacheSize)
    throws CDFException
```

Defines the number of 512-byte cache buffers to be used for the dotCDF file (for the current CDF). The concepts Chapter in the CDF User's Guide describes the caching scheme used by the CDF library.

Parameters:

`cacheSize` - the number of 512-byte cache buffers

Throws:

`CDFException` - if there was a problem setting the CDF cache size

confirmCDFCacheSize

```
public long confirmCDFCacheSize()
    throws CDFException
```

Gets the CDF cache size (the number of 512-byte cache buffers) set for this CDF.

Returns:

the number of 512-byte cache buffers set for this CDF

Throws:

`CDFException` - if there was a problem getting the CDF cache size

selectNegtoPosfp0

```
public void selectNegtoPosfp0(long negtoPosfp0)
    throws CDFException
```

Defines whether to translate -0.0 to 0.0 for reading or writing. Negative floating-point zero (-0.0) is legal on computers that use IEEE 754 floating-point representation (e.g. most UNIX-based computers and the PC) but is illegal on VAXes and DEC alphas running OpenVMS operating system. If this mode disabled, a warning (NEGATIVE_FP_ZERO) is returned when -0.0 is read from a CDF (and the decoding is that of a VAX or DEC Alpha running OpenVMS) or written to a CDF (and the encoding is that of a VAX or DEC Alpha running i OpenVMS).

Parameters:

`negtoPosfp0` - flag to translate -0.0 to 0.0 (NEGtoPOSfp0on = on, NEGtoPOSfp0off = off)

Throws:

`CDFException` - if there was a problem setting the -0.0 to 0.0 translation flag

confirmNegtoPosfp0

```
public long confirmNegtoPosfp0()
    throws CDFException
```

Gets the -0.0 to 0.0 translation flag set for this CDF.

Returns:

flag to translate -0.0 to 0.0 (NEGtoPOSfp0on = on, NEGtoPOSfp0off = off)

Throws:

`CDFException` - if there was a problem getting the value of the -0.0 to 0.0 translation flag

getFormat

```
public long getFormat()
```

Gets the CDF format defined for this CDF.

Returns:

the format of this CDF (SINGLE_FILE = single-file CDF, MULTI_FILE = multi-file CDF)

setFormat

```
public void setFormat(long format)
    throws CDFException
```

Specifies the format of this CDF. A CDF's format can't be changed once any variables are created. See section 1.4 of the CDF User's Guide for more detailed information about the file format options.

Parameters:

`format` - the CDF file format to be used that should be one of the following:

- `SINGLE_FILE` - This is the default. The CDF consists of only one file.
- `MULTI_FILE` - The CDF consists of one header file for control and attribute data and one additional file for each variable in the CDF.

Throws:

`CDFException` - if there was a problem setting a file format

getVersion

```
public java.lang.String getVersion()
```

Gets the CDF library version that was used to create this CDF (e.g. 2.6.7, etc.).

Returns:

the CDF library version number that was used to create this CDF

getMajority

```
public long getMajority()
```

Gets the variable majority defined for this CDF.

Returns:

the variable majority defined for this CDF (`ROW_MAJOR` = row major, `COLUMN_MAJOR` = column major)

setMajority

```
public void setMajority(long majority)
    throws CDFException
```

Sets the variable majority for this CDF. The variable majority of a CDF describes how variable values within each variable array (record) are stored. Each variable in a CDF has the same majority.

Parameters:

`majority` - The majority to be used in storing data (`ROW_MAJOR` = row major, `COLUMN_MAJOR` = column major)

Throws:

`CDFException` - if a problem occurred in setting a majority

getNumAttrs

```
public long getNumAttrrs()
```

Gets the total number of global and variable attributes in this CDF.

Returns:

the total number of global and variable attributes in this CDF

getNumGattrrs

```
public long getNumGattrrs()
```

Gets the number of global attributes in this CDF.

Returns:

the number of global attributes in this CDF file

getNumVattrrs

```
public long getNumVattrrs()
```

Gets the number of variable attributes in this CDF. Since r variables are not supported by the CDF Java APIs, the number of z variables is always returned.

Returns:

the number of variable attributes in this CDF file

getNumRvars

```
public long getNumRvars()
```

Gets the number of r variables. Zero is returned since r variables are not supported. Z variables can do everything r variables can do plus more.

Returns:

the number of r variables in this CDF file

getNumZvars

```
public long getNumZvars()
```

Gets the number of z variables in this CDF file.

Returns:

the number of z variables in this CDF file

getCopyright

```
public java.lang.String getCopyright()
```

Gets the CDF copyright statement for this CDF.

Returns:

the CDF copyright statement

selectReadOnlyMode

```
public void selectReadOnlyMode(long readOnly)
                             throws CDFException
```

Sets the desired read-only mode. See the description of the read-only flag defined in the open method in this class for details. Caveat: Arbitrary changing the read-only mode to READONLYon while doing writing/updating will cause a problem to the file if the checksum bit is turned on (as the checksum signature may not get updated and a warning for data integrity will be issued when the file is open later).

Parameters:

readOnly - read-only flag (READONLYon = on, READONLYoff = off)

Throws:

`CDFException` - if a problem occurred in setting a flag

confirmReadOnlyMode

```
public long confirmReadOnlyMode()
                             throws CDFException
```

Gets the value of the read-only mode flag set for this CDF file.

Returns:

read-only flag (READONLYon = on, READONLYoff = off)

Throws:

`CDFException` - if a problem occurred in getting the value of the read-only flag set for this CDF file

getCompressionType

```
public long getCompressionType()
```

Gets the compression type set for this CDF.

Returns:

the compression type set for this CDF - one of the following is returned:

- NO_COMPRESSION - no compression
- RLE_COMPRESSION - Run-length compression
- HUFF_COMPRESSION - Huffman compression
- AHUFF_COMPRESSION - Adaptive Huffman compression
- GZIP_COMPRESSION - Gnu's "zip" compression

getCompressionPct

```
public long getCompressionPct()
```

Gets the compression percentage set for this CDF.

Returns:

the compression percentage set for this CDF.

getCompressionParms

```
public long[] getCompressionParms()
```

Gets the compression parameters set for this CDF. See the description of the setCompression method in this class for more information.

Returns:

the compression parameter set for this CDF

setCompression

```
public void setCompression(long cType,
                           long[] cParms)
    throws CDFException
```

Sets the compression type and parameters for this CDF.

Parameters:

`cType` - the compression type to be applied to this CDF that should be one of the following:

- NO_COMPRESSION - no compression
- RLE_COMPRESSION - Run-length compression. Currently, only the run-length encoding of zeros is supported. The compression parameter must be set to RLE_OF_ZEROS.
- HUFF_COMPRESSION - Huffman compression. Currently, only optimal encoding trees are supported. The compression parameter must be set to OPTIMAL_ENCODING_TREES.
- AHUFF_COMPRESSION - Adaptive Huffman compression. Currently, only optimal encoding trees are supported. The compression parameter must be set to OPTIMAL_ENCODING_TREES.
- GZIP_COMPRESSION - Gnu's "zip" compression. The compression parameter may range from 1 to 9. 1 provides the least compression and requires less execution time. 9 provides the most compression but requires the most execution time.

`cParms` - Compression parameter. There is only one parameter for all the compression methods described above.

Throws:

`CDFException` - if a problem occurred in setting the compression type and parameters

getCompression

```
public java.lang.String getCompression()
    throws CDFException
```

Gets the string representation of the compression type and parameters defined for this CDF.

Returns:

the string representation of the compression type and parameters (e.g. GZIP.9, RLE.0, etc.) defined for this CDF

Throws:

`CDFException` - if a problem occurred in getting the compression type and parameters set for this CDF

confirmzMode

```
public long confirmzMode()  
    throws CDFException
```

Gets the zMode set for this CDF.

Returns:

'zMODEon2' is always returned since it is the only mode supported by the CDF Java APIs.

Throws:

CDFException - if a problem occurred in getting the zmode set for this CDF file

selectCompressCacheSize

```
public void selectCompressCacheSize(long compressCacheSize)  
    throws CDFException
```

Sets the number of 512-byte cache buffers to be used for the compression scratch file (for the current CDF). The Concepts Chapter in the CDF User's Guide describes the caching scheme used by the CDF library.

Parameters:

compressCacheSize - the number of 512-byte cache buffers to be used

Throws:

CDFException - if a problem occurs in setting the cache size

confirmCompressCacheSize

```
public long confirmCompressCacheSize()  
    throws CDFException
```

Gets the number of 512-byte cache buffers being used for the compression scratch file (for the current CDF).

Returns:

the number of 512-byte cache buffers being used

Throws:

CDFException - if a problem occurs in getting the cache size defined

selectStageCacheSize

```
public void selectStageCacheSize(long stageCacheSize)  
    throws CDFException
```

Sets the number of 512-byte cache buffers to be used for the staging scratch file (for the current CDF). The Concepts Chapter in the CDF User's Guide describes the caching scheme used by the CDF library.

Parameters:

stageCacheSize - the Number of cache buffers to be used

Throws:

CDFException - if a problem occurs in setting the cache size

confirmStageCacheSize

```
public long confirmStageCacheSize()  
    throws CDFException
```

Gets the number of 512-byte cache buffers defined for the staging scratch file.

Returns:

the number of 512-byte cache buffers defined for the staging scratch file

Throws:

`CDFException` - if a problem occurs in getting the number of cache buffers defined for the staging scratch file

getName

```
public java.lang.String getName()
```

Gets the name of this CDF.

Specified by:

`getName` in interface `CDFObject`

Returns:

the name of this CDF

rename

```
public void rename(java.lang.String path)
```

Renames the current CDF. It's here because `CDF.java` implements the `CDFObject` interface that defines three methods: `rename`, `delete`, `getName`. This method doesn't do anything now, but it will be refined to rename a single-CDF and multi-CDF files in the future.

Specified by:

`rename` in interface `CDFObject`

Parameters:

`path` - the new CDF name to be renamed to

delete

```
public void delete()  
    throws CDFException
```

Deletes this CDF file.

Specified by:

`delete` in interface `CDFObject`

Throws:

`CDFException` - if a problem occurs in deleting this CDF file

save

```
public void save()
```

throws `CDFException`

Saves this CDF file without closing. There are times the users will have to save the contents of a CDF file before some operations can be performed. For example, a CDF file must be saved first before records can be deleted properly for variables that are defined to have sparse and/or compressed records.

Throws:

`CDFException` - if there was a problem saving the contents of this CDF file

setFileBackward

```
public static void setFileBackward(long flag)
                        throws CDFException
```

Sets the file backward flag so that when a new CDF file is created, it will be created in either in the older V2.7 version or the current library version, i.e., V3.*. It only works for V3.* library. Setting this flag will overwrite environment variable CDF_FILEBACKWARD (or CDF\$FILEBACKWARD on OpenVMS) if it is set. All CDF files created after this static method call will be affected.

Parameters:

`flag` - The flag indicates whether to create a new CDF(s) in the backward version. BACKWARDFILEon means a backward file(s) is to be created and BACKWARDFILEoff means a V3.* file(s) is to be created.

Throws:

`CDFException` - if there was a problem

getFileBackward

```
public static boolean getFileBackward()
```

Gets the file backward flag.

Returns:

The flag indicating whether the CDF file was created in the older V2.7 version. It is only applicable for V3.* library. Returns true if backward files are to be created, false otherwise.

getFileBackwardEnvVar

```
public static int getFileBackwardEnvVar()
                        throws CDFException
```

Gets the value of the CDF_FILEBACKWARD environment variable.

Returns:

1 if the environment variable is set to true, 0 if not set or set to anything else.

Throws:

`CDFException` - if there was a problem

getLeapSecondsTableEnvVar

```
public static java.lang.String getLeapSecondsTableEnvVar()
                        throws CDFException
```

Gets the the CDF_LEAPSECONDSTABLE (or CDF\$LEAPSECONDSTABLE on VMS) environment variable.

Returns:

the string the environment variable is set to, null if not set

Throws:

`CDFException` - if there was a problem

getChecksumEnvVar

```
public static long getChecksumEnvVar()
                    throws CDFException
```

Gets the value of the CDF_CHECKSUM environment variable.

Returns:

1 if the environment variable is set to MD5, 0 if not set or set to anything else.

Throws:

`CDFException` - if there was a problem

setValidate

```
public static void setValidate(long mode)
                    throws CDFException
```

Sets the file validation mode so that when a CDF file is open, it will be validated accordingly. Setting this flag will overwrite environment variable CDF_VALIDATE (or CDF\$VALIDATE on OpenVMS) if it is set. If none is set, the default will have the files validated when open. All CDF files open after this static method call will be applied.

Parameters:

`mode` - The mode indicates whether to validate CDF(s) while open. **VALIDATEFILEon** means all files are subjected to be validated. **VALIDATEFILEoff** means no data validation will be performed.

Throws:

`CDFException` - if there was a problem

getValidate

```
public static boolean getValidate()
```

Gets the file validation mode.

Returns:

The mode indicating whether the CDF file is to be validated when it is open. Returns true if it will be validated, false otherwise.

getStatus

```
public long getStatus()
```

Gets the status of the most recent CDF JNI/library function call. This value can be examined and appropriate action can be taken.

The following example sends a signal to the JNI code to write a single data to the current CDF. JNI in turn performs the requested

operation. It then checks to see whether the requested operation was successfully performed or not.

```
variable.putSingleData(recNum, dimIndicies, data);
long status = cdf.getStatus();
if (status != CDF_OK) {
    String statusText = CDF.getStatusText(status);
    System.out.println ("status = "+statusText);
}
```

Returns:

the status of the most recent CDF JNI/library function call

getStatusText

```
public static java.lang.String getStatusText(long statusCode)
```

Gets the status text of the most recent CDF JNI/library function call.

The following example shows how to obtain the text representation of the status code returned from the getStatus method:

```
long status = cdf.getStatus();
if (status != CDF_OK) {
    String statusText = CDF.getStatusText(status);
    System.out.println ("status = "+statusText);
}
```

Parameters:

statusCode - status code to be translated

Returns:

the string representation of the passed status code

setInfoWarningOff

```
public void setInfoWarningOff()
```

Sets the informational (status code < 0) or warning messages (status code between -1 and -2000) coming from the CDF JNI/library function off. This is the default when a file is opened or created.

setInfoWarningOn

```
public void setInfoWarningOn()
```

Sets the informational (status code < 0) or warning messages (status code between -1 and -2000) coming from the CDF JNI/library function on.

toString

```
public java.lang.String toString()
```

Gets the name of this CDF.

Overrides:

toString in class java.lang.Object

Returns:

the name of this CDF

finalize

```
public void finalize()  
    throws java.lang.Throwable
```

Do the necessary cleanup when garbage collector reaps it.

Overrides:

finalize in class `java.lang.Object`

Throws:

`java.lang.Throwable` - if there was a problem doing cleanup

getDelegate

```
public CDFDelegate getDelegate()
```

This is a placeholder for future expansions/extensions.

Returns:

CDFDelegate object

setDelegate

```
public void setDelegate(CDFDelegate delegate)
```

This is a placeholder for future expansions/extensions.

Parameters:

`delegate` - The CDFDelegate executing the command

getAttributeID

```
public long getAttributeID(java.lang.String attrName)
```

Gets the id of the given attribute.

Parameters:

`attrName` - the name of the attribute to check

Returns:

the id of the named attribute if it exists, -1 otherwise

getAttribute

```
public Attribute getAttribute(long attrNum)  
    throws CDFException
```

Gets the attribute for the given attribute number.

Note: The attrNum may not necessarily correspond to the attribute number stored in the CDF file.

Parameters:

attrNum - the attribute number to get

Returns:

the Attribute object that corresponds to the requested attribute number

Throws:

`CDFException` - if the supplied attribute number does not exist

getAttribute

```
public Attribute getAttribute(java.lang.String attrName)
                        throws CDFException
```

Gets the attribute for the given attribute name.

The following example retrieves the attribute named "ValidMin":

```
Attribute validMin = cdf.getAttribute("ValidMin");
```

Parameters:

attrName - the name of the attribute to get

Returns:

the Attribute object that corresponds to the requested attribute name

Throws:

`CDFException` - if the supplied attribute name does not exist

getAttributes

```
public java.util.Vector getAttributes()
```

Gets all the global and variable attributes defined for this CDF. The following example retrieves all the global and variable attributes:

```
Vector attr = cdf.getAttributes();
```

Returns:

a vector that contains the global and variable attributes defined in this CDF

getGlobalAttributes

```
public java.util.Vector getGlobalAttributes()
```

Gets the global attributes defined for this CDF.

Returns:

A vector that contains the global attributes defined in this CDF

readCDFInfo

```
public java.util.Map readCDFInfo()
```

Gets the basic information about this CDF. The returned map has the following form: "CDFInfo": { "Format": "SINGLE", "Version": "3.8.0", "FileName": "test", "NumVars": 21, "Majority": "ROW" }

Returns:

A Map object that contains the basic information about the CDF.

readCDFGlobalAttributes

```
public java.util.Map readCDFGlobalAttributes()
```

Gets the global attributes and their entries defined for this CDF. Note: Each attribute's entry, an object, can be a single data or an array of values. The epoch data type into encoded date/time string.

Returns:

A Map object that contains the global attributes, as the keys, and entries, as the values. All are of object type. Each entry is also a map, which consists of entry number as the key and entry data as the value.

readCDFGlobalAttributes

```
public java.util.Map readCDFGlobalAttributes(boolean encoding)
```

Gets the global attributes and their entries defined for this CDF. Note: Each attribute's entry, an object, can be a single data or an array of values. The returned map has the following form: "GLOBAL_ATTR_NAME1": { "0": ..., "1": ... }, "GLOBAL_ATTR_NAME2": { "0": ..., "1": [4294967295, 2147483648] } "GLOBAL_ATTR_NAME3": { "0": ..., "1": ..., ... { }

Parameters:

encoding - A true/false flag to indicate whether to convert epoch data type into encoded date/time string.

Returns:

A Map object that contains the global attributes, as the keys, and entries, as the values. All are of object type. Each entry is also a map, which consists of entry number as the key and entry data as the value.

readCDFGlobalAttributes

```
public java.util.Map readCDFGlobalAttributes(java.lang.String attrName)
```

Gets a specified global attribute's entry(ies) defined for this CDF. Note: Each attribute's entry, an object, can be a single data or an array of values. The epoch data type into encoded date/time string.

Parameters:

attrName - A global attribute name

Returns:

A Map object that contains the global attributes, as the keys, and entries, as the values. All are of object type. Each entry is also a map, which consists of entry number as the key and entry data as the value.

readCDFGlobalAttributes

```
public java.util.Map readCDFGlobalAttributes(java.lang.String[] attrNames)
```

Gets a specified list of global attributes and their entries defined for this CDF. Note: Each attribute's entry, an object, can be a single data or an array of values. The epoch data type into encoded date/time string.

Parameters:

`attrNames` - An array of global attribute names

Returns:

A Map object that contains the global attributes, as the keys, and entries, as the values. All are of object type. Each entry is also a map, which consists of entry number as the key and entry data as the value.

readCDFGlobalAttributes

```
public java.util.Map readCDFGlobalAttributes(long attrNum)
```

Gets a specified global attribute's entry(ies) defined for this CDF. Note: Each attribute's entry, an object, can be a single data or an array of values. The epoch data type into encoded date/time string.

Parameters:

`attrNum` - A global attribute number

Returns:

A Map object that contains the global attributes, as the keys, and entries, as the values. All are of object type. Each entry is also a map, which consists of entry number as the key and entry data as the value.

readCDFGlobalAttributes

```
public java.util.Map readCDFGlobalAttributes(long[] attrNums)
```

Gets a specified list of global attributes and their entries defined for this CDF. Note: Each attribute's entry, an object, can be a single data or an array of values. The epoch data type into encoded date/time string.

Parameters:

`attrNums` - An array of global attribute numbers

Returns:

A Map object that contains the global attributes, as the keys, and entries, as the values. All are of object type. Each entry is also a map, which consists of entry number as the key and entry data as the value.

readCDFGlobalAttributes

```
public java.util.Map readCDFGlobalAttributes(java.lang.Object attrs,
                                             boolean encoding)
```

Gets a list of specified global attributes and their entries defined for this CDF. Note: Each attribute's entry, an object, can be a single data or an array of values.

Parameters:

`attrs` - An array of attribute names of numbers

`encoding` - A true/false flag to indicate whether to convert epoch data type into encoded date/time string.

Returns:

A Map object that contains the global attributes, as the keys, and entries, as the values. All are of object type. Each entry is also a map, which consists of entry number as the key and entry data as the value.

readCDFNoEntryAttributes

```
public java.util.Map readCDFNoEntryAttributes()
```

Gets a map of global attributes and variable attributes with no entry data.

Returns:

A Map object that contains up to two elements, one for global attributes and one for variable attributes. The value is the name(s) of the attributes() that has no entry data.

readCDFVariables

```
public java.util.Map readCDFVariables()
                        throws CDFException
```

Reads all variables' information in the CDF. The returned map has the following form: "Variables": { "Var_Name1": { "VarSpec": { "NumElements": 1, ... } "VarMetaData": { "VALIDMIN": 0 ... } "VarData": { ... } } "Var_Name2": { "VarSpec": { "NumElements": 1, ... } "VarMetaData": { "VALIDMIN": 0 ... } "VarData": { ... } } ... }

Returns:

A Map object that contains the basic variable information, its metadata and data from all variables

Throws:

`CDFException` - If there was a problem retrieving the variable information from this CDF file

readCDFVariablesSpec

```
public java.util.Map readCDFVariablesSpec()
                        throws CDFException
```

Reads all variables' specifications in the CDF. The returned map has the following form: "Variables": { "Var_Name1": { "VarSpec": { "NumElements": 1, "PadValue": "0000-01-01T00:00:00.000", "DataType": "CDF_EPOCH", "NumDims": 0 ... } } "Var_Name2": { "VarSpec": { "NumElements": 1, "PadValue": "0000-01-01T00:00:00.000", "DataType": "CDF_EPOCH", "NumDims": 0 ... } } ... }

Returns:

A Map object that contains the basic information for all variables

Throws:

`CDFException` - If there was a problem retrieving the variable information from this CDF file

readCDFVariablesMetaData

```
public java.util.Map readCDFVariablesMetaData()
                        throws CDFException
```

Reads all variables' metadata in the CDF. The returned map has the following form: "Variables": { "Var_Name1": { "VarMetaData": { "VALIDMIN": "2010-01-01T00:00:00.000", "VALIMAX": ... } } "Var_Name2": { "VarMetaData": { "VALIDMIN": 1, "VALIMAX": 10, ... } } ... }

Returns:

A Map object that contains the metadata for all variables

Throws:

`CDFException` - If there was a problem retrieving the variable information from this CDF file

readCDFVariablesData

```
public java.util.Map readCDFVariablesData()
                        throws CDFException
```

Reads all variables' data in the CDF. The returned map has the following form: "Variables": { "Var_Name1": { "VarData": { } } "Var_Name2": { "VarData": { } } ... }

Returns:

A Map object that contains the data from all variables

Throws:

`CDFException` - If there was a problem retrieving the variable information from this CDF file

readCDF

```
public java.util.Map readCDF()
```

Gets the full CDF information. Note: Each attribute's entry, an object, can be a single data or an array of values. CDF Epoch type data will be encoded in date/time string.

Returns:

A Map object that contains the CDF basic information, its global attributes and variables' specification, metadata and data.

readCDF

```
public java.util.Map readCDF(boolean encoding)
```

Gets the full CDF information. Note: Each attribute's entry, an object, can be a single data or an array of values. CDF Epoch type data will be encoded in date/time string.

Parameters:

`encoding` - A true/false flag indicates whether to encode epoch data type from metadata to date/time string.

Returns:

A Map object that contains the CDF basic information, its global attributes and variables' specification, metadata and data.

readCDF

```
public java.util.Map readCDF(boolean encoding,
                             boolean basic,
                             boolean globals,
                             boolean varinfo)
```

Gets the specified information from a CDF. Note: Each attribute's entry, an object, can be a single data or an array of values.

Parameters:

`encoding` - A true/false flag indicates whether to encode epoch data type from metadata to date/time string.

basic - A true/false flag indicates whether to read the basic information about the CDF

globals - A true/false flag indicates whether to read the global attributes in the CDF

varinfo - A true/false flag indicates whether to read each variable's information.

Returns:

A Map object that contains the CDF basic information, its global attributes and/or all variables' specification, metadata and data.

readCDF

```
public java.util.Map readCDF(boolean encoding,
                             boolean basic,
                             boolean globals,
                             boolean varinfo,
                             boolean varmeta,
                             boolean vardata)
```

Gets the specified information from a CDF. Note: Each attribute's entry, an object, can be a single data or an array of values.

Parameters:

encoding - A true/false flag indicates whether to encode epoch data type from metadata to date/time string.

basic - A true/false flag indicates whether to read the basic information about the CDF

globals - A true/false flag indicates whether to read the global attributes in the CDF

varinfo - A true/false flag indicates whether to read each variable's basic information.

varmeta - A true/false flag indicates whether to read each variable's metadata.

vardata - A true/false flag indicates whether to read each variable's data.

Returns:

A Map object that contains the CDF basic information, its global attributes and all variables' metadata and data.

readCDF

```
public java.util.Map readCDF(boolean encoding,
                             boolean basic,
                             boolean globals,
                             boolean varinfo,
                             boolean varmeta,
                             boolean vardata,
                             boolean noentry)
```

Gets the specified information from a CDF. Note: Each attribute's entry, an object, can be a single data or an array of values.

```
Map acdf = cdf.readCDF(true, true, true, true, true, true);
for (Object key : acdf.keySet()) {
    // May contain 3 key/value pairs: keys include "CDFinfo",
    // "GlobalAttributes" and "Variables".

    // Get key: "Variables"'s value -- a Map
    if (((String)key).equals("Variables")) {
        Map vars = (Map) acdf.get(key);
        if (vars == null) continue;
        for (Object varName : vars.keySet()) {
            // each key/value pair is variable name and its info
            System.out.println("** Variable: "+varName);
            Map var = (Map) vars.get(varName);
            // Each variable's info includes upto 3 key/value mappings:
            // "VarDef", "VarMetaData" and "VarData".
```

```
for (Object key1 : var.keySet()) {
    if (key1.equals("VarSpec")) {
        // Key: "VarSpec" has Variable specification
        Map specs = var.get(key1);
        for (Object key2 : specs.keySet()) {
            ....
        }
    } else if (key1.equals("VarMetaData")) {
        // Key: "VarMeataData" has variable metadata
        Map meta = var.get(key1);
        for (Object key2 : meta.keySet()) {
            ....
        }
    } else if ((key1.equals("VarData")) {
        // Key: "VarData" has variable data
        Object data = var.get(key1);
        ....
    } else {
        error....
    }
}
} else { // other keys: "CDFinfo", "GloblaAttributes" and their values
    System.out.println(key + " - \n      " + acdf.get(key));
}
}
```

Parameters:

- encoding - A true/false flag indicates whether to encode epoch data type from metadata to date/time string.
- basic - A true/false flag indicates whether to read the basic information about the CDF
- globals - A true/false flag indicates whether to read the global attributes in the CDF
- varinfo - A true/false flag indicates whether to read each variable's basic information.
- varmeta - A true/false flag indicates whether to read each variable's metadata.
- vardata - A true/false flag indicates whether to read each variable's data.
- noentry - A true/false flag indicates whether to collect attributes that have no entries

Returns:

A Map object that contains the CDF basic information, its global attributes and all variables' metadata and data.

getVariableAttributes

```
public java.util.Vector getVariableAttributes()
```

Gets the variable attributes defined for this CDF.

Returns:

A vector that contains the variable attributes defined in this CDF

getOrphanAttributes

```
public java.util.Vector getOrphanAttributes()
```

Gets the variable attributes defined for this CDF that are not associated with any variables.

Returns:

A vector that contains the empty variable attributes defined in this CDF.

getVariableID

```
public long getVariableID(java.lang.String varName)
```

Gets the ID of the given variable.

Parameters:

`varName` - the name of the variable to check

Returns:

-1 if the variable does not exist. The variable id if the variable does exist.

getVariable

```
public Variable getVariable(long varNum)
    throws CDFException
```

Gets the variable object for the given variable number.

Parameters:

`varNum` - variable number from which the variable is retrieved

Returns:

the variable object that corresponds to the variable id

Throws:

`CDFException` - if the supplied variable number does not exist

getVariable

```
public Variable getVariable(java.lang.String varName)
    throws CDFException
```

Gets the variable object for the given variable name.

The following example retrieves a variable called "Longitude":

```
Variable longitude = cdf.getVariable("Longitude");
```

Parameters:

`varName` - the variable name to get

Returns:

the variable object that corresponds to the variable name

Throws:

`CDFException` - if the supplied variable name does not exist

getVariables

```
public java.util.Vector getVariables()
```

Gets the z variables defined for this CDF.

Note: Since all CDFs opened or created with the CDFJava APIs are placed into zMODE 2, there are no rVariables. All variables are treated as zVariables.

Returns:

a Vector containing all the z variables defined in this CDF

getNumVars

```
public long getNumVars()
```

Gets the number of Z variables defined for this CDF.

Returns:

the number of variables **Note:** Since all CDFs opened or created with the CDFJava APIs are placed into zMODE 2, there are no rVariables. All variables are treated as zVariables.

getRecord

```
public java.util.Vector getRecord(long recNum,
                                java.lang.String[] strVars)
                                throws CDFException
```

Retrieves a logical record that consists of single variable record(s) from an arbitrary number of CDF variables. This is a convenient method for reading one or more variables' data in a single call, instead of reading individual variable's data one at a time.

Parameters:

recNum - the record number to retrieve data from

strVars - the variable (array of variable names) to retrieve data from

Returns:

the requested record in a Java vector that contains the variables' data.

The first object in the vector corresponds to the first variable's record, the second object in the vector corresponds to the second variable's record, and so on.

Throws:

CDFException - if there was a problem getting a record

Note: A virtual variable record is returned if the given record does not exist. Any error during data retrieval will cause the process to stop (an exception thrown) and thus nothing (a null object) will be returned.

getRecord

```
public java.util.Vector getRecord(long recNum,
                                java.lang.String[] strVars,
                                long[] status)
                                throws CDFException
```

Retrieves a logical record that consists of single variable record(s) from an arbitrary number of CDF variables. This is a convenient method for reading one or more variables' data in a single call, instead of reading individual variable's data one at a time.

Parameters:

recNum - the record number to retrieve data from

`strVars` - the variable (array of variable names) to retrieve data from

`status` - the individual status (array of statuses) for reading each variable record

Returns:

the requested record in a Java vector that contains the variables' data.

The first object in the vector corresponds to the first variable's record, the second object in the vector corresponds to the second variable's record, and so on.

Throws:

`CDFException` - if there was a problem getting a record

Note: A virtual variable record is returned if the given record does not exist. Any error during data retrieval will cause the process to stop (an exception thrown) and thus nothing (a null object) will be returned.

The following example reads the 2nd record from Longitude and Temperature and prints their contents.

```
String[] strVars = {"Longitude", "Temperature"};
Vector record;
long[] status = new long[2];
record = cdf.getRecord(1L, strVars, status);

// Check the contents of the 'status' array - optional

// var: Longitude - data type: CDF UINT2, dimensionality: 1:[3]
System.out.print ("      2nd record of Longitude -- ");
for (int i=0; i < 3; i++)
    System.out.print (((int[])record.elementAt(0))[i]+" ");
System.out.println ("");

// var: Temperature -- data type: CDF REAL4, dimensionality: 1:[3]
System.out.print ("      2nd record of Temperature -- ");
for (int i=0; i < 3; i++)
    System.out.print (((float[])record.elementAt(1))[i]+" ");
System.out.println ("");
```

getRecord

```
public java.util.Vector getRecord(long recNum,
                                long[] varIDs)
    throws CDFException
```

Retrieves a logical record that consists of single variable record(s) from an arbitrary number of CDF variables. This is a convenient method for reading one or more variables' data in a single call, instead of reading individual variable's data one at a time.

Parameters:

`recNum` - the record number to retrieve data from

`varIDs` - the variable IDs (array of variable IDs) to retrieve data from

Returns:

the requested record in a Java vector that contains the variables' data.

The first object in the vector corresponds to the first variable's record, the second object in the vector corresponds to the second variable's record, and so on.

Throws:

`CDFException` - if there was a problem getting a record

Note: A virtual variable record is returned if the given record does not exist. Any error during data retrieval will cause the process to stop (an exception thrown) and thus nothing (a null object) will be returned.

getRecord

```
public java.util.Vector getRecord(long recNum,
                                long[] varIDs,
                                long[] status)
    throws CDFException
```

Retrieves a logical record that consists of single variable record(s) from an arbitrary number of CDF variables. This is a convenient method for reading one or more variables' data in a single call, instead of reading individual variable's data one at a time.

Parameters:

`recNum` - the record number to retrieve data from

`varIDs` - the variable IDs (array of variable IDs) to retrieve data from

`status` - the individual status (array of statuses) for reading each variable record

Returns:

the requested record in a Java vector that contains the variables' data.
The first object in the vector corresponds to the first variable's record, the second object in the vector corresponds to the second variable's record, and so on.

Throws:

`CDFException` - if there was a problem getting a record

Note: A virtual variable record is returned if the given record does not exist. Any error during data retrieval will cause the process to stop (an exception thrown) and thus nothing (a null object) will be returned.

The following example reads the 2nd record from Longitude (`varIDs[0]`) and Temperature (`varIDs[1]`) and prints their contents.

```
long[] varIDs = {2, 10};    // Obtained from Variable.getID()
Vector record;
long[] status = new long[2];
record = cdf.getRecord(1L, varIDs, status);

// Check the contents of the 'status' array - optional

// var: Longitude - data type: CDF_UINT2, dimensionality: 1:[3]
System.out.print ("    2nd record of Longitude -- ");
for (int i=0; i < 3; i++)
    System.out.print (((int[])record.elementAt(0))[i]+" ");
System.out.println ("");

// var: Temperature - data type: CDF_REAL4, dimensionality: 1:[3]
System.out.print ("    2nd record of Temperature -- ");
for (int i=0; i < 3; i++)
    System.out.print (((float[])record.elementAt(1))[i]+" ");
System.out.println ("");
```

putRecord

```
public void putRecord(long recNum,
                     java.lang.String[] strVars,
                     java.util.Vector myData)
    throws CDFException
```

Writes a logical record that consists of single variable record(s) from an arbitrary number of CDF variables. This is a convenient method for writing one or more variables' data in a single call, instead of writing individual variable's data one at a time.

Parameters:

`recNum` - the record number to write data to

`strVars` - the variable (array of variable names) to write data to

`myData` - a Java vector that contains the variables' data.

The first object in the vector corresponds to the first variable's record, the second object in the vector corresponds to the second variable's record, and so on.

Throws:

`CDFException` - if there was a problem writing the record for any of the variables

Note: Any error during the data writing will cause the process to stop (an exception thrown) and thus the operation will not be completed. Nothing will be done if the element counts of parameters don't match.

putRecord

```
public void putRecord(long recNum,
    java.lang.String[] strVars,
    java.util.Vector myData,
    long[] status)
    throws CDFException
```

Writes a logical record that consists of single variable record(s) from an arbitrary number of CDF variables. This is a convenient method for writing one or more variables' data in a single call, instead of writing individual variable's data one at a time.

Parameters:

`recNum` - the record number to write data to

`strVars` - the variable (array of variable names) to write data to

`myData` - a Java vector that contains the variables' data.

The first object in the vector corresponds to the first variable's record, the second object in the vector corresponds to the second variable's record, and so on.

`status` - the individual status (array of statuses) for writing each variable record

Throws:

`CDFException` - if there was a problem writing the record for any of the variables

Note: Any error during the data writing will cause the process to stop (an exception thrown) and thus the operation will not be completed. Nothing will be done if the element counts of parameters don't match.

The following example writes the contents of a record (which consists of two CDF variables - Longitude and Temperature) to record number 2.

```
String[] strVars = {"Longitude",    // variable names in CDF
    "Temperature"};

// Longitude -- data type: CDF_UINT2 dimensionality: 1:[3]
int[] longitude_data = {333, 444, 555};

// Temperature -- data type: CDF_FLOAT dimensionality: 0:[]
Float temperature_data = new Float((float) 999.99);

Vector record = new Vector();
record.add(longitude_data);
record.add(temperature_data);

cdf.putRecord(1L, strVars, record); // Write a record to record #2
```

putRecord

```
public void putRecord(long recNum,
    long[] varIDs,
    java.util.Vector myData)
    throws CDFException
```

Writes a logical record that consists of single variable record(s) from an arbitrary number of CDF variables. This is a convenient

method for writing one or more variables' data in a single call, instead of writing individual variable's data one at a time.

Parameters:

`recNum` - the record number to write data to

`varIDs` - the variable IDs (array of variable IDs) to write data to

`myData` - a Java vector that contains the variables' data.

The first object in the vector corresponds to the first variable's record, the second object in the vector corresponds to the second variable's record, and so on.

Throws:

`CDFException` - if there was a problem writing the record for any of the variables

Note: Any error during the data writing will cause the process to stop (an exception thrown) and thus the operation will not be completed. Nothing will be done if the element counts of parameters don't match.

putRecord

```
public void putRecord(long recNum,
                     long[] varIDs,
                     java.util.Vector myData,
                     long[] status)
    throws CDFException
```

Writes a logical record that consists of single variable record(s) from an arbitrary number of CDF variables. This is a convenient method for writing one or more variables' data in a single call, instead of writing individual variable's data one at a time.

Parameters:

`recNum` - the record number to write data to

`varIDs` - the variable IDs (array of variable IDs) to write data to

`myData` - a Java vector that contains the variables' data.

The first object in the vector corresponds to the first variable's record, the second object in the vector corresponds to the second variable's record, and so on.

`status` - the individual status (array of statuses) for writing each variable record

Throws:

`CDFException` - if there was a problem writing the record for any of the variables

Note: Any error during the data writing will cause the process to stop (an exception thrown) and thus the operation will not be completed. Nothing will be done if the element counts of parameters don't match.

The following example writes the contents of a record (which consists of two CDF variables - Longitude and Temperature) by using variable IDs (instead of variable names) to record number 2.

```
long[] varIDs = {3, 9};    // Can be obtained from variable.getID()

// Longitude -- data type: CDF_UINT2 dimensionality: 1:[3]
int[] longitude_data = {333, 444, 555};

// Temperature -- data type: CDF_FLOAT dimensionality: 0:[]
Float temperature_data = new Float((float)999.99);

Vector record = new Vector();
record.add(longitude_data);
record.add(temperature_data);

cdf.putRecord(1L, varIDs, record);    // Write a record to record #2
```

setChecksum

```
public void setChecksum(long checksum)
                    throws CDFException
```

Specifies the checksum option applied to the CDF.

Parameters:

`checksum` - the checksum option to be used for this CDF. Currently, other than `NO_CHECKSUM` option, only `MD5_CHECKSUM` (using MD5 checksum algorithm) is supported.

Throws:

`CDFException` - if there was a problem with the passed option, setting the checksum or other vital information from this CDF file.

getChecksum

```
public long getChecksum()
```

Gets the checksum method, if any, applied to the CDF.

Returns:

the checksum method used for this CDF. Currently, it returns `NONE_CHECKSUM` (0) if no checksum is used; `MD5_CHECKSUM` (1) if MD5 method is used;

setLeapSecondLastUpdated

```
public void setLeapSecondLastUpdated(long lastUpdated)
                    throws CDFException
```

Set the leap second last updated for this CDF. Normally, a new CDF is created, this field is set automatically. Only to call this method if the CDF is based on an existing one.

Parameters:

`lastUpdated` - The last date that the leap second was updated. It is in `YYYYMMDD` form.

Throws:

`CDFException` - If a problem occurred in setting the desired field.

getLeapSecondLastUpdated

```
public long getLeapSecondLastUpdated()
```

Gets the date that the CDF has the last leap second updated.

Returns:

the date in `YYYYMMDD` that the last leap second was updated when the CDF is based (relevant to TT2000 variables).

verifyChecksum

```
public long verifyChecksum()
                    throws CDFException
```

Verifies the data integrity of the CDF file from its checksum.

Returns:

The status of data integrity check through its checksum. it should return CDF_OK if the integrity check is fine. Or, it may return a value of CHECKSUM_ERROR indicating the data integrity was compromised. Or, it may return other CDF error if it has problem reading the CDF data filed(s). No need to use this method as when the file is open, its data integrity is automatically checked with the used checksum method.

Throws:

`CDFException` - if there was a problem getting the checksum or other vital infomation from this CDF file

Overview

Package

Class

Tree

Deprecated

Index

Help

Prev Class

Next Class

Frames

No Frames

All Classes

Summary: Nested | Field | Constr | Method

Detail: Field | Constr | Method

gsfc.nssdc.cdf

Interface CDFConstants

All Known Implementing Classes:

[Attribute](#), [CDF](#), [CDFData](#), [CDFException](#), [CDFTTools](#), [CDFTT2000](#), [CDFUtils](#), [Entry](#), [Epoch](#), [Epoch16](#), [Variable](#)

public interface **CDFConstants**

This class defines the constants used by the CDF library and CDF Java APIs, and it mimics the cdf.h include file from the cdf distribution.

Version:

1.0

Field Summary

Fields	
Modifier and Type	Field and Description
static long	AHUFF_COMPRESSION
static long	ALPHAOSF1_DECODING
static long	ALPHAOSF1_ENCODING
static long	ALPHAVMSd_DECODING
static long	ALPHAVMSd_ENCODING
static long	ALPHAVMSg_DECODING
static long	ALPHAVMSg_ENCODING
static long	ALPHAVMSi_DECODING
static long	ALPHAVMSi_ENCODING
static long	ARM_BIG_DECODING
static long	ARM_BIG_ENCODING
static long	ARM_LITTLE_DECODING
static long	ARM_LITTLE_ENCODING
static long	ATTR_
static long	ATTR_EXISTENCE_
static long	ATTR_EXISTS
static long	ATTR_MAXgENTRY_
static long	ATTR_MAXrENTRY_
static long	ATTR_MAXzENTRY_
static long	ATTR_NAME_
static long	ATTR_NAME_TRUNC
static long	ATTR_NUMBER_

static long	ATTR_NUMgENTRIES_
static long	ATTR_NUMrENTRIES_
static long	ATTR_NUMzENTRIES_
static long	ATTR_SCOPE_
static long	BACKWARD_
static long	BACKWARDFILEoff
static long	BACKWARDFILEon
static long	BAD_ALLOCATE_RECS
static long	BAD_ARGUMENT
static long	BAD_ATTR_NAME
static long	BAD_ATTR_NUM
static long	BAD_BLOCKING_FACTOR
static long	BAD_CACHE_SIZE
static long	BAD_CDF_EXTENSION
static long	BAD_CDF_ID
static long	BAD_CDF_NAME
static long	BAD_CDFSTATUS
static long	BAD_CHECKSUM
static long	BAD_COMPRESSION_PARM
static long	BAD_DATA_TYPE
static long	BAD_DECODING
static long	BAD_DIM_COUNT
static long	BAD_DIM_INDEX
static long	BAD_DIM_INTERVAL
static long	BAD_DIM_SIZE
static long	BAD_ENCODING
static long	BAD_ENTRY_NUM
static long	BAD_FNC_OR_ITEM
static long	BAD_FORMAT
static long	BAD_INITIAL_RECS
static long	BAD_MAJORITY
static long	BAD_MALLOC
static long	BAD_NEGtoPOSfp0_MODE
static long	BAD_NUM_DIMS
static long	BAD_NUM_ELEMS
static long	BAD_NUM_STRINGS
static long	BAD_NUM_VARS
static long	BAD_READONLY_MODE
static long	BAD_REC_COUNT
static long	BAD_REC_INTERVAL
static long	BAD_REC_NUM
static long	BAD_SCOPE
static long	BAD_SCRATCH_DIR
static long	BAD_SPARSEARRAYS_PARM

static long	BAD_VAR_NAME
static long	BAD_VAR_NUM
static long	BAD_zMODE
static long	BADDATE_LEAPSECOND_UPDATED
static double	BeginUnixTimeEPOCH
static double	BeginUnixTimeEPOCH16
static long	BLOCKINGFACTOR_TOO_LARGE
static long	BLOCKINGFACTOR_TOO_SMALL
static long	BLOCKINGFACTOR_TOO_SMALL2
static long	CANNOT_ALLOCATE_RECORDS
static long	CANNOT_CHANGE
static long	CANNOT_COMPRESS
static long	CANNOT_CONVERT_WIDECHAR
static long	CANNOT_COPY
static long	CANNOT_INSERT_RECORDS
static long	CANNOT_SPARSEARRAYS
static long	CANNOT_SPARSERECORDS
static long	CDF_
static long	CDF_ACCESS_
static long	CDF_ATTR_NAME_LEN
static long	CDF_ATTR_NAME_LEN256
static long	CDF_BYTE
static long	CDF_CACHESIZE_
static long	CDF_CHAR
static long	CDF_CHECKSUM_
static long	CDF_CLOSE_ERROR
static long	CDF_COMPRESSION_
static long	CDF_COPYRIGHT_
static long	CDF_COPYRIGHT_LEN
static long	CDF_CREATE_ERROR
static long	CDF_DECODING_
static long	CDF_DELETE_ERROR
static long	CDF_DOUBLE
static long	CDF_ENCODING_
static long	CDF_EPOCH
static long	CDF_EPOCH16
static long	CDF_EXISTS
static long	CDF_FLOAT
static long	CDF_FORMAT_
static long	CDF_INCREMENT_
static long	CDF_INFO_
static long	CDF_INT1
static long	CDF_INT2
static long	CDF_INT4

static long	CDF_INT8
static long	CDF_INTERNAL_ERROR
static long	CDF_LEAPSECONDLASTUPDATED_
static long	CDF_MAJORITY_
static long	CDF_MAX_DIMS
static long	CDF_MAX_PARS
static long	CDF_MIN_DIMS
static long	CDF_NAME_
static long	CDF_NAME_TRUNC
static long	CDF_NEGtoPOSfp0_MODE_
static long	CDF_NUMATTRS_
static long	CDF_NUMgATTRS_
static long	CDF_NUMrVARS_
static long	CDF_NUMvATTRS_
static long	CDF_NUMzVARS_
static long	CDF_OK
static long	CDF_OPEN_ERROR
static long	CDF_PATHNAME_LEN
static long	CDF_READ_ERROR
static long	CDF_READONLY_MODE_
static long	CDF_REAL4
static long	CDF_REAL8
static long	CDF_RELEASE_
static long	CDF_SAVE_ERROR
static long	CDF_SCRATCHDIR_
static long	CDF_STATUS_
static long	CDF_STATUSTEXT_LEN
static long	CDF_TIME_TT2000
static long	CDF_UCHAR
static long	CDF_UINT1
static long	CDF_UINT2
static long	CDF_UINT4
static long	CDF_VAR_NAME_LEN
static long	CDF_VAR_NAME_LEN256
static long	CDF_VERSION_
static long	CDF_WARN
static long	CDF_WRITE_ERROR
static long	CDF_zMODE_
static long	CDFwithSTATS_
static long	CHECKSUM_
static long	CHECKSUM_ERROR
static long	CHECKSUM_NOT_ALLOWED
static long	CLOSE_
static long	COLUMN_MAJOR

static long	COMPRESS_CACHESIZE_
static long	COMPRESSION_ERROR
static long	CONFIRM_
static long	CORRUPTED_V2_CDF
static long	CORRUPTED_V3_CDF
static long	CREATE_
static long	CURgENTRY_EXISTENCE_
static long	CURrENTRY_EXISTENCE_
static long	CURzENTRY_EXISTENCE_
static long	DATATYPE_MISMATCH
static long	DATATYPE_SIZE_
static long	DECOMPRESSION_ERROR
static long	DECSTATION_DECODING
static long	DECSTATION_ENCODING
static byte	DEFAULT_BYTE_PADVALUE
static char	DEFAULT_CHAR_PADVALUE
static double	DEFAULT_DOUBLE_PADVALUE
static double	DEFAULT_EPOCH_PADVALUE
static double	DEFAULT_EPOCH16_PADVALUE
static float	DEFAULT_FLOAT_PADVALUE
static byte	DEFAULT_INT1_PADVALUE
static short	DEFAULT_INT2_PADVALUE
static int	DEFAULT_INT4_PADVALUE
static long	DEFAULT_INT8_PADVALUE
static float	DEFAULT_REAL4_PADVALUE
static double	DEFAULT_REAL8_PADVALUE
static long	DEFAULT_TT2000_PADVALUE
static char	DEFAULT_UCHAR_PADVALUE
static short	DEFAULT_UINT1_PADVALUE
static int	DEFAULT_UINT2_PADVALUE
static long	DEFAULT_UINT4_PADVALUE
static long	DELETE_
static long	DID_NOT_COMPRESS
static long	EMPTY_COMPRESSED_CDF
static long	END_OF_VAR
static long	EPOCH_STRING_LEN
static long	EPOCH_STRING_LEN_EXTEND
static long	EPOCH1_STRING_LEN
static long	EPOCH1_STRING_LEN_EXTEND
static long	EPOCH2_STRING_LEN
static long	EPOCH2_STRING_LEN_EXTEND
static long	EPOCH3_STRING_LEN
static long	EPOCH3_STRING_LEN_EXTEND
static long	EPOCH4_STRING_LEN

static long	EPOCH4_STRING_LEN_EXTEND
static long	EPOCHx_FORMAT_MAX
static long	EPOCHx_STRING_MAX
static long	FILLED_TT2000_VALUE
static long	FORCED_PARAMETER
static long	FUNCTION_NOT_SUPPORTED
static long	gENTRY_
static long	gENTRY_DATA_
static long	gENTRY_DATASPEC_
static long	gENTRY_DATATYPE_
static long	gENTRY_EXISTENCE_
static long	gENTRY_NUMELEMS_
static long	GET_
static long	GETCDFCHECKSUM_
static long	GETCDFFILEBACKWARD_
static long	GETCDFVALIDATE_
static long	GETLEAPSECONDSENVVAR_
static long	GLOBAL_SCOPE
static long	GZIP_COMPRESSION
static long	HOST_DECODING
static long	HOST_ENCODING
static long	HP_DECODING
static long	HP_ENCODING
static long	HUFF_COMPRESSION
static long	IA64VMSd_DECODING
static long	IA64VMSd_ENCODING
static long	IA64VMSg_DECODING
static long	IA64VMSg_ENCODING
static long	IA64VMSi_DECODING
static long	IA64VMSi_ENCODING
static long	IBM_PC_OVERFLOW
static long	IBMPC_DECODING
static long	IBMPC_ENCODING
static long	IBMRS_DECODING
static long	IBMRS_ENCODING
static long	ILLEGAL_EPOCH_FIELD
static double	ILLEGAL_EPOCH_VALUE
static long	ILLEGAL_FOR_SCOPE
static long	ILLEGAL_IN_zMODE
static long	ILLEGAL_ON_V1_CDF
static long	ILLEGAL_TT2000_VALUE
static long	IS_A_NETCDF
static long	LIB_COPYRIGHT_
static long	LIB_INCREMENT_

static long	LIB_RELEASE_
static long	LIB_subINCREMENT_
static long	LIB_VERSION_
static long	MAC_DECODING
static long	MAC_ENCODING
static long	MD5_CHECKSUM
static long	MULTI_FILE
static long	MULTI_FILE_FORMAT
static long	NA_FOR_VARIABLE
static long	NEGATIVE_FP_ZERO
static long	NEGtoPOSfp0off
static long	NEGtoPOSfp0on
static long	NETWORK_DECODING
static long	NETWORK_ENCODING
static long	NeXT_DECODING
static long	NeXT_ENCODING
static long	NO_ATTR_SELECTED
static long	NO_CDF_SELECTED
static long	NO_CHECKSUM
static long	NO_COMPRESSION
static long	NO_DELETE_ACCESS
static long	NO_ENTRY_SELECTED
static long	NO_MORE_ACCESS
static long	NO_PADVALUE_SPECIFIED
static long	NO_SPARSEARRAYS
static long	NO_SPARSERECORDS
static long	NO_STATUS_SELECTED
static long	NO_SUCH_ATTR
static long	NO_SUCH_CDF
static long	NO_SUCH_ENTRY
static long	NO_SUCH_RECORD
static long	NO_SUCH_VAR
static long	NO_VAR_SELECTED
static long	NO_VARS_IN_CDF
static long	NO_WRITE_ACCESS
static long	NONE_CHECKSUM
static long	NOT_A_CDF
static long	NOT_A_CDF_OR_NOT_SUPPORTED
static long	NOVARY
static long	NULL_
static long	OPEN_
static long	OPTIMAL_ENCODING_TREES
static long	OTHER_CHECKSUM
static long	PAD_SPARSERECORDS

static long	PPC_DECODING
static long	PPC_ENCODING
static long	PRECEEDING_RECORDS_ALLOCATED
static long	PREV_SPARSERECORDS
static long	PUT_
static long	READ_ONLY_DISTRIBUTION
static long	READ_ONLY_MODE
static long	READONLYoff
static long	READONLYon
static long	rENTRY_
static long	rENTRY_DATA_
static long	rENTRY_DATASPEC_
static long	rENTRY_DATATYPE_
static long	rENTRY_EXISTENCE_
static long	rENTRY_NAME_
static long	rENTRY_NUMELEMS_
static long	rENTRY_NUMSTRINGS_
static long	rENTRY_STRINGSDATA_
static long	RLE_COMPRESSION
static long	RLE_OF_ZEROs
static long	ROW_MAJOR
static long	rVAR_
static long	rVAR_ALLOCATEBLOCK_
static long	rVAR_ALLOCATEDFROM_
static long	rVAR_ALLOCATEDTO_
static long	rVAR_ALLOCATERECS_
static long	rVAR_BLOCKINGFACTOR_
static long	rVAR_CACHESIZE_
static long	rVAR_COMPRESSION_
static long	rVAR_DATA_
static long	rVAR_DATASPEC_
static long	rVAR_DATATYPE_
static long	rVAR_DIMVARYS_
static long	rVAR_EXISTENCE_
static long	rVAR_HYPERDATA_
static long	rVAR_INITIALRECS_
static long	rVAR_MAXallocREC_
static long	rVAR_MAXREC_
static long	rVAR_NAME_
static long	rVAR_nINDEXENTRIES_
static long	rVAR_nINDEXLEVELS_
static long	rVAR_nINDEXRECORDS_
static long	rVAR_NUMallocRECS_
static long	rVAR_NUMBER_

static long	rVAR_NUMELEMS_
static long	rVAR_NUMRECS_
static long	rVAR_PADVALUE_
static long	rVAR_RECORDS_
static long	rVAR_RECORDS_RENUMBER_
static long	rVAR_RECVAR_
static long	rVAR_RESERVEPERCENT_
static long	rVAR_SEQDATA_
static long	rVAR_SEQPOS_
static long	rVAR_SPARSEARRAYS_
static long	rVAR_SPARSERECORDS_
static long	rVARs_CACHESIZE_
static long	rVARs_DIMCOUNTS_
static long	rVARs_DIMINDICES_
static long	rVARs_DIMINTERVALS_
static long	rVARs_DIMSIZES_
static long	rVARs_MAXREC_
static long	rVARs_NUMDIMS_
static long	rVARs_RECCOUNT_
static long	rVARs_RECDATA_
static long	rVARs_RECINTERVAL_
static long	rVARs_RECNUMBER_
static long	SAVE_
static long	SCRATCH_CREATE_ERROR
static long	SCRATCH_DELETE_ERROR
static long	SCRATCH_READ_ERROR
static long	SCRATCH_WRITE_ERROR
static long	SELECT_
static long	SGi_DECODING
static long	SGi_ENCODING
static long	SINGLE_FILE
static long	SINGLE_FILE_FORMAT
static long	SOME_ALREADY_ALLOCATED
static long	STAGE_CACHESIZE_
static long	STATUS_TEXT_
static long	STRING_NOT_UTF8_ENCODING
static java.lang.String	STRINGDELIMITER
static long	SUN_DECODING
static long	SUN_ENCODING
static long	TOO_MANY_PARMS
static long	TOO_MANY_VARS
static long	TRY_TO_READ_NONSTRING_DATA
static long	TT2000_0_STRING_LEN
static long	TT2000_1_STRING_LEN

static long	TT2000_2_STRING_LEN
static long	TT2000_3_STRING_LEN
static long	TT2000_4_STRING_LEN
static long	TT2000_CDF_MAYNEEDUPDATE
static long	TT2000_TIME_ERROR
static long	TT2000_USED_OUTDATED_TABLE
static long	UNABLE_TO_PROCESS_CDF
static long	UNKNOWN_COMPRESSION
static long	UNKNOWN_SPARSENESS
static long	UNSUPPORTED_OPERATION
static long	VALIDATE_
static long	VALIDATEFILEoff
static long	VALIDATEFILEon
static long	VAR_ALREADY_CLOSED
static long	VAR_CLOSE_ERROR
static long	VAR_CREATE_ERROR
static long	VAR_DELETE_ERROR
static long	VAR_EXISTS
static long	VAR_NAME_TRUNC
static long	VAR_OPEN_ERROR
static long	VAR_READ_ERROR
static long	VAR_SAVE_ERROR
static long	VAR_WRITE_ERROR
static long	VARIABLE_SCOPE
static long	VARY
static long	VAX_DECODING
static long	VAX_ENCODING
static long	VIRTUAL_RECORD_DATA
static long	zENTRY_
static long	zENTRY_DATA_
static long	zENTRY_DATASPEC_
static long	zENTRY_DATATYPE_
static long	zENTRY_EXISTENCE_
static long	zENTRY_NAME_
static long	zENTRY_NUMELEMS_
static long	zENTRY_NUMSTRINGS_
static long	zENTRY_STRINGSDATA_
static long	ZLIB_COMPRESS_ERROR
static long	ZLIB_UNCOMPRESS_ERROR
static long	zMODEoff
static long	zMODEon1
static long	zMODEon2
static long	zVAR_
static long	zVAR_ALLOCATEBLOCK_

static long	zVAR_ALLOCATEDFROM_
static long	zVAR_ALLOCATEDTO_
static long	zVAR_ALLOCATERECS_
static long	zVAR_BLOCKINGFACTOR_
static long	zVAR_CACHESIZE_
static long	zVAR_COMPRESSION_
static long	zVAR_DATA_
static long	zVAR_DATASPEC_
static long	zVAR_DATATYPE_
static long	zVAR_DIMCOUNTS_
static long	zVAR_DIMINDICES_
static long	zVAR_DIMINTERVALS_
static long	zVAR_DIMSIZES_
static long	zVAR_DIMVARYS_
static long	zVAR_EXISTENCE_
static long	zVAR_HYPERDATA_
static long	zVAR_INITIALRECS_
static long	zVAR_MAXallocREC_
static long	zVAR_MAXREC_
static long	zVAR_NAME_
static long	zVAR_nINDEXENTRIES_
static long	zVAR_nINDEXLEVELS_
static long	zVAR_nINDEXRECORDS_
static long	zVAR_NUMallocRECS_
static long	zVAR_NUMBER_
static long	zVAR_NUMDIMS_
static long	zVAR_NUMELEMS_
static long	zVAR_NUMRECS_
static long	zVAR_PADVALUE_
static long	zVAR_RECCOUNT_
static long	zVAR_RECINTERVAL_
static long	zVAR_RECNUMBER_
static long	zVAR_RECORDS_
static long	zVAR_RECORDS_RENUMBER_
static long	zVAR_RECVARY_
static long	zVAR_RESERVEPERCENT_
static long	zVAR_SEQDATA_
static long	zVAR_SEQPOS_
static long	zVAR_SPARSEARRAYS_
static long	zVAR_SPASERECORDS_
static long	zVARs_CACHESIZE_
static long	zVARs_MAXREC_
static long	zVARs_RECDATA_
static long	zVARs_RECNUMBER_

Field Detail

CDF_MIN_DIMS

```
static final long CDF_MIN_DIMS
```

See Also:

[Constant Field Values](#)

CDF_MAX_DIMS

```
static final long CDF_MAX_DIMS
```

See Also:

[Constant Field Values](#)

CDF_VAR_NAME_LEN

```
static final long CDF_VAR_NAME_LEN
```

See Also:

[Constant Field Values](#)

CDF_VAR_NAME_LEN256

```
static final long CDF_VAR_NAME_LEN256
```

See Also:

[Constant Field Values](#)

CDF_ATTR_NAME_LEN

```
static final long CDF_ATTR_NAME_LEN
```

See Also:

[Constant Field Values](#)

CDF_ATTR_NAME_LEN256

```
static final long CDF_ATTR_NAME_LEN256
```

See Also:

[Constant Field Values](#)

CDF_COPYRIGHT_LEN

```
static final long CDF_COPYRIGHT_LEN
```

See Also:

[Constant Field Values](#)

CDF_STATUSTEXT_LEN

```
static final long CDF_STATUSTEXT_LEN
```

See Also:

[Constant Field Values](#)

CDF_PATHNAME_LEN

```
static final long CDF_PATHNAME_LEN
```

See Also:

[Constant Field Values](#)

EPOCH_STRING_LEN

```
static final long EPOCH_STRING_LEN
```

See Also:

[Constant Field Values](#)

EPOCH1_STRING_LEN

```
static final long EPOCH1_STRING_LEN
```

See Also:

[Constant Field Values](#)

EPOCH2_STRING_LEN

```
static final long EPOCH2_STRING_LEN
```

See Also:

[Constant Field Values](#)

EPOCH3_STRING_LEN

```
static final long EPOCH3_STRING_LEN
```

See Also:

[Constant Field Values](#)

EPOCH4_STRING_LEN

`static final long EPOCH4_STRING_LEN`

See Also:

[Constant Field Values](#)

EPOCHx_STRING_MAX

`static final long EPOCHx_STRING_MAX`

See Also:

[Constant Field Values](#)

EPOCHx_FORMAT_MAX

`static final long EPOCHx_FORMAT_MAX`

See Also:

[Constant Field Values](#)

EPOCH_STRING_LEN_EXTEND

`static final long EPOCH_STRING_LEN_EXTEND`

See Also:

[Constant Field Values](#)

EPOCH1_STRING_LEN_EXTEND

`static final long EPOCH1_STRING_LEN_EXTEND`

See Also:

[Constant Field Values](#)

EPOCH2_STRING_LEN_EXTEND

`static final long EPOCH2_STRING_LEN_EXTEND`

See Also:

[Constant Field Values](#)

EPOCH3_STRING_LEN_EXTEND

```
static final long EPOCH3_STRING_LEN_EXTEND
```

See Also:

[Constant Field Values](#)

EPOCH4_STRING_LEN_EXTEND

```
static final long EPOCH4_STRING_LEN_EXTEND
```

See Also:

[Constant Field Values](#)

TT2000_0_STRING_LEN

```
static final long TT2000_0_STRING_LEN
```

See Also:

[Constant Field Values](#)

TT2000_1_STRING_LEN

```
static final long TT2000_1_STRING_LEN
```

See Also:

[Constant Field Values](#)

TT2000_2_STRING_LEN

```
static final long TT2000_2_STRING_LEN
```

See Also:

[Constant Field Values](#)

TT2000_3_STRING_LEN

```
static final long TT2000_3_STRING_LEN
```

See Also:

[Constant Field Values](#)

TT2000_4_STRING_LEN

```
static final long TT2000_4_STRING_LEN
```

See Also:

[Constant Field Values](#)

CDF_INT1

```
static final long CDF_INT1
```

See Also:

[Constant Field Values](#)

CDF_INT2

```
static final long CDF_INT2
```

See Also:

[Constant Field Values](#)

CDF_INT4

```
static final long CDF_INT4
```

See Also:

[Constant Field Values](#)

CDF_INT8

```
static final long CDF_INT8
```

See Also:

[Constant Field Values](#)

CDF_UINT1

```
static final long CDF_UINT1
```

See Also:

[Constant Field Values](#)

CDF_UINT2

```
static final long CDF_UINT2
```

See Also:

[Constant Field Values](#)

CDF_UINT4

```
static final long CDF_UINT4
```

See Also:

Constant Field Values

CDF_REAL4

```
static final long CDF_REAL4
```

See Also:

[Constant Field Values](#)

CDF_REAL8

```
static final long CDF_REAL8
```

See Also:

[Constant Field Values](#)

CDF_EPOCH

```
static final long CDF_EPOCH
```

See Also:

[Constant Field Values](#)

CDF_EPOCH16

```
static final long CDF_EPOCH16
```

See Also:

[Constant Field Values](#)

CDF_TIME_TT2000

```
static final long CDF_TIME_TT2000
```

See Also:

[Constant Field Values](#)

CDF_BYTE

```
static final long CDF_BYTE
```

See Also:

[Constant Field Values](#)

CDF_FLOAT

```
static final long CDF_FLOAT
```

See Also:

[Constant Field Values](#)

CDF_DOUBLE

```
static final long CDF_DOUBLE
```

See Also:

[Constant Field Values](#)

CDF_CHAR

```
static final long CDF_CHAR
```

See Also:

[Constant Field Values](#)

CDF_UCHAR

```
static final long CDF_UCHAR
```

See Also:

[Constant Field Values](#)

NETWORK_ENCODING

```
static final long NETWORK_ENCODING
```

See Also:

[Constant Field Values](#)

SUN_ENCODING

```
static final long SUN_ENCODING
```

See Also:

[Constant Field Values](#)

VAX_ENCODING

```
static final long VAX_ENCODING
```

See Also:

[Constant Field Values](#)

DECSTATION_ENCODING

static final long DECSTATION_ENCODING

See Also:

[Constant Field Values](#)

SGi_ENCODING

static final long SGi_ENCODING

See Also:

[Constant Field Values](#)

IBMPC_ENCODING

static final long IBMPC_ENCODING

See Also:

[Constant Field Values](#)

IBMRS_ENCODING

static final long IBMRS_ENCODING

See Also:

[Constant Field Values](#)

HOST_ENCODING

static final long HOST_ENCODING

See Also:

[Constant Field Values](#)

PPC_ENCODING

static final long PPC_ENCODING

See Also:

[Constant Field Values](#)

HP_ENCODING

static final long HP_ENCODING

See Also:

[Constant Field Values](#)

NeXT_ENCODING

```
static final long NeXT_ENCODING
```

See Also:

[Constant Field Values](#)

ALPHAOSF1_ENCODING

```
static final long ALPHAOSF1_ENCODING
```

See Also:

[Constant Field Values](#)

ALPHAVMSd_ENCODING

```
static final long ALPHAVMSd_ENCODING
```

See Also:

[Constant Field Values](#)

ALPHAVMSg_ENCODING

```
static final long ALPHAVMSg_ENCODING
```

See Also:

[Constant Field Values](#)

ALPHAVMSi_ENCODING

```
static final long ALPHAVMSi_ENCODING
```

See Also:

[Constant Field Values](#)

ARM_LITTLE_ENCODING

```
static final long ARM_LITTLE_ENCODING
```

See Also:

[Constant Field Values](#)

ARM_BIG_ENCODING

```
static final long ARM_BIG_ENCODING
```

See Also:

[Constant Field Values](#)

IA64VMSi_ENCODING

```
static final long IA64VMSi_ENCODING
```

See Also:

[Constant Field Values](#)

IA64VMSd_ENCODING

```
static final long IA64VMSd_ENCODING
```

See Also:

[Constant Field Values](#)

IA64VMSg_ENCODING

```
static final long IA64VMSg_ENCODING
```

See Also:

[Constant Field Values](#)

NETWORK_DECODING

```
static final long NETWORK_DECODING
```

See Also:

[Constant Field Values](#)

SUN_DECODING

```
static final long SUN_DECODING
```

See Also:

[Constant Field Values](#)

VAX_DECODING

```
static final long VAX_DECODING
```

See Also:

[Constant Field Values](#)

DECSTATION_DECODING

static final long DECSTATION_DECODING

See Also:

[Constant Field Values](#)

SGi_DECODING

static final long SGi_DECODING

See Also:

[Constant Field Values](#)

IBMPC_DECODING

static final long IBMPC_DECODING

See Also:

[Constant Field Values](#)

IBMRS_DECODING

static final long IBMRS_DECODING

See Also:

[Constant Field Values](#)

HOST_DECODING

static final long HOST_DECODING

See Also:

[Constant Field Values](#)

PPC_DECODING

static final long PPC_DECODING

See Also:

[Constant Field Values](#)

MAC_ENCODING

static final long MAC_ENCODING

See Also:

[Constant Field Values](#)

MAC_DECODING

```
static final long MAC_DECODING
```

See Also:

[Constant Field Values](#)

HP_DECODING

```
static final long HP_DECODING
```

See Also:

[Constant Field Values](#)

NeXT_DECODING

```
static final long NeXT_DECODING
```

See Also:

[Constant Field Values](#)

ALPHAOSF1_DECODING

```
static final long ALPHAOSF1_DECODING
```

See Also:

[Constant Field Values](#)

ALPHAVMSd_DECODING

```
static final long ALPHAVMSd_DECODING
```

See Also:

[Constant Field Values](#)

ALPHAVMSg_DECODING

```
static final long ALPHAVMSg_DECODING
```

See Also:

[Constant Field Values](#)

ALPHAVMSi_DECODING

```
static final long ALPHAVMSi_DECODING
```

See Also:

[Constant Field Values](#)

ARM_LITTLE_DECODING

```
static final long ARM_LITTLE_DECODING
```

See Also:

[Constant Field Values](#)

ARM_BIG_DECODING

```
static final long ARM_BIG_DECODING
```

See Also:

[Constant Field Values](#)

IA64VMSd_DECODING

```
static final long IA64VMSd_DECODING
```

See Also:

[Constant Field Values](#)

IA64VMSg_DECODING

```
static final long IA64VMSg_DECODING
```

See Also:

[Constant Field Values](#)

IA64VMSi_DECODING

```
static final long IA64VMSi_DECODING
```

See Also:

[Constant Field Values](#)

VARY

```
static final long VARY
```

See Also:

[Constant Field Values](#)

NOVARY

static final long NOVARY

See Also:

[Constant Field Values](#)

ROW_MAJOR

static final long ROW_MAJOR

See Also:

[Constant Field Values](#)

COLUMN_MAJOR

static final long COLUMN_MAJOR

See Also:

[Constant Field Values](#)

SINGLE_FILE

static final long SINGLE_FILE

See Also:

[Constant Field Values](#)

MULTI_FILE

static final long MULTI_FILE

See Also:

[Constant Field Values](#)

GLOBAL_SCOPE

static final long GLOBAL_SCOPE

See Also:

[Constant Field Values](#)

VARIABLE_SCOPE

static final long VARIABLE_SCOPE

See Also:

Constant Field Values

READONLYon
<pre>static final long READONLYon</pre>
See Also:
Constant Field Values

READONLYoff
<pre>static final long READONLYoff</pre>
See Also:
Constant Field Values

zMODEoff
<pre>static final long zMODEoff</pre>
See Also:
Constant Field Values

zMODEon1
<pre>static final long zMODEon1</pre>
See Also:
Constant Field Values

zMODEon2
<pre>static final long zMODEon2</pre>
See Also:
Constant Field Values

NEGtoPOSfp0on
<pre>static final long NEGtoPOSfp0on</pre>
See Also:
Constant Field Values

NEGtoPOSfp0off

```
static final long NEGtoPOSfp0off
```

See Also:

[Constant Field Values](#)

BACKWARDFILEon

```
static final long BACKWARDFILEon
```

See Also:

[Constant Field Values](#)

BACKWARDFILEoff

```
static final long BACKWARDFILEoff
```

See Also:

[Constant Field Values](#)

VALIDATEFILEon

```
static final long VALIDATEFILEon
```

See Also:

[Constant Field Values](#)

VALIDATEFILEoff

```
static final long VALIDATEFILEoff
```

See Also:

[Constant Field Values](#)

NO_CHECKSUM

```
static final long NO_CHECKSUM
```

See Also:

[Constant Field Values](#)

NONE_CHECKSUM

```
static final long NONE_CHECKSUM
```

See Also:

[Constant Field Values](#)

MD5_CHECKSUM

```
static final long MD5_CHECKSUM
```

See Also:

[Constant Field Values](#)

OTHER_CHECKSUM

```
static final long OTHER_CHECKSUM
```

See Also:

[Constant Field Values](#)

CDF_MAX_PARMS

```
static final long CDF_MAX_PARMS
```

See Also:

[Constant Field Values](#)

NO_COMPRESSION

```
static final long NO_COMPRESSION
```

See Also:

[Constant Field Values](#)

RLE_COMPRESSION

```
static final long RLE_COMPRESSION
```

See Also:

[Constant Field Values](#)

HUFF_COMPRESSION

```
static final long HUFF_COMPRESSION
```

See Also:

[Constant Field Values](#)

AHUFF_COMPRESSION

```
static final long AHUFF_COMPRESSION
```

See Also:

[Constant Field Values](#)

GZIP_COMPRESSION

static final long GZIP_COMPRESSION

See Also:

[Constant Field Values](#)

RLE_OF_ZEROs

static final long RLE_OF_ZEROs

See Also:

[Constant Field Values](#)

OPTIMAL_ENCODING_TREES

static final long OPTIMAL_ENCODING_TREES

See Also:

[Constant Field Values](#)

NO_SPARSEARRAYS

static final long NO_SPARSEARRAYS

See Also:

[Constant Field Values](#)

NO_SPARSERECORDS

static final long NO_SPARSERECORDS

See Also:

[Constant Field Values](#)

PAD_SPARSERECORDS

static final long PAD_SPARSERECORDS

See Also:

[Constant Field Values](#)

PREV_SPARSERECORDS

```
static final long PREV_SPARSERECORDS
```

See Also:

[Constant Field Values](#)

DEFAULT_BYTE_PADVALUE

```
static final byte DEFAULT_BYTE_PADVALUE
```

See Also:

[Constant Field Values](#)

DEFAULT_INT1_PADVALUE

```
static final byte DEFAULT_INT1_PADVALUE
```

See Also:

[Constant Field Values](#)

DEFAULT_UINT1_PADVALUE

```
static final short DEFAULT_UINT1_PADVALUE
```

See Also:

[Constant Field Values](#)

DEFAULT_INT2_PADVALUE

```
static final short DEFAULT_INT2_PADVALUE
```

See Also:

[Constant Field Values](#)

DEFAULT_UINT2_PADVALUE

```
static final int DEFAULT_UINT2_PADVALUE
```

See Also:

[Constant Field Values](#)

DEFAULT_INT4_PADVALUE

```
static final int DEFAULT_INT4_PADVALUE
```

See Also:

[Constant Field Values](#)

DEFAULT_UINT4_PADVALUE

```
static final long DEFAULT_UINT4_PADVALUE
```

See Also:

[Constant Field Values](#)

DEFAULT_INT8_PADVALUE

```
static final long DEFAULT_INT8_PADVALUE
```

See Also:

[Constant Field Values](#)

DEFAULT_REAL4_PADVALUE

```
static final float DEFAULT_REAL4_PADVALUE
```

See Also:

[Constant Field Values](#)

DEFAULT_FLOAT_PADVALUE

```
static final float DEFAULT_FLOAT_PADVALUE
```

See Also:

[Constant Field Values](#)

DEFAULT_REAL8_PADVALUE

```
static final double DEFAULT_REAL8_PADVALUE
```

See Also:

[Constant Field Values](#)

DEFAULT_DOUBLE_PADVALUE

```
static final double DEFAULT_DOUBLE_PADVALUE
```

See Also:

[Constant Field Values](#)

DEFAULT_CHAR_PADVALUE

```
static final char DEFAULT_CHAR_PADVALUE
```

See Also:

Constant Field Values

DEFAULT_UCHAR_PADVALUE

```
static final char DEFAULT_UCHAR_PADVALUE
```

See Also:

Constant Field Values

DEFAULT_EPOCH_PADVALUE

```
static final double DEFAULT_EPOCH_PADVALUE
```

See Also:

Constant Field Values

DEFAULT_EPOCH16_PADVALUE

```
static final double DEFAULT_EPOCH16_PADVALUE
```

See Also:

Constant Field Values

DEFAULT_TT2000_PADVALUE

```
static final long DEFAULT_TT2000_PADVALUE
```

See Also:

Constant Field Values

ILLEGAL_EPOCH_VALUE

```
static final double ILLEGAL_EPOCH_VALUE
```

See Also:

Constant Field Values

ILLEGAL_TT2000_VALUE

```
static final long ILLEGAL_TT2000_VALUE
```

See Also:

Constant Field Values

FILLED_TT2000_VALUE

```
static final long FILLED_TT2000_VALUE
```

See Also:

[Constant Field Values](#)

VIRTUAL_RECORD_DATA

```
static final long VIRTUAL_RECORD_DATA
```

See Also:

[Constant Field Values](#)

DID_NOT_COMPRESS

```
static final long DID_NOT_COMPRESS
```

See Also:

[Constant Field Values](#)

VAR_ALREADY_CLOSED

```
static final long VAR_ALREADY_CLOSED
```

See Also:

[Constant Field Values](#)

SINGLE_FILE_FORMAT

```
static final long SINGLE_FILE_FORMAT
```

See Also:

[Constant Field Values](#)

NO_PADVALUE_SPECIFIED

```
static final long NO_PADVALUE_SPECIFIED
```

See Also:

[Constant Field Values](#)

NO_VARS_IN_CDF

```
static final long NO_VARS_IN_CDF
```

See Also:

[Constant Field Values](#)

MULTI_FILE_FORMAT

```
static final long MULTI_FILE_FORMAT
```

See Also:

[Constant Field Values](#)

SOME_ALREADY_ALLOCATED

```
static final long SOME_ALREADY_ALLOCATED
```

See Also:

[Constant Field Values](#)

PRECEEDING_RECORDS_ALLOCATED

```
static final long PRECEEDING_RECORDS_ALLOCATED
```

See Also:

[Constant Field Values](#)

TT2000_CDF_MAYNEEDUPDATE

```
static final long TT2000_CDF_MAYNEEDUPDATE
```

See Also:

[Constant Field Values](#)

BLOCKINGFACTOR_TOO_SMALL

```
static final long BLOCKINGFACTOR_TOO_SMALL
```

See Also:

[Constant Field Values](#)

BLOCKINGFACTOR_TOO_SMALL2

```
static final long BLOCKINGFACTOR_TOO_SMALL2
```

See Also:

[Constant Field Values](#)

STRING_NOT_UTF8_ENCODING

```
static final long STRING_NOT_UTF8_ENCODING
```

See Also:

Constant Field Values

BLOCKINGFACTOR_TOO_LARGE

```
static final long BLOCKINGFACTOR_TOO_LARGE
```

See Also:

Constant Field Values

CDF_OK

```
static final long CDF_OK
```

See Also:

Constant Field Values

ATTR_NAME_TRUNC

```
static final long ATTR_NAME_TRUNC
```

See Also:

Constant Field Values

CDF_NAME_TRUNC

```
static final long CDF_NAME_TRUNC
```

See Also:

Constant Field Values

VAR_NAME_TRUNC

```
static final long VAR_NAME_TRUNC
```

See Also:

Constant Field Values

NEGATIVE_FP_ZERO

```
static final long NEGATIVE_FP_ZERO
```

See Also:

Constant Field Values

FORCED_PARAMETER

```
static final long FORCED_PARAMETER
```

See Also:

[Constant Field Values](#)

NA_FOR_VARIABLE

```
static final long NA_FOR_VARIABLE
```

See Also:

[Constant Field Values](#)

CDF_WARN

```
static final long CDF_WARN
```

See Also:

[Constant Field Values](#)

ATTR_EXISTS

```
static final long ATTR_EXISTS
```

See Also:

[Constant Field Values](#)

BAD_CDF_ID

```
static final long BAD_CDF_ID
```

See Also:

[Constant Field Values](#)

BAD_DATA_TYPE

```
static final long BAD_DATA_TYPE
```

See Also:

[Constant Field Values](#)

BAD_DIM_SIZE

```
static final long BAD_DIM_SIZE
```

See Also:

[Constant Field Values](#)

BAD_DIM_INDEX

```
static final long BAD_DIM_INDEX
```

See Also:

[Constant Field Values](#)

BAD_ENCODING

```
static final long BAD_ENCODING
```

See Also:

[Constant Field Values](#)

BAD_MAJORITY

```
static final long BAD_MAJORITY
```

See Also:

[Constant Field Values](#)

BAD_NUM_DIMS

```
static final long BAD_NUM_DIMS
```

See Also:

[Constant Field Values](#)

BAD_REC_NUM

```
static final long BAD_REC_NUM
```

See Also:

[Constant Field Values](#)

BAD_SCOPE

```
static final long BAD_SCOPE
```

See Also:

[Constant Field Values](#)

BAD_NUM_ELEMS

```
static final long BAD_NUM_ELEMS
```

See Also:

[Constant Field Values](#)

CDF_OPEN_ERROR

```
static final long CDF_OPEN_ERROR
```

See Also:

[Constant Field Values](#)

CDF_EXISTS

```
static final long CDF_EXISTS
```

See Also:

[Constant Field Values](#)

BAD_FORMAT

```
static final long BAD_FORMAT
```

See Also:

[Constant Field Values](#)

BAD_ALLOCATE_RECS

```
static final long BAD_ALLOCATE_RECS
```

See Also:

[Constant Field Values](#)

BAD_CDF_EXTENSION

```
static final long BAD_CDF_EXTENSION
```

See Also:

[Constant Field Values](#)

NO_SUCH_ATTR

```
static final long NO_SUCH_ATTR
```

See Also:

[Constant Field Values](#)

NO_SUCH_ENTRY

```
static final long NO_SUCH_ENTRY
```

See Also:

[Constant Field Values](#)

NO_SUCH_VAR

```
static final long NO_SUCH_VAR
```

See Also:

[Constant Field Values](#)

VAR_READ_ERROR

```
static final long VAR_READ_ERROR
```

See Also:

[Constant Field Values](#)

VAR_WRITE_ERROR

```
static final long VAR_WRITE_ERROR
```

See Also:

[Constant Field Values](#)

BAD_ARGUMENT

```
static final long BAD_ARGUMENT
```

See Also:

[Constant Field Values](#)

IBM_PC_OVERFLOW

```
static final long IBM_PC_OVERFLOW
```

See Also:

[Constant Field Values](#)

TOO_MANY_VARS

```
static final long TOO_MANY_VARS
```

See Also:

[Constant Field Values](#)

VAR_EXISTS

```
static final long VAR_EXISTS
```

See Also:

[Constant Field Values](#)

BAD_MALLOC

```
static final long BAD_MALLOC
```

See Also:

[Constant Field Values](#)

NOT_A_CDF

```
static final long NOT_A_CDF
```

See Also:

[Constant Field Values](#)

CORRUPTED_V2_CDF

```
static final long CORRUPTED_V2_CDF
```

See Also:

[Constant Field Values](#)

VAR_OPEN_ERROR

```
static final long VAR_OPEN_ERROR
```

See Also:

[Constant Field Values](#)

BAD_INITIAL_RECS

```
static final long BAD_INITIAL_RECS
```

See Also:

[Constant Field Values](#)

BAD_BLOCKING_FACTOR

```
static final long BAD_BLOCKING_FACTOR
```

See Also:

Constant Field Values

END_OF_VAR

```
static final long END_OF_VAR
```

See Also:

Constant Field Values

BAD_CDFSTATUS

```
static final long BAD_CDFSTATUS
```

See Also:

Constant Field Values

CDF_INTERNAL_ERROR

```
static final long CDF_INTERNAL_ERROR
```

See Also:

Constant Field Values

BAD_NUM_VARS

```
static final long BAD_NUM_VARS
```

See Also:

Constant Field Values

BAD_REC_COUNT

```
static final long BAD_REC_COUNT
```

See Also:

Constant Field Values

BAD_REC_INTERVAL

```
static final long BAD_REC_INTERVAL
```

See Also:

Constant Field Values

BAD_DIM_COUNT

`static final long BAD_DIM_COUNT`

See Also:

[Constant Field Values](#)

BAD_DIM_INTERVAL

`static final long BAD_DIM_INTERVAL`

See Also:

[Constant Field Values](#)

BAD_VAR_NUM

`static final long BAD_VAR_NUM`

See Also:

[Constant Field Values](#)

BAD_ATTR_NUM

`static final long BAD_ATTR_NUM`

See Also:

[Constant Field Values](#)

BAD_ENTRY_NUM

`static final long BAD_ENTRY_NUM`

See Also:

[Constant Field Values](#)

BAD_ATTR_NAME

`static final long BAD_ATTR_NAME`

See Also:

[Constant Field Values](#)

BAD_VAR_NAME

`static final long BAD_VAR_NAME`

See Also:

[Constant Field Values](#)

NO_ATTR_SELECTED

static final long NO_ATTR_SELECTED

See Also:

[Constant Field Values](#)

NO_ENTRY_SELECTED

static final long NO_ENTRY_SELECTED

See Also:

[Constant Field Values](#)

NO_VAR_SELECTED

static final long NO_VAR_SELECTED

See Also:

[Constant Field Values](#)

BAD_CDF_NAME

static final long BAD_CDF_NAME

See Also:

[Constant Field Values](#)

CANNOT_CHANGE

static final long CANNOT_CHANGE

See Also:

[Constant Field Values](#)

NO_STATUS_SELECTED

static final long NO_STATUS_SELECTED

See Also:

[Constant Field Values](#)

NO_CDF_SELECTED

static final long NO_CDF_SELECTED

See Also:

[Constant Field Values](#)

READ_ONLY_DISTRIBUTION

`static final long READ_ONLY_DISTRIBUTION`

See Also:

[Constant Field Values](#)

CDF_CLOSE_ERROR

`static final long CDF_CLOSE_ERROR`

See Also:

[Constant Field Values](#)

VAR_CLOSE_ERROR

`static final long VAR_CLOSE_ERROR`

See Also:

[Constant Field Values](#)

BAD_FNC_OR_ITEM

`static final long BAD_FNC_OR_ITEM`

See Also:

[Constant Field Values](#)

ILLEGAL_ON_V1_CDF

`static final long ILLEGAL_ON_V1_CDF`

See Also:

[Constant Field Values](#)

BAD_CACHE_SIZE

`static final long BAD_CACHE_SIZE`

See Also:

[Constant Field Values](#)

CDF_CREATE_ERROR

static final long CDF_CREATE_ERROR

See Also:

[Constant Field Values](#)

NO_SUCH_CDF

static final long NO_SUCH_CDF

See Also:

[Constant Field Values](#)

VAR_CREATE_ERROR

static final long VAR_CREATE_ERROR

See Also:

[Constant Field Values](#)

READ_ONLY_MODE

static final long READ_ONLY_MODE

See Also:

[Constant Field Values](#)

ILLEGAL_IN_zMODE

static final long ILLEGAL_IN_zMODE

See Also:

[Constant Field Values](#)

BAD_zMODE

static final long BAD_zMODE

See Also:

[Constant Field Values](#)

BAD_READONLY_MODE

static final long BAD_READONLY_MODE

See Also:

Constant Field Values

CDF_READ_ERROR

static final long CDF_READ_ERROR

See Also:

Constant Field Values

CDF_WRITE_ERROR

static final long CDF_WRITE_ERROR

See Also:

Constant Field Values

ILLEGAL_FOR_SCOPE

static final long ILLEGAL_FOR_SCOPE

See Also:

Constant Field Values

NO_MORE_ACCESS

static final long NO_MORE_ACCESS

See Also:

Constant Field Values

BAD_DECODING

static final long BAD_DECODING

See Also:

Constant Field Values

BAD_NEGtoPOSfp0_MODE

static final long BAD_NEGtoPOSfp0_MODE

See Also:

Constant Field Values

UNSUPPORTED_OPERATION

```
static final long UNSUPPORTED_OPERATION
```

See Also:

[Constant Field Values](#)

CDF_SAVE_ERROR

```
static final long CDF_SAVE_ERROR
```

See Also:

[Constant Field Values](#)

VAR_SAVE_ERROR

```
static final long VAR_SAVE_ERROR
```

See Also:

[Constant Field Values](#)

NO_WRITE_ACCESS

```
static final long NO_WRITE_ACCESS
```

See Also:

[Constant Field Values](#)

NO_DELETE_ACCESS

```
static final long NO_DELETE_ACCESS
```

See Also:

[Constant Field Values](#)

CDF_DELETE_ERROR

```
static final long CDF_DELETE_ERROR
```

See Also:

[Constant Field Values](#)

VAR_DELETE_ERROR

```
static final long VAR_DELETE_ERROR
```

See Also:

[Constant Field Values](#)

UNKNOWN_COMPRESSION

static final long UNKNOWN_COMPRESSION

See Also:

[Constant Field Values](#)

CANNOT_COMPRESS

static final long CANNOT_COMPRESS

See Also:

[Constant Field Values](#)

DECOMPRESSION_ERROR

static final long DECOMPRESSION_ERROR

See Also:

[Constant Field Values](#)

COMPRESSION_ERROR

static final long COMPRESSION_ERROR

See Also:

[Constant Field Values](#)

EMPTY_COMPRESSED_CDF

static final long EMPTY_COMPRESSED_CDF

See Also:

[Constant Field Values](#)

BAD_COMPRESSION_PARM

static final long BAD_COMPRESSION_PARM

See Also:

[Constant Field Values](#)

UNKNOWN_SPARSENESS

static final long UNKNOWN_SPARSENESS

See Also:

Constant Field Values

CANNOT_SPARSERECORDS

```
static final long CANNOT_SPARSERECORDS
```

See Also:

Constant Field Values

CANNOT_SPARSEARRAYS

```
static final long CANNOT_SPARSEARRAYS
```

See Also:

Constant Field Values

TOO_MANY_PARMS

```
static final long TOO_MANY_PARMS
```

See Also:

Constant Field Values

NO_SUCH_RECORD

```
static final long NO_SUCH_RECORD
```

See Also:

Constant Field Values

CANNOT_ALLOCATE_RECORDS

```
static final long CANNOT_ALLOCATE_RECORDS
```

See Also:

Constant Field Values

CANNOT_COPY

```
static final long CANNOT_COPY
```

See Also:

Constant Field Values

SCRATCH_DELETE_ERROR

`static final long SCRATCH_DELETE_ERROR`

See Also:

[Constant Field Values](#)

SCRATCH_CREATE_ERROR

`static final long SCRATCH_CREATE_ERROR`

See Also:

[Constant Field Values](#)

SCRATCH_READ_ERROR

`static final long SCRATCH_READ_ERROR`

See Also:

[Constant Field Values](#)

SCRATCH_WRITE_ERROR

`static final long SCRATCH_WRITE_ERROR`

See Also:

[Constant Field Values](#)

BAD_SPARSEARRAYS_PARM

`static final long BAD_SPARSEARRAYS_PARM`

See Also:

[Constant Field Values](#)

BAD_SCRATCH_DIR

`static final long BAD_SCRATCH_DIR`

See Also:

[Constant Field Values](#)

DATATYPE_MISMATCH

`static final long DATATYPE_MISMATCH`

See Also:

[Constant Field Values](#)

NOT_A_CDF_OR_NOT_SUPPORTED

```
static final long NOT_A_CDF_OR_NOT_SUPPORTED
```

See Also:

[Constant Field Values](#)

CORRUPTED_V3_CDF

```
static final long CORRUPTED_V3_CDF
```

See Also:

[Constant Field Values](#)

ILLEGAL_EPOCH_FIELD

```
static final long ILLEGAL_EPOCH_FIELD
```

See Also:

[Constant Field Values](#)

BAD_CHECKSUM

```
static final long BAD_CHECKSUM
```

See Also:

[Constant Field Values](#)

CHECKSUM_ERROR

```
static final long CHECKSUM_ERROR
```

See Also:

[Constant Field Values](#)

CHECKSUM_NOT_ALLOWED

```
static final long CHECKSUM_NOT_ALLOWED
```

See Also:

[Constant Field Values](#)

IS_A_NETCDF

```
static final long IS_A_NETCDF
```

See Also:

Constant Field Values

TT2000_TIME_ERROR

```
static final long TT2000_TIME_ERROR
```

See Also:

[Constant Field Values](#)

UNABLE_TO_PROCESS_CDF

```
static final long UNABLE_TO_PROCESS_CDF
```

See Also:

[Constant Field Values](#)

ZLIB_COMPRESS_ERROR

```
static final long ZLIB_COMPRESS_ERROR
```

See Also:

[Constant Field Values](#)

ZLIB_UNCOMPRESS_ERROR

```
static final long ZLIB_UNCOMPRESS_ERROR
```

See Also:

[Constant Field Values](#)

CANNOT_INSERT_RECORDS

```
static final long CANNOT_INSERT_RECORDS
```

See Also:

[Constant Field Values](#)

TT2000_USED_OUTDATED_TABLE

```
static final long TT2000_USED_OUTDATED_TABLE
```

See Also:

[Constant Field Values](#)

BADDATE_LEAPSECOND_UPDATED

```
static final long BADDATE_LEAPSECOND_UPDATED
```

See Also:

[Constant Field Values](#)

FUNCTION_NOT_SUPPORTED

```
static final long FUNCTION_NOT_SUPPORTED
```

See Also:

[Constant Field Values](#)

TRY_TO_READ_NONSTRING_DATA

```
static final long TRY_TO_READ_NONSTRING_DATA
```

See Also:

[Constant Field Values](#)

BAD_NUM_STRINGS

```
static final long BAD_NUM_STRINGS
```

See Also:

[Constant Field Values](#)

CANNOT_CONVERT_WIDECHAR

```
static final long CANNOT_CONVERT_WIDECHAR
```

See Also:

[Constant Field Values](#)

CREATE_

```
static final long CREATE_
```

See Also:

[Constant Field Values](#)

OPEN_

```
static final long OPEN_
```

See Also:

[Constant Field Values](#)

DELETE_

```
static final long DELETE_
```

See Also:

[Constant Field Values](#)

CLOSE_

```
static final long CLOSE_
```

See Also:

[Constant Field Values](#)

SELECT_

```
static final long SELECT_
```

See Also:

[Constant Field Values](#)

CONFIRM_

```
static final long CONFIRM_
```

See Also:

[Constant Field Values](#)

GET_

```
static final long GET_
```

See Also:

[Constant Field Values](#)

PUT_

```
static final long PUT_
```

See Also:

[Constant Field Values](#)

SAVE_

```
static final long SAVE_
```

See Also:

Constant Field Values

BACKWARD_

```
static final long BACKWARD_
```

See Also:

[Constant Field Values](#)

GETCDDFFILEBACKWARD_

```
static final long GETCDDFFILEBACKWARD_
```

See Also:

[Constant Field Values](#)

CHECKSUM_

```
static final long CHECKSUM_
```

See Also:

[Constant Field Values](#)

GETCDFCHECKSUM_

```
static final long GETCDFCHECKSUM_
```

See Also:

[Constant Field Values](#)

VALIDATE_

```
static final long VALIDATE_
```

See Also:

[Constant Field Values](#)

GETCDFVALIDATE_

```
static final long GETCDFVALIDATE_
```

See Also:

[Constant Field Values](#)

GETLEAPSECONDSENVVAR_

```
static final long GETLEAPSECONDSENVVAR_
```

See Also:

[Constant Field Values](#)

NULL_

```
static final long NULL_
```

See Also:

[Constant Field Values](#)

CDF_

```
static final long CDF_
```

See Also:

[Constant Field Values](#)

CDF_NAME_

```
static final long CDF_NAME_
```

See Also:

[Constant Field Values](#)

CDF_ENCODING_

```
static final long CDF_ENCODING_
```

See Also:

[Constant Field Values](#)

CDF_DECODING_

```
static final long CDF_DECODING_
```

See Also:

[Constant Field Values](#)

CDF_MAJORITY_

```
static final long CDF_MAJORITY_
```

See Also:

[Constant Field Values](#)

CDF_FORMAT_

static final long CDF_FORMAT_

See Also:

[Constant Field Values](#)

CDF_COPYRIGHT_

static final long CDF_COPYRIGHT_

See Also:

[Constant Field Values](#)

CDF_NUMrVARS_

static final long CDF_NUMrVARS_

See Also:

[Constant Field Values](#)

CDF_NUMzVARS_

static final long CDF_NUMzVARS_

See Also:

[Constant Field Values](#)

CDF_NUMATTRS_

static final long CDF_NUMATTRS_

See Also:

[Constant Field Values](#)

CDF_NUMgATTRS_

static final long CDF_NUMgATTRS_

See Also:

[Constant Field Values](#)

CDF_NUMvATTRS_

static final long CDF_NUMvATTRS_

See Also:

Constant Field Values

CDF_VERSION_

```
static final long CDF_VERSION_
```

See Also:

[Constant Field Values](#)

CDF_RELEASE_

```
static final long CDF_RELEASE_
```

See Also:

[Constant Field Values](#)

CDF_INCREMENT_

```
static final long CDF_INCREMENT_
```

See Also:

[Constant Field Values](#)

CDF_STATUS_

```
static final long CDF_STATUS_
```

See Also:

[Constant Field Values](#)

CDF_READONLY_MODE_

```
static final long CDF_READONLY_MODE_
```

See Also:

[Constant Field Values](#)

CDF_zMODE_

```
static final long CDF_zMODE_
```

See Also:

[Constant Field Values](#)

CDF_NEGtoPOSfp0_MODE_

```
static final long CDF_NEGtoPOSfp0_MODE_
```

See Also:

[Constant Field Values](#)

LIB_COPYRIGHT_

```
static final long LIB_COPYRIGHT_
```

See Also:

[Constant Field Values](#)

LIB_VERSION_

```
static final long LIB_VERSION_
```

See Also:

[Constant Field Values](#)

LIB_RELEASE_

```
static final long LIB_RELEASE_
```

See Also:

[Constant Field Values](#)

LIB_INCREMENT_

```
static final long LIB_INCREMENT_
```

See Also:

[Constant Field Values](#)

LIB_subINCREMENT_

```
static final long LIB_subINCREMENT_
```

See Also:

[Constant Field Values](#)

rVARs_NUMDIMS_

```
static final long rVARs_NUMDIMS_
```

See Also:

[Constant Field Values](#)

rVARs_DIMSIZES_

```
static final long rVARs_DIMSIZES_
```

See Also:

[Constant Field Values](#)

rVARs_MAXREC_

```
static final long rVARs_MAXREC_
```

See Also:

[Constant Field Values](#)

rVARs_RECDATA_

```
static final long rVARs_RECDATA_
```

See Also:

[Constant Field Values](#)

rVARs_RECNUMBER_

```
static final long rVARs_RECNUMBER_
```

See Also:

[Constant Field Values](#)

rVARs_RECCOUNT_

```
static final long rVARs_RECCOUNT_
```

See Also:

[Constant Field Values](#)

rVARs_RECINTERVAL_

```
static final long rVARs_RECINTERVAL_
```

See Also:

[Constant Field Values](#)

rVARs_DIMINDICES_

```
static final long rVARs_DIMINDICES_
```

See Also:

[Constant Field Values](#)

rVARs_DIMCOUNTS_

```
static final long rVARs_DIMCOUNTS_
```

See Also:

[Constant Field Values](#)

rVARs_DIMINTERVALS_

```
static final long rVARs_DIMINTERVALS_
```

See Also:

[Constant Field Values](#)

rVAR_

```
static final long rVAR_
```

See Also:

[Constant Field Values](#)

rVAR_NAME_

```
static final long rVAR_NAME_
```

See Also:

[Constant Field Values](#)

rVAR_DATATYPE_

```
static final long rVAR_DATATYPE_
```

See Also:

[Constant Field Values](#)

rVAR_NUMELEMS_

```
static final long rVAR_NUMELEMS_
```

See Also:

[Constant Field Values](#)

rVAR_RECVARY_

```
static final long rVAR_RECVARY_
```

See Also:

[Constant Field Values](#)

rVAR_DIMVARYS_

```
static final long rVAR_DIMVARYS_
```

See Also:

[Constant Field Values](#)

rVAR_NUMBER_

```
static final long rVAR_NUMBER_
```

See Also:

[Constant Field Values](#)

rVAR_DATA_

```
static final long rVAR_DATA_
```

See Also:

[Constant Field Values](#)

rVAR_HYPERDATA_

```
static final long rVAR_HYPERDATA_
```

See Also:

[Constant Field Values](#)

rVAR_SEQDATA_

```
static final long rVAR_SEQDATA_
```

See Also:

[Constant Field Values](#)

rVAR_SEQPOS_

```
static final long rVAR_SEQPOS_
```

See Also:

[Constant Field Values](#)

rVAR_MAXREC_

```
static final long rVAR_MAXREC_
```

See Also:

[Constant Field Values](#)

rVAR_MAXallocREC_

```
static final long rVAR_MAXallocREC_
```

See Also:

[Constant Field Values](#)

rVAR_DATASPEC_

```
static final long rVAR_DATASPEC_
```

See Also:

[Constant Field Values](#)

rVAR_PADVALUE_

```
static final long rVAR_PADVALUE_
```

See Also:

[Constant Field Values](#)

rVAR_INITIALRECS_

```
static final long rVAR_INITIALRECS_
```

See Also:

[Constant Field Values](#)

rVAR_BLOCKINGFACTOR_

```
static final long rVAR_BLOCKINGFACTOR_
```

See Also:

[Constant Field Values](#)

rVAR_nINDEXRECORDS_

```
static final long rVAR_nINDEXRECORDS_
```

See Also:

Constant Field Values

rVAR_nINDEXENTRIES_

```
static final long rVAR_nINDEXENTRIES_
```

See Also:

Constant Field Values

rVAR_EXISTENCE_

```
static final long rVAR_EXISTENCE_
```

See Also:

Constant Field Values

zVARs_MAXREC_

```
static final long zVARs_MAXREC_
```

See Also:

Constant Field Values

zVARs_RECDATA_

```
static final long zVARs_RECDATA_
```

See Also:

Constant Field Values

zVAR_

```
static final long zVAR_
```

See Also:

Constant Field Values

zVAR_NAME_

```
static final long zVAR_NAME_
```

See Also:

Constant Field Values

zVAR_DATATYPE_

```
static final long zVAR_DATATYPE_
```

See Also:

[Constant Field Values](#)

zVAR_NUMELEMS_

```
static final long zVAR_NUMELEMS_
```

See Also:

[Constant Field Values](#)

zVAR_NUMDIMS_

```
static final long zVAR_NUMDIMS_
```

See Also:

[Constant Field Values](#)

zVAR_DIMSIZES_

```
static final long zVAR_DIMSIZES_
```

See Also:

[Constant Field Values](#)

zVAR_RECVARY_

```
static final long zVAR_RECVARY_
```

See Also:

[Constant Field Values](#)

zVAR_DIMVARYS_

```
static final long zVAR_DIMVARYS_
```

See Also:

[Constant Field Values](#)

zVAR_NUMBER_

```
static final long zVAR_NUMBER_
```

See Also:

[Constant Field Values](#)

zVAR_DATA_

```
static final long zVAR_DATA_
```

See Also:

[Constant Field Values](#)

zVAR_HYPERDATA_

```
static final long zVAR_HYPERDATA_
```

See Also:

[Constant Field Values](#)

zVAR_SEQDATA_

```
static final long zVAR_SEQDATA_
```

See Also:

[Constant Field Values](#)

zVAR_SEQPOS_

```
static final long zVAR_SEQPOS_
```

See Also:

[Constant Field Values](#)

zVAR_MAXREC_

```
static final long zVAR_MAXREC_
```

See Also:

[Constant Field Values](#)

zVAR_MAXallocREC_

```
static final long zVAR_MAXallocREC_
```

See Also:

[Constant Field Values](#)

zVAR_DATASPEC_

```
static final long zVAR_DATASPEC_
```

See Also:

Constant Field Values

zVAR_PADVALUE_

static final long zVAR_PADVALUE_

See Also:

Constant Field Values

zVAR_INITIALRECS_

static final long zVAR_INITIALRECS_

See Also:

Constant Field Values

zVAR_BLOCKINGFACTOR_

static final long zVAR_BLOCKINGFACTOR_

See Also:

Constant Field Values

zVAR_nINDEXRECORDS_

static final long zVAR_nINDEXRECORDS_

See Also:

Constant Field Values

zVAR_nINDEXENTRIES_

static final long zVAR_nINDEXENTRIES_

See Also:

Constant Field Values

zVAR_EXISTENCE_

static final long zVAR_EXISTENCE_

See Also:

Constant Field Values

zVAR_RECNUMBER_

```
static final long zVAR_RECNUMBER_
```

See Also:

[Constant Field Values](#)

zVAR_RECCOUNT_

```
static final long zVAR_RECCOUNT_
```

See Also:

[Constant Field Values](#)

zVAR_RECINTERVAL_

```
static final long zVAR_RECINTERVAL_
```

See Also:

[Constant Field Values](#)

zVAR_DIMINDICES_

```
static final long zVAR_DIMINDICES_
```

See Also:

[Constant Field Values](#)

zVAR_DIMCOUNTS_

```
static final long zVAR_DIMCOUNTS_
```

See Also:

[Constant Field Values](#)

zVAR_DIMINTERVALS_

```
static final long zVAR_DIMINTERVALS_
```

See Also:

[Constant Field Values](#)

ATTR_

```
static final long ATTR_
```

See Also:

[Constant Field Values](#)

ATTR_SCOPE_

```
static final long ATTR_SCOPE_
```

See Also:

[Constant Field Values](#)

ATTR_NAME_

```
static final long ATTR_NAME_
```

See Also:

[Constant Field Values](#)

ATTR_NUMBER_

```
static final long ATTR_NUMBER_
```

See Also:

[Constant Field Values](#)

ATTR_MAXgENTRY_

```
static final long ATTR_MAXgENTRY_
```

See Also:

[Constant Field Values](#)

ATTR_NUMgENTRIES_

```
static final long ATTR_NUMgENTRIES_
```

See Also:

[Constant Field Values](#)

ATTR_MAXrENTRY_

```
static final long ATTR_MAXrENTRY_
```

See Also:

[Constant Field Values](#)

ATTR_NUMrENTRIES_

```
static final long ATTR_NUMrENTRIES_
```

See Also:

Constant Field Values

ATTR_MAXzENTRY_

```
static final long ATTR_MAXzENTRY_
```

See Also:
[Constant Field Values](#)

ATTR_NUMzENTRIES_

```
static final long ATTR_NUMzENTRIES_
```

See Also:
[Constant Field Values](#)

ATTR_EXISTENCE_

```
static final long ATTR_EXISTENCE_
```

See Also:
[Constant Field Values](#)

gENTRY_

```
static final long gENTRY_
```

See Also:
[Constant Field Values](#)

gENTRY_EXISTENCE_

```
static final long gENTRY_EXISTENCE_
```

See Also:
[Constant Field Values](#)

gENTRY_DATATYPE_

```
static final long gENTRY_DATATYPE_
```

See Also:
[Constant Field Values](#)

gENTRY_NUMELEMS_

```
static final long gENTRY_NUMELEMS_
```

See Also:

[Constant Field Values](#)

gENTRY_DATASPEC_

```
static final long gENTRY_DATASPEC_
```

See Also:

[Constant Field Values](#)

gENTRY_DATA_

```
static final long gENTRY_DATA_
```

See Also:

[Constant Field Values](#)

rENTRY_

```
static final long rENTRY_
```

See Also:

[Constant Field Values](#)

rENTRY_NAME_

```
static final long rENTRY_NAME_
```

See Also:

[Constant Field Values](#)

rENTRY_EXISTENCE_

```
static final long rENTRY_EXISTENCE_
```

See Also:

[Constant Field Values](#)

rENTRY_DATATYPE_

```
static final long rENTRY_DATATYPE_
```

See Also:

[Constant Field Values](#)

rENTRY_NUMELEMS_

```
static final long rENTRY_NUMELEMS_
```

See Also:

[Constant Field Values](#)

rENTRY_DATASPEC_

```
static final long rENTRY_DATASPEC_
```

See Also:

[Constant Field Values](#)

rENTRY_DATA_

```
static final long rENTRY_DATA_
```

See Also:

[Constant Field Values](#)

zENTRY_

```
static final long zENTRY_
```

See Also:

[Constant Field Values](#)

zENTRY_NAME_

```
static final long zENTRY_NAME_
```

See Also:

[Constant Field Values](#)

zENTRY_EXISTENCE_

```
static final long zENTRY_EXISTENCE_
```

See Also:

[Constant Field Values](#)

zENTRY_DATATYPE_

```
static final long zENTRY_DATATYPE_
```

See Also:

Constant Field Values

zENTRY_NUMELEMS_

static final long zENTRY_NUMELEMS_

See Also:

Constant Field Values

zENTRY_DATASPEC_

static final long zENTRY_DATASPEC_

See Also:

Constant Field Values

zENTRY_DATA_

static final long zENTRY_DATA_

See Also:

Constant Field Values

STATUS_TEXT_

static final long STATUS_TEXT_

See Also:

Constant Field Values

CDF_CACHESIZE_

static final long CDF_CACHESIZE_

See Also:

Constant Field Values

rVARs_CACHESIZE_

static final long rVARs_CACHESIZE_

See Also:

Constant Field Values

zVARs_CACHESIZE_

static final long zVARs_CACHESIZE_

See Also:

[Constant Field Values](#)

rVAR_CACHESIZE_

static final long rVAR_CACHESIZE_

See Also:

[Constant Field Values](#)

zVAR_CACHESIZE_

static final long zVAR_CACHESIZE_

See Also:

[Constant Field Values](#)

zVARs_RECNUMBER_

static final long zVARs_RECNUMBER_

See Also:

[Constant Field Values](#)

rVAR_ALLOCATERECS_

static final long rVAR_ALLOCATERECS_

See Also:

[Constant Field Values](#)

zVAR_ALLOCATERECS_

static final long zVAR_ALLOCATERECS_

See Also:

[Constant Field Values](#)

DATATYPE_SIZE_

static final long DATATYPE_SIZE_

See Also:

[Constant Field Values](#)

CURgENTRY_EXISTENCE_

static final long CURgENTRY_EXISTENCE_

See Also:

[Constant Field Values](#)

CURrENTRY_EXISTENCE_

static final long CURrENTRY_EXISTENCE_

See Also:

[Constant Field Values](#)

CURzENTRY_EXISTENCE_

static final long CURzENTRY_EXISTENCE_

See Also:

[Constant Field Values](#)

CDF_INFO_

static final long CDF_INFO_

See Also:

[Constant Field Values](#)

CDF_COMPRESSION_

static final long CDF_COMPRESSION_

See Also:

[Constant Field Values](#)

zVAR_COMPRESSION_

static final long zVAR_COMPRESSION_

See Also:

[Constant Field Values](#)

zVAR_SPARSERECORDS_

static final long zVAR_SPARSERECORDS_

See Also:

[Constant Field Values](#)

zVAR_SPARSEARRAYS_

`static final long zVAR_SPARSEARRAYS_`

See Also:

[Constant Field Values](#)

zVAR_ALLOCATEBLOCK_

`static final long zVAR_ALLOCATEBLOCK_`

See Also:

[Constant Field Values](#)

zVAR_NUMRECS_

`static final long zVAR_NUMRECS_`

See Also:

[Constant Field Values](#)

zVAR_NUMMallocRECS_

`static final long zVAR_NUMMallocRECS_`

See Also:

[Constant Field Values](#)

rVAR_COMPRESSION_

`static final long rVAR_COMPRESSION_`

See Also:

[Constant Field Values](#)

rVAR_SPARSERECORDS_

`static final long rVAR_SPARSERECORDS_`

See Also:

[Constant Field Values](#)

rVAR_SPARSEARRAYS_

```
static final long rVAR_SPARSEARRAYS_
```

See Also:

[Constant Field Values](#)

rVAR_ALLOCATEBLOCK_

```
static final long rVAR_ALLOCATEBLOCK_
```

See Also:

[Constant Field Values](#)

rVAR_NUMRECS_

```
static final long rVAR_NUMRECS_
```

See Also:

[Constant Field Values](#)

rVAR_NUMMallocRECS_

```
static final long rVAR_NUMMallocRECS_
```

See Also:

[Constant Field Values](#)

rVAR_ALLOCATEDFROM_

```
static final long rVAR_ALLOCATEDFROM_
```

See Also:

[Constant Field Values](#)

rVAR_ALLOCATEDTO_

```
static final long rVAR_ALLOCATEDTO_
```

See Also:

[Constant Field Values](#)

zVAR_ALLOCATEDFROM_

```
static final long zVAR_ALLOCATEDFROM_
```

See Also:

Constant Field Values

zVAR_ALLOCATEDTO_

static final long zVAR_ALLOCATEDTO_

See Also:

Constant Field Values

zVAR_nINDEXLEVELS_

static final long zVAR_nINDEXLEVELS_

See Also:

Constant Field Values

rVAR_nINDEXLEVELS_

static final long rVAR_nINDEXLEVELS_

See Also:

Constant Field Values

CDF_SCRATCHDIR_

static final long CDF_SCRATCHDIR_

See Also:

Constant Field Values

rVAR_RESERVEPERCENT_

static final long rVAR_RESERVEPERCENT_

See Also:

Constant Field Values

zVAR_RESERVEPERCENT_

static final long zVAR_RESERVEPERCENT_

See Also:

Constant Field Values

rVAR_RECORDS_

```
static final long rVAR_RECORDS_
```

See Also:

[Constant Field Values](#)

zVAR_RECORDS_

```
static final long zVAR_RECORDS_
```

See Also:

[Constant Field Values](#)

STAGE_CACHESIZE_

```
static final long STAGE_CACHESIZE_
```

See Also:

[Constant Field Values](#)

COMPRESS_CACHESIZE_

```
static final long COMPRESS_CACHESIZE_
```

See Also:

[Constant Field Values](#)

CDF_CHECKSUM_

```
static final long CDF_CHECKSUM_
```

See Also:

[Constant Field Values](#)

rVAR_RECORDS_RENUMBER_

```
static final long rVAR_RECORDS_RENUMBER_
```

See Also:

[Constant Field Values](#)

zVAR_RECORDS_RENUMBER_

```
static final long zVAR_RECORDS_RENUMBER_
```

See Also:

[Constant Field Values](#)

CDF_LEAPSECONDLASTUPDATED_

```
static final long CDF_LEAPSECONDLASTUPDATED_
```

See Also:

[Constant Field Values](#)

rENTRY_STRINGSDATA_

```
static final long rENTRY_STRINGSDATA_
```

See Also:

[Constant Field Values](#)

zENTRY_STRINGSDATA_

```
static final long zENTRY_STRINGSDATA_
```

See Also:

[Constant Field Values](#)

rENTRY_NUMSTRINGS_

```
static final long rENTRY_NUMSTRINGS_
```

See Also:

[Constant Field Values](#)

zENTRY_NUMSTRINGS_

```
static final long zENTRY_NUMSTRINGS_
```

See Also:

[Constant Field Values](#)

CDFwithSTATS_

```
static final long CDFwithSTATS_
```

See Also:

[Constant Field Values](#)

CDF_ACCESS_

```
static final long CDF_ACCESS_
```

See Also:

[Constant Field Values](#)

STRINGDELIMITER

```
static final java.lang.String STRINGDELIMITER
```

BeginUnixTimeEPOCH

```
static final double BeginUnixTimeEPOCH
```

See Also:

[Constant Field Values](#)

BeginUnixTimeEPOCH16

```
static final double BeginUnixTimeEPOCH16
```

See Also:

[Constant Field Values](#)

Overview	Package	Class	Tree	Deprecated	Index	Help
Prev Class	Next Class	Frames	No Frames	All Classes		
Summary: Nested Field Constr Method			Detail: Field Constr Method			

gsfc.nssdc.cdf

Class CDFData

java.lang.Object
gsfc.nssdc.cdf.CDFData

All Implemented Interfaces:

CDFConstants, CDFObject

```
public class CDFData
extends java.lang.Object
implements CDFObject, CDFConstants
```

This class acts as the glue between the Java code and the Java Native Interface (JNI) code. This class applies only to the Variable object. It handles its data. This class translates a multi-dimensional array data into a 1-dimensional (1D) array prior to sending data to the JNI code for processing. Similarly, data retrieved in 1D array from the JNI code is properly dimensioned for usage or further manipulation.

Version:

1.0, 2.0 03/18/05 Selection of current CDF and variable are done as part of operations passed to JNI. JNI call is synchronized so only one process is allowed in a JVM, due to multi-thread safety. The select method will never be called., 3.0 06/09/09 The number of dimesions returned from the get method depends on the variable dimensions and dimesional elements: e.g., 2-dim (2x1 or 1x2) will have a 2-dim, not 1-dim, object returned, while 2-dim (1x1) returns an object of a single item, not an array.

See Also:

Variable, CDFException

Field Summary

Fields inherited from interface gsfc.nssdc.cdf.CDFConstants

AHUFF COMPRESSION, ALPHAOSF1 DECODING, ALPHAOSF1 ENCODING, ALPHAVMSd DECODING, ALPHAVMSd ENCODING, ALPHAVMSG DECODING, ALPHAVMSG ENCODING, ALPHAVMSI DECODING, ALPHAVMSI ENCODING, ARM BIG DECODING, ARM BIG ENCODING, ARM LITTLE DECODING, ARM LITTLE ENCODING, ATTR, ATTR EXISTENCE, ATTR EXISTS, ATTR MAXgENTRY, ATTR MAXrENTRY, ATTR MAXzENTRY, ATTR NAME, ATTR NAME TRUNC, ATTR NUMBER, ATTR NUMgENTRIES, ATTR NUMrENTRIES, ATTR NUMzENTRIES, ATTR SCOPE, BACKWARD, BACKWARDFILEoff, BACKWARDFILEon, BAD ALLOCATE RECS, BAD ARGUMENT, BAD ATTR NAME, BAD ATTR NUM, BAD BLOCKING FACTOR, BAD CACHE SIZE, BAD CDF EXTENSION, BAD CDF ID, BAD CDF NAME, BAD CDFSTATUS, BAD CHECKSUM, BAD COMPRESSION PARM, BAD DATA TYPE, BAD DECODING, BAD DIM COUNT, BAD DIM INDEX, BAD DIM INTERVAL, BAD DIM SIZE, BAD ENCODING, BAD ENTRY NUM, BAD FNC OR ITEM, BAD FORMAT, BAD INITIAL RECS, BAD MAJORITY, BAD MALLOC, BAD NEGtoPOSfp0 MODE, BAD NUM DIMS, BAD NUM ELEMS, BAD NUM STRINGS, BAD NUM VARS, BAD READONLY MODE, BAD REC COUNT, BAD REC INTERVAL, BAD REC NUM, BAD SCOPE, BAD SCRATCH DIR, BAD SPARSEARRAYS PARM, BAD VAR NAME, BAD VAR NUM, BAD zMODE, BADDATE LEAPSECOND UPDATED, BeginUnixTimeEPOCH, BeginUnixTimeEPOCH16, BLOCKINGFACTOR TOO LARGE, BLOCKINGFACTOR TOO SMALL, BLOCKINGFACTOR TOO SMALL2, CANNOT ALLOCATE RECORDS, CANNOT CHANGE, CANNOT COMPRESS, CANNOT CONVERT WIDECCHAR, CANNOT COPY, CANNOT INSERT RECORDS, CANNOT SPARSEARRAYS, CANNOT SPARSERECORDS, CDF, CDF ACCESS, CDF ATTR NAME LEN, CDF ATTR NAME LEN256, CDF BYTE, CDF CACHESIZE, CDF CHAR, CDF CHECKSUM, CDF CLOSE ERROR, CDF COMPRESSION, CDF COPYRIGHT, CDF COPYRIGHT LEN, CDF CREATE ERROR, CDF DECODING, CDF DELETE ERROR, CDF DOUBLE, CDF ENCODING, CDF EPOCH, CDF EPOCH16, CDF EXISTS, CDF FLOAT, CDF FORMAT, CDF INCREMENT, CDF INFO, CDF INT1, CDF INT2, CDF INT4, CDF INT8, CDF INTERNAL ERROR, CDF LEAPSECONDLASTUPDATED, CDF MAJORITY, CDF MAX DIMS, CDF MAX PARMS, CDF MIN DIMS, CDF NAME, CDF NAME TRUNC, CDF NEGtoPOSfp0 MODE, CDF NUMATTRS, CDF NUMgATTRS, CDF NUMrVARS, CDF NUMvATTRS, CDF NUMzVARS, CDF OK, CDF OPEN ERROR, CDF PATHNAME LEN, CDF READ ERROR, CDF READONLY MODE, CDF REAL4, CDF REAL8, CDF RELEASE, CDF SAVE ERROR, CDF SCRATCHDIR, CDF STATUS, CDF STATUSTEXT LEN, CDF TIME TT2000, CDF UCHAR, CDF UINT1, CDF UINT2, CDF UINT4, CDF VAR NAME LEN, CDF VAR NAME LEN256, CDF VERSION, CDF WARN, CDF WRITE ERROR, CDF zMODE, CDFwithSTATS, CHECKSUM, CHECKSUM ERROR, CHECKSUM NOT ALLOWED, CLOSE, COLUMN MAJOR, COMPRESS CACHESIZE, COMPRESSION ERROR, CONFIRM, CORRUPTED V2 CDF, CORRUPTED V3 CDF, CREATE, CURgENTRY EXISTENCE, CURrENTRY EXISTENCE, CURzENTRY EXISTENCE, DATATYPE MISMATCH, DATATYPE SIZE, DECOMPRESSION ERROR, DECSTATION DECODING, DECSTATION ENCODING, DEFAULT BYTE PADVALUE, DEFAULT CHAR PADVALUE, DEFAULT DOUBLE PADVALUE, DEFAULT_EPOCH_PADVALUE, DEFAULT_EPOCH16_PADVALUE, DEFAULT_FLOAT_PADVALUE, DEFAULT_INT1_PADVALUE,

DEFAULT INT2 PADVALUE, DEFAULT INT4 PADVALUE, DEFAULT INT8 PADVALUE, DEFAULT REAL4 PADVALUE, DEFAULT REAL8 PADVALUE, DEFAULT TT2000 PADVALUE, DEFAULT UCHAR PADVALUE, DEFAULT UINT1 PADVALUE, DEFAULT UINT2 PADVALUE, DEFAULT UINT4 PADVALUE, DELETE, DID NOT COMPRESS, EMPTY_COMPRESSED_CDF, END OF VAR, EPOCH STRING LEN, EPOCH STRING LEN EXTEND, EPOCH1 STRING LEN, EPOCH1 STRING LEN EXTEND, EPOCH2 STRING LEN, EPOCH2 STRING LEN EXTEND, EPOCH3 STRING LEN, EPOCH3 STRING LEN EXTEND, EPOCH4 STRING LEN, EPOCH4 STRING LEN EXTEND, EPOCHx FORMAT MAX, EPOCHx STRING MAX, FILLED TT2000 VALUE, FORCED PARAMETER, FUNCTION NOT SUPPORTED, gENTRY, gENTRY DATA, gENTRY DATASPEC, gENTRY DATATYPE, gENTRY EXISTENCE, gENTRY NUMELEMS, GET, GETCDFCHECKSUM, GETCDFFILEBACKWARD, GETCDFVALIDATE, GETLEAPSECONDSENVVAR, GLOBAL SCOPE, GZIP COMPRESSION, HOST DECODING, HOST ENCODING, HP DECODING, HP ENCODING, HUFF COMPRESSION, IA64VMSd DECODING, IA64VMSd ENCODING, IA64VMSg DECODING, IA64VMSg ENCODING, IA64VMSi DECODING, IA64VMSi ENCODING, IBM PC OVERFLOW, IBMPC DECODING, IBMPC ENCODING, IBMRS DECODING, IBMRS ENCODING, ILLEGAL EPOCH FIELD, ILLEGAL EPOCH VALUE, ILLEGAL FOR SCOPE, ILLEGAL_IN_zMODE, ILLEGAL ON V1 CDF, ILLEGAL TT2000 VALUE, IS A NETCDF, LIB COPYRIGHT, LIB INCREMENT, LIB RELEASE, LIB subINCREMENT, LIB VERSION, MAC DECODING, MAC ENCODING, MD5 CHECKSUM, MULTI FILE, MULTI FILE FORMAT, NA FOR VARIABLE, NEGATIVE FP ZERO, NEGtoPOSfp0off, NEGtoPOSfp0on, NETWORK DECODING, NETWORK ENCODING, NEXT DECODING, Next ENCODING, NO ATTR SELECTED, NO CDF SELECTED, NO CHECKSUM, NO COMPRESSION, NO DELETE ACCESS, NO ENTRY SELECTED, NO MORE ACCESS, NO PADVALUE SPECIFIED, NO SPARSEARRAYS, NO SPARSERECORDS, NO STATUS SELECTED, NO SUCH ATTR, NO SUCH CDF, NO SUCH ENTRY, NO SUCH RECORD, NO SUCH VAR, NO VAR SELECTED, NO VARS IN CDF, NO WRITE ACCESS, NONE CHECKSUM, NOT A CDF, NOT A CDF OR NOT SUPPORTED, NOVARY, NULL OPEN, OPTIMAL ENCODING TREES, OTHER CHECKSUM, PAD SPARSERECORDS, PPC DECODING, PPC ENCODING, PRECEDING RECORDS ALLOCATED, PREV SPARSERECORDS, PUT, READ ONLY DISTRIBUTION, READ_ONLY_MODE, READONLYoff, READONLYon, rENTRY, rENTRY DATA, rENTRY DATASPEC, rENTRY DATATYPE, rENTRY EXISTENCE, rENTRY NAME, rENTRY NUMELEMS, rENTRY NUMSTRINGS, rENTRY STRINGSDATA, RLE COMPRESSION, RLE OF ZEROS, ROW MAJOR, rVAR, rVAR ALLOCATEBLOCK, rVAR ALLOCATEDFROM, rVAR ALLOCATEDTO, rVAR ALLOCATERECS, rVAR BLOCKINGFACTOR, rVAR CACHESIZE, rVAR COMPRESSION, rVAR DATA, rVAR DATASPEC, rVAR DATATYPE, rVAR DIMVARYS, rVAR EXISTENCE, rVAR HYPERDATA, rVAR INITIALRECS, rVAR MAXallocREC, rVAR MAXREC, rVAR NAME, rVAR nINDEXENTRIES, rVAR nINDEXLEVELS, rVAR nINDEXRECORDS, rVAR NUMallocRECS, rVAR NUMBER, rVAR NUMELEMS, rVAR NUMRECS, rVAR PADVALUE, rVAR RECORDS, rVAR RECORDS RENUMBER, rVAR RECVAR, rVAR RESERVEPERCENT, rVAR SEQDATA, rVAR SEQPOS, rVAR SPARSEARRAYS, rVAR SPARSERECORDS, rVARs CACHESIZE, rVARs DIMCOUNTS, rVARs DIMINDICES, rVARs DIMINTERVALS, rVARs DIMSIZES, rVARs MAXREC, rVARs NUMDIMS, rVARs RECCOUNT, rVARs RECDATA, rVARs RECINTERVAL, rVARs RECNUMBER, SAVE, SCRATCH CREATE ERROR, SCRATCH DELETE ERROR, SCRATCH READ ERROR, SCRATCH WRITE ERROR, SELECT, SGI DECODING, SGI ENCODING, SINGLE FILE, SINGLE FILE FORMAT, SOME ALREADY ALLOCATED, STAGE CACHESIZE, STATUS TEXT, STRING NOT UTF8 ENCODING, STRINGDELIMITER, SUN DECODING, SUN ENCODING, TOO MANY PARMS, TOO MANY VARS, TRY TO READ NONSTRING DATA, TT2000 0 STRING LEN, TT2000 1 STRING LEN, TT2000 2 STRING LEN, TT2000 3 STRING LEN, TT2000 4 STRING LEN, TT2000 CDF MAYNEEDUPDATE, TT2000 TIME ERROR, TT2000 USED OUTDATED TABLE, UNABLE TO PROCESS CDF, UNKNOWN COMPRESSION, UNKNOWN SPARSENESS, UNSUPPORTED OPERATION, VALIDATE, VALIDATEFILEoff, VALIDATEFILEon, VAR ALREADY CLOSED, VAR CLOSE ERROR, VAR CREATE ERROR, VAR DELETE ERROR, VAR EXISTS, VAR NAME TRUNC, VAR OPEN ERROR, VAR READ ERROR, VAR SAVE ERROR, VAR WRITE ERROR, VARIABLE SCOPE, VARY, VAX DECODING, VAX ENCODING, VIRTUAL RECORD DATA, zENTRY, zENTRY DATA, zENTRY DATASPEC, zENTRY DATATYPE, zENTRY EXISTENCE, zENTRY NAME, zENTRY NUMELEMS, zENTRY NUMSTRINGS, zENTRY STRINGSDATA, ZLIB COMPRESS ERROR, ZLIB UNCOMPRESS ERROR, zMODEoff, zMODEon1, zMODEon2, zVAR, zVAR ALLOCATEBLOCK, zVAR ALLOCATEDFROM, zVAR ALLOCATEDTO, zVAR ALLOCATERECS, zVAR BLOCKINGFACTOR, zVAR CACHESIZE, zVAR COMPRESSION, zVAR DATA, zVAR DATASPEC, zVAR DATATYPE, zVAR DIMCOUNTS, zVAR DIMINDICES, zVAR DIMINTERVALS, zVAR DIMSIZES, zVAR DIMVARYS, zVAR EXISTENCE, zVAR HYPERDATA, zVAR INITIALRECS, zVAR MAXallocREC, zVAR MAXREC, zVAR NAME, zVAR nINDEXENTRIES, zVAR nINDEXLEVELS, zVAR nINDEXRECORDS, zVAR NUMallocRECS, zVAR NUMBER, zVAR NUMDIMS, zVAR NUMELEMS, zVAR NUMRECS, zVAR PADVALUE, zVAR RECCOUNT, zVAR RECINTERVAL, zVAR RECNUMBER, zVAR RECORDS, zVAR RECORDS RENUMBER, zVAR RECVAR, zVAR RESERVEPERCENT, zVAR SEQDATA, zVAR SEQPOS, zVAR SPARSEARRAYS, zVAR SPARSERECORDS, zVARs CACHESIZE, zVARs MAXREC, zVARs RECDATA, zVARs RECNUMBER

Method Summary

Methods	
Modifier and Type	Method and Description
void	delete() See the description of the getName() method in this class.
void	dump() Dump data information and values, one row at a time, to the stderr.
void	dumpData() Dumps variable data, one row at a time per record.
void	dumpDataWithFormat (java.lang.String format) Dumps variable data, one row at a time per record, with format.
java.lang.Object	getData() Returns an object that is properly dimensioned.
long[]	getDimCounts() Gets the value of the dimension counts that represents the number of elements read or write starting at the location <dimension index> for a hyper get/put function.

long[]	getDimIndices() Gets the starting dimension index within a record for a hyper get/put function.
long[]	getDimIntervals() Gets the value of the dimension intervals that represent the number of elements to skip between reads or writes for a hyper get/put function.
int[]	getDimSizes() Gets the dimension sizes of this variable.
java.lang.String	getName() CDFData implements CDFObject to enable CDFDelegate calls.
int	getnDims() Gets the dimensionality of this variable.
java.lang.Object	getRawData() Returns an object of a 1-dimensional array, which presents a sequence of raw data values retrieved and presented by JNI from a CDF file.
long	getRecCount() Gets the number of records to read or write for a hyper get/put function.
long	getRecInterval() Gets the number of records to skip for a hyper get/put function.
long	getRecStart() Gets the record number at which a hyper get/put function starts.
void	rename() (java.lang.String name) See the description of the getName() method in this class.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Method Detail

getData

```
public java.lang.Object getData()
```

Returns an object that is properly dimensioned. The returned object can be casted in an application for usage or further manipulation.

The following example retrieves the Temperature data. The user should know how the data was stored before casting the generic object to a variable.

```
Variable var = cdf.getVariable("Temperature");
CDFData data = var.getHyperDataObject (recNum,
                                       recCount,
                                       recInterval,
                                       dimIndicies,
                                       dimSizes,
                                       dimCounts);

long[][] temperature = (long [][]) data.getData();
```

Returns:

a generic Object that is properly dimensioned

getRawData

```
public java.lang.Object getRawData()
```

Returns an object of a 1-dimensional array, which presents a sequence of raw data values retrieved and presented by JNI from a CDF file. The data stream may or may not reflect how the data is stored in the file, depending the file majority. It is up to the calling application to decipher the data stream. Note: for column-major CDF files, the sequence of the returned data stream is reordered so data can be properly assigned into Java's arrays. Normally, getData method should be called so the retrieved data are properly dimensioned.

The following example retrieves the 2-D Temperature data. The user should know how to organize the data, e.g., number of records, row/column major, data type, data value sequence, etc.

```
Variable var = cdf.getVariable("Temperature");
CDFData data = var.getHyperDataObject (recNum,
                                       recCount,
                                       recInterval,
                                       dimIndicies,
                                       dimSizes,
                                       dimCounts);

long[] temperature = (long []) data.getRawData();
```

Returns:

a generic Object that is properly dimensioned

getnDims

```
public int getnDims()
```

Gets the dimensionality of this variable.

```
Variable var = cdf.getVariable("Temperature");
CDFData data = var.getHyperDataObject (recNum,
                                       recCount,
                                       recInterval,
                                       dimIndicies,
                                       dimSizes,
                                       dimCounts);

long[][] temperature = (long [][]) data.getData();
nDims = data.getnDims(); // Gives the dimensionality of temperature
```

Returns:

the dimensionality of this variable

getDimSizes

```
public int[] getDimSizes()
```

Gets the dimension sizes of this variable. For example, 3 X 10 (3 rows and 10 columns) two-dimentional array is returned as an one-dimensional integer array, containing 3 in the first element and 10 in the second element.

Returns:

the dimension sizes of this variable

getRecStart

```
public long getRecStart()
```

Gets the record number at which a hyper get/put function starts.

Returns:

the starting record number for a hyper get/put function

getRecCount

```
public long getRecCount()
```

Gets the number of records to read or write for a hyper get/put function.

Returns:

the number of records involved for a hyper get/put function involves

getRecInterval

```
public long getRecInterval()
```

Gets the number of records to skip for a hyper get/put function. The record interval of 1 represents every record. The value of 2 represents every other record, the value of 3 represents every third record and so on.

Returns:

the value of record interval

getDimIndices

```
public long[] getDimIndices()
```

Gets the starting dimension index within a record for a hyper get/put function. Dimension index indicates where the data search started from within a record. Let's say a record is comprised of a 2x5 two-dimensional array (2 rows and 5 columns). If the index returned from this method has a value of {1,0}, then the data search was performed starting at the first element of the second row. Similarly, the value of {0,0} represents that the data search search was performed starting at the first element of the first record.

Returns:

the dimension index for this variable

getDimCounts

```
public long[] getDimCounts()
```

Gets the value of the dimension counts that represents the number of elements read or write starting at the location <dimension index> for a hyper get/put function.

Returns:

the dimension counts for this variable

getDimIntervals

```
public long[] getDimIntervals()
```

Gets the value of the dimension intervals that represent the number of elements to skip between reads or writes for a hyper get/put function. The value of 1 represents every element. The value of 2 represents every other element, and the value of 3 represents every third element and so on.

Returns:

the dimension intervals for this variable

dumpData

```
public void dumpData()
```

Dumps variable data, one row at a time per record. This is a generic utility for dumping data to a screen. Data can be scalar or 1-dimensional or multi-dimensional array of any data type. This method dumps the data without using format.

The following example retrieves the first record, comprised of 3x5 (3 rows and 5 columns) array, into a generic object and dumps its contents to screen one row at a time. In this case three rows will be displayed on a screen, each row containing 5 elements.

```
CDFData data;
long[] dimIndices = {0,0};
long[] dimIntervals = {3,5};
long[] dimSizes = {1,1};
data = var.getHyperDataObject(0L,          // record start
                              1,          // record counts
                              1,          // record interval
                              dimIndices,
                              dimSizes,
                              dimIntervals);

data.dumpData();
```

dumpDataWithFormat

```
public void dumpDataWithFormat(java.lang.String format)
```

Dumps variable data, one row at a time per record, with format. This is a generic * utility for dumping data to a screen. Data can be scalar or 1-dimensional or multi-dimensional array of any data type. The format is only applicable to variables of numerical data type. the format comes from variable's FORMAT attribute entry. Note: The FORMAT might be in original C or Fortran format form. This format is mainly used for floating point data. The following example retrieves the first record, comprised of 3x5 (3 rows and 5 columns) array, into a generic object and dumps its contents to screen one row at a time. In this case three rows will be displayed on a screen, each row containing 5 elements.

```
CDFData data;
String format = (String) var.getEntryData("FORMAT");
long[] dimIndices = {0,0};
long[] dimIntervals = {3,5};
long[] dimSizes = {1,1};
data = var.getHyperDataObject(0L,          // record start
                              1,          // record counts
                              1,          // record interval
                              dimIndices,
                              dimSizes,
                              dimIntervals);

data.dumpDataWithFormat(format);
```

Parameters:

format - A string format

dump

```
public void dump()
```

Dump data information and values, one row at a time, to the stderr. This method is provided for debugging purposes only. The information is printed in the following manner: <VAR_TYPE><VAR_#Elements> nDims:[sizes]
recStart/recCount/recInterval/dimIndices/dimsSizes/dimIntervals/dataArraySignature <values row-by-row>

getName

```
public java.lang.String getName()
```

CDFData implements CDFObject to enable CDFDelegate calls. CDFObject specifies the following three methods: getName(), rename(String), and delete(). Since CDFData implements CDFObject, it must have the methods defined in CDFObject. That's why this method is here; it doesn't do anything.

Specified by:

```
getName in interface CDFObject
```

Returns:

the name of the current object

rename

```
public void rename(java.lang.String name)
               throws CDFException
```

See the description of the getName() method in this class.

Specified by:

```
rename in interface CDFObject
```

Parameters:

name - the new object name

Throws:

CDFException - No exception is thrown since this method is a placeholder

delete

```
public void delete()
               throws CDFException
```

See the description of the getName() method in this class.

Specified by:

```
delete in interface CDFObject
```

Throws:

CDFException - No exception is thrown since this method is a placeholder

gsfc.nssdc.cdf

Interface CDFDelegate

All Known Implementing Classes:

CDFNativeLibrary

public interface **CDFDelegate**

This class defines the method that is responsible for acting as the gateway between the CDF Java code and the CDF library. The CDFNativeLibrary class that implementing this interface will cause the JNI to be loaded. This class is available only to the CDF object that uses the CDFDelegate to make requests to JNI. All CDF's other objects, i.e., Attribute, Entry, Variable (and its CDFData), need to refer to the containing CDF object to make requests.

Version:

1.0

See Also:

CDFNativeLibrary

Method Summary

Methods	
Modifier and Type	Method and Description
void	cdflib (CDF theCDF, CDFObject cdfObject, java.util.Vector cmds) Defines the method that is responsible for acting as the gateway between the CDF Java code and the CDF library.

Method Detail

cdflib

```
void cdflib(CDF theCDF,
            CDFObject cdfObject,
            java.util.Vector cmds)
    throws CDFException
```

Defines the method that is responsible for acting as the gateway between the CDF Java code and the CDF library. This method is responsible for sending Java's request to the CDF library and returning the results from the CDF library to the Java side.

Parameters:

theCDF - the current CDF to be processed

cdfObject - the calling CDF object (e.g. Attribute, variable, etc.)

cmds - a Vector that contains the CDF internal interface library commands to be executed

Throws:

`CDFException` - if an error occurs processing the requested commands in JNI

Overview Package **Class** Tree Deprecated Index Help

Prev Class **Next Class** Frames No Frames All Classes

Summary: Nested | Field | Constr | Method Detail: Field | Constr | Method

gsfc.nssdc.cdf

Class CDFException

java.lang.Object
 java.lang.Throwable
 java.lang.Exception
 gsfc.nssdc.cdf.CDFException

All Implemented Interfaces:

CDFConstants, java.io.Serializable

```
public class CDFException
extends java.lang.Exception
implements CDFConstants
```

This class defines the informational, warning, and error messages that can arise from CDF operations.

See Also:

[Serialized Form](#)

Field Summary

Fields inherited from interface gsfc.nssdc.cdf.CDFConstants

AHUFF COMPRESSION, ALPHAOSf1 DECODING, ALPHAOSf1 ENCODING, ALPHAVMSd DECODING, ALPHAVMSd ENCODING, ALPHAVMSg DECODING, ALPHAVMSg ENCODING, ALPHAVMSi DECODING, ALPHAVMSi ENCODING, ARM BIG DECODING, ARM BIG ENCODING, ARM LITTLE DECODING, ARM LITTLE ENCODING, ATTR, ATTR EXISTENCE, ATTR EXISTS, ATTR MAXgENTRY, ATTR MAXrENTRY, ATTR MAXZENTRY, ATTR NAME, ATTR NAME TRUNC, ATTR NUMBER, ATTR NUMgENTRIES, ATTR NUMrENTRIES, ATTR NUMzENTRIES, ATTR SCOPE, BACKWARD, BACKWARDFILEoff, BACKWARDFILEon, BAD ALLOCATE RECS, BAD ARGUMENT, BAD ATTR NAME, BAD ATTR NUM, BAD BLOCKING FACTOR, BAD CACHE SIZE, BAD CDF EXTENSION, BAD CDF ID, BAD CDF NAME, BAD CDFSTATUS, BAD CHECKSUM, BAD COMPRESSION PARM, BAD DATA TYPE, BAD DECODING, BAD DIM COUNT, BAD DIM INDEX, BAD DIM INTERVAL, BAD DIM SIZE, BAD ENCODING, BAD ENTRY NUM, BAD FNC OR ITEM, BAD FORMAT, BAD INITIAL RECS, BAD MAJORITY, BAD MALLOC, BAD NEGtoPOSfp0 MODE, BAD NUM DIMS, BAD NUM ELEMS, BAD NUM STRINGS, BAD NUM VARS, BAD READONLY MODE, BAD REC COUNT, BAD REC INTERVAL, BAD REC NUM, BAD SCOPE, BAD SCRATCH DIR, BAD SPARSEARRAYS PARM, BAD VAR NAME, BAD VAR NUM, BAD zMODE, BADDATE LEAPSECOND UPDATED, BeginUnixTimeEPOCH, BeginUnixTimeEPOCH16, BLOCKINGFACTOR TOO LARGE, BLOCKINGFACTOR TOO SMALL, BLOCKINGFACTOR TOO SMALL2, CANNOT ALLOCATE RECORDS, CANNOT CHANGE, CANNOT COMPRESS, CANNOT CONVERT WIDECCHAR, CANNOT COPY, CANNOT INSERT RECORDS, CANNOT SPARSEARRAYS, CANNOT SPARSERECORDS, CDF, CDF ACCESS, CDF ATTR NAME LEN, CDF ATTR NAME LEN256, CDF BYTE, CDF CACHESIZE, CDF CHAR, CDF CHECKSUM, CDF CLOSE ERROR, CDF COMPRESSION, CDF COPYRIGHT, CDF COPYRIGHT LEN, CDF CREATE ERROR, CDF DECODING, CDF DELETE ERROR, CDF DOUBLE, CDF ENCODING, CDF EPOCH, CDF EPOCH16, CDF EXISTS, CDF FLOAT, CDF FORMAT, CDF INCREMENT, CDF INFO, CDF INT1, CDF INT2, CDF INT4, CDF INT8, CDF INTERNAL ERROR, CDF LEAPSECONDLASTUPDATED, CDF MAJORITY, CDF MAX DIMS, CDF MAX PARMS, CDF MIN DIMS, CDF NAME, CDF NAME TRUNC, CDF NEGtoPOSfp0 MODE, CDF NUMATTRS, CDF NUMgATTRS, CDF NUMrVARS, CDF NUMvATTRS, CDF NUMzVARS, CDF OK, CDF OPEN ERROR, CDF PATHNAME LEN, CDF READ ERROR, CDF READONLY MODE, CDF REAL4, CDF REAL8, CDF RELEASE, CDF SAVE ERROR, CDF SCRATCHDIR, CDF STATUS, CDF STATUSTEXT LEN, CDF TIME TT2000, CDF UCHAR, CDF UINT1, CDF UINT2, CDF UINT4, CDF VAR NAME LEN, CDF VAR NAME LEN256, CDF VERSION, CDF WARN, CDF WRITE ERROR, CDF zMODE, CDFwithSTATS, CHECKSUM, CHECKSUM ERROR, CHECKSUM NOT ALLOWED, CLOSE, COLUMN MAJOR, COMPRESS CACHESIZE, COMPRESSION ERROR, CONFIRM, CORRUPTED V2 CDF, CORRUPTED V3 CDF, CREATE, CURgENTRY EXISTENCE, CURgENTRY EXISTENCE, CURZENTRY EXISTENCE, DATATYPE MISMATCH, DATATYPE SIZE, DECOMPRESSION ERROR, DECSTATION DECODING, DECSTATION ENCODING, DEFAULT BYTE PADVALUE, DEFAULT CHAR PADVALUE, DEFAULT DOUBLE PADVALUE, DEFAULT EPOCH PADVALUE, DEFAULT EPOCH16 PADVALUE, DEFAULT FLOAT PADVALUE, DEFAULT INT1 PADVALUE, DEFAULT INT2 PADVALUE, DEFAULT INT4 PADVALUE, DEFAULT INT8 PADVALUE, DEFAULT REAL4 PADVALUE, DEFAULT REAL8 PADVALUE, DEFAULT TT2000 PADVALUE, DEFAULT UCHAR PADVALUE, DEFAULT UINT1 PADVALUE, DEFAULT UINT2 PADVALUE, DEFAULT UINT4 PADVALUE, DELETE, DID NOT COMPRESS, EMPTY COMPRESSED CDF, END OF VAR, EPOCH STRING LEN, EPOCH STRING LEN EXTEND, EPOCH1 STRING LEN, EPOCH1 STRING LEN EXTEND, EPOCH2 STRING LEN, EPOCH2 STRING LEN EXTEND, EPOCH3 STRING LEN, EPOCH3 STRING LEN EXTEND, EPOCH4 STRING LEN, EPOCH4 STRING LEN EXTEND, EPOCHx FORMAT MAX, EPOCHx STRING MAX, FILLED TT2000 VALUE, FORCED PARAMETER, FUNCTION NOT SUPPORTED, gENTRY, gENTRY DATA, gENTRY DATASPEC, gENTRY DATATYPE, gENTRY EXISTENCE, gENTRY NUMELEMS, GET, GETCDFCHECKSUM, GETCDFFILEBACKWARD, GETCDFVALIDATE, GETLEAPSECONDSENVVAR, GLOBAL SCOPE, GZIP COMPRESSION, HOST DECODING, HOST ENCODING, HP DECODING, HP ENCODING, HUFF COMPRESSION,

IA64VMSd_DECODING, IA64VMSd_ENCODING, IA64VMSg_DECODING, IA64VMSg_ENCODING, IA64VMSi_DECODING, IA64VMSi_ENCODING, IBM_PC_OVERFLOW, IBMPc_DECODING, IBMPc_ENCODING, IBMRs_DECODING, IBMRs_ENCODING, ILLEGAL_EPOCH_FIELD, ILLEGAL_EPOCH_VALUE, ILLEGAL_FOR_SCOPE, ILLEGAL_IN_zMODE, ILLEGAL_ON_V1_CDF, ILLEGAL_TT2000_VALUE, IS_A_NETCDF, LIB_COPYRIGHT, LIB_INCREMENT, LIB_RELEASE, LIB_subINCREMENT, LIB_VERSION, MAC_DECODING, MAC_ENCODING, MD5_CHECKSUM, MULTI_FILE, MULTI_FILE_FORMAT, NA_FOR_VARIABLE, NEGATIVE_FP_ZERO, NEGtoPOSfp0off, NEGtoPOSfp0on, NETWORK_DECODING, NETWORK_ENCODING, NExt_DECODING, NExt_ENCODING, NO_ATTR_SELECTED, NO_CDF_SELECTED, NO_CHECKSUM, NO_COMPRESSION, NO_DELETE_ACCESS, NO_ENTRY_SELECTED, NO_MORE_ACCESS, NO_PADVALUE_SPECIFIED, NO_SPARSEARRAYS, NO_SPARSERECORDS, NO_STATUS_SELECTED, NO_SUCH_ATTR, NO_SUCH_CDF, NO_SUCH_ENTRY, NO_SUCH_RECORD, NO_SUCH_VAR, NO_VAR_SELECTED, NO_VARS_IN_CDF, NO_WRITE_ACCESS, NONE_CHECKSUM, NOT_A_CDF, NOT_A_CDF_OR_NOT_SUPPORTED, NOVARY, NULL, OPEN, OPTIMAL_ENCODING_TREES, OTHER_CHECKSUM, PAD_SPARSERECORDS, PPC_DECODING, PPC_ENCODING, PRECEEDING_RECORDS_ALLOCATED, PREV_SPARSERECORDS, PUT, READ_ONLY_DISTRIBUTION, READ_ONLY_MODE, READONLYoff, READONLYon, rENTRY, rENTRY_DATA, rENTRY_DATASPEC, rENTRY_DATATYPE, rENTRY_EXISTENCE, rENTRY_NAME, rENTRY_NUMELEMS, rENTRY_NUMSTRINGS, rENTRY_STRINGSDATA, rLE_COMPRESSION, rLE_OF_ZEROS, ROW_MAJOR, rVAR, rVAR_ALLOCATEBLOCK, rVAR_ALLOCATEDFROM, rVAR_ALLOCATEDTO, rVAR_ALLOCATERECS, rVAR_BLOCKINGFACTOR, rVAR_CACHESIZE, rVAR_COMPRESSION, rVAR_DATA, rVAR_DATASPEC, rVAR_DATATYPE, rVAR_DIMVARYS, rVAR_EXISTENCE, rVAR_HYPERDATA, rVAR_INITIALRECS, rVAR_MAXallocREC, rVAR_MAXREC, rVAR_NAME, rVAR_nINDEXENTRIES, rVAR_nINDEXLEVELS, rVAR_nINDEXRECORDS, rVAR_NUMallocRECS, rVAR_NUMBER, rVAR_NUMELEMS, rVAR_NUMRECS, rVAR_PADVALUE, rVAR_RECORDS, rVAR_RECORDS_RENUMBER, rVAR_RECVAR, rVAR_RESERVEPERCENT, rVAR_SEQDATA, rVAR_SEQPOS, rVAR_SPARSEARRAYS, rVAR_SPARSERECORDS, rVARs_CACHESIZE, rVARs_DIMCOUNTS, rVARs_DIMINDICES, rVARs_DIMINTERVALS, rVARs_DIMSIZES, rVARs_MAXREC, rVARs_NUMDIMS, rVARs_RECCOUNT, rVARs_RECDATA, rVARs_RECINTERVAL, rVARs_RECNUMBER, rVARs_SAVE, SCRATCH_CREATE_ERROR, SCRATCH_DELETE_ERROR, SCRATCH_READ_ERROR, SCRATCH_WRITE_ERROR, SELECT, SGI_DECODING, SGI_ENCODING, SINGLE_FILE, SINGLE_FILE_FORMAT, SOME_ALREADY_ALLOCATED, STAGE_CACHESIZE, STATUS_TEXT, STRING_NOT_UTF8_ENCODING, STRINGDELIMITER, SUN_DECODING, SUN_ENCODING, TOO_MANY_PARMS, TOO_MANY_VARS, TRY_TO_READ_NONSTRING_DATA, TT2000_0_STRING_LEN, TT2000_1_STRING_LEN, TT2000_2_STRING_LEN, TT2000_3_STRING_LEN, TT2000_4_STRING_LEN, TT2000_CDF_MAYNEEDUPDATE, TT2000_TIME_ERROR, TT2000_USED_OUTDATED_TABLE, UNABLE_TO_PROCESS_CDF, UNKNOWN_COMPRESSION, UNKNOWN_SPARSENESS, UNSUPPORTED_OPERATION, VALIDATE, VALIDATEFILEoff, VALIDATEFILEon, VAR_ALREADY_CLOSED, VAR_CLOSE_ERROR, VAR_CREATE_ERROR, VAR_DELETE_ERROR, VAR_EXISTS, VAR_NAME_TRUNC, VAR_OPEN_ERROR, VAR_READ_ERROR, VAR_SAVE_ERROR, VAR_WRITE_ERROR, VARIABLE_SCOPE, VARY, VAX_DECODING, VAX_ENCODING, VIRTUAL_RECORD_DATA, zENTRY, zENTRY_DATA, zENTRY_DATASPEC, zENTRY_DATATYPE, zENTRY_EXISTENCE, zENTRY_NAME, zENTRY_NUMELEMS, zENTRY_NUMSTRINGS, zENTRY_STRINGSDATA, ZLIB_COMPRESS_ERROR, ZLIB_UNCOMPRESS_ERROR, zMODEoff, zMODEon1, zMODEon2, zVAR, zVAR_ALLOCATEBLOCK, zVAR_ALLOCATEDFROM, zVAR_ALLOCATEDTO, zVAR_ALLOCATERECS, zVAR_BLOCKINGFACTOR, zVAR_CACHESIZE, zVAR_COMPRESSION, zVAR_DATA, zVAR_DATASPEC, zVAR_DATATYPE, zVAR_DIMCOUNTS, zVAR_DIMINDICES, zVAR_DIMINTERVALS, zVAR_DIMSIZES, zVAR_DIMVARYS, zVAR_EXISTENCE, zVAR_HYPERDATA, zVAR_INITIALRECS, zVAR_MAXallocREC, zVAR_MAXREC, zVAR_NAME, zVAR_nINDEXENTRIES, zVAR_nINDEXLEVELS, zVAR_nINDEXRECORDS, zVAR_NUMallocRECS, zVAR_NUMBER, zVAR_NUMDIMS, zVAR_NUMELEMS, zVAR_NUMRECS, zVAR_PADVALUE, zVAR_RECCOUNT, zVAR_RECINTERVAL, zVAR_RECNUMBER, zVAR_RECORDS, zVAR_RECORDS_RENUMBER, zVAR_RECVAR, zVAR_RESERVEPERCENT, zVAR_SEQDATA, zVAR_SEQPOS, zVAR_SPARSEARRAYS, zVAR_SPARSERECORDS, zVARs_CACHESIZE, zVARs_MAXREC, zVARs_RECDATA, zVARs_RECNUMBER

Constructor Summary

Constructors

Constructor and Description

`CDFException(long statusCode)`

Takes a status code and throws a CDFException with the message that corresponds to the status code that is passed in.

`CDFException(long statusCode, java.lang.String where)`

Takes a status code and throws a CDFException with the message that corresponds to the status code that is passed in.

`CDFException(java.lang.String message)`

Takes a text message from the calling program and throws a CDFException.

Method Summary

Methods

Modifier and Type Method and Description

long

`getCurrentStatus ()`

Gets the status code that caused CDFException.

static java.lang.String

`getStatusMsg(long statusCode)`

Get the status text message for the given status code.

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

CDFException

```
public CDFException(java.lang.String message)
```

Takes a text message from the calling program and throws a CDFException.

Parameters:

message - the message to be thrown with CDFException

CDFException

```
public CDFException(long statusCode)
```

Takes a status code and throws a CDFException with the message that corresponds to the status code that is passed in.

Parameters:

statusCode - the CDF statusCode to be thrown

CDFException

```
public CDFException(long statusCode,
                    java.lang.String where)
```

Takes a status code and throws a CDFException with the message that corresponds to the status code that is passed in. It also specifies where (which routine) the problem was.

Parameters:

statusCode - the CDF statusCode to be thrown

where - the place (routine/method) where the problem occurred

Method Detail

getCurrentStatus

```
public long getCurrentStatus()
```

Gets the status code that caused CDFException. This method comes in handy when there are times one may want to examine the cause of the CDFException and determine whether to continue or not.

```
try {
    ...
} catch (CDFException e) {
    if (e.getCurrentStatus() == NO_SUCH_VAR) {
        Variable latitude = Variable.create(cdf, "Latitude",
                                           CDF_INT1,
                                           numElements,
                                           numDims,
                                           dimSizes,
                                           recVary,
                                           dimVary);

        ...
    } else {
        System.out.println ("StatusCode = "+e.getCurrentStatus());
        e.printStackTrace();
    }
}
```

Returns:

the status code that caused CDFException

getStatusMsg

```
public static java.lang.String getStatusMsg(long statusCode)
```

Get the status text message for the given status code.

Parameters:

statusCode - the status code from which the status text is retrieved

Returns:

the status text message for the given status code

gsfc.nssdc.cdf

Class CDFNativeLibrary

java.lang.Object
gsfc.nssdc.cdf.CDFNativeLibrary

All Implemented Interfaces:

CDFDelegate

```
public class CDFNativeLibrary
extends java.lang.Object
implements CDFDelegate
```

This class implements the method that act as the gateway between the CDF Java APIs and the CDF library.

Version:

Version 1.0

Constructor Summary

Constructors

Constructor and Description

CDFNativeLibrary()

Method Summary

Methods

Modifier and Type	Method and Description
void	<code>cdflib(CDF theCDF, CDFObject cdfObject, java.util.Vector cmds)</code> Calls the Java Native Interface (JNI) program, cdfNativeLibrary.c.

Methods inherited from class java.lang.Object

`equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

Constructor Detail

CDFNativeLibrary

```
public CDFNativeLibrary()
```

Method Detail

cdflib

```
public void cdflib(CDF theCDF,
                  CDFObject cdfObject,
                  java.util.Vector cmds)
    throws CDFException
```

Calls the Java Native Interface (JNI) program, cdfNativeLibrary.c. This method is internal and called by various core CDF Java programs.

End users should never call this method from their applications.

Specified by:

```
cdflib in interface CDFDelegate
```

Parameters:

- theCDF - the CDF being dealt with
- cdfObject - the calling program/object (e.g. Variable.java, Attribute.java, etc.)
- cmds - a vector that contains the CDFlib commands to be executed

Throws:

CDFException - if a problem occurs while executing the requested CDFlib commands in cdfNativeLibrary.c.

gsfc.nssdc.cdf

Interface CDFObject

All Known Implementing Classes:

[Attribute](#), [CDF](#), [CDFData](#), [Entry](#), [Variable](#)

public interface **CDFObject**

CDFObject provides the base interface for all CDF objects. CDF objects mean the CDF, Attribute, Entry and Variable objects. All these objects need to implement this interface.

Version:

1.0

Method Summary

Methods	
Modifier and Type	Method and Description
void	delete () Deletes the current object.
java.lang.String	getName () Returns the name of the current object.
void	rename (java.lang.String name) Renames the current object.

Method Detail

getName
<pre>java.lang.String getName()</pre> Returns the name of the current object. Returns: the name of the current object
rename
<pre>void rename(java.lang.String name) throws CDFException</pre> Renames the current object.

Parameters:

name - the new object name

Throws:

CDFException - if an error occurs renaming the current object

delete

```
void delete()  
    throws CDFException
```

Deletes the current object.

Throws:

CDFException - if an error occurs deleting the current object

Overview

Package

Class

Tree

Deprecated

Index

Help

Prev Class

Next Class

Frames

No Frames

All Classes

Summary: Nested | Field | Constr | Method

Detail: Field | Constr | Method

gsfc.nssdc.cdf

Class CDFTools

java.lang.Object
gsfc.nssdc.cdf.CDFTools

All Implemented Interfaces:

CDFConstants

```
public class CDFTools
extends java.lang.Object
implements CDFConstants
```

CDFTools.java Created: Tue Nov 24 16:14:50 1998

Version:

\$Id: CDFTools.java,v 1.1.1.1 2023/08/01 12:28:29 mhliu Exp \$

Field Summary

Fields	
Modifier and Type	Field and Description
static int	ALL_VALUES
static int	NAMED_VALUES
static int	NO_REPORTS
static int	NO_VALUES
static int	NRV_VALUES
static int	REPORT_ERRORS
static int	REPORT_INFORMATION
static int	REPORT_WARNINGS
static int	RV_VALUES

Fields inherited from interface gsfc.nssdc.cdf.CDFConstants
AHUFF COMPRESSION, ALPHAOSf1 DECODING, ALPHAOSf1 ENCODING, ALPHAVMSd DECODING, ALPHAVMSd ENCODING, ALPHAVMSg DECODING, ALPHAVMSg ENCODING, ALPHAVMSi DECODING, ALPHAVMSi ENCODING, ARM BIG DECODING, ARM BIG ENCODING, ARM LITTLE DECODING, ARM LITTLE ENCODING, ATTR , ATTR EXISTENCE ,ATTR EXISTS, ATTR MAXgENTRY , ATTR MAXrENTRY , ATTR MAXZENTRY , ATTR NAME , ATTR NAME TRUNC, ATTR NUMBER , ATTR NUMgENTRIES , ATTR NUMrENTRIES , ATTR NUMzENTRIES , ATTR SCOPE , BACKWARD , BACKWARDFILEoff, BACKWARDFILEon, BAD ALLOCATE RECS, BAD ARGUMENT, BAD ATTR NAME, BAD ATTR NUM, BAD BLOCKING FACTOR, BAD CACHE SIZE, BAD CDF EXTENSION, BAD CDF ID, BAD CDF NAME, BAD CDFSTATUS, BAD CHECKSUM, BAD COMPRESSION PARM, BAD DATA TYPE, BAD DECODING, BAD DIM COUNT, BAD DIM INDEX, BAD DIM INTERVAL, BAD DIM SIZE, BAD ENCODING, BAD ENTRY NUM, BAD FNC OR ITEM, BAD FORMAT, BAD INITIAL RECS, BAD MAJORITY, BAD MALLOC, BAD NEGtoPOSfp0 MODE, BAD NUM DIMS, BAD NUM ELEMS, BAD NUM STRINGS, BAD NUM VARS, BAD READONLY MODE, BAD REC COUNT, BAD REC INTERVAL, BAD REC NUM, BAD SCOPE, BAD SCRATCH DIR, BAD SPARSEARRAYS PARM, BAD VAR NAME, BAD VAR NUM, BAD zMODE, BADDATE LEAPSECOND UPDATED, BeginUnixTimeEPOCH, BeginUnixTimeEPOCH16, BLOCKINGFACTOR TOO LARGE, BLOCKINGFACTOR TOO SMALL, BLOCKINGFACTOR TOO SMALL2, CANNOT ALLOCATE RECORDS, CANNOT CHANGE, CANNOT COMPRESS, CANNOT CONVERT WIDECCHAR, CANNOT COPY, CANNOT INSERT RECORDS, CANNOT SPARSEARRAYS, CANNOT SPARSERECORDS, CDF , CDF ACCESS , CDF ATTR NAME LEN, CDF ATTR NAME LEN256, CDF BYTE, CDF CACHESIZE , CDF CHAR, CDF CHECKSUM , CDF CLOSE ERROR, CDF COMPRESSION , CDF COPYRIGHT , CDF COPYRIGHT LEN, CDF CREATE ERROR, CDF DECODING , CDF DELETE ERROR, CDF DOUBLE, CDF ENCODING , CDF EPOCH, CDF EPOCH16, CDF EXISTS, CDF FLOAT, CDF FORMAT , CDF INCREMENT , CDF INFO , CDF INTI,

CDF INT2, CDF INT4, CDF INT8, CDF INTERNAL_ERROR, CDF LEAPSECONDLASTUPDATED, CDF MAJORITY, CDF MAX_DIMS, CDF MAX_PARMS, CDF MIN_DIMS, CDF NAME, CDF NAME_TRUNC, CDF NEGtoPOSfp0_MODE, CDF NUMATTRS, CDF NUMgATTRS, CDF NUMrVARS, CDF NUMvATTRS, CDF NUMzVARS, CDF OK, CDF OPEN_ERROR, CDF PATHNAME_LEN, CDF READ_ERROR, CDF READONLY_MODE, CDF REAL4, CDF REAL8, CDF RELEASE, CDF SAVE_ERROR, CDF SCRATCHDIR, CDF STATUS, CDF STATUSTEXT_LEN, CDF TIME TT2000, CDF UCHAR, CDF UINT1, CDF UINT2, CDF UINT4, CDF VAR_NAME_LEN, CDF VAR_NAME_LEN256, CDF_VERSION, CDF_WARN, CDF WRITE_ERROR, CDF zMODE, CDFwithSTATS, CHECKSUM, CHECKSUM_ERROR, CHECKSUM_NOT_ALLOWED, CLOSE, COLUMN_MAJOR, COMPRESS_CACHESIZE, COMPRESSION_ERROR, CONFIRM, CORRUPTED_V2_CDF, CORRUPTED_V3_CDF, CREATE, CURgENTRY_EXISTENCE, CURrENTRY_EXISTENCE, CURzENTRY_EXISTENCE, DATATYPE_MISMATCH, DATATYPE_SIZE, DECOMPRESSION_ERROR, DECSTATION_DECODING, DECSTATION_ENCODING, DEFAULT_BYTE_PADVALUE, DEFAULT_CHAR_PADVALUE, DEFAULT_DOUBLE_PADVALUE, DEFAULT_EPOCH_PADVALUE, DEFAULT_EPOCH16_PADVALUE, DEFAULT_FLOAT_PADVALUE, DEFAULT_INT1_PADVALUE, DEFAULT_INT2_PADVALUE, DEFAULT_INT4_PADVALUE, DEFAULT_INT8_PADVALUE, DEFAULT_REAL4_PADVALUE, DEFAULT_REAL8_PADVALUE, DEFAULT_TT2000_PADVALUE, DEFAULT_UCHAR_PADVALUE, DEFAULT_UINT1_PADVALUE, DEFAULT_UINT2_PADVALUE, DEFAULT_UINT4_PADVALUE, DELETE, DID_NOT_COMPRESS, EMPTY_COMPRESSED_CDF, END_OF_VAR, EPOCH_STRING_LEN, EPOCH_STRING_LEN_EXTEND, EPOCH1_STRING_LEN, EPOCH1_STRING_LEN_EXTEND, EPOCH2_STRING_LEN, EPOCH2_STRING_LEN_EXTEND, EPOCH3_STRING_LEN, EPOCH3_STRING_LEN_EXTEND, EPOCH4_STRING_LEN, EPOCH4_STRING_LEN_EXTEND, EPOCHx_FORMAT_MAX, EPOCHx_STRING_MAX, FILLED_TT2000_VALUE, FORCED_PARAMETER, FUNCTION_NOT_SUPPORTED, gENTRY, gENTRY_DATA, gENTRY_DATASPEC, gENTRY_DATATYPE, gENTRY_EXISTENCE, gENTRY_NUMELEMS, GET, GETCDFCHECKSUM, GETCDFFILEBACKWARD, GETCDFVALIDATE, GETLEAPSECONDSENVVAR, GLOBAL_SCOPE, GZIP_COMPRESSION, HOST_DECODING, HOST_ENCODING, HP_DECODING, HP_ENCODING, HUFF_COMPRESSION, IA64VMSd_DECODING, IA64VMSd_ENCODING, IA64VMSg_DECODING, IA64VMSg_ENCODING, IA64VMSi_DECODING, IA64VMSi_ENCODING, IBM_PC_OVERFLOW, IBMPC_DECODING, IBMPC_ENCODING, IBMRs_DECODING, IBMRs_ENCODING, ILLEGAL_EPOCH_FIELD, ILLEGAL_EPOCH_VALUE, ILLEGAL_FOR_SCOPE, ILLEGAL_IN_zMODE, ILLEGAL_ON_V1_CDF, ILLEGAL_TT2000_VALUE, IS_A_NETCDF, LIB_COPYRIGHT, LIB_INCREMENT, LIB_RELEASE, LIB_subINCREMENT, LIB_VERSION, MAC_DECODING, MAC_ENCODING, MD5_CHECKSUM, MULTI_FILE, MULTI_FILE_FORMAT, NA_FOR_VARIABLE, NEGATIVE_FP_ZERO, NEGtoPOSfp0off, NEGtoPOSfp0on, NETWORK_DECODING, NETWORK_ENCODING, Next_DECODING, Next_ENCODING, NO_ATTR_SELECTED, NO_CDF_SELECTED, NO_CHECKSUM, NO_COMPRESSION, NO_DELETE_ACCESS, NO_ENTRY_SELECTED, NO_MORE_ACCESS, NO_PADVALUE_SPECIFIED, NO_SPARSEARRAYS, NO_SPARSERECORDS, NO_STATUS_SELECTED, NO_SUCH_ATTR, NO_SUCH_CDF, NO_SUCH_ENTRY, NO_SUCH_RECORD, NO_SUCH_VAR, NO_VAR_SELECTED, NO_VARS_IN_CDF, NO_WRITE_ACCESS, NONE_CHECKSUM, NOT_A_CDF, NOT_A_CDF_OR_NOT_SUPPORTED, NOVARY, NULL_OPEN, OPTIMAL_ENCODING_TREES, OTHER_CHECKSUM, PAD_SPARSERECORDS, PPC_DECODING, PPC_ENCODING, PRECEDING_RECORDS_ALLOCATED, PREV_SPARSERECORDS, PUT, READ_ONLY_DISTRIBUTION, READ_ONLY_MODE, READONLYoff, READONLYon, rENTRY, rENTRY_DATA, rENTRY_DATASPEC, rENTRY_DATATYPE, rENTRY_EXISTENCE, rENTRY_NAME, rENTRY_NUMELEMS, rENTRY_NUMSTRINGS, rENTRY_STRINGSDATA, RLE_COMPRESSION, RLE_OF_ZEROS, ROW_MAJOR, rVAR, rVAR_ALLOCATEBLOCK, rVAR_ALLOCATEDFROM, rVAR_ALLOCATEDTO, rVAR_ALLOCATERECS, rVAR_BLOCKINGFACTOR, rVAR_CACHESIZE, rVAR_COMPRESSION, rVAR_DATA, rVAR_DATASPEC, rVAR_DATATYPE, rVAR_DIMVARYS, rVAR_EXISTENCE, rVAR_HYPERDATA, rVAR_INITIALRECS, rVAR_MAXallocREC, rVAR_MAXREC, rVAR_NAME, rVAR_nINDEXENTRIES, rVAR_nINDEXLEVELS, rVAR_nINDEXRECORDS, rVAR_NUMallocRECS, rVAR_NUMBER, rVAR_NUMELEMS, rVAR_NUMRECS, rVAR_PADVALUE, rVAR_RECORDS, rVAR_RECORDS_RENUMBER, rVAR_RECVAR, rVAR_RESERVEPERCENT, rVAR_SEQDATA, rVAR_SEQPOS, rVAR_SPARSEARRAYS, rVAR_SPARSERECORDS, rVARs_CACHESIZE, rVARs_DIMCOUNTS, rVARs_DIMINDICES, rVARs_DIMINTERVALS, rVARs_DIMSIZES, rVARs_MAXREC, rVARs_NUMDIMS, rVARs_RECCOUNT, rVARs_RECDATA, rVARs_RECINTERVAL, rVARs_RECNUMBER, SAVE, SCRATCH_CREATE_ERROR, SCRATCH_DELETE_ERROR, SCRATCH_READ_ERROR, SCRATCH_WRITE_ERROR, SELECT, SGI_DECODING, SGI_ENCODING, SINGLE_FILE, SINGLE_FILE_FORMAT, SOME_ALREADY_ALLOCATED, STAGE_CACHESIZE, STATUS_TEXT, STRING_NOT_UTF8_ENCODING, STRINGDELIMITER, SUN_DECODING, SUN_ENCODING, TOO_MANY_PARMS, TOO_MANY_VARS, TRY_TO_READ_NONSTRING_DATA, TT2000_0_STRING_LEN, TT2000_1_STRING_LEN, TT2000_2_STRING_LEN, TT2000_3_STRING_LEN, TT2000_4_STRING_LEN, TT2000_CDF_MAYNEEDUPDATE, TT2000_TIME_ERROR, TT2000_USED_OUTDATED_TABLE, UNABLE_TO_PROCESS_CDF, UNKNOWN_COMPRESSION, UNKNOWN_SPARSENESS, UNSUPPORTED_OPERATION, VALIDATE, VALIDATEFILEoff, VALIDATEFILEon, VAR_ALREADY_CLOSED, VAR_CLOSE_ERROR, VAR_CREATE_ERROR, VAR_DELETE_ERROR, VAR_EXISTS, VAR_NAME_TRUNC, VAR_OPEN_ERROR, VAR_READ_ERROR, VAR_SAVE_ERROR, VAR_WRITE_ERROR, VARIABLE_SCOPE, VARY, VAX_DECODING, VAX_ENCODING, VIRTUAL_RECORD_DATA, zENTRY, zENTRY_DATA, zENTRY_DATASPEC, zENTRY_DATATYPE, zENTRY_EXISTENCE, zENTRY_NAME, zENTRY_NUMELEMS, zENTRY_NUMSTRINGS, zENTRY_STRINGSDATA, ZLIB_COMPRESS_ERROR, ZLIB_UNCOMPRESS_ERROR, zMODEoff, zMODEon1, zMODEon2, zVAR, zVAR_ALLOCATEBLOCK, zVAR_ALLOCATEDFROM, zVAR_ALLOCATEDTO, zVAR_ALLOCATERECS, zVAR_BLOCKINGFACTOR, zVAR_CACHESIZE, zVAR_COMPRESSION, zVAR_DATA, zVAR_DATASPEC, zVAR_DATATYPE, zVAR_DIMCOUNTS, zVAR_DIMINDICES, zVAR_DIMINTERVALS, zVAR_DIMSIZES, zVAR_DIMVARYS, zVAR_EXISTENCE, zVAR_HYPERDATA, zVAR_INITIALRECS, zVAR_MAXallocREC, zVAR_MAXREC, zVAR_NAME, zVAR_nINDEXENTRIES, zVAR_nINDEXLEVELS, zVAR_nINDEXRECORDS, zVAR_NUMallocRECS, zVAR_NUMBER, zVAR_NUMDIMS, zVAR_NUMELEMS, zVAR_NUMRECS, zVAR_PADVALUE, zVAR_RECCOUNT, zVAR_RECINTERVAL, zVAR_RECNUMBER, zVAR_RECORDS, zVAR_RECORDS_RENUMBER, zVAR_RECVAR, zVAR_RESERVEPERCENT, zVAR_SEQDATA, zVAR_SEQPOS, zVAR_SPARSEARRAYS, zVAR_SPARSERECORDS, zVARs_CACHESIZE, zVARs_MAXREC, zVARs_RECDATA, zVARs_RECNUMBER

Constructor Summary

Constructors

Constructor and Description

CDFTools ()

Method Summary

Methods	
Modifier and Type	Method and Description
static void	skeletonCDF (java.lang.String skeletonName, java.lang.String cdfName, boolean delete, boolean log, boolean neg2posfp0, boolean statistics, int zMode, int reportType, int cacheSizeD) skeletonCDF produces a CDF file from a skeleton table.
static void	skeletonCDF (java.lang.String skeletonName, java.lang.String cdfName, boolean delete, boolean log, boolean neg2posfp0, boolean statistics, int zMode, int reportType, int cacheSizeD, int cacheSizeS) skeletonCDF produces a CDF file from a skeleton table.
static void	skeletonCDF (java.lang.String skeletonName, java.lang.String cdfName, boolean delete, boolean log, boolean neg2posfp0, boolean statistics, int zMode, int reportType, int cacheSizeD, int cacheSizeS, int cacheSizeC) skeletonCDF produces a CDF file from a skeleton table.
static void	skeletonCDF (java.lang.String skeletonName, java.lang.String cdfName, boolean delete, boolean log, boolean neg2posfp0, boolean statistics, int zMode, int reportType, java.lang.String cacheSize) skeletonCDF produces a CDF file from a skeleton table.
static void	skeletonTable (java.lang.String skeletonName, java.lang.String cdfName, boolean log, boolean format, boolean neg2posfp0, boolean statistics, boolean screen, boolean page, int values, java.lang.String[] valueList, int zMode, int reportType, int cacheSize) skeletonTable produces a skeleton table from a CDF.
static void	skeletonTable (java.lang.String skeletonName, java.lang.String cdfName, boolean log, boolean format, boolean neg2posfp0, boolean statistics, boolean screen, boolean page, int values, java.lang.String[] valueList, int zMode, int reportType, int cacheSizeD, int cacheSizeS) skeletonTable produces a skeleton table from a CDF.
static void	skeletonTable (java.lang.String skeletonName, java.lang.String cdfName, boolean log, boolean format, boolean neg2posfp0, boolean statistics, boolean screen, boolean page, int values, java.lang.String[] valueList, int zMode, int reportType, int cacheSizeD, int cacheSizeS, int cacheSizeC) skeletonTable produces a skeleton table from a CDF.
static void	skeletonTable (java.lang.String skeletonName, java.lang.String cdfName, boolean log, boolean format, boolean neg2posfp0, boolean statistics, boolean screen, boolean page, int values, java.lang.String[] valueList, int zMode, int reportType, java.lang.String cacheSize) skeletonTable produces a skeleton table from a CDF.
static void	skeletonTable (java.lang.String skeletonName, java.lang.String cdfName, boolean log, boolean format, boolean neg2posfp0, boolean statistics, boolean screen, boolean page, int values, java.lang.String[] valueList, int zMode, int reportType, java.lang.String cacheSize, java.lang.String advFormat) skeletonTable produces a skeleton table from a CDF.

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Detail

NO_VALUES
public static final int NO_VALUES
See Also: Constant Field Values

NRV_VALUES

```
public static final int NRV_VALUES
```

See Also:

[Constant Field Values](#)

RV_VALUES

```
public static final int RV_VALUES
```

See Also:

[Constant Field Values](#)

ALL_VALUES

```
public static final int ALL_VALUES
```

See Also:

[Constant Field Values](#)

NAMED_VALUES

```
public static final int NAMED_VALUES
```

See Also:

[Constant Field Values](#)

NO_REPORTS

```
public static final int NO_REPORTS
```

See Also:

[Constant Field Values](#)

REPORT_ERRORS

```
public static final int REPORT_ERRORS
```

See Also:

[Constant Field Values](#)

REPORT_WARNINGS

```
public static final int REPORT_WARNINGS
```

See Also:

[Constant Field Values](#)

REPORT_INFORMATION

```
public static final int REPORT_INFORMATION
```

See Also:

[Constant Field Values](#)

Constructor Detail

CDFTools

```
public CDFTools()
```

Method Detail

skeletonTable

```
public static void skeletonTable(java.lang.String skeletonName,
                                java.lang.String cdfName,
                                boolean log,
                                boolean format,
                                boolean neg2posfp0,
                                boolean statistics,
                                boolean screen,
                                boolean page,
                                int values,
                                java.lang.String[] valueList,
                                int zMode,
                                int reportType,
                                int cacheSize)
                                throws java.io.IOException,
                                       java.lang.InterruptedException
```

skeletonTable produces a skeleton table from a CDF. A skeleton table is a text file which can be read by the SkeletonCDF program to build a skeleton CDF.

Parameters:

- skeletonName - is the pathname of the skeleton table to be created. (Do not enter an extension because ".skt" is appended automatically). If **null** is specified, the skeleton table is named <cdfName>.skt in the current directory
- cdfName - The pathname of the CDF from which the skeleton table will be created. Do not enter an extension.
- log - Specifies whether or not messages are displayed as the program executes.
- format - Specifies whether or not the FORMAT attribute is used when writing variable values (if the FORMAT attribute exists and an entry exists for the variable).

`neg2posfp0` - Specifies whether or not -0.0 is converted to 0.0 by the CDF library when read from a CDF. -0.0 is an illegal floating point value on VAXes and DEC Alphas running OpenVMS.

`statistics` - Specifies whether or not caching statistics are displayed at the end of each CDF.

`screen` - Specifies whether or not the skeleton table is displayed on the terminal screen (written to the "standard output"). If not, the skeleton table is written to a file.

`page` - If the skeleton table is being displayed on the terminal screen, specifies whether or not the output is displayed one page (screen) at a time.

`values` - Specifies which variable values are to be put in the skeleton table. It may be one of the following...

CDFTools.NO_VALUES

Ignore all NRV data values.

CDFTools.NRV_VALUES

Put NRV data values in the skeleton table.

CDFTools.RV_VALUES

Put RV variable values in the skeleton table.

CDFTools.ALL_VALUES

Put all variable values in the skeleton table.

CDFTools.NAMED_VALUES

Put named variables values in the skeleton table. This requires that `valueList` be non-null

`valueList` - the named variables to list values.

`zMode` - Specifies which `zMode` should be used. May be one of the following...

0

Indicates that `zMode` is disabled.

1

Indicates that `zMode/1` should be used (the dimension variances of `rVariables` will be preserved).

2

Indicates that `zMode/2` should be used (the dimensions of `rVariables` having a variance of `NOVARY` (false) are hidden).

`reportType` - Specifies the types of return status codes from the CDF library which should be reported/displayed. `report` is a bit mask made up from the following `CDFTools.NO_REPORTS`, `CDFTools.REPORT_ERRORS`, `CDFTools.REPORT_WARNINGS` and `CDFTools.REPORT_INFORMATION`

`cacheSize` - The number of buffers to be used for the CDF's `dotCDF` file. Pass 0 to use the default.

Throws:

`java.io.IOException` - An exception is thrown if the file is bad or non-existent

`java.lang.InterruptedException` - An exception is thrown if an interrupt is issued **Note:**
When running an application that use this static method, make sure this **cdf.base** system property is defined (to the cdf installation). For example,
`java -Dcdf.base=/home/cdf/cdf34_1-dist MyApp`

skeletonTable

```
public static void skeletonTable(java.lang.String skeletonName,  
                                java.lang.String cdfName,  
                                boolean log,  
                                boolean format,  
                                boolean neg2posfp0,  
                                boolean statistics,  
                                boolean screen,  
                                boolean page,  
                                int values,  
                                java.lang.String[] valueList,  
                                int zMode,  
                                int reportType,  
                                int cacheSizeD,  
                                int cacheSizeS)  
                                throws java.io.IOException,  
                                       java.lang.InterruptedException
```

skeletonTable produces a skeleton table from a CDF. A skeleton table is a text file which can be read by the SkeletonCDF program to build a skeleton CDF.

Parameters:

`skeletonName` - is the pathname of the skeleton table to be created. (Do not enter an extension because ".skt" is appended automatically). If **null** is specified, the skeleton table is named <cdfName>.skt in the current directory

`cdfName` - The pathname of the CDF from which the skeleton table will be created. Do not enter an extension.

`log` - Specifies whether or not messages are displayed as the program executes.

`format` - Specifies whether or not the FORMAT attribute is used when writing variable values (if the FORMAT attribute exists and an entry exists for the variable).

`neg2posfp0` - Specifies whether or not -0.0 is converted to 0.0 by the CDF library when read from a CDF. -0.0 is an illegal floating point value on VAXes and DEC Alphas running OpenVMS.

`statistics` - Specifies whether or not caching statistics are displayed at the end of each CDF.

`screen` - Specifies whether or not the skeleton table is displayed on the terminal screen (written to the "standard output"). If not, the skeleton table is written to a file.

`page` - If the skeleton table is being displayed on the terminal screen, specifies whether or not the output is displayed one page (screen) at a time.

`values` - Specifies which variable values are to be put in the skeleton table. It may be one of the following...

CDFTools.NO_VALUES

Ignore all NRV data values.

CDFTools.NRV_VALUES

Put NRV data values in the skeleton table.

CDFTools.RV_VALUES

Put RV variable values in the skeleton table.

CDFTools.ALL_VALUES

Put all variable values in the skeleton table.

CDFTools.NAMED_VALUES

Put named variables values in the skeleton table. This requires that valueList be non-null

valueList - the named variables to list values.

zMode - Specifies which zMode should be used. May be one of the following...

0

Indicates that zMode is disabled.

1

Indicates that zMode/1 should be used (the dimension variances of rVariables will be preserved).

2

Indicates that zMode/2 should be used (the dimensions of rVariables having a variance of NOVARY (false) are hidden.

reportType - Specifies the types of return status codes from the CDF library which should be reported/displayed. report is a bit mask made up from the following CDFTools.NO_REPORTS, CDFTools.REPORT_ERRORS, CDFTools.REPORT_WARNINGS and CDFTools.REPORT_INFORMATION

cacheSizeD - The number of buffers to be used for the CDF's dotCDF file. Pass 0 to use the default.

cacheSizeS - The number of buffers to be used for the CDF's staging file. Pass 0 to use the default.

Throws:

java.io.IOException - An exception is thrown if the file is bad or non-existent

java.lang.InterruptedException - An exception is thrown if an interrupt is issued **Note:**
When running an application that use this static method, make sure this **cdf.base** system property is defined (to the cdf installation). For example,
java -Dcdf.base=/home/cdf/cdf34_1-dist MyApp

skeletonTable

```
public static void skeletonTable(java.lang.String skeletonName,
                                java.lang.String cdfName,
                                boolean log,
                                boolean format,
                                boolean neg2posfp0,
                                boolean statistics,
```

```

        boolean screen,
        boolean page,
        int values,
        java.lang.String[] valueList,
        int zMode,
        int reportType,
        int cacheSizeD,
        int cacheSizeS,
        int cacheSizeC)
            throws java.io.IOException,
                   java.lang.InterruptedException

```

skeletonTable produces a skeleton table from a CDF. A skeleton table is a text file which can be read by the SkeletonCDF program to build a skeleton CDF.

Parameters:

skeletonName - is the pathname of the skeleton table to be created. (Do not enter an extension because ".skt" is appended automatically). If **null** is specified, the skeleton table is named <cdfName>.skt in the current directory

cdfName - The pathname of the CDF from which the skeleton table will be created. Do not enter an extension.

log - Specifies whether or not messages are displayed as the program executes.

format - Specifies whether or not the FORMAT attribute is used when writing variable values (if the FORMAT attribute exists and an entry exists for the variable).

neg2posfp0 - Specifies whether or not -0.0 is converted to 0.0 by the CDF library when read from a CDF. -0.0 is an illegal floating point value on VAXes and DEC Alphas running OpenVMS.

statistics - Specifies whether or not caching statistics are displayed at the end of each CDF.

screen - Specifies whether or not the skeleton table is displayed on the terminal screen (written to the "standard output"). If not, the skeleton table is written to a file.

page - If the skeleton table is being displayed on the terminal screen, specifies whether or not the output is displayed one page (screen) at a time.

values - Specifies which variable values are to be put in the skeleton table. It may be one of the following...

CDFTools.NO_VALUES

Ignore all NRV data values.

CDFTools.NRV_VALUES

Put NRV data values in the skeleton table.

CDFTools.RV_VALUES

Put RV variable values in the skeleton table.

CDFTools.ALL_VALUES

Put all variable values in the skeleton table.

CDFTools.NAMED_VALUES

Put named variables values in the skeleton table. This requires that valueList be non-null

`valueList` - the named variables to list values.

`zMode` - Specifies which `zMode` should be used. May be one of the following...

0

Indicates that `zMode` is disabled.

1

Indicates that `zMode/1` should be used (the dimension variances of `rVariables` will be preserved).

2

Indicates that `zMode/2` should be used (the dimensions of `rVariables` having a variance of `NOVARY` (false) are hidden).

`reportType` - Specifies the types of return status codes from the CDF library which should be reported/displayed. `report` is a bit mask made up from the following `CDFTools.NO_REPORTS`, `CDFTools.REPORT_ERRORS`, `CDFTools.REPORT_WARNINGS` and `CDFTools.REPORT_INFORMATION`

`cacheSizeD` - The number of buffers to be used for the CDF's dotCDF file. Pass 0 to use the default.

`cacheSizeS` - The number of buffers to be used for the CDF's staging file. Pass 0 to use the default.

`cacheSizeC` - The number of buffers to be used for the CDF's compression scratch file. Pass 0 to use the default.

Throws:

`java.io.IOException` - An exception is thrown if the file is bad or non-existent

`java.lang.InterruptedException` - An exception is thrown if an interrupt is issued **Note:**
When running an application that use this static method, make sure this **`cdf.base`** system property is defined (to the cdf installation). For example,
`java -Dcdf.base=/home/cdf/cdf34_1-dist MyApp`

skeletonTable

```
public static void skeletonTable(java.lang.String skeletonName,
                                java.lang.String cdfName,
                                boolean log,
                                boolean format,
                                boolean neg2posfp0,
                                boolean statistics,
                                boolean screen,
                                boolean page,
                                int values,
                                java.lang.String[] valueList,
                                int zMode,
                                int reportType,
                                java.lang.String cacheSize)
    throws java.io.IOException,
           java.lang.InterruptedException
```

`skeletonTable` produces a skeleton table from a CDF. A skeleton table is a text file which can be read by the `SkeletonCDF` program to build a skeleton CDF.

Parameters:

`skeletonName` - is the pathname of the skeleton table to be created. (Do not enter an extension because ".skt" is appended

automatically). If **null** is specified, the skeleton table is named <cdfName>.skt in the current directory

`cdfName` - The pathname of the CDF from which the skeleton table will be created. Do not enter an extension.

`log` - Specifies whether or not messages are displayed as the program executes.

`format` - Specifies whether or not the FORMAT attribute is used when writing variable values (if the FORMAT attribute exists and an entry exists for the variable).

`neg2posfp0` - Specifies whether or not -0.0 is converted to 0.0 by the CDF library when read from a CDF. -0.0 is an illegal floating point value on VAXes and DEC Alphas running OpenVMS.

`statistics` - Specifies whether or not caching statistics are displayed at the end of each CDF.

`screen` - Specifies whether or not the skeleton table is displayed on the terminal screen (written to the "standard output"). If not, the skeleton table is written to a file.

`page` - If the skeleton table is being displayed on the terminal screen, specifies whether or not the output is displayed one page (screen) at a time.

`values` - Specifies which variable values are to be put in the skeleton table. It may be one of the following...

CDFTools.NO_VALUES

Ignore all NRV data values.

CDFTools.NRV_VALUES

Put NRV data values in the skeleton table.

CDFTools.RV_VALUES

Put RV variable values in the skeleton table.

CDFTools.ALL_VALUES

Put all variable values in the skeleton table.

CDFTools.NAMED_VALUES

Put named variables values in the skeleton table. This requires that `valueList` be non-null

`valueList` - the named variables to list values.

`zMode` - Specifies which `zMode` should be used. May be one of the following...

0

Indicates that `zMode` is disabled.

1

Indicates that `zMode/1` should be used (the dimension variances of `rVariables` will be preserved).

2

Indicates that zMode/2 should be used (the dimensions of rVariables having a variance of NOVARY (false) are hidden.

reportType - Specifies the types of return status codes from the CDF library which should be reported/displayed. **report** is a bit mask made up from the following CDFTools.NO_REPORTS, CDFTools.REPORT_ERRORS, CDFTools.REPORT_WARNINGS and CDFTools.REPORT_INFORMATION

cacheSize - The number of buffers to be used for the CDF's dotCDF file, staging file, and compression scratch file. This field used only in the CDF access process will not change anything to the contents of the skeleton table. Large number(s) will likely reduce physical I/Os if variable data are involved. If this field is null, the default cache sizes chosen by the CDF library are used. The cache sizes are specified with a comma-separated list of <number><type> pairs where <number> is the number of cache buffers and <type> is the type of file. The file <type>'s are as follows: 'd' for the dotCDF file, 's' for the staging file, and 'c' for the compression scratch file. For example, '200d,100s' specifies 200 cache buffers for the dotCDF file and 100 cache buffers for the staging file. The dotCDF file cache size can also be specified without the 'd' <type> for compatibility with older CDF releases (eg. '200,100s'). Note that not all of the file types must be specified. Those not specified will receive a default cache size.

Throws:

`java.io.IOException` - An exception is thrown if the file is bad or non-existent

`java.lang.InterruptedException` - An exception is thrown if an interrupt is issued **Note:** When running an application that use this static method, make sure this **cdf.base** system property is defined (to the cdf installation). For example,

```
java -Dcdf.base=/home/cdf/cdf34_1-dist MyApp
```

skeletonTable

```
public static void skeletonTable(java.lang.String skeletonName,
                                java.lang.String cdfName,
                                boolean log,
                                boolean format,
                                boolean neg2posfp0,
                                boolean statistics,
                                boolean screen,
                                boolean page,
                                int values,
                                java.lang.String[] valueList,
                                int zMode,
                                int reportType,
                                java.lang.String cacheSize,
                                java.lang.String advFormat)
    throws java.io.IOException,
           java.lang.InterruptedException
```

skeletonTable produces a skeleton table from a CDF. A skeleton table is a text file which can be read by the SkeletonCDF program to build a skeleton CDF.

Parameters:

skeletonName - is the pathname of the skeleton table to be created. (Do not enter an extension because ".skt" is appended automatically). If **null** is specified, the skeleton table is named <cdfName>.skt in the current directory

cdfName - The pathname of the CDF from which the skeleton table will be created. Do not enter an extension.

log - Specifies whether or not messages are displayed as the program executes.

format - Specifies whether or not the FORMAT attribute is used when writing variable values (if the FORMAT attribute exists and an entry exists for the variable). Metadata always uses noformat form.

`neg2posfp0` - Specifies whether or not -0.0 is converted to 0.0 by the CDF library when read from a CDF. -0.0 is an illegal floating point value on VAXes and DEC Alphas running OpenVMS.

`statistics` - Specifies whether or not caching statistics are displayed at the end of each CDF.

`screen` - Specifies whether or not the skeleton table is displayed on the terminal screen (written to the "standard output"). If not, the skeleton table is written to a file.

`page` - If the skeleton table is being displayed on the terminal screen, specifies whether or not the output is displayed one page (screen) at a time.

`values` - Specifies which variable values are to be put in the skeleton table. It may be one of the following...

CDFTools.NO_VALUES

Ignore all NRV data values.

CDFTools.NRV_VALUES

Put NRV data values in the skeleton table.

CDFTools.RV_VALUES

Put RV variable values in the skeleton table.

CDFTools.ALL_VALUES

Put all variable values in the skeleton table.

CDFTools.NAMED_VALUES

Put named variables values in the skeleton table. This requires that `valueList` be non-null

`valueList` - the named variables to list values.

`zMode` - Specifies which `zMode` should be used. May be one of the following...

0

Indicates that `zMode` is disabled.

1

Indicates that `zMode/1` should be used (the dimension variances of `rVariables` will be preserved).

2

Indicates that `zMode/2` should be used (the dimensions of `rVariables` having a variance of `NOVARY` (false) are hidden.

`reportType` - Specifies the types of return status codes from the CDF library which should be reported/displayed. `report` is a bit mask made up from the following `CDFTools.NO_REPORTS`, `CDFTools.REPORT_ERRORS`, `CDFTools.REPORT_WARNINGS` and `CDFTools.REPORT_INFORMATION`

`cacheSize` - The number of buffers to be used for the CDF's dotCDF file, staging file, and compression scratch file. This field used only in the CDF access process will not change anything to the contents of the skeleton table. Large number(s) will likely reduce physical I/Os if variable data are involved. If this field is null, the default cache sizes chosen by the CDF library are used.

The cache sizes are specified with a comma-separated list of <number><type> pairs where <number> is the number of cache buffers and <type> is the type of file. The file <type>'s are as follows: 'd' for the dotCDF file, 's' for the staging file, and 'c' for the compression scratch file. For example, '200d,100s' specifies 200 cache buffers for the dotCDF file and 100 cache buffers for the staging file. The dotCDF file cache size can also be specified without the 'd' <type> for compatibility with older CDF releases (eg. '200,100s'). Note that not all of the file types must be specified. Those not specified will receive a default cache size.

advFormat - This new argument supersedes the prior format argument. It accepts one of "best", "no", "metaonly", "dataonly" or "all" options. "best" option all use the best approach to encode floating point data with a higher precision, even larger than the FORMAT attribute for both metadata and data. "no" option will not use and FORMAT attribute, "metaonly" will use FORMAT attribute for metadata only. "dataonly" will use FORMAT attribute for data only. "all" option will use FORMAT attribute for both metadata and data. "best" option is the default. If null is passed in, which is the old method calling this method, it is changed to "best" option that works as C based tool would do.

Throws:

java.io.IOException - An exception is thrown if the file is bad or non-existent

java.lang.InterruptedException - An exception is thrown if an interrupt is issued **Note:**
When running an application that use this static method, make sure this **cdf.base** system property is defined (to the cdf installation). For example,
java -Dcdf.base=/home/cdf/cdf34_1-dist MyApp

skeletonCDF

```
public static void skeletonCDF(java.lang.String skeletonName,
                               java.lang.String cdfName,
                               boolean delete,
                               boolean log,
                               boolean neg2posfp0,
                               boolean statistics,
                               int zMode,
                               int reportType,
                               int cacheSized)
    throws java.io.IOException,
           java.lang.InterruptedException
```

skeletonCDF produces a CDF file from a skeleton table. A skeleton table is a text file which can be made through a text editor, or by SkeletonCDF program from an existng CDF.

Parameters:

- skeletonName - is the pathname of the skeleton table to be used to create a CDF. (Do not enter an extension because ".skt" is appended automatically). If **null** is specified, the skeleton table is named <cdfName>.skt in the current directory
- cdfName - The pathname of the created CDF from the skeleton table. Do not enter an extension.
- delete - specifies whether or not the CDF should be deleted if it already exists.
- log - Specifies whether or not messages are displayed as the program executes.
- neg2posfp0 - Specifies whether or not -0.0 is converted to 0.0 by the CDF library when read from a CDF. -0.0 is an illegal floating point value on VAXes and DEC Alphas running OpenVMS.
- statistics - Specifies whether or not caching statistics are displayed at the end of each CDF.
- zMode - Specifies which zMode should be used. May be one of the following...

Indicates that zMode is disabled.

1

Indicates that zMode/1 should be used (the dimension variances of rVariables will be preserved).

2

Indicates that zMode/2 should be used (the dimensions of rVariables having a variance of NOVARY (false) are hidden).

`reportType` - Specifies the types of return status codes from the CDF library which should be reported/displayed. `report` is a bit mask made up from the following CDFTools.NO_REPORTS, CDFTools.REPORT_ERRORS, CDFTools.REPORT_WARNINGS and CDFTools.REPORT_INFORMATION

`cacheSizeD` - The number of buffers to be used for the CDF's dotCDF file. Pass 0 to use the default.

Throws:

`java.io.IOException` - An exception is thrown if the file is bad or non-existent

`java.lang.InterruptedException` - An exception is thrown if an interrupt is issued **Note:**

When running an application that use this static method, make sure this **cdf.base** system property is defined (to the cdf installation). For example,

```
java -Dcdf.base=/home/cdf/cdf34_1-dist MyApp
```

skeletonCDF

```
public static void skeletonCDF(java.lang.String skeletonName,
                               java.lang.String cdfName,
                               boolean delete,
                               boolean log,
                               boolean neg2posfp0,
                               boolean statistics,
                               int zMode,
                               int reportType,
                               int cacheSizeD,
                               int cacheSizeS)
    throws java.io.IOException,
           java.lang.InterruptedException
```

`skeletonCDF` produces a CDF file from a skeleton table. A skeleton table is a text file which can be made through a text editor, or by `SkeletonCDF` program from an existng CDF.

Parameters:

`skeletonName` - is the pathname of the skeleton table to be used to create a CDF. (Do not enter an extension because ".skt" is appended automatically). If **null** is specified, the skeleton table is named <cdfName>.skt in the current directory

`cdfName` - The pathname of the created CDF from the skeleton table. Do not enter an extension.

`delete` - specifies whether or not the CDF should be deleted if it already exists.

`log` - Specifies whether or not messages are displayed as the program executes.

`neg2posfp0` - Specifies whether or not -0.0 is converted to 0.0 by the CDF library when read from a CDF. -0.0 is an illegal floating point value on VAXes and DEC Alphas running OpenVMS.

`statistics` - Specifies whether or not caching statistics are displayed at the end of each CDF.

zMode - Specifies which zMode should be used. May be one of the following...

0

Indicates that zMode is disabled.

1

Indicates that zMode/1 should be used (the dimension variances of rVariables will be preserved).

2

Indicates that zMode/2 should be used (the dimensions of rVariables having a variance of NOVARY (false) are hidden.

reportType - Specifies the types of return status codes from the CDF library which should be reported/displayed. report is a bit mask made up from the following CDFTools.NO_REPORTS, CDFTools.REPORT_ERRORS, CDFTools.REPORT_WARNINGS and CDFTools.REPORT_INFORMATION

cacheSizeD - The number of buffers to be used for the CDF's dotCDF file. Pass 0 to use the default.

cacheSizeS - The number of buffers to be used for the CDF's staging file. Pass 0 to use the default.

Throws:

java.io.IOException - An exception is thrown if the file is bad or non-existent

java.lang.InterruptedException - An exception is thrown if an interrupt is issued **Note:**
When running an application that use this static method, make sure this **cdf.base** system property is defined (to the cdf installation). For example,
java -Dcdf.base=/home/cdf/cdf34_1-dist MyApp

skeletonCDF

```
public static void skeletonCDF(java.lang.String skeletonName,
                               java.lang.String cdfName,
                               boolean delete,
                               boolean log,
                               boolean neg2posfp0,
                               boolean statistics,
                               int zMode,
                               int reportType,
                               int cacheSizeD,
                               int cacheSizeS,
                               int cacheSizeC)
    throws java.io.IOException,
           java.lang.InterruptedException
```

skeletonCDF produces a CDF file from a skeleton table. A skeleton table is a text file which can be made through a text editor, or by SkeletonCDF program from an existng CDF.

Parameters:

skeletonName - is the pathname of the skeleton table to be used to create a CDF. (Do not enter an extension because ".skt" is appended automatically). If **null** is specified, the skeleton table is named <cdfName>.skt in the current directory

cdfName - The pathname of the created CDF from the skeleton table. Do not enter an extension.

delete - specifies whether or not the CDF should be deleted if it already exists.

`log` - Specifies whether or not messages are displayed as the program executes.

`neg2posfp0` - Specifies whether or not -0.0 is converted to 0.0 by the CDF library when read from a CDF. -0.0 is an illegal floating point value on VAXes and DEC Alphas running OpenVMS.

`statistics` - Specifies whether or not caching statistics are displayed at the end of each CDF.

`zMode` - Specifies which `zMode` should be used. May be one of the following...

0

Indicates that `zMode` is disabled.

1

Indicates that `zMode/1` should be used (the dimension variances of `rVariables` will be preserved).

2

Indicates that `zMode/2` should be used (the dimensions of `rVariables` having a variance of `NOVARY` (false) are hidden).

`reportType` - Specifies the types of return status codes from the CDF library which should be reported/displayed. `report` is a bit mask made up from the following `CDFTools.NO_REPORTS`, `CDFTools.REPORT_ERRORS`, `CDFTools.REPORT_WARNINGS` and `CDFTools.REPORT_INFORMATION`

`cacheSizeD` - The number of buffers to be used for the CDF's dotCDF file. Pass 0 to use the default.

`cacheSizeS` - The number of buffers to be used for the CDF's staging file. Pass 0 to use the default.

`cacheSizeC` - The number of buffers to be used for the CDF's compression scratch file. Pass 0 to use the default.

Throws:

`java.io.IOException` - An exception is thrown if the file is bad or non-existent

`java.lang.InterruptedException` - An exception is thrown if an interrupt is issued **Note:**
When running an application that use this static method, make sure this **cdf.base** system property is defined (to the cdf installation). For example,
`java -Dcdf.base=/home/cdf/cdf34_1-dist MyApp`

skeletonCDF

```
public static void skeletonCDF(java.lang.String skeletonName,
                               java.lang.String cdfName,
                               boolean delete,
                               boolean log,
                               boolean neg2posfp0,
                               boolean statistics,
                               int zMode,
                               int reportType,
                               java.lang.String cacheSize)
    throws java.io.IOException,
           java.lang.InterruptedException
```

`skeletonCDF` produces a CDF file from a skeleton table. A skeleton table is a text file which can be made through a text editor, or by `SkeletonCDF` program from an existng CDF.

Parameters:

`skeletonName` - is the pathname of the skeleton table to be used to create a CDF. (Do not enter an extension because ".skt" is appended automatically). If `null` is specified, the skeleton table is named `<cdfName>.skt` in the current directory

`cdfName` - The pathname of the created CDF from the skeleton table. Do not enter an extension.

`delete` - specifies whether or not the CDF should be deleted if it already exists.

`log` - Specifies whether or not messages are displayed as the program executes.

`neg2posfp0` - Specifies whether or not -0.0 is converted to 0.0 by the CDF library when read from a CDF. -0.0 is an illegal floating point value on VAXes and DEC Alphas running OpenVMS.

`statistics` - Specifies whether or not caching statistics are displayed at the end of each CDF.

`zMode` - Specifies which `zMode` should be used. May be one of the following...

0

Indicates that `zMode` is disabled.

1

Indicates that `zMode/1` should be used (the dimension variances of `rVariables` will be preserved).

2

Indicates that `zMode/2` should be used (the dimensions of `rVariables` having a variance of `NOVARY` (false) are hidden.

`reportType` - Specifies the types of return status codes from the CDF library which should be reported/displayed. `report` is a bit mask made up from the following `CDFTools.NO_REPORTS`, `CDFTools.REPORT_ERRORS`, `CDFTools.REPORT_WARNINGS` and `CDFTools.REPORT_INFORMATION`

`cacheSize` - The number of buffers to be used for the CDF's dotCDF file, staging file, and compression scratch file. This field used only in the CDF access process will not change the contents of the CDF. Large number(s) will likely reduce physical I/Os if variable data are involved. If this field is null, default cache sizes chosen by the CDF library are used. The cache sizes are specified with a comma-separated list of `<number><type>` pairs where `<number>` is the number of cache buffers and `<type>` is the type of file. The file `<type>`'s are as follows: ``d'` for the dotCDF file, ``s'` for the staging file, and ``c'` for the compression scratch file. For example, `'200d,100s'` specifies 200 cache buffers for the dotCDF file and 100 cache buffers for the staging file. The dotCDF file cache size can also be specified without the ``d' <type>` for compatibility with older CDF releases (eg. `'200,100s'`). Note that not all of the file types must be specified. Those not specified will receive a default cache size.

Throws:

`java.io.IOException` - An exception is thrown if the file is bad or non-existent

`java.lang.InterruptedException` - An exception is thrown if an interrupt is issued **Note:**

When running an application that use this static method, make sure this **`cdf.base`** system property is defined (to the cdf installation). For example,

`java -Dcdf.base=/home/cdf/cdf34_1-dist MyApp`

Overview	Package	Class	Tree	Deprecated	Index	Help		
Prev Class	Next Class		Frames	No Frames	All Classes			
Summary: Nested Field Constr Method			Detail: Field Constr Method					

Overview	Package	Class	Tree	Deprecated	Index	Help
Prev Class	Next Class	Frames	No Frames	All Classes		
Summary: Nested Field Constr Method			Detail: Field Constr Method			

gsfc.nssdc.cdf.util

Class CDFTT2000

java.lang.Object
gsfc.nssdc.cdf.util.CDFTT2000

All Implemented Interfaces:

CDFConstants

```
public class CDFTT2000
extends java.lang.Object
implements CDFConstants
```

This class contains the handy utility routines (methods) called by the CDF applications to handle epoch data of CDF's CDF_TIME_TT2000 data type.

Version:

1.0, 2.0 01/05/15 Add a new leap second for 2015/07/01., 3.0 10/20/16 Add a new leap second for 2016/01/01.

Field Summary

Fields inherited from interface gsfc.nssdc.cdf.CDFConstants

AHUFF COMPRESSION, ALPHAOSF1 DECODING, ALPHAOSF1 ENCODING, ALPHAVMSd DECODING, ALPHAVMSd ENCODING, ALPHAVMSg DECODING, ALPHAVMSg ENCODING, ALPHAVMSi DECODING, ALPHAVMSi ENCODING, ARM BIG DECODING, ARM BIG ENCODING, ARM LITTLE DECODING, ARM LITTLE ENCODING, ATTR, ATTR EXISTENCE, ATTR EXISTS, ATTR MAXgENTRY, ATTR MAXrENTRY, ATTR MAXzENTRY, ATTR NAME, ATTR NAME TRUNC, ATTR NUMBER, ATTR NUMgENTRIES, ATTR NUMrENTRIES, ATTR NUMzENTRIES, ATTR SCOPE, BACKWARD, BACKWARDFILEoff, BACKWARDFILEon, BAD ALLOCATE RECS, BAD ARGUMENT, BAD ATTR NAME, BAD ATTR NUM, BAD BLOCKING FACTOR, BAD CACHE SIZE, BAD CDF EXTENSION, BAD CDF ID, BAD CDF NAME, BAD CDFSTATUS, BAD CHECKSUM, BAD COMPRESSION PARM, BAD DATA TYPE, BAD DECODING, BAD DIM COUNT, BAD DIM INDEX, BAD DIM INTERVAL, BAD DIM SIZE, BAD ENCODING, BAD ENTRY NUM, BAD FNC OR ITEM, BAD FORMAT, BAD INITIAL RECS, BAD MAJORITY, BAD MALLOC, BAD NEGtoPOSfp0 MODE, BAD NUM DIMS, BAD NUM ELEMS, BAD NUM STRINGS, BAD NUM VARS, BAD READONLY MODE, BAD REC COUNT, BAD REC INTERVAL, BAD REC NUM, BAD SCOPE, BAD SCRATCH DIR, BAD SPARSEARRAYS PARM, BAD VAR NAME, BAD VAR NUM, BAD zMODE, BADDATE LEAPSECOND UPDATED, BeginUnixTimeEPOCH, BeginUnixTimeEPOCH16, BLOCKINGFACTOR TOO LARGE, BLOCKINGFACTOR TOO SMALL, BLOCKINGFACTOR TOO SMALL2, CANNOT ALLOCATE RECORDS, CANNOT CHANGE, CANNOT COMPRESS, CANNOT CONVERT WIDECHAR, CANNOT COPY, CANNOT INSERT RECORDS, CANNOT SPARSEARRAYS, CANNOT SPARSERECORDS, CDF, CDF ACCESS, CDF ATTR NAME LEN, CDF ATTR NAME LEN256, CDF BYTE, CDF CACHESIZE, CDF CHAR, CDF CHECKSUM, CDF CLOSE ERROR, CDF COMPRESSION, CDF COPYRIGHT, CDF COPYRIGHT LEN, CDF CREATE ERROR, CDF DECODING, CDF DELETE ERROR, CDF DOUBLE, CDF ENCODING, CDF EPOCH, CDF EPOCH16, CDF EXISTS, CDF FLOAT, CDF FORMAT, CDF INCREMENT, CDF INFO, CDF INT1, CDF INT2, CDF INT4, CDF INT8, CDF INTERNAL ERROR, CDF LEAPSECONDLASTUPDATED, CDF MAJORITY, CDF MAX DIMS, CDF MAX PARMS, CDF MIN DIMS, CDF NAME, CDF NAME TRUNC, CDF NEGtoPOSfp0 MODE, CDF NUMATTRS, CDF NUMgATTRS, CDF NUMrVARS, CDF NUMvATTRS, CDF NUMzVARS, CDF OK, CDF OPEN ERROR, CDF PATHNAME LEN, CDF READ ERROR, CDF READONLY MODE, CDF REAL4, CDF REAL8, CDF RELEASE, CDF SAVE ERROR, CDF SCRATCHDIR, CDF STATUS, CDF STATUSTEXT LEN, CDF TIME TT2000, CDF UCHAR, CDF UINT1, CDF UINT2, CDF UINT4, CDF VAR NAME LEN, CDF VAR NAME LEN256, CDF VERSION, CDF WARN, CDF WRITE ERROR, CDF zMODE, CDFwithSTATS, CHECKSUM, CHECKSUM ERROR, CHECKSUM NOT ALLOWED, CLOSE, COLUMN MAJOR, COMPRESS CACHESIZE, COMPRESSION ERROR, CONFIRM, CORRUPTED V2 CDF, CORRUPTED V3 CDF, CREATE, CURgENTRY EXISTENCE, CURrENTRY EXISTENCE, CURzENTRY EXISTENCE, DATATYPE MISMATCH, DATATYPE SIZE, DECOMPRESSION ERROR, DECSTATION DECODING, DECSTATION ENCODING, DEFAULT BYTE PADVALUE, DEFAULT CHAR PADVALUE, DEFAULT DOUBLE PADVALUE, DEFAULT EPOCH PADVALUE, DEFAULT EPOCH16 PADVALUE, DEFAULT FLOAT PADVALUE, DEFAULT INT1 PADVALUE, DEFAULT INT2 PADVALUE, DEFAULT INT4 PADVALUE, DEFAULT INT8 PADVALUE, DEFAULT REAL4 PADVALUE, DEFAULT REAL8 PADVALUE, DEFAULT TT2000 PADVALUE, DEFAULT UCHAR PADVALUE, DEFAULT UINT1 PADVALUE, DEFAULT UINT2 PADVALUE, DEFAULT UINT4 PADVALUE, DELETE, DID NOT COMPRESS, EMPTY COMPRESSED CDF, END OF VAR, EPOCH STRING LEN, EPOCH STRING LEN EXTEND, EPOCH1 STRING LEN, EPOCH1 STRING LEN EXTEND, EPOCH2 STRING LEN, EPOCH2 STRING LEN EXTEND, EPOCH3 STRING LEN, EPOCH3 STRING LEN EXTEND, EPOCH4 STRING LEN, EPOCH4 STRING LEN EXTEND, EPOCHx FORMAT MAX, EPOCHx STRING MAX, FILLED TT2000 VALUE, FORCED PARAMETER, FUNCTION NOT SUPPORTED, gENTRY, gENTRY DATA, gENTRY DATASPEC, gENTRY DATATYPE, gENTRY EXISTENCE, gENTRY NUMELEMS, GET, GETCDFCHECKSUM, GETCDFFILEBACKWARD, GETCDFVALIDATE, GETLEAPSECONDSENVVAR, GLOBAL SCOPE, GZIP COMPRESSION, HOST DECODING, HOST ENCODING, HP DECODING, HP ENCODING, HUFF COMPRESSION, IA64VMSd DECODING, IA64VMSd ENCODING, IA64VMSg DECODING, IA64VMSg ENCODING, IA64VMSi DECODING, IA64VMSi ENCODING, IBM_PC_OVERFLOW, IBMPC DECODING, IBMPC ENCODING, IBMRS DECODING,

IBMRS ENCODING, ILLEGAL EPOCH FIELD, ILLEGAL EPOCH VALUE, ILLEGAL FOR SCOPE, ILLEGAL_IN_zMODE, ILLEGAL ON V1 CDF, ILLEGAL TT2000 VALUE, IS A NETCDF, LIB COPYRIGHT, LIB INCREMENT, LIB RELEASE, LIB subINCREMENT, LIB VERSION, MAC DECODING, MAC ENCODING, MD5 CHECKSUM, MULTI FILE, MULTI FILE FORMAT, NA FOR VARIABLE, NEGATIVE FP ZERO, NEGtoPOSfp0off, NEGtoPOSfp0on, NETWORK DECODING, NETWORK ENCODING, Next DECODING, NeXt ENCODING, NO ATTR SELECTED, NO CDF SELECTED, NO CHECKSUM, NO COMPRESSION, NO DELETE ACCESS, NO ENTRY SELECTED, NO MORE ACCESS, NO PADVALUE SPECIFIED, NO SPARSEARRAYS, NO SPARSERECORDS, NO STATUS SELECTED, NO SUCH ATTR, NO SUCH CDF, NO SUCH ENTRY, NO SUCH RECORD, NO SUCH VAR, NO VAR SELECTED, NO VARS IN CDF, NO WRITE ACCESS, NONE CHECKSUM, NOT A CDF, NOT A CDF OR NOT SUPPORTED, NOVARY, NULL, OPEN, OPTIMAL ENCODING TREES, OTHER CHECKSUM, PAD SPARSERECORDS, PPC DECODING, PPC ENCODING, PRECEDING RECORDS ALLOCATED, PREV SPARSERECORDS, PUT, READ ONLY DISTRIBUTION, READ_ONLY_MODE, READONLYoff, READONLYon, rENTRY, rENTRY DATA, rENTRY DATASPEC, rENTRY DATATYPE, rENTRY EXISTENCE, rENTRY NAME, rENTRY NUMELEMS, rENTRY NUMSTRINGS, rENTRY STRINGSDATA, RLE COMPRESSION, RLE OF ZEROS, ROW MAJOR, rVAR, rVAR ALLOCATEBLOCK, rVAR ALLOCATEDFROM, rVAR ALLOCATEDTO, rVAR ALLOCATERECS, rVAR BLOCKINGFACTOR, rVAR CACHESIZE, rVAR COMPRESSION, rVAR DATA, rVAR DATASPEC, rVAR DATATYPE, rVAR DIMVARYS, rVAR EXISTENCE, rVAR HYPERDATA, rVAR INITIALRECS, rVAR MAXallocREC, rVAR MAXREC, rVAR NAME, rVAR nINDEXENTRIES, rVAR nINDEXLEVELS, rVAR nINDEXRECORDS, rVAR NUMallocRECS, rVAR NUMBER, rVAR NUMELEMS, rVAR NUMRECS, rVAR PADVALUE, rVAR RECORDS, rVAR RECORDS RENUMBER, rVAR RECVAR, rVAR RESERVEPERCENT, rVAR SEQDATA, rVAR SEQPOS, rVAR SPARSEARRAYS, rVAR SPARSERECORDS, rVARs CACHESIZE, rVARs DIMCOUNTS, rVARs DIMINDICES, rVARs DIMINTERVALS, rVARs DIMSIZES, rVARs MAXREC, rVARs NUMDIMS, rVARs RECCOUNT, rVARs RECDATA, rVARs RECINTERVAL, rVARs RECNUMBER, SAVE, SCRATCH CREATE ERROR, SCRATCH DELETE ERROR, SCRATCH READ ERROR, SCRATCH WRITE ERROR, SELECT, SGI DECODING, SGI ENCODING, SINGLE FILE, SINGLE FILE FORMAT, SOME ALREADY ALLOCATED, STAGE CACHESIZE, STATUS TEXT, STRING NOT UTF8 ENCODING, STRINGDELIMITER, SUN DECODING, SUN ENCODING, TOO MANY PARMS, TOO MANY VARS, TRY TO READ NONSTRING DATA, TT2000 0 STRING LEN, TT2000 1 STRING LEN, TT2000 2 STRING LEN, TT2000 3 STRING LEN, TT2000 4 STRING LEN, TT2000 CDF MAYNEEDUPDATE, TT2000 TIME ERROR, TT2000 USED OUTDATED TABLE, UNABLE TO PROCESS CDF, UNKNOWN COMPRESSION, UNKNOWN SPARSENESS, UNSUPPORTED OPERATION, VALIDATE, VALIDATEfileoff, VALIDATEfileon, VAR ALREADY CLOSED, VAR CLOSE ERROR, VAR CREATE ERROR, VAR DELETE ERROR, VAR EXISTS, VAR NAME TRUNC, VAR OPEN ERROR, VAR READ ERROR, VAR SAVE ERROR, VAR WRITE ERROR, VARIABLE SCOPE, VARY, VAX DECODING, VAX ENCODING, VIRTUAL RECORD DATA, zENTRY, zENTRY DATA, zENTRY DATASPEC, zENTRY DATATYPE, zENTRY EXISTENCE, zENTRY NAME, zENTRY NUMELEMS, zENTRY NUMSTRINGS, zENTRY STRINGSDATA, ZLIB COMPRESS ERROR, ZLIB UNCOMPRESS ERROR, zMODEoff, zMODEon1, zMODEon2, zVAR, zVAR ALLOCATEBLOCK, zVAR ALLOCATEDFROM, zVAR ALLOCATEDTO, zVAR ALLOCATERECS, zVAR BLOCKINGFACTOR, zVAR CACHESIZE, zVAR COMPRESSION, zVAR DATA, zVAR DATASPEC, zVAR DATATYPE, zVAR DIMCOUNTS, zVAR DIMINDICES, zVAR DIMINTERVALS, zVAR DIMSIZES, zVAR DIMVARYS, zVAR EXISTENCE, zVAR HYPERDATA, zVAR INITIALRECS, zVAR MAXallocREC, zVAR MAXREC, zVAR NAME, zVAR nINDEXENTRIES, zVAR nINDEXLEVELS, zVAR nINDEXRECORDS, zVAR NUMallocRECS, zVAR NUMBER, zVAR NUMDIMS, zVAR NUMELEMS, zVAR NUMRECS, zVAR PADVALUE, zVAR RECCOUNT, zVAR RECINTERVAL, zVAR RECNUMBER, zVAR RECORDS, zVAR RECORDS RENUMBER, zVAR RECVAR, zVAR RESERVEPERCENT, zVAR SEQDATA, zVAR SEQPOS, zVAR SPARSEARRAYS, zVAR SPARSERECORDS, zVARs CACHESIZE, zVARs MAXREC, zVARs RECDATA, zVARs RECNUMBER

Constructor Summary

Constructors
Constructor and Description
CDFTT2000 ()

Method Summary

Methods	
Modifier and Type	Method and Description
static long[]	breakdown (long nanoSecSinceJ2000) Breaks a TT2000 epoch value down into its full, UTC-based date/time component parts.
static long[][]	breakdown (long[] nanoSecSinceJ2000) Breaks an array of TT2000 epoch values down into two dimensional array, the first dimension being the count of the epoch values, and the second dimension being their full, UTC-based date/time component parts for each value.
static long[]	breakdownTT2000 (long nanoSecSinceJ2000) Breaks a TT2000 epoch value down into its full, UTC-based date/time component parts - new name as toUTCparts.
static long[]	breakdownTT2000withBasedLeapDay (long tt2000, int yymdd)

breakdownTT2000withBasedLeapDay.

static long[]	CDFgetLastDateinLeapSecondsTable() /** This method returns the last UTC date that a leap second was added in the leap second table used in the class.
static double[][]	CDFgetLeapSecondsTable() This method returns the leap seconds table.
static int	CDFgetLeapSecondsTableStatus() This method returns the status code reflecting whether the leap seconds are from a external file, defined by an environment variable, or the leap seconds are based on the hard-coded table in the class.
static int	CDFgetRowsinLeapSecondsTable() This method returns the number of entries in the leap seconds table.
static long[]	compute (long[] year, long[] month, long[] day) Computes an array of TT2000 epochs, nanoseconds since J2000, based on its UTC-based date/time component parts.
static long[]	compute (long[] year, long[] month, long[] day, long[] hour) Computes an array of TT2000 epochs, nanoseconds since J2000, based on its UTC-based date/time component parts.
static long[]	compute (long[] year, long[] month, long[] day, long[] hour, long[] minute) Computes an array of TT2000 epochs, nanoseconds since J2000, based on its * UTC-based date/time component parts.
static long[]	compute (long[] year, long[] month, long[] day, long[] hour, long[] minute, long[] second) Computes an array of TT2000 epochs, nanoseconds since J2000, based on its * UTC-based date/time component parts.
static long[]	compute (long[] year, long[] month, long[] day, long[] hour, long[] minute, long[] second, long[] msec) Computes an array of TT2000 epochs, nanoseconds since J2000, based on its * UTC-based date/time component parts.
static long[]	compute (long[] year, long[] month, long[] day, long[] hour, long[] minute, long[] second, long[] msec, long[] usec) Computes an array of TT2000 epochs, nanoseconds since J2000, based on its * UTC-based date/time component parts.
static long[]	compute (long[] year, long[] month, long[] day, long[] hour, long[] minute, long[] second, long[] msec, long[] usec, long[] nsec) Computes an array of TT2000 epochs, nanoseconds since J2000, based on its * UTC-based date/time component parts.
static long	compute (long year, long month, long day, long hour, long minute, long second, long msec, long usec, long nsec) Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
static long	computeTT2000 (double year, double month, double day) Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
static long	computeTT2000 (double year, double month, double day, double hour) Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
static long	computeTT2000 (double year, double month, double day, double hour, double minute) Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
static long	computeTT2000 (double year, double month, double day, double hour, double minute, double second) Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.

static long	<code>computeTT2000</code> (double year, double month, double day, double hour, double minute, double second, double milsec) Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
static long	<code>computeTT2000</code> (double year, double month, double day, double hour, double minute, double second, double milsec, double micsec) Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
static long	<code>computeTT2000</code> (double year, double month, double day, double hour, double minute, double second, double msec, double usec, double nsec) Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts - a new name from fromUTCparts.
static long	<code>computeTT2000withBasedLeapDay</code> (double yy, double mm, double dd, double hh, double mn, double ss, double ms, double us, double ns, int yymmdd) This method returns the TT2000 time in nanoseconds based on the last leap second day.
static long	<code>computeTT2000withBasedLeapDay</code> (long yy, long mm, long dd, long hh, long mn, long ss, long ms, long us, long ns, int yymmdd) This method returns the TT2000 time in nanoseconds based on the last leap second day.
static java.lang.String	<code>encode</code> (long nanoSecSinceJ2000) Converts an epoch value in TT2000 type into a readable, UTC-based date/time string in ISO 8601 style.
static java.lang.String[]	<code>encode</code> (long[] nanoSecSinceJ2000) Converts an array of epoch values in TT2000 type into an array of readable, UTC-based date/time strings in ISO 8601 style.
static java.lang.String[]	<code>encode</code> (long[] nanoSecSinceJ2000, int style) Converts an array of epoch values in TT2000 type into readable, UTC-based date/time strings of chosen style.
static java.lang.String	<code>encode</code> (long nanoSecSinceJ2000, int style) Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of chosen style.
static java.lang.String	<code>encodeTT2000withBasedLeapDay</code> (long tt2000, int yymmdd) encodeTT2000withBasedLeapDay.
static long	<code>fromGregorianTime</code> (java.util.GregorianCalendar gc) This method converts the UTC-based date/time in a GregorianCalendar class object to TT2000 time.
static long	<code>fromUTCEPOCH</code> (double epoch) Convert an epoch value in CDF_EPOCH type to TT2000 type.
static long	<code>fromUTCEPOCH16</code> (double[] epoch) Convert an epoch data in CDF_EPOCH16 type to TT2000 type.
static long[]	<code>fromUTCISO8601string</code> (java.lang.String string) This method parses an input, UTC-based, date/time string in ISO 8601 and returns their date/time components.
static long	<code>fromUTCparts</code> (double year, double month, double day) Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
static long	<code>fromUTCparts</code> (double year, double month, double day, double hour) Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
static long	<code>fromUTCparts</code> (double year, double month, double day, double hour, double minute) Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based

	date/time component parts.
static long	fromUTCparts (double year, double month, double day, double hour, double minute, double second) Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
static long	fromUTCparts (double year, double month, double day, double hour, double minute, double second, double milsec) Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
static long	fromUTCparts (double year, double month, double day, double hour, double minute, double second, double milsec, double micsec) Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
static long	fromUTCparts (double year, double month, double day, double hour, double minute, double second, double msec, double usec, double nsec) Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
static long	fromUTCstring (java.lang.String string) This method parses an input, UTC-based, date/time string and returns a TT2000 epoch value, nanoseconds since J2000.
static java.lang.String	getLeapSecondsTableEnvVar () Find the environment variable "CDF_LEAPSECONDSTABLE" that is defined for the leap seconds table for CDF.
static double	LeapSecondsfromYMD (long year, long month, long day) Find the leap seconds from a given, UTC-based year/month/day.
static long	parse (java.lang.String string) This method parses an input date/time string and returns a TT2000 epoch value, nanoseconds since J2000.
static long[]	parse (java.lang.String[] strings) This method parses an array of input date/time strings and returns an array of TT2000 epoch values, nanoseconds since J2000.
static long	parseTT2000 (java.lang.String string) This method parses an input, UTC-based, date/time string and returns a TT2000 epoch value, nanoseconds since J2000.
static long[]	parseTT2000 (java.lang.String[] strings) This method parses an input, UTC-based, date/time strings and returns a TT2000 epoch value array, nanoseconds since J2000.
static long	parseTT2000withBasedLeapDay (java.lang.String tt2000, int yymmdd) parseTT2000withBasedLeapDay .
static java.lang.String	toEncode (long nanoSecSinceJ2000) Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of ISO 8601 forme.
static java.lang.String[]	toEncode (long[] nanoSecSinceJ2000) Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of ISO8601 style (style 3).
static java.lang.String[]	toEncode (long[] nanoSecSinceJ2000, int style) Converts an array of epoch values in TT2000 type into readable, UTC-based date/time strings of chosen style.
static java.lang.String	toEncode (long nanoSecSinceJ2000, int style) Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of chosen style.
static java.lang.String	toEncode (java.lang.Long nanoSecSinceJ2000, int style) Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of chosen style.

static java.lang.Object	toEncode (java.lang.Object epoch) Converts an epoch object in TT2000 type into a scalar or array(s) of readable, UTC-based date/time string of ISO8601 style (style 3).
static java.util.GregorianCalendar	toGregorianTime (long tt2000) This method converts the UTC-based date/time in TT2000 type to a GregorianCalendar class object in default, local time zone.
static java.util.GregorianCalendar	toGregorianTime (long tt2000, java.util.TimeZone tz) This method converts the UTC-based date/time in TT2000 type to a GregorianCalendar class object in specified time zone.
static long	toParse (java.lang.String string) This method parses an input, UTC-based, date/time string and returns a TT2000 epoch value, nanoseconds since J2000.
static long[]	toParse (java.lang.String[] strings) This method parses an input, UTC-based, date/time strings and returns a TT2000 epoch value array, nanoseconds since J2000.
static double	toUTCEPOCH (long nanoSecSinceJ2000) Convert an epoch value in TT2000 type to CDF_EPOCH type.
static double	toUTCEPOCH16 (long nanoSecSinceJ2000, double[] epoch) Convert an epoch value in TT2000 type to CDF_EPOCH16 type.
static long[]	toUTCparts (long nanoSecSinceJ2000) Breaks a TT2000 epoch value down into its full, UTC-based date/time component parts.
static java.lang.String	toUTCstring (long nanoSecSinceJ2000) Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of ISO 8601 style.
static java.lang.String	toUTCstring (java.lang.Long nanoSecSinceJ2000) Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of ISO 8601 style.
static java.lang.String[]	toUTCstring (long[] nanoSecSinceJ2000) Converts an iarray of epoch values in TT2000 type into readable, UTC-based date/time strings of ISO 8601 style.
static java.lang.String[]	toUTCstring (long[] nanoSecSinceJ2000, int style) Converts an array of epoch values in TT2000 type into readable, UTC-based date/time strings of chosen style.
static java.lang.String	toUTCstring (long nanoSecSinceJ2000, int style) Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of chosen style.
static java.lang.String	toUTCstring (java.lang.Long nanoSecSinceJ2000, int style) Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of chosen style.
static double	TT2000toUnixTime (long epoch) Converts a TT2000 value to a unix time of a double value (seconds from 1970-01-01 00:00:00 UTC).
static double[]	TT2000toUnixTime (long[] epoch) Converts an array of TT2000 values to an array of unix time of a double value (seconds from 1970-01-01 00:00:00 UTC).
static long	UnixTimetoTT2000 (double unixTime) Converts a Unix time of a double value (seconds from 1970-01-01 00:00:00 UTC) to a TT2000 time.
static long[]	UnixTimetoTT2000 (double[] unixTimes) Converts an array of Unix time of double values (seconds from 1970-01-01 00:00:00 UTC) to an array of TT2000 times.

Methods inherited from class java.lang.Object

`equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

Constructor Detail

CDFTT2000

```
public CDFTT2000()
```

Method Detail

getLeapSecondsTableEnvVar

```
public static java.lang.String getLeapSecondsTableEnvVar()
```

Find the environment variable "CDF_LEAPSECONDSTABLE" that is defined for the leap seconds table for CDF.

Returns:

the leap seconds environment variable if defined null if not.

LeapSecondsfromYMD

```
public static double LeapSecondsfromYMD(long year,
                                         long month,
                                         long day)
```

Find the leap seconds from a given, UTC-based year/month/day.

Parameters:

- `year` - the year
- `month` - the month
- `day` - the day

Returns:

the leap second value (TAI-UTC)

breakdownTT2000

```
public static long[] breakdownTT2000(long nanoSecSinceJ2000)
```

Breaks a TT2000 epoch value down into its full, UTC-based date/time component parts - new name as toUTCparts.

Parameters:

- `nanoSecSinceJ2000` - the epoch value, in nanoseconds since J2000, to break down

Returns:

an array of long containing the epoch parts:

Index	Part
0	year
1	month
2	day
3	hour
4	minute
5	second
6	millisecond
7	microsecond
8	nanosecond

toUTCparts

```
public static long[] toUTCparts(long nanoSecSinceJ2000)
```

Breaks a TT2000 epoch value down into its full, UTC-based date/time component parts.

Parameters:

nanoSecSinceJ2000 - the epoch value, in nanoseconds since J2000, to break down

Returns:

an array of long containing the epoch parts:

Index	Part
0	year
1	month
2	day
3	hour
4	minute
5	second
6	millisecond
7	microsecond
8	nanosecond

breakdown

```
public static long[] breakdown(long nanoSecSinceJ2000)
```

Breaks a TT2000 epoch value down into its full, UTC-based date/time component parts.

Parameters:

nanoSecSinceJ2000 - the epoch value, in nanoseconds since J2000, to break down

Returns:

an array of long containing the epoch parts:

Index	Part
-------	------

0	year
1	month
2	day
3	hour
4	minute
5	second
6	millisecond
7	microsecond
8	nanosecond

breakdown

```
public static long[][] breakdown(long[] nanoSecSinceJ2000)
```

Breaks an array of TT2000 epoch values down into two dimensional array, the first dimension being the count of the epoch values, and the second dimension being their full, UTC-based date/time component parts for each value.

Parameters:

nanoSecSinceJ2000 - an array of epoch values, in nanoseconds since J2000, to break down

Returns:

a 2-dim array of long, the first dimension being the value count while the second dimension containing the epoch parts, as follows:

Index	Part
0	year
1	month
2	day
3	hour
4	minute
5	second
6	millisecond
7	microsecond
8	nanosecond

or null if null or an empty input array is detected

computeTT2000

```
public static long computeTT2000(double year,
                                double month,
                                double day)
    throws CDFException
```

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts. The day field can contain a fraction of a day - a new name from fromUTCparts.

Parameters:

year - the year, a full year in double

month - the month, a full month in double

day - the day, either the day of the month or day of the year (DOY). For DOY, month has to be one (1), otherwise an exception is thrown. It is in double

Returns:

the TT2000 epoch value in long

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

fromUTCparts

```
public static long fromUTCparts(double year,
                                double month,
                                double day)
                                throws CDFException
```

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts. The day field can contain a fraction of a day.

Parameters:

year - the year, a full year in double

month - the month, a full month in double

day - the day, either the day of the month or day of the year (DOY). For DOY, month has to be one (1), otherwise an exception is thrown. It is in double

Returns:

the TT2000 epoch value in long

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

computeTT2000

```
public static long computeTT2000(double year,
                                  double month,
                                  double day,
                                  double hour)
                                  throws CDFException
```

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts. The hour field can contain a fraction of a hour - a new name from `fromUTCparts`.

Parameters:

year - the year, a full year in double

month - the month, a full month in double

day - the day, either the day of the month or day of the year (DOY). For DOY, month has to be one (1), otherwise an exception is thrown. A full day in double

hour - the hour in double **Note:** Avoid passing in the time component that extends into the next day as that could present a potential problem.

Returns:

the TT2000 epoch value in long

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

fromUTCparts

```
public static long fromUTCparts(double year,
                                double month,
                                double day,
                                double hour)
    throws CDFException
```

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts. The hour field can contain a fraction of a hour.

Parameters:

- `year` - the year, a full year in double
- `month` - the month, a full month in double
- `day` - the day, either the day of the month or day of the year (DOY). For DOY, month has to be one (1), otherwise an exception is thrown. A full day in double
- `hour` - the hour in double **Note:** Avoid passing in the time component that extends into the next day as that could present a potential problem.

Returns:

the TT2000 epoch value in long

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

computeTT2000

```
public static long computeTT2000(double year,
                                   double month,
                                   double day,
                                   double hour,
                                   double minute)
    throws CDFException
```

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts. The minute field can contain a fraction of a minute - a new name from `fromUTCparts`.

Parameters:

- `year` - the year, a full year in double
- `month` - the month, a full month in double
- `day` - the day, either the day of the month or day of the year (DOY). For DOY, month has to be one (1), otherwise an exception is thrown. A full day in double
- `hour` - the hour, a full hour in double
- `minute` - the minute in double **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

the TT2000 epoch value in long

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

fromUTCparts

```
public static long fromUTCparts(double year,
                                double month,
                                double day,
                                double hour,
                                double minute)
                                throws CDFException
```

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts. The minute field can contain a fraction of a minute.

Parameters:

- `year` - the year, a full year in double
- `month` - the month, a full month in double
- `day` - the day, either the day of the month or day of the year (DOY). For DOY, month has to be one (1), otherwise an exception is thrown. A full day in double
- `hour` - the hour, a full hour in double
- `minute` - the minute in double **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

the TT2000 epoch value in long

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

computeTT2000

```
public static long computeTT2000(double year,
                                   double month,
                                   double day,
                                   double hour,
                                   double minute,
                                   double second)
                                   throws CDFException
```

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts. The second field can contain a fraction of a second - a new name from `fromUTCparts`.

Parameters:

- `year` - the year, a full year in double
- `month` - the month, a full month in double
- `day` - the day, either the day of the month or day of the year (DOY). For DOY, month has to be one (1), otherwise an exception is thrown. A full day in double
- `hour` - the hour, a full hour in double
- `minute` - the minute, a full minute in double
- `second` - the second in double **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

the TT2000 epoch value in long

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

fromUTCparts

```
public static long fromUTCparts(double year,
                                double month,
                                double day,
                                double hour,
                                double minute,
                                double second)
                                throws CDFException
```

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts. The second field can contain a fraction of a second.

Parameters:

- year - the year, a full year in double
- month - the month, a full month in double
- day - the day, either the day of the month or day of the year (DOY). For DOY, month has to be one (1), otherwise an exception is thrown. A full day in double
- hour - the hour, a full hour in double
- minute - the minute, a full minute in double
- second - the second in double **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

the TT2000 epoch value in long

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

computeTT2000

```
public static long computeTT2000(double year,
                                  double month,
                                  double day,
                                  double hour,
                                  double minute,
                                  double second,
                                  double milsec)
                                  throws CDFException
```

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts. The millisecond field can contain a fraction of a millisecond - a new name from fromUTCparts.

Parameters:

- year - the year, a full year in double
- month - the month, a full month in double
- day - the day, either the day of the month or day of the year (DOY). For DOY, month has to be one (1), otherwise an exception is thrown. A full day in double
- hour - the hour, a full hour in double

minute - the minute, a full minute in double

second - the second, a full second in double

milsec - the millisecond in double **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

the TT2000 epoch value in long

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

fromUTCparts

```
public static long fromUTCparts(double year,
                                double month,
                                double day,
                                double hour,
                                double minute,
                                double second,
                                double milsec)
    throws CDFException
```

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts. The millisecond field can contain a fraction of a millisecond.

Parameters:

year - the year, a full year in double

month - the month, a full month in double

day - the day, either the day of the month or day of the year (DOY). For DOY, month has to be one (1), otherwise an exception is thrown. A full day in double

hour - the hour, a full hour in double

minute - the minute, a full minute in double

second - the second, a full second in double

milsec - the millisecond in double **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

the TT2000 epoch value in long

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

computeTT2000

```
public static long computeTT2000(double year,
                                  double month,
                                  double day,
                                  double hour,
                                  double minute,
                                  double second,
                                  double milsec,
                                  double micsec)
    throws CDFException
```

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts. The microsecond field

can contain a fraction, which usually indicates the end of the parameter list - a new name from fromUTCparts.

Parameters:

- year - the year, a full year in double
- month - the month, a full month in double
- day - the day, either the day of the month or day of the year (DOY). For DOY, month has to be one (1), otherwise an exception is thrown. A full day in double
- hour - the hour, a full hour in double
- minute - the minute, a full minute in double
- second - the second, a full second in double
- milsec - the millisecond, a full millisecond in double
- micsec - the microsecond in double **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

- the TT2000 epoch value in long

Throws:

- `CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

fromUTCparts

```
public static long fromUTCparts(double year,
                                double month,
                                double day,
                                double hour,
                                double minute,
                                double second,
                                double milsec,
                                double micsec)
    throws CDFException
```

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts. The microsecond field can contain a fraction, which usually indicates the end of the parameter list.

Parameters:

- year - the year, a full year in double
- month - the month, a full month in double
- day - the day, either the day of the month or day of the year (DOY). For DOY, month has to be one (1), otherwise an exception is thrown. A full day in double
- hour - the hour, a full hour in double
- minute - the minute, a full minute in double
- second - the second, a full second in double
- milsec - the millisecond, a full millisecond in double
- micsec - the microsecond in double **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

- the TT2000 epoch value in long

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

computeTT2000

```
public static long computeTT2000(double year,
                                double month,
                                double day,
                                double hour,
                                double minute,
                                double second,
                                double msec,
                                double usec,
                                double nsec)
    throws CDFException
```

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts - a new name from `fromUTCparts`.

Parameters:

- `year` - the year, a full year in double
- `month` - the month, a full month in double
- `day` - the day, either the day of the month or day of the year (DOY). For DOY, month has to be one (1), otherwise an exception is thrown. A full day in double
- `hour` - the hour, a full hour in double
- `minute` - the minute, a full minute in double
- `second` - the second, a full second in double
- `msec` - the millisecond, a full millisecond in double
- `usec` - the microsecond, a full microsecond in double
- `nsec` - the nanosecond, a full nanosecond in double **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

the TT2000 epoch value in long

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

fromUTCparts

```
public static long fromUTCparts(double year,
                                double month,
                                double day,
                                double hour,
                                double minute,
                                double second,
                                double msec,
                                double usec,
                                double nsec)
    throws CDFException
```

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.

Parameters:

- `year` - the year, a full year in double
- `month` - the month, a full month in double

day - the day, either the day of the month or day of the year (DOY). For DOY, month has to be one (1). A full day in double

hour - the hour, a full hour in double

minute - the minute, a full minute in double

second - the second, a full second in double

msec - the millisecond, a full millisecond in double

usec - the microsecond, a full microsecond in double

nsec - the nanosecond, a full nanosecond in double **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

the TT2000 epoch value in long

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

compute

```
public static long compute(long year,
                           long month,
                           long day,
                           long hour,
                           long minute,
                           long second,
                           long msec,
                           long usec,
                           long nsec)
    throws CDFException
```

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.

Parameters:

year - the year, a full year in long

month - the month, a full month in long

day - the day, a full day in long

hour - the hour, a full hour in long

minute - the minute, a full minute in long

second - the second, a full second in long

msec - the millisecond, a full millisecond in long

usec - the microsecond, a full microsecond in long

nsec - the nanosecond, a full nanosecond in long **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

the TT2000 epoch value in long

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

compute

```
public static long[] compute(long[] year,
                             long[] month,
                             long[] day)
    throws CDFException
```

Computes an array of TT2000 epochs, nanoseconds since J2000, based on its UTC-based date/time component parts.

Parameters:

- year - an array of years, a full year in long
- month - an array of months, a full month in long
- day - an array of days, a full day in long

Returns:

the TT2000 epoch values in long or null if an invalid input array(s) is detected

Throws:

CDFException - an TT2000_TIME_ERROR if an illegal component value is detected.

compute

```
public static long[] compute(long[] year,
                             long[] month,
                             long[] day,
                             long[] hour)
    throws CDFException
```

Computes an array of TT2000 epochs, nanoseconds since J2000, based on its UTC-based date/time component parts.

Parameters:

- year - an array of years, a full year in long
- month - an array of months, a full month in long
- day - an array of days, a full day in long
- hour - an array of hours, a full hour in long **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

the TT2000 epoch value in long or null if an invalid input array(s) is detected

Throws:

CDFException - an TT2000_TIME_ERROR if an illegal component value is detected.

compute

```
public static long[] compute(long[] year,
                             long[] month,
                             long[] day,
                             long[] hour,
                             long[] minute)
    throws CDFException
```

Computes an array of TT2000 epochs, nanoseconds since J2000, based on its * UTC-based date/time component parts.

Parameters:

- year - an array of years, a full year in long

month - an array of months, a full month in long

day - an array of days, a full day in long

hour - an array of hours, a full hour in long

minute - an array of minutes, a full minute in long **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

the TT2000 epoch values in long or null if an invalid input array(s) is detected

Throws:

[CDFException](#) - an TT2000_TIME_ERROR if an illegal component value is detected.

compute

```
public static long[] compute(long[] year,
                             long[] month,
                             long[] day,
                             long[] hour,
                             long[] minute,
                             long[] second)
    throws CDFException
```

Computes an array of TT2000 epochs, nanoseconds since J2000, based on its * UTC-based date/time component parts.

Parameters:

year - an array of years, a full year in long

month - an array of months, a full month in long

day - an array of days, a full day in long

hour - an array of hours, a full hour in long

minute - an array of minutes, a full minute in long

second - an array of seconds, a full second in long **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

the TT2000 epoch value in long or null if an invalid input array(s) is detected

Throws:

[CDFException](#) - an TT2000_TIME_ERROR if an illegal component value is detected.

compute

```
public static long[] compute(long[] year,
                             long[] month,
                             long[] day,
                             long[] hour,
                             long[] minute,
                             long[] second,
                             long[] msec)
    throws CDFException
```

Computes an array of TT2000 epochs, nanoseconds since J2000, based on its * UTC-based date/time component parts.

Parameters:

year - an array of years, a full year in long

month - an array of months, a full month in long

day - an array of days, a full day in long

hour - an array of hours, a full hour in long

minute - an array of minutes, a full minute in long

second - an array of seconds, a full second in long

msec - an array of milliseconds, a full millisecond in long **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

the TT2000 epoch values in long or null if an invalid input array(s) is detected

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

compute

```
public static long[] compute(long[] year,
                             long[] month,
                             long[] day,
                             long[] hour,
                             long[] minute,
                             long[] second,
                             long[] msec,
                             long[] usec)
    throws CDFException
```

Computes an array of TT2000 epochs, nanoseconds since J2000, based on its * UTC-based date/time component parts.

Parameters:

year - an array of years, a full year in long

month - an array of months, a full month in long

day - an array of days, a full day in long

hour - an array of hours, a full hour in long

minute - an array of minutes, a full minute in long

second - an array of seconds, a full second in long

msec - an array of milliseconds, a full millisecond in long

usec - an array of microseconds, a full microsecond in long **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

the TT2000 epoch value in long or null if an invalid input array(s) is detected

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

compute

```
public static long[] compute(long[] year,
                             long[] month,
                             long[] day,
                             long[] hour,
```

```
long[] minute,  
long[] second,  
long[] msec,  
long[] usec,  
long[] nsec)  
throws CDFException
```

Computes an array of TT2000 epochs, nanoseconds since J2000, based on its * UTC-based date/time component parts.

Parameters:

- year - an array of years, a full year in long
- month - an array of months, a full month in long
- day - an array of days, a full day in long
- hour - an array of hours, a full hour in long
- minute - an array of minutes, a full minute in long
- second - an array of seconds, a full second in long
- msec - an array of milliseconds, a full millisecond in long
- usec - an array of microseconds, a full microsecond in long
- nsec - an array of nanoseconds, a full nanosecond in long **Note:** Avoid passing in the time components that extend into the next day as that could present a potential problem.

Returns:

the TT2000 epoch values in long or null if an invalid input array(s) is detected

Throws:

CDFException - an TT2000_TIME_ERROR if an illegal component value is detected.

toUTCEPOCH

```
public static double toUTCEPOCH(long nanoSecSinceJ2000)  
throws CDFException
```

Convert an epoch value in TT2000 type to CDF_EPOCH type.

Parameters:

nanoSecSinceJ2000 - the nanoseconds since J2000

Returns:

the epoch value

Throws:

CDFException - an ILLEGAL_EPOCH_FIELD if an illegal component value is detected.

fromUTCEPOCH

```
public static long fromUTCEPOCH(double epoch)  
throws CDFException
```

Convert an epoch value in CDF_EPOCH type to TT2000 type. Reset the predefined CDF_EPOCH value of -1.0E31, -1.0E-31, or the default 0.0 or -0.0 (all are invalid for TT2000) to 0.

Parameters:

epoch

- the CDF_EPOCH value

Returns:

the TT2000 epoch in nanoseconds since J2000

Throws:

`CDFException` - an TT2000_TIME_ERROR if date is out of the valid range for TT2000.

toUTCEPOCH16

```
public static double toUTCEPOCH16(long nanoSecSinceJ2000,  
                                double[] epoch)  
    throws CDFException
```

Convert an epoch value in TT2000 type to CDF_EPOCH16 type.

Parameters:

- `nanoSecSinceJ2000` - the nanoseconds since J2000
- `epoch` - the returned CDF_EPOCH16 value, a double[2] object

Returns:

the status

Throws:

`CDFException` - an ILLEGAL_EPOCH_FIELD if an illegal component value is detected.

fromUTCEPOCH16

```
public static long fromUTCEPOCH16(double[] epoch)  
    throws CDFException
```

Convert an epoch data in CDF_EPOCH16 type to TT2000 type. Reset the predefined CDF_EPOCH value of -1.0E31, -1.0E-31, or the default 0.0 or -0.0 (all are invalid for TT2000) to 0.

Parameters:

- `epoch` - the CDF_EPOCH16 value, a double[2] object

Returns:

the TT2000 epoch in nanoseconds since J2000

Throws:

`CDFException` - an TT2000_TIME_ERROR if date is out of the valid range for TT2000.

toUTCstring

```
public static java.lang.String toUTCstring(java.lang.Long nanoSecSinceJ2000)
```

Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of ISO 8601 style.

Examples: yyyy-mm-ddThh:mm:ss.aaaaaaaaa
 1990-04-01T03:05:02.000000000
 1993-10-10T23:45:49.777888999

Parameters:

nanoSecSinceJ2000 - the TT2000 epoch value, nanoseconds since J2000, in Long object

Returns:

A string representation of the epoch in ISO 8601

toUTCstring

```
public static java.lang.String toUTCstring(long nanoSecSinceJ2000)
```

Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of ISO 8601 style.

Examples: yyyy-mm-ddThh:mm:ss.ccccccccc
 1990-04-01T03:05:02.000000000
 1993-10-10T23:45:49.777888999

Parameters:

nanoSecSinceJ2000 - the TT2000 epoch value, nanoseconds since J2000, in long

Returns:

A string representation of the epoch

toUTCstring

```
public static java.lang.String[] toUTCstring(long[] nanoSecSinceJ2000)
```

Converts an iarray of epoch values in TT2000 type into readable, UTC-based date/time strings of ISO 8601 style.

Examples: yyyy-mm-ddThh:mm:ss.ccccccccc
 1990-04-01T03:05:02.000000000
 1993-10-10T23:45:49.777888999

Parameters:

nanoSecSinceJ2000 - the TT2000 epoch values, nanoseconds since J2000, in long

Returns:

A string array representation of the epochs

toUTCstring

```
public static java.lang.String toUTCstring(java.lang.Long nanoSecSinceJ2000,  
                                           int style)
```

Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of chosen style.

Style:0 dd-mmm-yyyy hh:mm:ss.ccccccccc
Examples: 01-Apr-1990 03:05:02.000000000
 10-Oct-1993 23:45:49.777888999

Style:1 yyyymmdd.ccccccccc
Examples: 19900401.1234567890
 19931010.9998887776

Style:2 yyyymmddhhmmss
Examples: 19900401030502
 19931010234549

Style:3 yyyy-mm-ddThh:mm:ss.ccccccccc
Examples: 1990-04-01T03:05:02.000000000

```
1993-10-10T23:45:49.777888999
This is the default, ISO 8601, output.

Style:4      yyyy-mm-ddThh:mm:ss.CCCCCCCCCZ
Examples:    1990-04-01T03:05:02.000000000Z
              1993-10-10T23:45:49.777888999Z
```

These styles are the same as those expected by fromUTCstring.

Parameters:

- nanoSecSinceJ2000 - the TT2000 epoch value, nanoseconds since J2000, in Long object
- style - the style (from 0 to 4, 3 being the default), an optional

Returns:

A string representation of the epoch

toEncode

```
public static java.lang.String toEncode(java.lang.Long nanoSecSinceJ2000,
                                         int style)
```

Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of chosen style.

```
Style:0      dd-mmm-yyyy hh:mm:ss.CCCCCCCCC
Examples:    01-Apr-1990 03:05:02.000000000
              10-Oct-1993 23:45:49.777888999

Style:1      yyyymmdd.CCCCCCCCC
Examples:    19900401.1234567890
              19931010.9998887776

Style:2      yyyymmddhhmmss
Examples:    19900401030502
              19931010234549

Style:3      yyyy-mm-ddThh:mm:ss.CCCCCCCCC
Examples:    1990-04-01T03:05:02.000000000
              1993-10-10T23:45:49.777888999
This is the default, ISO 8601, output.

Style:4      yyyy-mm-ddThh:mm:ss.CCCCCCCCCZ
Examples:    1990-04-01T03:05:02.000000000Z
              1993-10-10T23:45:49.777888999Z
```

These styles are the same as those expected by fromUTCstring.

Parameters:

- nanoSecSinceJ2000 - the TT2000 epoch value, nanoseconds since J2000, in Long object
- style - the style (from 0 to 4, 3 being the default), an optional

Returns:

A string representation of the epoch

toEncode

```
public static java.lang.String toEncode(long nanoSecSinceJ2000)
```

Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of ISO 8601 forme.

```
Examples:    1990-04-01T03:05:02.000000000
              1993-10-10T23:45:49.777888999
This is the default, ISO 8601, output.
```

These styles are the same as those expected by fromUTCstring.

Parameters:

nanoSecSinceJ2000 - the TT2000 epoch value, nanoseconds since J2000, in long

Returns:

A string representation of the epoch

toEncode

```
public static java.lang.String toEncode(long nanoSecSinceJ2000,
                                     int style)
```

Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of chosen style.

Style:0 dd-mmm-yyyy hh:mm:ss.ccccccccc
Examples: 01-Apr-1990 03:05:02.000000000
 10-Oct-1993 23:45:49.777888999

Style:1 yyyyymmdd.ccccccccc
Examples: 19900401.1234567890
 19931010.9998887776

Style:2 yyyyymmddhhmmss
Examples: 19900401030502
 19931010234549

Style:3 yyyy-mm-ddThh:mm:ss.ccccccccc
Examples: 1990-04-01T03:05:02.000000000
 1993-10-10T23:45:49.777888999
This is the default, ISO 8601, output.

Style:4 yyyy-mm-ddThh:mm:ss.cccccccccZ
Examples: 1990-04-01T03:05:02.000000000Z
 1993-10-10T23:45:49.777888999Z

These styles are the same as those expected by fromUTCstring.

Parameters:

nanoSecSinceJ2000 - the TT2000 epoch value, nanoseconds since J2000, in long

style - the style (from 0 to 4, 3 being the default), an optional

Returns:

A string representation of the epoch

toEncode

```
public static java.lang.Object toEncode(java.lang.Object epoch)
```

Converts an epoch object in TT2000 type into a scalar or array(s) of readable, UTC-based date/time string of ISO8601 style (style 3). Each string is presented in the following form:

Examples: 1990-04-01T03:05:02.000000000
 1993-10-10T23:45:49.777888999

Parameters:

epoch - the TT2000 epoch object, nanoseconds since J2000, in long

Returns:

A string or array(s) of strings representation of the epoch

toEncode

```
public static java.lang.String[] toEncode(long[] nanoSecSinceJ2000)
```

Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of ISO8601 style (style 3).

```
Examples: 1990-04-01T03:05:02.000000000
          1993-10-10T23:45:49.777888999
```

/** Converts an array of epoch values in TT2000 type into readable, UTC-based date/time strings of ISO8601 style.

```
Examples: 1990-04-01T03:05:02.000000000
          1993-10-10T23:45:49.777888999
```

Parameters:

nanoSecSinceJ2000 - the TT2000 epoch values, nanoseconds since J2000, in long

Returns:

A string array representation of the epochs

toEncode

```
public static java.lang.String[] toEncode(long[] nanoSecSinceJ2000,
                                         int style)
```

Converts an array of epoch values in TT2000 type into readable, UTC-based date/time strings of chosen style.

```
Style:0      dd-mmm-yyyy hh:mm:ss.aaaaaaaaa
Examples:    01-Apr-1990 03:05:02.000000000
            10-Oct-1993 23:45:49.777888999
```

```
Style:1      yyyyymmdd.aaaaaaaaa
Examples:    19900401.1234567890
            19931010.9998887776
```

```
Style:2      yyyyymmddhhmmss
Examples:    19900401030502
            19931010234549
```

```
Style:3      yyyy-mm-ddThh:mm:ss.aaaaaaaaa
Examples:    1990-04-01T03:05:02.000000000
            1993-10-10T23:45:49.777888999
This is the default, ISO 8601, output.
```

```
Style:4      yyyy-mm-ddThh:mm:ss.aaaaaaaaaZ
Examples:    1990-04-01T03:05:02.000000000Z
            1993-10-10T23:45:49.777888999Z
```

These styles are the same as those expected by fromUTCstring.

Parameters:

nanoSecSinceJ2000 - the TT2000 epoch values, nanoseconds since J2000, in long

style - the style (from 0 to 4, 3 being the default), an optional

Returns:

A string array representation of the epoch

toUTCstring

```
public static java.lang.String toUTCstring(long nanoSecSinceJ2000,
                                         int style)
```

Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of chosen style.

```
Style:0      dd-mmm-yyyy hh:mm:ss.aaaaaaaaaa
Examples:    01-Apr-1990 03:05:02.0000000000
             10-Oct-1993 23:45:49.7778889999

Style:1      yyyyymmdd.aaaaaaaaaa
Examples:    19900401.1234567890
             19931010.9998887776

Style:2      yyyyymmddhhmmss
Examples:    19900401030502
             19931010234549

Style:3      yyyy-mm-ddThh:mm:ss.aaaaaaaaaa
Examples:    1990-04-01T03:05:02.0000000000
             1993-10-10T23:45:49.7778889999
This is the default, ISO 8601, output.

Style:4      yyyy-mm-ddThh:mm:ss.aaaaaaaaaaZ
Examples:    1990-04-01T03:05:02.0000000000Z
             1993-10-10T23:45:49.7778889999Z
```

These styles are the same as those expected by fromUTCstring.

Parameters:

- nanoSecSinceJ2000 - the TT2000 epoch value, nanoseconds since J2000, in long
- style - the style (from 0 to 4, 3 being the default), an optional

Returns:

A string representation of the epoch

toUTCstring

```
public static java.lang.String[] toUTCstring(long[] nanoSecSinceJ2000,
                                             int style)
```

Converts an array of epoch values in TT2000 type into readable, UTC-based date/time strings of chosen style.

```
Style:0      dd-mmm-yyyy hh:mm:ss.aaaaaaaaaa
Examples:    01-Apr-1990 03:05:02.0000000000
             10-Oct-1993 23:45:49.7778889999

Style:1      yyyyymmdd.aaaaaaaaaa
Examples:    19900401.1234567890
             19931010.9998887776

Style:2      yyyyymmddhhmmss
Examples:    19900401030502
             19931010234549

Style:3      yyyy-mm-ddThh:mm:ss.aaaaaaaaaa
Examples:    1990-04-01T03:05:02.0000000000
             1993-10-10T23:45:49.7778889999
This is the default, ISO 8601, output.

Style:4      yyyy-mm-ddThh:mm:ss.aaaaaaaaaaZ
Examples:    1990-04-01T03:05:02.0000000000Z
             1993-10-10T23:45:49.7778889999Z
```

These styles are the same as those expected by fromUTCstring.

Parameters:

`nanoSecSinceJ2000` - the TT2000 epoch values, nanoseconds since J2000, in long

`style` - the style (from 0 to 3, as the default), an optional

Returns:

A string array representation of the epochs

encode

```
public static java.lang.String[] encode(long[] nanoSecSinceJ2000,
                                       int style)
```

Converts an array of epoch values in TT2000 type into readable, UTC-based date/time strings of chosen style.

Style:0 dd-mmm-yyyy hh:mm:ss.ccccccccc
Examples: 01-Apr-1990 03:05:02.000000000
 10-Oct-1993 23:45:49.777888999

Style:1 yyyyymmdd.ccccccccc
Examples: 19900401.1234567890
 19931010.9998887776

Style:2 yyyyymmddhhmmss
Examples: 19900401030502
 19931010234549

Style:3 yyyy-mm-ddThh:mm:ss.ccccccccc
Examples: 1990-04-01T03:05:02.000000000
 1993-10-10T23:45:49.777888999
This is the default, ISO 8601, output.

Style:4 yyyy-mm-ddThh:mm:ss.cccccccccZ
Examples: 1990-04-01T03:05:02.000000000Z
 1993-10-10T23:45:49.777888999Z

These styles are the same as those expected by `fromUTCstring`.

Parameters:

`nanoSecSinceJ2000` - the TT2000 epoch values, nanoseconds since J2000, in long

`style` - the style (from 0 to 3, as the default), an optional

Returns:

A string array representation of the epochs

encode

```
public static java.lang.String encode(long nanoSecSinceJ2000)
```

Converts an epoch value in TT2000 type into a readable, UTC-based date/time string in ISO 8601 style.

Examples: yyyy-mm-ddThh:mm:ss.ccccccccc
 1990-04-01T03:05:02.000000000
 1993-10-10T23:45:49.777888999

Parameters:

`nanoSecSinceJ2000` - the TT2000 epoch value, nanoseconds since J2000, in long

Returns:

A string representation of the epoch

encode

```
public static java.lang.String[] encode(long[] nanoSecSinceJ2000)
```

Converts an array of epoch values in TT2000 type into an array of readable, UTC-based date/time strings in ISO 8601 style.

Examples: yyyy-mm-ddThh:mm:ss.CCCCCCCCCC
 1990-04-01T03:05:02.0000000000
 1993-10-10T23:45:49.7778889999

Parameters:

 nanoSecSinceJ2000 - the TT2000 epoch value, nanoseconds since J2000, in long

Returns:

 strings representing the epochs or null if null or an empty input array is detected

encode

```
public static java.lang.String encode(long nanoSecSinceJ2000,  
                                      int style)
```

Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of chosen style.

Style:0 dd-mmm-yyyy hh:mm:ss.CCCCCCCCCC
Examples: 01-Apr-1990 03:05:02.0000000000
 10-Oct-1993 23:45:49.7778889999

Style:1 yyyymmdd.CCCCCCCCCC
Examples: 19900401.1234567890
 19931010.9998887776

Style:2 yyyymmddhhmmss
Examples: 19900401030502
 19931010234549

Style:3 yyyy-mm-ddThh:mm:ss.CCCCCCCCCC
Examples: 1990-04-01T03:05:02.0000000000
 1993-10-10T23:45:49.7778889999

This is the default, ISO 8601, output.

Style:4 yyyy-mm-ddThh:mm:ss.CCCCCCCCCCZ
Examples: 1990-04-01T03:05:02.000000000Z
 1993-10-10T23:45:49.777888999Z

These styles are the same as those expected by fromUTCstring.

Parameters:

 nanoSecSinceJ2000 - the TT2000 epoch value, nanoseconds since J2000, in long

 style - the style (from 0 to 3, as the default), an optional

Returns:

 A string representation of the epoch

parseTT2000

```
public static long parseTT2000(java.lang.String string)  
                                      throws CDFException
```

This method parses an input, UTC-based, date/time string and returns a TT2000 epoch value, nanoseconds since J2000. The string must be in one of the styles as shown below. Month abbreviations may be in any case and are always the first three letters of the month - a new name from fromUTCstring.

A TT2000 epoch the epoch value in nanoseconds since J2000

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

parseTT2000

```
public static long[] parseTT2000(java.lang.String[] strings)
                               throws CDFException
```

This method parses an input, UTC-based, date/time strings and returns a TT2000 epoch value array, nanoseconds since J2000. The string must be in one of the styles as shown below. Month abbreviations may be in any case and are always the first three letters of the month - a new name from fromUTCstring.

```
Style:0      dd-mmm-yyyy hh:mm:ss.CCCCCCCCCC
Examples:    01-Apr-1990 03:05:02.0000000000
              10-Oct-1993 23:45:49.7778889999

Style:1      yyyymmdd.CCCCCCCCCC
Examples:    19900401.1234567890
              19931010.9998887776

Style:2      yyyymmddhhmmss
Examples:    19900401030502
              19931010234549

Style:3      yyyy-mm-ddThh:mm:ss.CCCCCCCCCC
Examples:    1990-04-01T03:05:02.0000000000
              1993-10-10T23:45:49.7778889999

Style:4      yyyy-mm-ddThh:mm:ss.CCCCCCCCCCZ
Examples:    1990-04-01T03:05:02.0000000000Z
              1993-10-10T23:45:49.7778889999Z
```

These styles are the same as those created by toUTCstring.

Parameters:

`strings` - the epoch array in string representation

Returns:

A TT2000 epoch the epoch values in nanoseconds since J2000

Throws:

`CDFException` - an `TT2000_TIME_ERROR` if an illegal component value is detected.

toParse

```
public static long[] toParse(java.lang.String[] strings)
                           throws CDFException
```

This method parses an input, UTC-based, date/time strings and returns a TT2000 epoch value array, nanoseconds since J2000. The string must be in one of the styles as shown below. Month abbreviations may be in any case and are always the first three letters of the month - a new name from fromUTCstring.

```
Style:0      dd-mmm-yyyy hh:mm:ss.CCCCCCCCCC
Examples:    01-Apr-1990 03:05:02.0000000000
              10-Oct-1993 23:45:49.7778889999

Style:1      yyyymmdd.CCCCCCCCCC
Examples:    19900401.1234567890
              19931010.9998887776

Style:2      yyyymmddhhmmss
Examples:    19900401030502
```

19931010234549

Style:3 yyyy-mm-ddThh:mm:ss.aaaaaaaaa
Examples: 1990-04-01T03:05:02.000000000
 1993-10-10T23:45:49.777888999

Style:4 yyyy-mm-ddThh:mm:ss.aaaaaaaaaZ
Examples: 1990-04-01T03:05:02.000000000Z
 1993-10-10T23:45:49.777888999Z

These styles are the same as those created by toUTCstring.

Parameters:

strings - the epoch array in string representation

Returns:

A TT2000 epoch the epoch values in nanoseconds since J2000

Throws:

CDFException - an TT2000_TIME_ERROR if an illegal component value is detected.

fromUTCstring

```
public static long fromUTCstring(java.lang.String string)
                             throws CDFException
```

This method parses an input, UTC-based, date/time string and returns a TT2000 epoch value, nanoseconds since J2000. The string must be in one of the styles as shown below. Month abbreviations may be in any case and are always the first three letters of the month.

Style:0 dd-mmm-yyyy hh:mm:ss.aaaaaaaaa
Examples: 01-Apr-1990 03:05:02.000000000
 10-Oct-1993 23:45:49.777888999

Style:1 yyyymmdd.aaaaaaaaa
Examples: 19900401.1234567890
 19931010.9998887776

Style:2 yyyymmddhhmmss
Examples: 19900401030502
 19931010234549

Style:3 yyyy-mm-ddThh:mm:ss.aaaaaaaaa
Examples: 1990-04-01T03:05:02.000000000
 1993-10-10T23:45:49.777888999

Style:4 yyyy-mm-ddThh:mm:ss.aaaaaaaaaZ
Examples: 1990-04-01T03:05:02.000000000Z
 1993-10-10T23:45:49.777888999Z

These styles are the same as those created by toUTCstring.

Parameters:

string - the epoch in string representation

Returns:

A TT2000 epoch the epoch value in nanoseconds since J2000

Throws:

CDFException - an TT2000_TIME_ERROR if an illegal component value is detected.

fromUTCISO8601string

```
public static long[] fromUTCISO8601string(java.lang.String string)
                                throws CDFException
```

This method parses an input, UTC-based, date/time string in ISO 8601 and returns their date/time components. String has to be in ISO 8601 form: yyyy-mm-ddThh:mm:ss.cccccccc 1990-04-01T03:05:02.000000000 1993-10-10T23:45:49.777888999

Parameters:

string - the epoch in string representation

Returns:

UTC date/time components

Throws:

CDFException - an TT2000_TIME_ERROR if an illegal component value is detected.

parse

```
public static long parse(java.lang.String string)
                        throws CDFException
```

This method parses an input date/time string and returns a TT2000 epoch value, nanoseconds since J2000. The string must be in one of the styles as shown below. Month abbreviations may be in any case and are always the first three letters of the month.

Style:0 dd-mmm-yyyy hh:mm:ss.cccccccc
Examples: 01-Apr-1990 03:05:02.000000000
 10-Oct-1993 23:45:49.777888999

Style:1 yyyymmdd.cccccccc
Examples: 19900401.1234567890
 19931010.9998887776

Style:2 yyyymmddhhmmss
Examples: 19900401030502
 19931010234549

Style:3 yyyy-mm-ddThh:mm:ss.cccccccc
Examples: 1990-04-01T03:05:02.000000000
 1993-10-10T23:45:49.777888999

Style:4 yyyy-mm-ddThh:mm:ss.ccccccccZ
Examples: 1990-04-01T03:05:02.000000000Z
 1993-10-10T23:45:49.777888999Z

These styles are the same as those created by toUTCstring.

Parameters:

string - the epoch in string representation

Returns:

A TT2000 epoch the epoch value in nanoseconds since J2000

Throws:

CDFException - an TT2000_TIME_ERROR if an illegal component value is detected.

parse

```
public static long[] parse(java.lang.String[] strings)
                        throws CDFException
```

This method parses an array of input date/time strings and returns an array of TT2000 epoch values, nanoseconds since J2000. The

string must be in one of the styles as shown below. Month abbreviations may be in any case and are always the first three letters of the month.

```
Style:0      dd-mmm-yyyy hh:mm:ss.CCCCCCCCCC
Examples:    01-Apr-1990 03:05:02.0000000000
              10-Oct-1993 23:45:49.7778889999

Style:1      yyyymmdd.CCCCCCCCCC
Examples:    19900401.1234567890
              19931010.9998887776

Style:2      yyyymmddhhmmss
Examples:    19900401030502
              19931010234549

Style:3      yyyy-mm-ddThh:mm:ss.CCCCCCCCCC
Examples:    1990-04-01T03:05:02.0000000000
              1993-10-10T23:45:49.7778889999

Style:4      yyyy-mm-ddThh:mm:ss.CCCCCCCCCCZ
Examples:    1990-04-01T03:05:02.0000000000Z
              1993-10-10T23:45:49.7778889999Z
```

These styles are the same as those created by toUTCstring.

Parameters:

strings - an array of epochs in string representation

Returns:

TT2000 epoch values in nanoseconds since J2000 or null if null or an empty input array is detected

Throws:

CDFException - an TT2000_TIME_ERROR if an illegal component value is detected.

CDFgetLastDateinLeapSecondsTable

```
public static long[] CDFgetLastDateinLeapSecondsTable()

/** This method returns the last UTC date that a leap second was added in the leap second table used in the class. This can be used
to check whether the table is up-to-date.
```

Returns:

the date (year, month, day) in a long array

fromGregorianTime

```
public static long fromGregorianTime(java.util.GregorianCalendar gc)

This method converts the UTC-based date/time in a GregorianCalendar class object to TT2000 time.
```

Parameters:

gc - the Gregorian calendar object

Returns:

the TT2000 time

toGregorianTime

```
public static java.util.GregorianCalendar toGregorianTime(long tt2000)
```

This method converts the UTC-based date/time in TT2000 type to a GregorianCalendar class object in default, local time zone.

Parameters:

tt2000 - the TT2000 data value

Returns:

a GregorianCalendar object

toGregorianTime

```
public static java.util.GregorianCalendar toGregorianTime(long tt2000,
                                                         java.util.TimeZone tz)
```

This method converts the UTC-based date/time in TT2000 type to a GregorianCalendar class object in specified time zone.

Parameters:

tt2000 - the TT2000 data value

tz - the time zone

Returns:

a GregorianCalendar object

CDFgetLeapSecondsTableStatus

```
public static int CDFgetLeapSecondsTableStatus()
```

This method returns the status code reflecting whether the leap seconds are from a external file, defined by an environment variable, or the leap seconds are based on the hard-coded table in the class.

Returns:

status 1 if form a file, 0 hard-coded

CDFgetLeapSecondsTable

```
public static double[][] CDFgetLeapSecondsTable()
```

This method returns the leap seconds table.

Returns:

table The table contents of the leap seconds

CDFgetRowsinLeapSecondsTable

```
public static int CDFgetRowsinLeapSecondsTable()
```

This method returns the number of entries in the leap seconds table.

Returns:

enrtyCnt The entry count in the leap seconds table

computeTT2000withBasedLeapDay

```
public static long computeTT2000withBasedLeapDay(long yy,
                                                    long mm,
                                                    long dd,
                                                    long hh,
                                                    long mn,
                                                    long ss,
                                                    long ms,
                                                    long us,
                                                    long ns,
                                                    int yymmdd)
```

This method returns the TT2000 time in nanoseconds based on the last leap second day.

Parameters:

- yy - the year, a full year in long
- mm - the month, a full month in long
- dd - the day, a full day in long
- hh - the hour, a full hour in long
- mn - the minute, a full minute in long
- ss - the second, a full second in long
- ms - the millisecond, a full millisecond in long
- us - the microsecond, a full microsecond in long
- ns - the nanosecond, a full nanosecond in long
- yymmdd - the last leap second day (in YYYYMMDD) the UTC date is based upon, an int value

Returns:

TT2000 time in nanoseconds

computeTT2000withBasedLeapDay

```
public static long computeTT2000withBasedLeapDay(double yy,
                                                    double mm,
                                                    double dd,
                                                    double hh,
                                                    double mn,
                                                    double ss,
                                                    double ms,
                                                    double us,
                                                    double ns,
                                                    int yymmdd)
```

This method returns the TT2000 time in nanoseconds based on the last leap second day. This function works similarly to fromUTCparts, with an adjustment if necessary. It returns the TT2000 from UTC date/time based on the passed last leap second day, while fromUTCparts function returns based on the day from the last entry in the current leap second table (LST). If the based leap second day is not a zero (0) or if the UTC date/time is extended over the next leap second day in the LST, one second(s) will be adjusted (deduction), due to the newly added leap second(s) in the LST. Otherwise, it returns the same value as fromUTCparts.

Parameters:

- yy - the year, a full year in double
- mm - the month, a full month in double
- dd - the day, a full day in double
- hh - the hour, a full hour in double

- `mn` - the minute, a full minute in double
- `ss` - the second, a full second in double
- `ms` - the millisecond, a full millisecond in double
- `us` - the microsecond, a full microsecond in double
- `ns` - the nanosecond, a full nanosecond in double
- `yymmdd` - the last leap second day (in YYYYMMDD) the UTC date is based upon, an int value

Returns:

TT2000 time in nanoseconds

breakdownTT2000withBasedLeapDay

```
public static long[] breakdownTT2000withBasedLeapDay(long tt2000,
                                                    int yymmdd)
```

breakdownTT2000withBasedLeapDay. This method is similar to toUTCparts (aka breakdown), with an adjustment if necessary. It returns UTC date/time from TT2000 value based on the passed last leap second day, while toUTCparts method is based on the last leap second updated day in the current leap second table (LST). If the based leap second day is zero (0), this method functions just like toUTCparts. If the TT2000 value was computed based on the LST that was not up-to-date, one second(s) adjustment (addition) might be necessary if its value crosses over the next new leap second day in the LST.

Parameters:

- `tt2000` - the nanoseconds since J2000
- `yymmdd` - the last leap second day (in YYYYMMDD) the UTC date is based upon, an int value

Returns:

TT2000 time in nanoseconds

encodeTT2000withBasedLeapDay

```
public static java.lang.String encodeTT2000withBasedLeapDay(long tt2000,
                                                            int yymmdd)
```

encodeTT2000withBasedLeapDay. This method is similar to toUTCstring (aka encodeTT2000), with an adjustment if necessary. It encodes TT2000 to UTC string in ISO 8601 form based on the passed last leap second day, while toUTC_string method is based on the last leap second updated day in the current leap second table (LST). If the based leap second day is zero (0), this method functions just like toUTCstring. If the TT2000 value was computed based on the LST that was not up-to-date, one second(s) adjustment (addition) might be necessary if its value crosses over the next new leap second day in the LST.

Parameters:

- `tt2000` - the nanoseconds since J2000 with leap seconds second day
- `yymmdd` - the last leap second day (in YYYYMMDD) the UTC date is based upon, an int value

Returns:

TT2000 an ISO 8601 UTC string

parseTT2000withBasedLeapDay

```
public static long parseTT2000withBasedLeapDay(java.lang.String tt2000,
                                                int yymmdd)
```

parseTT2000withBasedLeapDay. This method is similar to fromUTCstring (aka parseTT2000), with an adjustment if necessary. It returns a TT2000 value from the UTC string in ISO 8601 form based on the passed last leap second day, while fromUTCstring method is based on the last leap second updated day in the current leap second table (LST). If the based leap second day is zero (0), this method functions just like fromUTCstring. If the UTC string was encoded based on the LST that was not up-to-date, one second(s) adjustment (addition) might be necessary if its day crosses over the next new leap second day in the LST.

Parameters:

- tt2000 - the UTC string (in ISO 8601 form) based on the last leap second day
- yymmdd - the last leap second day (in YYYYMMDD) the UTC date is based upon, an int value

Returns:

TT2000 time in nanoseconds

TT2000toUnixTime

```
public static double TT2000toUnixTime(long epoch)
```

Converts a TT2000 value to a unix time of a double value (seconds from 1970-01-01 00:00:00 UTC). The unix time will have a time resolution of microseconds at its fraction part. Note: As unix time does not have leap seconds, the converted time might not be properly presented. Also, TT2000 have a higher time resolution than the unix time. The conversion might not precisely preserve the microseconds due to the floating point presentation.

Parameters:

- epoch - the epoch value

Returns:

A unix time value

TT2000toUnixTime

```
public static double[] TT2000toUnixTime(long[] epoch)
```

Converts an array of TT2000 values to an array of unix time of a double value (seconds from 1970-01-01 00:00:00 UTC). The unix time will have a time resolution of microseconds at its fraction part. Note: As unix time does not have leap seconds, the converted time might not be properly presented. Also, TT2000 have a higher time resolution than the unix time. The conversion might not precisely preserve the microseconds due to the floating point presentation.

Parameters:

- epoch - the epoch values

Returns:

Array of unix time values

UnixTimetoTT2000

```
public static long UnixTimetoTT2000(double unixTime)
```

Converts a Unix time of a double value (seconds from 1970-01-01 00:00:00 UTC) to a TT2000 time. The unix time can have a time resolution of milliseconds or microseconds at its fraction part. Note: As unix time does not have leap seconds, the converted time might not be properly presented. Also, TT2000 have a higher time resolution than the unix time. The conversion might not precisely preserve the microseconds due to the floating point presentation.

Parameters:

`unixTime` - the unix time value

Returns:

An TT2000 value

UnixTimetoTT2000

```
public static long[] UnixTimetoTT2000(double[] unixTimes)
```

Converts an array of Unix time of double values (seconds from 1970-01-01 00:00:00 UTC) to an array of TT2000 times. The unix time can have a time resolution of milliseconds or microseconds at its fraction part. Note: As unix time does not have leap seconds, the converted time might not be properly presented. Also, TT2000 may have a higher time resolution than the unix time. The conversion might not precisely preserve the microseconds due to the floating point presentation.

Parameters:

`unixTimes` - the unix time values

Returns:

An array of TT2000 values

Overview	Package	Class	Tree	Deprecated	Index	Help
Prev Class	Next Class	Frames	No Frames	All Classes		
Summary: Nested	Field	Constr	Method	Detail: Field	Constr	Method

gsfc.nssdc.cdf.util

Class CDFUtils

java.lang.Object
gsfc.nssdc.cdf.util.CDFUtils

All Implemented Interfaces:

CDFConstants

```
public class CDFUtils
extends java.lang.Object
implements CDFConstants
```

This class contains the handy utility routines (methods) called by the core CDF Java APIs.

Version:

1.0

Field Summary

Fields inherited from interface gsfc.nssdc.cdf.CDFConstants

AHUFF COMPRESSION, ALPHAOSF1 DECODING, ALPHAOSF1 ENCODING, ALPHAVMSd DECODING, ALPHAVMSd ENCODING, ALPHAVMSg DECODING, ALPHAVMSg ENCODING, ALPHAVMSi DECODING, ALPHAVMSi ENCODING, ARM BIG DECODING, ARM BIG ENCODING, ARM LITTLE DECODING, ARM LITTLE ENCODING, ATTR, ATTR EXISTENCE, ATTR EXISTS, ATTR MAXgENTRY, ATTR MAXrENTRY, ATTR MAXZENTRY, ATTR NAME, ATTR NAME TRUNC, ATTR NUMBER, ATTR NUMgENTRIES, ATTR NUMrENTRIES, ATTR NUMzENTRIES, ATTR SCOPE, BACKWARD, BACKWARDFILEoff, BACKWARDFILEon, BAD ALLOCATE RECS, BAD ARGUMENT, BAD ATTR NAME, BAD ATTR NUM, BAD BLOCKING FACTOR, BAD CACHE SIZE, BAD CDF EXTENSION, BAD CDF ID, BAD CDF NAME, BAD CDFSTATUS, BAD CHECKSUM, BAD COMPRESSION PARM, BAD DATA TYPE, BAD DECODING, BAD DIM COUNT, BAD DIM INDEX, BAD DIM INTERVAL, BAD DIM SIZE, BAD ENCODING, BAD ENTRY NUM, BAD FNC OR ITEM, BAD FORMAT, BAD INITIAL RECS, BAD MAJORITY, BAD MALLOC, BAD NEGtoPOSfp0 MODE, BAD NUM DIMS, BAD NUM ELEMS, BAD NUM STRINGS, BAD NUM VARS, BAD READONLY MODE, BAD REC COUNT, BAD REC INTERVAL, BAD REC NUM, BAD SCOPE, BAD SCRATCH DIR, BAD SPARSEARRAYS PARM, BAD VAR NAME, BAD VAR NUM, BAD zMODE, BADDATE LEAPSECOND UPDATED, BeginUnixTimeEPOCH, BeginUnixTimeEPOCH16, BLOCKINGFACTOR TOO LARGE, BLOCKINGFACTOR TOO SMALL, BLOCKINGFACTOR TOO SMALL2, CANNOT ALLOCATE RECORDS, CANNOT CHANGE, CANNOT COMPRESS, CANNOT CONVERT WIDECHAR, CANNOT COPY, CANNOT INSERT RECORDS, CANNOT SPARSEARRAYS, CANNOT SPARSERECS, CDF, CDF ACCESS, CDF ATTR NAME LEN, CDF ATTR NAME LEN256, CDF BYTE, CDF CACHESIZE, CDF CHAR, CDF CHECKSUM, CDF CLOSE ERROR, CDF COMPRESSION, CDF COPYRIGHT, CDF COPYRIGHT LEN, CDF CREATE ERROR, CDF DECODING, CDF DELETE ERROR, CDF DOUBLE, CDF ENCODING, CDF EPOCH, CDF EPOCH16, CDF EXISTS, CDF FLOAT, CDF FORMAT, CDF INCREMENT, CDF INFO, CDF INT1, CDF INT2, CDF INT4, CDF INT8, CDF INTERNAL ERROR, CDF LEAPSECONDLASTUPDATED, CDF MAJORITY, CDF MAX DIMS, CDF MAX PARMS, CDF MIN DIMS, CDF NAME, CDF NAME TRUNC, CDF NEGtoPOSfp0 MODE, CDF NUMATTRS, CDF NUMgATTRS, CDF NUMrVARS, CDF NUMvATTRS, CDF NUMzVARS, CDF OK, CDF OPEN ERROR, CDF PATHNAME LEN, CDF READ ERROR, CDF READONLY MODE, CDF REAL4, CDF REAL8, CDF RELEASE, CDF SAVE ERROR, CDF SCRATCHDIR, CDF STATUS, CDF STATUSTEXT LEN, CDF TIME TT2000, CDF UCHAR, CDF UINT1, CDF UINT2, CDF UINT4, CDF VAR NAME LEN, CDF VAR NAME LEN256, CDF VERSION, CDF WARN, CDF WRITE ERROR, CDF zMODE, CDFwithSTATS, CHECKSUM, CHECKSUM ERROR, CHECKSUM NOT ALLOWED, CLOSE, COLUMN MAJOR, COMPRESS CACHESIZE, COMPRESSION ERROR, CONFIRM, CORRUPTED V2 CDF, CORRUPTED V3 CDF, CREATE, CURgENTRY EXISTENCE, CURgENTRY EXISTENCE, CURgENTRY EXISTENCE, DATATYPE MISMATCH, DATATYPE SIZE, DECOMPRESSION ERROR, DECSTATION DECODING, DECSTATION ENCODING, DEFAULT BYTE PADVALUE, DEFAULT CHAR PADVALUE, DEFAULT DOUBLE PADVALUE, DEFAULT EPOCH PADVALUE, DEFAULT EPOCH16 PADVALUE, DEFAULT FLOAT PADVALUE, DEFAULT INT1 PADVALUE, DEFAULT INT2 PADVALUE, DEFAULT INT4 PADVALUE, DEFAULT INT8 PADVALUE, DEFAULT REAL4 PADVALUE, DEFAULT REAL8 PADVALUE, DEFAULT TT2000 PADVALUE, DEFAULT UCHAR PADVALUE, DEFAULT UINT1 PADVALUE, DEFAULT UINT2 PADVALUE, DEFAULT UINT4 PADVALUE, DELETE, DID NOT COMPRESS, EMPTY COMPRESSED CDF, END OF VAR, EPOCH STRING LEN, EPOCH STRING LEN EXTEND, EPOCH1 STRING LEN, EPOCH1 STRING LEN EXTEND, EPOCH2 STRING LEN, EPOCH2 STRING LEN EXTEND, EPOCH3 STRING LEN, EPOCH3 STRING LEN EXTEND, EPOCH4 STRING LEN, EPOCH4 STRING LEN EXTEND, EPOCHx FORMAT MAX, EPOCHx STRING MAX, FILLED TT2000 VALUE, FORCED PARAMETER, FUNCTION NOT SUPPORTED, gENTRY, gENTRY DATA, gENTRY DATASPEC, gENTRY DATATYPE, gENTRY EXISTENCE, gENTRY NUMELEMS, GET, GETCDFCHECKSUM, GETCDFFILEBACKWARD, GETCDFVALIDATE, GETLEAPSECONDSENVVAR, GLOBAL SCOPE, GZIP COMPRESSION, HOST DECODING, HOST ENCODING, HP DECODING, HP ENCODING, HUFF COMPRESSION, IA64VMSd DECODING, IA64VMSd ENCODING, IA64VMSg DECODING, IA64VMSg ENCODING, IA64VMSi DECODING, IA64VMSi ENCODING, IBM PC OVERFLOW, IBMPC DECODING, IBMPC ENCODING, IBMRs DECODING, IBMRs ENCODING, ILLEGAL EPOCH FIELD, ILLEGAL EPOCH VALUE, ILLEGAL FOR SCOPE, ILLEGAL IN zMODE, ILLEGAL_ON_V1_CDF, ILLEGAL_TT2000_VALUE, IS_A_NETCDF, LIB_COPYRIGHT, LIB_INCREMENT,

LIB RELEASE , LIB subINCREMENT , LIB VERSION , MAC DECODING, MAC ENCODING, MD5 CHECKSUM, MULTI FILE, MULTI_FILE FORMAT, NA FOR VARIABLE, NEGATIVE FP ZERO, NEGtoPOSfp0ooff, NEGtoPOSfp0on, NETWORK DECODING, NETWORK ENCODING, Next DECODING, Next ENCODING, NO ATTR SELECTED, NO CDF SELECTED, NO CHECKSUM, NO COMPRESSION, NO DELETE ACCESS, NO ENTRY SELECTED, NO MORE ACCESS, NO PADVALUE SPECIFIED, NO SPARSEARRAYS, NO SPARSERECORDS, NO STATUS SELECTED, NO SUCH_ATTR, NO SUCH CDF, NO SUCH ENTRY, NO SUCH RECORD, NO SUCH VAR, NO VAR SELECTED, NO VARS IN CDF, NO WRITE ACCESS, NONE CHECKSUM, NOT A CDF, NOT A CDF OR NOT SUPPORTED, NOVARY, NULL , OPEN , OPTIMAL ENCODING TREES, OTHER CHECKSUM, PAD SPARSERECORDS, PPC DECODING, PPC ENCODING, PRECEEDING RECORDS ALLOCATED, PREV SPARSERECORDS, PUT , READ ONLY DISTRIBUTION, READ_ONLY_MODE, READONLYoff, READONLYon, rENTRY , rENTRY DATA , rENTRY DATASPEC , rENTRY DATATYPE , rENTRY EXISTENCE , rENTRY NAME , rENTRY NUMELEMS , rENTRY NUMSTRINGS , rENTRY STRINGSDATA , RLE COMPRESSION, RLE OF ZEROS, ROW MAJOR, rVAR , rVAR ALLOCATEBLOCK , rVAR ALLOCATEDFROM , rVAR ALLOCATEDTO , rVAR ALLOCATERECS , rVAR BLOCKINGFACTOR , rVAR CACHESIZE , rVAR COMPRESSION , rVAR DATA , rVAR DATASPEC , rVAR DATATYPE , rVAR DIMVARYS , rVAR EXISTENCE , rVAR HYPERDATA , rVAR INITIALRECS , rVAR MAXallocREC , rVAR MAXREC , rVAR NAME , rVAR nINDEXENTRIES , rVAR nINDEXLEVELS , rVAR nINDEXRECORDS , rVAR NUMallocRECS , rVAR NUMBER , rVAR NUMELEMS , rVAR NUMRECS , rVAR PADVALUE , rVAR RECORDS , rVAR RECORDS_RENUMBER , rVAR RECVAR , rVAR RESERVEPERCENT , rVAR SEQDATA , rVAR SEQPOS , rVAR SPARSEARRAYS , rVAR SPARSERECORDS , rVARs CACHESIZE , rVARs DIMCOUNTS , rVARs DIMINDICES , rVARs DIMINTERVALS , rVARs DIMSIZES , rVARs MAXREC , rVARs NUMDIMS , rVARs RECCOUNT , rVARs RECDATA , rVARs RECINTERVAL , rVARs RECNUMBER , SAVE , SCRATCH CREATE ERROR, SCRATCH DELETE ERROR, SCRATCH READ ERROR, SCRATCH WRITE ERROR, SELECT , SGI DECODING, SGI ENCODING, SINGLE FILE, SINGLE FILE FORMAT, SOME ALREADY ALLOCATED, STAGE CACHESIZE , STATUS TEXT , STRING NOT UTF8 ENCODING, STRINGDELIMITER, SUN DECODING, SUN ENCODING, TOO MANY PARMS, TOO MANY VARS, TRY TO READ NONSTRING DATA, TT2000 0 STRING LEN, TT2000 1 STRING_LEN, TT2000 2 STRING LEN, TT2000 3 STRING LEN, TT2000 4 STRING_LEN, TT2000_CDF MAYNEEDUPDATE, TT2000 TIME ERROR, TT2000 USED OUTDATED TABLE, UNABLE TO PROCESS CDF, UNKNOWN COMPRESSION, UNKNOWN SPARSENESS, UNSUPPORTED OPERATION, VALIDATE , VALIDATEFILEoff, VALIDATEFILEon, VAR ALREADY CLOSED, VAR CLOSE ERROR, VAR CREATE ERROR, VAR DELETE ERROR, VAR EXISTS, VAR NAME TRUNC, VAR OPEN ERROR, VAR READ ERROR, VAR SAVE_ERROR, VAR WRITE ERROR, VARIABLE SCOPE, VARY , VAX DECODING, VAX ENCODING, VIRTUAL RECORD DATA, zENTRY , zENTRY DATA , zENTRY DATASPEC , zENTRY DATATYPE , zENTRY EXISTENCE , zENTRY NAME , zENTRY NUMELEMS , zENTRY NUMSTRINGS , zENTRY STRINGSDATA , ZLIB COMPRESS ERROR, ZLIB UNCOMPRESS_ERROR, zMODEoff, zMODEon1, zMODEon2, zVAR , zVAR ALLOCATEBLOCK , zVAR ALLOCATEDFROM , zVAR ALLOCATEDTO , zVAR ALLOCATERECS , zVAR BLOCKINGFACTOR , zVAR CACHESIZE , zVAR COMPRESSION , zVAR DATA , zVAR DATASPEC , zVAR DATATYPE , zVAR DIMCOUNTS , zVAR DIMINDICES , zVAR DIMINTERVALS , zVAR DIMSIZES , zVAR DIMVARYS , zVAR EXISTENCE , zVAR HYPERDATA , zVAR INITIALRECS , zVAR MAXallocREC , zVAR MAXREC , zVAR NAME , zVAR nINDEXENTRIES , zVAR nINDEXLEVELS , zVAR nINDEXRECORDS , zVAR NUMallocRECS , zVAR NUMBER , zVAR NUMDIMS , zVAR NUMELEMS , zVAR NUMRECS , zVAR PADVALUE , zVAR RECCOUNT , zVAR RECINTERVAL , zVAR RECNUMBER , zVAR RECORDS , zVAR RECORDS_RENUMBER , zVAR RECVAR , zVAR RESERVEPERCENT , zVAR SEQDATA , zVAR SEQPOS , zVAR SPARSEARRAYS , zVAR SPARSERECORDS , zVARs CACHESIZE , zVARs MAXREC , zVARs RECDATA , zVARs RECNUMBER

Constructor Summary

Constructors

Constructor and Description

CDFUtils()

Method Summary

Methods

Modifier and Type	Method and Description
static java.lang.String[]	breakIntoStrings (java.lang.String data) Break down a merged string into their original array of strings.
static boolean	cdfFileExists (java.lang.String fileName) Checks the existence of the given CDF file name.
static java.lang.String	CFtoJformat (java.lang.String cfFormat) Convert a C/Fortran-based print format to a corresponding Java style format for numerical data.
static byte[]	Cp1252toUTF8 (java.lang.Object cp1252)
static java.lang.String	CtoJformat (java.lang.String cFormat) Convert a C-based print format to a corresponding Java style format for numerical data.
static java.lang.String	FtoJformat (java.lang.String fFormat) Convert a Fortran-based print format to a corresponding Java style format for numerical data.

static long	getDataTypeValue (java.lang.String cdfDataType) Gets the long value of the given CDF data type in string.
static long[]	getDimensionSizes (java.lang.Object obj)
static long	getLeapSecondLastUpdated (CDF cdf) Gets the date of the given CDF's last updated for the leap second.
static long	getLongChecksum (java.lang.String checksum) Gets the long value of the given CDF's checksum in string.
static long	getLongCompressionType (java.lang.String compressionType) Gets the long representation of the given CDF compression type in string.
static long	getLongEncoding (java.lang.String encodingType) Gets the long value of the given CDF encoding type in string.
static long	getLongFormat (java.lang.String formatType) Gets the long value of the given CDF file format in string.
static long	getLongMajority (java.lang.String majorityType) Gets the long value of the given CDF majority.
static long	getLongSparseRecord (java.lang.String sparseRecordType) Gets the long value of the given sparse record type in string.
static int	getNumDimensions (java.lang.Object obj)
static long	getNumElements (long dataType, java.lang.Object data) Gets the number of elements contained in the given data object.
static long	getNumStrings (java.lang.Object data) Gets the number of strings contained in the given data object.
static java.lang.String	getSignature (java.lang.Object obj) Gets the java signature of the given object.
static java.lang.String	getStringChecksum (CDF cdf) Gets the string value of the given CDF's checksum.
static java.lang.String	getStringChecksum (long checksumType) Gets the string value of the given CDF's checksum.
static java.lang.String	getStringCompressionType (CDF cdf) Gets the string representation of the given CDF file's compression type.
static java.lang.String	getStringCompressionType (long compressionType) Gets the string representation of the given CDF compression type.
static java.lang.String	getStringCompressionType (Variable var) Gets the string representation of the given variable's compression type.
static java.lang.String	getStringData (java.lang.Object data) Returns the string value of the given data.
static java.lang.String	getStringData (java.lang.Object data, int epochType) Returns the string value of the given data.
static java.lang.String	getStringData (java.lang.Object data, java.lang.String separator) Returns the string of the value of the given data.
static java.lang.String	getStringData (java.lang.Object data, java.lang.String separator, int epochType) Returns the string of the value of the given data.
static java.lang.String	getStringData (java.lang.Object data, java.lang.String separator, int epochType, java.lang.String addZ) Returns the string of the value of the given data.
static java.lang.String	getStringDataType (Entry entry) Gets the string value of the CDF data type for the given entry.
static java.lang.String	getStringDataType (long cdfDataType) Gets the string representation of the given CDF data type.
static java.lang.String	getStringDataType (Variable var) Gets the string value of the CDF data type for the given variable.

static java.lang.String	getStringDecoding (CDF cdf) Gets the string value of the given CDF file's decoding type.
static java.lang.String	getStringDecoding (long decodingType) Gets the string value of the given CDF decoding type .
static java.lang.String	getStringEncoding (CDF cdf) Get the string value of the given CDF's encoding type.
static java.lang.String	getStringEncoding (long encodingType) Gets the string value of the given CDF encoding type.
static java.lang.String	getStringFloatingData (java.lang.Object data, java.lang.String format, java.lang.String separator) Returns the string of the value of the given data.
static java.lang.String	getStringFormat (CDF cdf) Gets the string value of the given CDF's file format.
static java.lang.String	getStringFormat (long formatType) Gets the string value of the given CDF's file format.
static java.lang.String	getStringMajority (CDF cdf) Gets the string value of the given CDF file's majority.
static java.lang.String	getStringMajority (long majorityType) Gets the string value of the given CDF majority.
static java.lang.String	getStringSparseRecord (long sparseRecordType) Gets the string value of the given sparse record type.
static java.lang.String	getStringSparseRecord (Variable var) Gets the string value of the given variable's sparse record type.
static boolean	isEpochDataType (long dataType) Returns whether a CDF data type is an epoch related type.
static int	isFloatingPadValue (double value) Check if a double data is a pad value.
static int	isFloatingPadValue (float value) Check if a float data is a pad value.
static int	isFloatingPadValue (long dataType, double value) Check if a data is a floating point and its value is a pad value.
static int	isFloatingPadValue (long dataType, float value) Check if a data is a floating point and its value is a pad value.
static int	isFloatingPadValue (long dataType, java.lang.Object value) Check if a data is a floating point and its value is a pad value.
static int	isFloatingPadValue (java.lang.Object value) Check if a data is a floating point and its value is a pad value.
static boolean	isStringDataType (long dataType) Returns whether a CDF data type is a string type.
static java.lang.String	mergeFromStrings (java.lang.Object data) Merge an array of strings into a single string with "\ N ", a 3-char separator.
static void	printData (java.lang.Object data) Prints the value of the given data on the screen.
static void	printData (java.lang.Object data, int which) Prints the value of the given data on the screen.
static void	printData (java.lang.Object data, int which, boolean iso8601) Prints the value of the given data on the screen.
static void	printData (java.lang.Object data, int which, boolean iso8601, java.lang.String addZ) Prints the value of the given data on the screen.
static void	printData (java.lang.Object data, long dataType) Prints the value of the given data on the screen.

static void	printData (java.lang.Object data, java.io.PrintWriter outWriter) Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc.
static void	printData (java.lang.Object data, java.io.PrintWriter outWriter, int which) Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc.
static void	printData (java.lang.Object data, java.io.PrintWriter outWriter, int which, boolean iso8601) Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc.
static void	printData (java.lang.Object data, java.io.PrintWriter outWriter, int which, boolean iso8601, java.lang.String addZ) Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc.
static void	printDataWithFormat (java.lang.Object data, java.lang.String format) Prints the value of the given data on the screen.
static void	printDataWithFormat (java.lang.Object data, java.lang.String format, int which) Prints the value of the given data on the screen.
static void	printDataWithFormat (java.lang.Object data, java.lang.String format, int which, boolean iso8601) Prints the value of the given data on the screen.
static void	printDataWithFormat (java.lang.Object data, java.lang.String format, int which, boolean iso8601, java.lang.String addZ) Prints the value of the given data on the screen.
static void	printDataWithFormat (java.lang.Object data, java.lang.String format, java.io.PrintWriter outWriter) Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc.
static void	printDataWithFormat (java.lang.Object data, java.lang.String format, java.io.PrintWriter outWriter, int which) Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc.
static void	printDataWithFormat (java.lang.Object data, java.lang.String format, java.io.PrintWriter outWriter, int which, boolean iso8601) Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc.
static void	printDataWithFormat (java.lang.Object data, java.lang.String format, java.io.PrintWriter outWriter, int which, boolean iso8601, java.lang.String addZ) Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc.
static byte[]	UTF16LEtoUTF8 (java.lang.Object utf16)
static byte[]	UTF8toCpl252 (java.lang.Object utf8)
static byte[]	UTF8toUTF16LE (java.lang.Object utf8)

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

CDFUtils

```
public CDFUtils()
```

Method Detail

getSignature

```
public static java.lang.String getSignature(java.lang.Object obj)
```

Gets the java signature of the given object.

NOTE: Java primitive data types (e.g. int, long, byte, etc.) are not Objects. Thus they must be passed-in as an Object by using a wrapper (e.g. Integer(23)).

Signature	Java Programming Language Type
[Z	array of boolean
[B	array of byte
[C	array of char
[S	array of short
[I	array of int
[J	array of long
[F	array of float
[D	array of double
L fully-qualified-class	fully-qualified class
L fully-qualified-class;	array of fully-qualified class
java.lang.Boolean	Boolean
Ljava.lang.Boolean;	array of Boolean
java.lang.Byte	Byte
Ljava.lang.Byte;	array of Byte
java.lang.Short	Short
Ljava.lang.Short;	array of Short
java.lang.Integer	Integer
Ljava.lang.Integer;	array of Integer
java.lang.Long	Long
Ljava.lang.Long;	array of Long
java.lang.Float	Float
Ljava.lang.Float;	array of Float
java.lang.Double	Double
Ljava.lang.Double;	array of Double
java.lang.String	String
Ljava.lang.String;	array of String

Parameters:

obj - the object from which Java signature is retrieved

Returns:

Java signature of the given object

getNumElements

```
public static long getNumElements(long dataType,
                                java.lang.Object data)
                                throws CDFException
```

Gets the number of elements contained in the given data object.

Parameters:

dataType - the CDF data type of the object to be examined

data - the data object to be examined

Returns:

If the data is a string: number of characters in the string
If the data is an array: number of elements in the array
Otherwise: 1

Throws:

`CDFException` - if a problem occurs getting the number of elements

getNumStrings

```
public static long getNumStrings(java.lang.Object data)
```

Gets the number of strings contained in the given data object.

Parameters:

data - the data object to be examined

Returns:

The number of strings if the object is of string type and the data has the predefined `STRINGDELIMITER` (as `"\n"`) delimiter in it.
Or, 0 if non-string data type.

printData

```
public static void printData(java.lang.Object data)
```

Prints the value of the given data on the screen. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

Parameters:

data - the data to be printed

printData

```
public static void printData(java.lang.Object data,
                             int which,
                             boolean iso8601)
```

Prints the value of the given data on the screen. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

Parameters:

data - the data to be printed

which - the Epoch data type data indicator 1 if `CDF_EPOCH`, 2 if `CDF_EPOCH16` or 3 if `CDF_TIME_TT2000` 0 Otherwise

iso8601 - the ISO 8601 indicator for EPOCH data

printData

```
public static void printData(java.lang.Object data,
                             int which,
                             boolean iso8601,
```

```
java.lang.String addZ)
```

Prints the value of the given data on the screen. Data can be a java primitive data type, Java Object (non-array), or one or multi-dimensional array of primitive Java data type.

Parameters:

- data - the data to be printed
- which - the Epoch data type data indicator 1 if CDF_EPOCH, 2 if CDF_EPOCH16 or 3 if CDF_TIME_TT2000 0 Otherwise
- iso8601 - the ISO 8601 indicator for EPOCH data
- addZ - Added the passed string to the end, (likely a "Z", to all CDF epoch data types, not just CDF_TIME_TT2000)

printData

```
public static void printData(java.lang.Object data,
                             int which)
```

Prints the value of the given data on the screen. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

Parameters:

- data - the data to be printed
- which - the Epoch data type data indicator 1 if CDF_EPOCH, 2 if CDF_EPOCH16 or 3 if CDF_TIME_TT2000 0 Otherwise

printData

```
public static void printData(java.lang.Object data,
                             long dataType)
```

Prints the value of the given data on the screen. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

Parameters:

- data - the data to be printed
- dataType - the CDF data type of the data

printData

```
public static void printData(java.lang.Object data,
                             java.io.PrintWriter outWriter)
```

Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

The following example will send the contents of the given data to "myoutput.dat".

```
OutputStreamWriter outWriter = null;
PrintWriter out = null;
try {
    outWriter = new OutputStreamWriter("myoutput.dat", "UTF-8");
    out = new PrintWriter(outWriter, true);
} catch (Exception e) {
    System.out.println ("Exception occurred: "+e);
}
CDFUtils.printData (data, out);
```

Parameters:

- data - the data to be printed
- outWriter - the print writer to which formatted representations of the object/data is printed as a text-output stream

printData

```
public static void printData(java.lang.Object data,
                             java.io.PrintWriter outWriter,
                             int which)
```

Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

Parameters:

- data - the data to be printed
- outWriter - the print writer to which formatted representations of the object/data is printed as a text-output stream
- which - the Epoch data type data indicator 1 if CDF_EPOCH, 2 if CDF_EPOCH16 or 3 if CDF_TIME_TT2000 0 Otherwise

printData

```
public static void printData(java.lang.Object data,
                             java.io.PrintWriter outWriter,
                             int which,
                             boolean iso8601)
```

Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

Parameters:

- data - the data to be printed
- outWriter - the print writer to which formatted representations of the object/data is printed as a text-output stream
- which - the Epoch data type data indicator 1 if CDF_EPOCH, 2 if CDF_EPOCH16 or 3 if CDF_TIME_TT2000 0 Otherwise
- iso8601 - the ISO 8601 indicator for EPOCH data

printData

```
public static void printData(java.lang.Object data,
                             java.io.PrintWriter outWriter,
                             int which,
                             boolean iso8601,
                             java.lang.String addZ)
```

Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

Parameters:

- data - the data to be printed
- outWriter - the print writer to which formatted representations of the object/data is printed as a text-output stream
- which - the Epoch data type data indicator 1 if CDF_EPOCH, 2 if CDF_EPOCH16 or 3 if CDF_TIME_TT2000
- iso8601 - the ISO 8601 indicator for EPOCH data

addZ - Added the passed string to the end of an ISO8601 format string, (likely a "Z", to all CDF epoch data types, not just CDF_TIME_TT2000).

printDataWithFormat

```
public static void printDataWithFormat(java.lang.Object data,
                                     java.lang.String format)
```

Prints the value of the given data on the screen. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type. The format is mainly applicable to floating point typed data.

Parameters:

- data - the data to be printed
- format - the format specifically for the floating point data

printDataWithFormat

```
public static void printDataWithFormat(java.lang.Object data,
                                     java.lang.String format,
                                     int which,
                                     boolean iso8601)
```

Prints the value of the given data on the screen. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type. Note: The format is mainly used for floating point data.

Parameters:

- data - the data to be printed
- format - the format specifically for the floating point data
- which - the Epoch data type data indicator 1 if CDF_EPOCH, 2 if CDF_EPOCH16 or 3 if CDF_TIME_TT2000 0 otherwise
- iso8601 - the ISO 8601 indicator for EPOCH data

printDataWithFormat

```
public static void printDataWithFormat(java.lang.Object data,
                                     java.lang.String format,
                                     int which,
                                     boolean iso8601,
                                     java.lang.String addZ)
```

Prints the value of the given data on the screen. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type. Note: The format is mainly used for floating point data.

Parameters:

- data - the data to be printed
- format - the format specifically for the floating point data
- which - the Epoch data type data indicator 1 if CDF_EPOCH, 2 if CDF_EPOCH16 or 3 if CDF_TIME_TT2000
- iso8601 - the ISO 8601 indicator for EPOCH data
- addZ - Added the passed string to the end, (likely a "Z", to all CDF epoch data types, not just CDF_TIME_TT2000)

printDataWithFormat

```
public static void printDataWithFormat(java.lang.Object data,
                                     java.lang.String format,
                                     int which)
```

Prints the value of the given data on the screen. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

Parameters:

- data - the data to be printed
- format - the format specifically for the floating point data
- which - the Epoch data type data indicator 1 if CDF_EPOCH, 2 if CDF_EPOCH16 or 3 if CDF_TIME_TT2000 0 otherwise

printDataWithFormat

```
public static void printDataWithFormat(java.lang.Object data,
                                     java.lang.String format,
                                     java.io.PrintWriter outWriter)
```

Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

The following example will send the contents of the given data to "myoutput.dat".

```
OutputStreamWriter outWriter = null;
PrintWriter out = null;
try {
    outWriter = new OutputStreamWriter("myoutput.dat", "UTF-8");
    out = new PrintWriter(outWriter, true);
} catch (Exception e) {
    System.out.println ("Exception occurred: "+e);
}
CDFUtils.printData (data, out);
```

Parameters:

- data - the data to be printed
- format - the format specifically for the floating point data
- outWriter - the print writer to which formatted representations of the object/data is printed as a text-output stream

printDataWithFormat

```
public static void printDataWithFormat(java.lang.Object data,
                                     java.lang.String format,
                                     java.io.PrintWriter outWriter,
                                     int which)
```

Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

Parameters:

- data - the data to be printed
- format - the format specifically for the floating point data
- outWriter - the print writer to which formatted representations of the object/data is printed as a text-output stream
- which - the Epoch data type data indicator 1 if CDF_EPOCH, 2 if CDF_EPOCH16 or 3 if CDF_TIME_TT2000

printDataWithFormat

```
public static void printDataWithFormat(java.lang.Object data,
                                     java.lang.String format,
                                     java.io.PrintWriter outWriter,
                                     int which,
                                     boolean iso8601)
```

Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

Parameters:

- data - the data to be printed
- format - the format specifically for the floating point data
- outWriter - the print writer to which formatted representations of the object/data is printed as a text-output stream
- which - the Epoch data type data indicator 1 if CDF_EPOCH, 2 if CDF_EPOCH16 or 3 if CDF_TIME_TT2000
- iso8601 - the ISO 8601 indicator for EPOCH data

printDataWithFormat

```
public static void printDataWithFormat(java.lang.Object data,
                                     java.lang.String format,
                                     java.io.PrintWriter outWriter,
                                     int which,
                                     boolean iso8601,
                                     java.lang.String addZ)
```

Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

Parameters:

- data - the data to be printed
- format - the format specifically for the floating point data
- outWriter - the print writer to which formatted representations of the object/data is printed as a text-output stream
- which - the Epoch data type data indicator 1 if CDF_EPOCH, 2 if CDF_EPOCH16 or 3 if CDF_TIME_TT2000
- iso8601 - the ISO 8601 indicator for EPOCH data
- addZ - Added the passed string to the end of an ISO8601 format string, (likely a "Z", to all CDF epoch data types, not just CDF_TIME_TT2000).

getStringData

```
public static java.lang.String getStringData(java.lang.Object data)
```

Returns the string value of the given data. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

Parameters:

- data - the data to be parsed

Returns:

- The string value of the given data/object.
- If the data is an array, its elements are delimited by a space.

mergeFromStrings

```
public static java.lang.String mergeFromStrings(java.lang.Object data)
```

Merge an array of strings into a single string with "\ N ", a 3-char separator.

Parameters:

data - the strings to be merged.

Returns:

The merged string.
If the input is any single string, then it returns as is.

breakIntoStrings

```
public static java.lang.String[] breakIntoStrings(java.lang.String data)
```

Break down a merged string into their original array of strings. This is a reversed method of MergeStrings. The merged string uses "\ N ", a 3-char, as the separator.

Parameters:

data - the merged string to be broken down.

Returns:

An array of strings.
If the input string has no separator, it is a single string. The returned array will have only one element.

getStringData

```
public static java.lang.String getStringData(java.lang.Object data,
                                             int epochType)
```

Returns the string value of the given data. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

Parameters:

data - the data to be encoded.

epochType - epoch type indicator (==1 CDF_EPOCH, ==2 CDF_EPOCH16, ==0 others)

Returns:

The string value of the given data/object.
If the data is an array, its elements are delimited by a space.

getStringData

```
public static java.lang.String getStringData(java.lang.Object data,
                                             java.lang.String separator)
```

Returns the string of the value of the given data. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

Parameters:

`data` - the data to be encoded.

`separator` - the delimiter for array elements.

Returns:

The string value of the given data/object.

If the data is an array, its elements are delimited by the user defined separator.

getStringData

```
public static java.lang.String getStringData(java.lang.Object data,
                                             java.lang.String separator,
                                             int epochType)
```

Returns the string of the value of the given data. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

Parameters:

`data` - the data to be encoded.

`separator` - the delimiter for array elements.

`epochType` - Epoch or Epoch16 data type indicator
== 1 for EPOCH, == 2 for EPOCH16, == 3 for TT2000, == 0 for other data types

Returns:

The string value of the given data/object.

If the data is an array, its elements are delimited by the user defined separator.

getStringData

```
public static java.lang.String getStringData(java.lang.Object data,
                                             java.lang.String separator,
                                             int epochType,
                                             java.lang.String addZ)
```

Returns the string of the value of the given data. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive Java data type.

Parameters:

`data` - the data to be encoded.

`separator` - the delimiter for array elements.

`epochType` - Epoch or Epoch16 data type indicator
== 1 for EPOCH, == 2 for EPOCH16, == 3 for TT2000, == 0 for other data types

`addZ` - Added the passed string to the end, likely a "Z", to CDF_TIME_TT2000 data type

Returns:

The string value of the given data/object.

If the data is an array, its elements are delimited by the user defined separator.

getStringFloatingData

```
public static java.lang.String getStringFloatingData(java.lang.Object data,
                                                     java.lang.String format,
```

```
java.lang.String separator)
```

Returns the string of the value of the given data. Data can be a java primitive data type, Java Object (non-array), or 1-dimensional array of primitive or Java data type. The data shall be one of CDF numerical data types. The value will be formatted in format form if it is presented.

Parameters:

- `data` - the data to be encoded.
- `format` - the data format to be used.
- `separator` - the delimiter for array elements.

Returns:

- The string value of the given data/object.
- If the data is an array, its elements are delimited by the user defined separator.

getStringDataType

```
public static java.lang.String getStringDataType(Variable var)
```

Gets the string value of the CDF data type for the given variable.

Parameters:

- `var` - the CDF variable to be examined

Returns:

- See `getStringDataType (long cdfDataType)` for possible return values.

getStringDataType

```
public static java.lang.String getStringDataType(Entry entry)
```

Gets the string value of the CDF data type for the given entry.

Parameters:

- `entry` - the entry to be examined

Returns:

- String representation of the entry's CDF data type. See `getStringDataType (long cdfDataType)` for possible return values.

isStringDataType

```
public static boolean isStringDataType(long dataType)
```

Returns whether a CDF data type is a string type.

Parameters:

- `dataType` - the data type to be examined

Returns:

- true if it is (CDF_CHAR or CDF_UCHAR) false otherwise

isEpochDataType

```
public static boolean isEpochDataType(long dataType)
```

Returns whether a CDF data type is an epoch related type.

Parameters:

dataType - the data type to be examined

Returns:

true if it is (CDF_EPOCH, CDF_EPOCH16 or CDF_TIME_TT2000) false otherwise

getStringDataType

```
public static java.lang.String getStringDataType(long cdfDataType)
```

Gets the string representation of the given CDF data type.

Parameters:

cdfDataType - the CDF data type to be examined and translated

It should be one of the following:

- CDF_BYTE
- CDF_CHAR
- CDF_UCHAR
- CDF_INT1
- CDF_UINT1
- CDF_INT2
- CDF_UINT2
- CDF_INT4
- CDF_UINT4
- CDF_INT8
- CDF_REAL4
- CDF_FLOAT
- CDF_REAL8
- CDF_DOUBLE
- CDF_EPOCH
- CDF_EPOCH16
- CDF_TIME_TT2000

Returns:

String representation of cdfDataType. The returned value is one of the valid values describe above for cdfDataType. "UNKNOWN" is returned if invalid cdfDataType is given.

getDataTypeValue

```
public static long getDataTypeValue(java.lang.String cdfDataType)
```

Gets the long value of the given CDF data type in string. This is a reverse function from getStringDataType.

Parameters:

cdfDataType - the string CDF data type to be examined and translated. It should be one of the following values:

- CDF_BYTE
- CDF_CHAR
- CDF_UCHAR

- CDF_INT1
- CDF_UINT1
- CDF_INT2
- CDF_UINT2
- CDF_INT4
- CDF_UINT4
- CDF_INT8
- CDF_REAL4
- CDF_FLOAT
- CDF_REAL8
- CDF_DOUBLE
- CDF_EPOCH
- CDF_EPOCH16
- CDF_TIME_TT2000

Returns:

long representation of cdfDataType. The returned value is one of the valid values described above for cdfDataType. -1 is returned if invalid cdfDataType is given.

getStringCompressionType

```
public static java.lang.String getStringCompressionType(long compressionType)
```

Gets the string representation of the given CDF compression type.

Parameters:

- compressionType - the CDF compression type to be translated. it should be one of the following:
- NO_COMPRESSION
 - RLE_COMPRESSION
 - HUFF_COMPRESSION
 - AHUFF_COMPRESSION
 - GZIP_COMPRESSION

Returns:

- String representation of compressionType. The returned value is one of the following:
- NONE
 - RLE
 - Huffman
 - Adaptive Huffman
 - GZIP
 - UNKNOWN (for unknown compressionType)

getLongCompressionType

```
public static long getLongCompressionType(java.lang.String compressionType)
```

Gets the long representation of the given CDF compression type in string.

Parameters:

- compressionType - the CDF compression type to be translated. It should be one of the following:
- NONE
 - RLE
 - Huffman
 - Adaptive Huffman
 - GZIP

Returns:

- long representation of compressionType. The returned value is one of the following:
- NO_COMPRESSION
 - RLE_COMPRESSION
 - HUFF_COMPRESSION
 - AHUFF_COMPRESSION
 - GZIP_COMPRESSION
 - -1 (for unknown compressionType)

getStringCompressionType

```
public static java.lang.String getStringCompressionType(Variable var)
```

Gets the string representation of the given variable's compression type.

Parameters:

var - the variable to be examined

Returns:

string representation of the given variable's compression type. See getStringCompressionType(long compressionType) for possible return values.

getStringCompressionType

```
public static java.lang.String getStringCompressionType(CDF cdf)
```

Gets the string representation of the given CDF file's compression type.

Parameters:

cdf - the CDF to be examined

Returns:

string representation of the given CDF file's compression type. See getStringCompressionType(long compressionType) for possible return values.

getStringEncoding

```
public static java.lang.String getStringEncoding(long encodingType)
```

Gets the string value of the given CDF encoding type.

Parameters:

- encodingType - the CDF encoding type to be examined. It should be one of the following:
- NETWORK_ENCODING
 - SUN_ENCODING
 - DECSTATION_ENCODING
 - SGi_ENCODING
 - IBMPC_ENCODING
 - IBMRS_ENCODING
 - HOST_ENCODING
 - PPC_ENCODING
 - HP_ENCODING
 - NeXT_ENCODING

- ALPHAOSF1_ENCODING
- ALPHAVMSd_ENCODING
- ALPHAVMSg_ENCODING
- ALPHAVMSi_ENCODING
- ARM_LITTLE_ENCODING
- ARM_BIG_ENCODING
- IA64VMSi_ENCODING
- IA64VMSd_ENCODING
- IA64VMSg_ENCODING

Returns:

string representation of encodingType. The returned value is one of the following:

- NETWORK
- SUN
- DECSTATION
- SGi
- IBMPC
- IBMRS
- HOST
- PPC
- HP
- NeXT
- ALPHAOSF1
- ALPHAVMSd
- ALPHAVMSg
- ALPHAVMSi
- ARM_LITTLE
- ARM_BIG
- IA64VMSi
- IA64VMSd
- IA64VMSg
- UNKNOWN (for unknown encodingType)

getLongEncoding

```
public static long getLongEncoding(java.lang.String encodingType)
```

Gets the long value of the given CDF encoding type in string.

Parameters:

encodingType - the CDF encoding type to be examined. It should be one of the following:

- NETWORK
- SUN
- DECSTATION
- SGi
- IBMPC
- IBMRS
- HOST
- PPC
- HP
- NeXT
- ALPHAOSF1
- ALPHAVMSd
- ALPHAVMSg
- ALPHAVMSi
- ARM_LITTLE
- ARM_BIG
- IA64VMSi

- IA64VMSd
- IA64VMSg

Returns:

long representation of encodingType. The returned value is one of the following:

- NETWORK_ENCODING
- SUN_ENCODING
- DECSTATION_ENCODING
- SGi_ENCODING
- IBMPC_ENCODING
- IBMRS_ENCODING
- HOST_ENCODING
- PPC_ENCODING
- HP_ENCODING
- NeXT_ENCODING
- ALPHAOSF1_ENCODING
- ALPHAVMSd_ENCODING
- ALPHAVMSg_ENCODING
- ALPHAVMSi_ENCODING
- ARM_LITTLE_ENCODING
- ARM_BIG_ENCODING
- IA64VMSi_ENCODING
- IA64VMSd_ENCODING
- IA64VMSg_ENCODING
- -1 (for unknown encodingType)

getStringEncoding

```
public static java.lang.String getStringEncoding(CDF cdf)
```

Get the string value of the given CDF's encoding type.

Parameters:

cdf - the CDF to be examined

Returns:

string representation of the given CDF's encoding type. See getStringEncoding(long encodingType) for possible return values.

getStringDecoding

```
public static java.lang.String getStringDecoding(long decodingType)
                                           throws CDFException
```

Gets the string value of the given CDF decoding type

.

Parameters:

decodingType - the CDF decoding type to be examined. It should be one of the following:

- NETWORK_DECODING
- SUN_DECODING
- DECSTATION_DECODING
- SGi_DECODING
- IBMPC_DECODING
- IBMRS_DECODING
- HOST_DECODING

- PPC_DECODING
- HP_DECODING
- NeXT_DECODING
- ALPHAOSF1_DECODING
- ALPHAVMSd_DECODING
- ALPHAVMSg_DECODING
- ALPHAVMSi_DECODING
- ARM_LITTLE_DECODING
- ARM_BIG_DECODING
- IA64VMSi_DECODING
- IA64VMSd_DECODING
- IA64VMSg_DECODING
- -1 (for unknown encodingType)

Returns:

string representation of decodingType. See getStringEncoding (long encodingType) for possible return values.

Throws:

CDFException - if a problem occurs getting the string value of the given decoding type

getStringDecoding

```
public static java.lang.String getStringDecoding(CDF cdf)
                                     throws CDFException
```

Gets the string value of the given CDF file's decoding type.

Parameters:

cdf - the CDF to be examined

Returns:

string representation of the given CDF file's decoding type. See getStringEncoding (long encodingType) for possible return values.

Throws:

CDFException - if a problem occurs getting the value of the decoding type defined for the given CDF

getStringMajority

```
public static java.lang.String getStringMajority(long majorityType)
```

Gets the string value of the given CDF majority.

Parameters:

majorityType - the CDF majority to be translated

Returns:

string representation of majorityType. The returned value is one of the following:

- ROW
- COLUMN
- UNKNOWN (for unknown majorityType)

getLongMajority

```
public static long getLongMajority(java.lang.String majorityType)
```

Gets the long value of the given CDF majority.

Parameters:

`majorityType` - the CDF majority to be translated. It should be either ROW or COLUMN

Returns:

long representation of `majorityType`. The returned value is one of the following:

- ROW_MAJOR
- COLUMN_MAJOR
- -1 (for unknown `majorityType`)

getStringMajority

```
public static java.lang.String getStringMajority(CDF cdf)
```

Gets the string value of the given CDF file's majority.

Parameters:

`cdf` - the CDF to be examined

Returns:

string representation of the given CDF file's majority. The returned value is one of the following:

- ROW
- COLUMN

getStringFormat

```
public static java.lang.String getStringFormat(long formatType)
```

Gets the string value of the given CDF's file format.

Parameters:

`formatType` - the CDF file format to be translated. It should be either SINGLE or MULTI

Returns:

string representation of `formatType`. The returned value is either SINGLE, MULTI, or UNKNOWN.

getLongFormat

```
public static long getLongFormat(java.lang.String formatType)
```

Gets the long value of the given CDF file format in string.

Parameters:

`formatType` - the CDF file format to be translated. It should be either SINGLE or MULTI.

Returns:

long representation of `formatType`. The returned value is one of the following:

- SINGLE_FILE
- MULTI_FILE
- -1 (for unknown format type)

getStringFormat

```
public static java.lang.String getStringFormat(CDF cdf)
```

Gets the string value of the given CDF's file format.

Parameters:

`cdf` - the CDF to be examined

Returns:

string representation of given CDF's file format. The returned value is either SINGLE, MULTI, or UNKNOWN.

getStringSparseRecord

```
public static java.lang.String getStringSparseRecord(long sparseRecordType)
```

Gets the string value of the given sparse record type.

Parameters:

`sparseRecordType` - the sparse record type to be translated. It should be one of the following:

- NO_SPARSERECORDS
- PAD_SPARSERECORDS
- PREV_SPARSERECORDS

Returns:

string representation of `sparseRecordType`. The returned value is one of the following:

- None
- PAD
- PREV
- UNKNOWN

getLongChecksum

```
public static long getLongChecksum(java.lang.String checksum)
```

Gets the long value of the given CDF's checksum in string.

Parameters:

`checksum` - the checksum string of which to be translated.

Returns:

long value of checksum type. The returned value is either NONE_CHECKSUM, MD5_CHECKSUM, or OTHER_CHECKSUM.

getLeapSecondLastUpdated

```
public static long getLeapSecondLastUpdated(CDF cdf)
                                     throws CDFException
```

Gets the date of the given CDF's last updated for the leap second.

Parameters:

`cdf` - the CDF with which its leap second last updated.

Returns:

value (in YYYYMMDD) representation of leap second last updated, if set. -1 if the value is not set (prior to CDF V3.5.1).

Throws:

`CDFException` - An exception is thrown if the operation fails

getStringChecksum

```
public static java.lang.String getStringChecksum(CDF cdf)
```

Gets the string value of the given CDF's checksum.

Parameters:

`cdf` - the CDF with which its checksum to be translated.

Returns:

string representation of checksum type. The returned value is either NONE, MD5, or OTHER.

getStringChecksum

```
public static java.lang.String getStringChecksum(long checksumType)
```

Gets the string value of the given CDF's checksum.

Parameters:

`checksumType` - the CDF checksum to be translated. It should be either NO_CHECKSUM (or NONE_CHECKSUM) or MD5_CHECKSUM

Returns:

string representation of checksumType. The returned value is either NONE, MD5, or OTHER.

getLongSparseRecord

```
public static long getLongSparseRecord(java.lang.String sparseRecordType)
```

Gets the long value of the given sparse record type in string.

Parameters:

`sparseRecordType` - the sparse record type to be translated. It should be one of the following:

- None
- PAD or sRecords.PAD
- PREV or sRecords.PREV

Returns:

long representation of sparseRecordType. The returned value is one of the following:

- NO_SPARSERECORDS
- PAD_SPARSERECORDS
- PREV_SPARSERECORDS
- -1 (for unknown sparse record type)

getStringSparseRecord

```
public static java.lang.String getStringSparseRecord(Variable var)
```

Gets the string value of the given variable's sparse record type.

Parameters:

`var` - the variable to be examined

Returns:

string representation of the given variable's sparse record type. The returned value is one of the following:

- None
- PAD
- PREV
- UNKNOWN

cdfFileExists

```
public static boolean cdfFileExists(java.lang.String fileName)
```

Checks the existence of the given CDF file name. If the file name doesn't have ".cdf" file extension, it adds ".cdf" suffix at the end of the file name before checking the existence of the file. If the file exists in the current directory, it returns TRUE. Otherwise, FALSE is returned.

Parameters:

`fileName` - the name of the CDF file to be checked for existence

Returns:

true - if fileName exists in the current directory
false - if fileName doesn't exist in the current directory

CFtoJformat

```
public static java.lang.String CFtoJformat(java.lang.String cfFormat)
```

Convert a C/Fortran-based print format to a corresponding Java style format for numerical data.

Parameters:

`cfFormat` - C/Fortran-based format string

Returns:

Java style format or null if not a valid or a non-handled C/Fortran format

FtoJformat

```
public static java.lang.String FtoJformat(java.lang.String fFormat)
```

Convert a Fortran-based print format to a corresponding Java style format for numerical data. Limited Fortran format with I, F, E and G forms.

Parameters:

`fFormat` - Fortran-based format string

Returns:

jFormat Java style format or null if not a valid or a non-handled Fortran format

CtoJformat

```
public static java.lang.String CtoJformat(java.lang.String cFormat)
```

Convert a C-based print format to a corresponding Java style format for numerical data. Limited C format with I, F, E and G forms.

Parameters:

cFormat - C-based format string

Returns:

jFormat Java style format or null if not a valid or a non-handled Fortran format

isFloatingPadValue

```
public static int isFloatingPadValue(long dataType,
                                     java.lang.Object value)
```

Check if a data is a floating point and its value is a pad value.

Parameters:

dataType - The data type of the data

value - A single data object

Returns:

1 if the data is of floating point and it is a pad value 0 otherwise

isFloatingPadValue

```
public static int isFloatingPadValue(java.lang.Object value)
```

Check if a data is a floating point and its value is a pad value.

Parameters:

value - A data object

Returns:

1 if the data is of floating point and it is a pad value 0 otherwise

isFloatingPadValue

```
public static int isFloatingPadValue(long dataType,
                                     float value)
```

Check if a data is a floating point and its value is a pad value.

Parameters:

dataType - The data type of the data

value - The float data

Returns:

1 if the data is of floating point and it is a pad value 0 otherwise

isFloatingPadValue

```
public static int isFloatingPadValue(long dataType,
                                   double value)
```

Check if a data is a floating point and its value is a pad value.

Parameters:

dataType - The data type of the data

value - The double data

Returns:

1 if the data is of floating point and it is a pad value 0 otherwise

isFloatingPadValue

```
public static int isFloatingPadValue(float value)
```

Check if a float data is a pad value.

Parameters:

value - a float data

Returns:

1 if the data is a pad value 0 otherwise

isFloatingPadValue

```
public static int isFloatingPadValue(double value)
```

Check if a double data is a pad value.

Parameters:

value - a double data

Returns:

1 if the data is a pad value 0 otherwise

getNumDimensions

```
public static int getNumDimensions(java.lang.Object obj)
```

getDimensionSizes

```
public static long[] getDimensionSizes(java.lang.Object obj)
```

UTF8toUTF16LE

```
public static byte[] UTF8toUTF16LE(java.lang.Object utf8)
```

UTF16LEtoUTF8

```
public static byte[] UTF16LEtoUTF8(java.lang.Object utf16)
```

UTF8toCp1252

```
public static byte[] UTF8toCp1252(java.lang.Object utf8)
```

Cp1252toUTF8

```
public static byte[] Cp1252toUTF8(java.lang.Object cp1252)
```

Overview	Package	Class	Tree	Deprecated	Index	Help
Prev Class	Next Class	Frames	No Frames	All Classes		
Summary: Nested Field Constr Method				Detail: Field Constr Method		

gsfc.nssdc.cdf

Class Entry

java.lang.Object
gsfc.nssdc.cdf.Entry

All Implemented Interfaces:

CDFConstants, CDFObject

```
public class Entry
extends java.lang.Object
implements CDFObject, CDFConstants
```

This class describes a CDF global or variable attribute entry.

Note: In the Java CDF API there is no concept of an rEntry since r variables are not supported. Only z variables are supported since it is far superior and efficient than r variables.

Version:

1.0, 2.0 03/18/05 Selection of current CDF, attribute and entry are done as part of operations passed to JNI. JNI call is synchronized so only one process is allowed in a JVM, due to multi-thread safety. The select method will never be called.

See Also:

Attribute

Field Summary

Fields inherited from interface gsfc.nssdc.cdf.CDFConstants

AHUFF COMPRESSION, ALPHAOSf1 DECODING, ALPHAOSf1 ENCODING, ALPHAVMSd DECODING, ALPHAVMSd ENCODING, ALPHAVMSg DECODING, ALPHAVMSg ENCODING, ALPHAVMSi DECODING, ALPHAVMSi ENCODING, ARM BIG DECODING, ARM BIG ENCODING, ARM LITTLE DECODING, ARM LITTLE ENCODING, ATTR, ATTR EXISTENCE, ATTR EXISTS, ATTR MAXgENTRY, ATTR MAXrENTRY, ATTR MAXZENTRY, ATTR NAME, ATTR NAME TRUNC, ATTR NUMBER, ATTR NUMgENTRIES, ATTR NUMrENTRIES, ATTR NUMzENTRIES, ATTR SCOPE, BACKWARD, BACKWARDFILEoff, BACKWARDFILEon, BAD ALLOCATE RECS, BAD ARGUMENT, BAD ATTR NAME, BAD ATTR NUM, BAD BLOCKING FACTOR, BAD CACHE SIZE, BAD CDF EXTENSION, BAD CDF ID, BAD CDF NAME, BAD CDFSTATUS, BAD CHECKSUM, BAD COMPRESSION PARM, BAD DATA TYPE, BAD DECODING, BAD DIM COUNT, BAD DIM INDEX, BAD DIM INTERVAL, BAD DIM SIZE, BAD ENCODING, BAD ENTRY NUM, BAD FNC OR ITEM, BAD FORMAT, BAD INITIAL RECS, BAD MAJORITY, BAD MALLOC, BAD NEGtoPOSfp0 MODE, BAD NUM DIMS, BAD NUM ELEMS, BAD NUM STRINGS, BAD NUM VARS, BAD READONLY MODE, BAD REC COUNT, BAD REC INTERVAL, BAD REC NUM, BAD SCOPE, BAD SCRATCH DIR, BAD SPARSEARRAYS PARM, BAD VAR NAME, BAD VAR NUM, BAD zMODE, BADDATE LEAPSECOND UPDATED, BeginUnixTimeEPOCH, BeginUnixTimeEPOCH16, BLOCKINGFACTOR TOO LARGE, BLOCKINGFACTOR TOO SMALL, BLOCKINGFACTOR TOO SMALL2, CANNOT ALLOCATE RECORDS, CANNOT CHANGE, CANNOT COMPRESS, CANNOT CONVERT WIDECHAR, CANNOT COPY, CANNOT INSERT RECORDS, CANNOT SPARSEARRAYS, CANNOT SPARSERECORDS, CDF, CDF ACCESS, CDF ATTR NAME LEN, CDF ATTR NAME LEN256, CDF BYTE, CDF CACHESIZE, CDF CHAR, CDF CHECKSUM, CDF CLOSE ERROR, CDF COMPRESSION, CDF COPYRIGHT, CDF COPYRIGHT LEN, CDF CREATE ERROR, CDF DECODING, CDF DELETE ERROR, CDF DOUBLE, CDF ENCODING, CDF EPOCH, CDF EPOCH16, CDF EXISTS, CDF FLOAT, CDF FORMAT, CDF INCREMENT, CDF INFO, CDF INT1, CDF INT2, CDF INT4, CDF INT8, CDF INTERNAL ERROR, CDF LEAPSECONDLASTUPDATED, CDF MAJORITY, CDF MAX DIMS, CDF MAX PARMS, CDF MIN DIMS, CDF NAME, CDF NAME TRUNC, CDF NEGtoPOSfp0 MODE, CDF NUMATTRS, CDF NUMgATTRS, CDF NUMrVARS, CDF NUMvATTRS, CDF NUMzVARS, CDF OK, CDF OPEN ERROR, CDF PATHNAME LEN, CDF READ ERROR, CDF READONLY MODE, CDF REAL4, CDF REAL8, CDF RELEASE, CDF SAVE ERROR, CDF SCRATCHDIR, CDF STATUS, CDF STATUSTEXT LEN, CDF TIME TT2000, CDF UCHAR, CDF UINT1, CDF UINT2, CDF UINT4, CDF VAR NAME LEN, CDF VAR NAME LEN256, CDF VERSION, CDF WARN, CDF WRITE ERROR, CDF zMODE, CDFwithSTATS, CHECKSUM, CHECKSUM ERROR, CHECKSUM NOT ALLOWED, CLOSE, COLUMN MAJOR, COMPRESS CACHESIZE, COMPRESSION ERROR, CONFIRM, CORRUPTED V2 CDF, CORRUPTED V3 CDF, CREATE, CURgENTRY EXISTENCE, CURrENTRY EXISTENCE, CURzENTRY EXISTENCE, DATATYPE MISMATCH, DATATYPE SIZE, DECOMPRESSION ERROR, DECSTATION DECODING, DECSTATION ENCODING, DEFAULT BYTE PADVALUE, DEFAULT CHAR PADVALUE, DEFAULT DOUBLE PADVALUE, DEFAULT EPOCH PADVALUE, DEFAULT EPOCH16 PADVALUE, DEFAULT FLOAT PADVALUE, DEFAULT INT1 PADVALUE, DEFAULT INT2 PADVALUE, DEFAULT INT4 PADVALUE, DEFAULT INT8 PADVALUE, DEFAULT REAL4 PADVALUE, DEFAULT REAL8 PADVALUE, DEFAULT TT2000 PADVALUE, DEFAULT UCHAR PADVALUE, DEFAULT UINT1 PADVALUE, DEFAULT UINT2 PADVALUE, DEFAULT UINT4 PADVALUE, DELETE, DID NOT COMPRESS, EMPTY COMPRESSED CDF,

END OF VAR, EPOCH STRING LEN, EPOCH STRING LEN EXTEND, EPOCH1 STRING LEN, EPOCH1 STRING LEN EXTEND, EPOCH2 STRING LEN, EPOCH2 STRING LEN EXTEND, EPOCH3 STRING LEN, EPOCH3 STRING LEN EXTEND, EPOCH4 STRING LEN, EPOCH4 STRING LEN EXTEND, EPOCHx FORMAT MAX, EPOCHx STRING MAX, FILLED TT2000 VALUE, FORCED PARAMETER, FUNCTION NOT SUPPORTED, gENTRY, gENTRY DATA, gENTRY DATASPEC, gENTRY DATATYPE, gENTRY EXISTENCE, gENTRY NUMElems, GET, GETCDFCHECKSUM, GETCDFFILEBACKWARD, GETCDFVALIDATE, GETLEAPSECONDSENVVAR, GLOBAL SCOPE, GZIP COMPRESSION, HOST DECODING, HOST ENCODING, HP DECODING, HP ENCODING, HUFF COMPRESSION, IA64VMSd DECODING, IA64VMSd ENCODING, IA64VMSg DECODING, IA64VMSg ENCODING, IA64VMSi DECODING, IA64VMSi ENCODING, IBM PC OVERFLOW, IBMPC DECODING, IBMPC ENCODING, IBMRS DECODING, IBMRS ENCODING, ILLEGAL EPOCH FIELD, ILLEGAL EPOCH VALUE, ILLEGAL FOR SCOPE, ILLEGAL IN zMODE, ILLEGAL ON V1 CDF, ILLEGAL TT2000 VALUE, IS A NETCDF, LIB COPYRIGHT, LIB INCREMENT, LIB RELEASE, LIB subINCREMENT, LIB VERSION, MAC DECODING, MAC ENCODING, MD5 CHECKSUM, MULTI FILE, MULTI FILE FORMAT, NA FOR VARIABLE, NEGATIVE FP ZERO, NEGtoPOSfp0off, NEGtoPOSfp0on, NETWORK DECODING, NETWORK ENCODING, Next DECODING, Next ENCODING, NO ATTR SELECTED, NO CDF SELECTED, NO CHECKSUM, NO COMPRESSION, NO DELETE ACCESS, NO ENTRY SELECTED, NO MORE ACCESS, NO PADVALUE SPECIFIED, NO SPARSEARRAYS, NO SPARSERECORDS, NO STATUS SELECTED, NO SUCH ATTR, NO SUCH CDF, NO SUCH ENTRY, NO SUCH RECORD, NO SUCH VAR, NO VAR SELECTED, NO VARS IN CDF, NO WRITE ACCESS, NONE CHECKSUM, NOT A CDF, NOT A CDF OR NOT SUPPORTED, NOVARY, NULL, OPEN, OPTIMAL ENCODING TREES, OTHER CHECKSUM, PAD SPARSERECORDS, PPC DECODING, PPC ENCODING, PRECEEDING RECORDS ALLOCATED, PREV SPARSERECORDS, PUT, READ ONLY DISTRIBUTION, READ ONLY MODE, READONLYoff, READONLYon, rENTRY, rENTRY DATA, rENTRY DATASPEC, rENTRY DATATYPE, rENTRY EXISTENCE, rENTRY NAME, rENTRY NUMElems, rENTRY NUMSTRINGS, rENTRY STRINGSDATA, RLE COMPRESSION, RLE OF ZEROS, ROW MAJOR, rVAR, rVAR ALLOCATEBLOCK, rVAR ALLOCATEDFROM, rVAR ALLOCATEDTO, rVAR ALLOCATERECS, rVAR BLOCKINGFACTOR, rVAR CACHESIZE, rVAR COMPRESSION, rVAR DATA, rVAR DATASPEC, rVAR DATATYPE, rVAR DIMVARYS, rVAR EXISTENCE, rVAR HYPERDATA, rVAR INITIALRECS, rVAR MAXallocREC, rVAR MAXREC, rVAR NAME, rVAR nINDEXENTRIES, rVAR nINDEXLEVELS, rVAR nINDEXRECORDS, rVAR NUMallocRECS, rVAR NUMBER, rVAR NUMElems, rVAR NUMRECS, rVAR PADVALUE, rVAR RECORDS, rVAR RECORDS RENUMBER, rVAR RECVAR, rVAR RESERVEPERCENT, rVAR SEQDATA, rVAR SEQPOS, rVAR SPARSEARRAYS, rVAR SPARSERECORDS, rVARs CACHESIZE, rVARs DIMCOUNTS, rVARs DIMINDICES, rVARs DIMINTERVALS, rVARs DIMSIZES, rVARs MAXREC, rVARs NUMDIMS, rVARs RECCOUNT, rVARs RECDATA, rVARs RECINTERVAL, rVARs RECNUMBER, SAVE, SCRATCH CREATE ERROR, SCRATCH DELETE ERROR, SCRATCH READ ERROR, SCRATCH WRITE ERROR, SELECT, SGI DECODING, SGI ENCODING, SINGLE FILE, SINGLE FILE FORMAT, SOME ALREADY ALLOCATED, STAGE CACHESIZE, STATUS TEXT, STRING NOT UTF8 ENCODING, STRINGDELIMITER, SUN DECODING, SUN ENCODING, TOO MANY PARMS, TOO MANY VARS, TRY TO READ NONSTRING DATA, TT2000 0 STRING LEN, TT2000 1 STRING LEN, TT2000 2 STRING LEN, TT2000 3 STRING LEN, TT2000 4 STRING LEN, TT2000 CDF MAYNEEDUPDATE, TT2000 TIME ERROR, TT2000 USED OUTDATED TABLE, UNABLE TO PROCESS CDF, UNKNOWN COMPRESSION, UNKNOWN SPARSENESS, UNSUPPORTED OPERATION, VALIDATE, VALIDATEFILEoff, VALIDATEFILEon, VAR ALREADY CLOSED, VAR CLOSE ERROR, VAR CREATE ERROR, VAR DELETE ERROR, VAR EXISTS, VAR NAME TRUNC, VAR OPEN ERROR, VAR READ ERROR, VAR SAVE ERROR, VAR WRITE ERROR, VARIABLE SCOPE, VARY, VAX DECODING, VAX ENCODING, VIRTUAL RECORD DATA, zENTRY, zENTRY DATA, zENTRY DATASPEC, zENTRY DATATYPE, zENTRY EXISTENCE, zENTRY NAME, zENTRY NUMElems, zENTRY NUMSTRINGS, zENTRY STRINGSDATA, ZLIB COMPRESS ERROR, ZLIB UNCOMPRESS ERROR, zMODEoff, zMODEon1, zMODEon2, zVAR, zVAR ALLOCATEBLOCK, zVAR ALLOCATEDFROM, zVAR ALLOCATEDTO, zVAR ALLOCATERECS, zVAR BLOCKINGFACTOR, zVAR CACHESIZE, zVAR COMPRESSION, zVAR DATA, zVAR DATASPEC, zVAR DATATYPE, zVAR DIMCOUNTS, zVAR DIMINDICES, zVAR DIMINTERVALS, zVAR DIMSIZES, zVAR DIMVARYS, zVAR EXISTENCE, zVAR HYPERDATA, zVAR INITIALRECS, zVAR MAXallocREC, zVAR MAXREC, zVAR NAME, zVAR nINDEXENTRIES, zVAR nINDEXLEVELS, zVAR nINDEXRECORDS, zVAR NUMallocRECS, zVAR NUMBER, zVAR NUMDIMS, zVAR NUMElems, zVAR NUMRECS, zVAR PADVALUE, zVAR RECCOUNT, zVAR RECINTERVAL, zVAR RECNUMBER, zVAR RECORDS, zVAR RECORDS RENUMBER, zVAR RECVAR, zVAR RESERVEPERCENT, zVAR SEQDATA, zVAR SEQPOS, zVAR SPARSEARRAYS, zVAR SPARSERECORDS, zVARs CACHESIZE, zVARs MAXREC, zVARs RECDATA, zVARs RECNUMBER

Method Summary

Methods	
Modifier and Type	Method and Description
static Entry	create (Attribute myAttribute, long id, long dataType, java.lang.Object data) Creates a new global or variable attribute entry.
void	delete () Deletes this entry.
java.lang.Object	getData () Gets the data for this entry.
long	getDataType () Gets the CDF data type of this entry.
long	getID () Gets the ID of this entry.
java.lang.String	getName () Gets the name of this entry.
long	getNumElements () Gets the number of elements in this entry.

long	getNumStrings() Gets the number of strings in the data.
long	getScope() Gets the scope of the attribute this entry in in.
void	putData (long dataType, java.lang.Object data) Put the entry data into the CDF.
void	rename (java.lang.String name) This method is here as a placeholder since the Entry class implements the CDFObjcet interface that includes "rename".
void	updateDataSpec (long dataType, long numElements) Update the data specification (data type and number of elements) of the entry.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Method Detail

create

```
public static Entry create(Attribute myAttribute,
    long id,
    long dataType,
    java.lang.Object data)
    throws CDFException
```

Creates a new global or variable attribute entry. One can create as many global and variable entries as needed. The following example creates four entries for the global attribute "Project":

```
Attribute project = Attribute.create(cdf, "Project", GLOBAL_SCOPE);
Entry.create(project, 0, CDF_CHAR, "Project name: IMAGE");
Entry.create(project, 1, CDF_CHAR, "Description 1");
Entry.create(project, 2, CDF_CHAR, "Description 2");
```

The following example creates a variable attribute entry for the variable "Longitude" associated with the attribute "VALIDMIN":

```
Variable longitude = cdf.getVariable("Longitude");
Attribute validMin = Attribute.create(cdf, "VALIDMIN",
    VARIABLE_SCOPE);
Entry.create(validMin, longitude.getID(), CDF_INT2,
    new Short((short)10));
OR
longitude.putEntry(validMin, CDF_INT2, new Short((short)180));
```

Parameters:

- myAttribute - the attribute to which this entry belongs
- id - the entry id
- dataType - the CDF data type for this entry that should be one of the following:
 - CDF_BYTE - 1-byte, signed integer
 - CDF_CHAR - 1-byte, signed character
 - CDF_INT1 - 1-byte, signed integer
 - CDF_UCHAR - 1-byte, unsigned character
 - CDF_UINT1 - 1-byte, unsigned integer
 - CDF_INT2 - 2-byte, signed integer
 - CDF_UNIT2 - 2-byte, unsigned integer
 - CDF_INT4 - 4-byte, signed integer

- CDF_UINT4 - 4-byte, unsigned integer
- CDF_INT8 - 8-byte, signed integer
- CDF_REAL4 - 4-byte, floating point
- CDF_FLOAT - 4-byte, floating point
- CDF_REAL8 - 8-byte, floating point
- CDF_DOUBLE - 8-byte, floating point
- CDF_EPOCH - 8-byte, floating point
- CDF_EPOCH16 - 2*8-byte, floating point
- CDF_TIME_TT2000 - 8-byte, signed integer

data - the entry data to be added

Note: From CDF V3.7.0, the string typed data of variable entry can be an array of strings. Data from previous versions can only be a single string.

Returns:

newly created attribute entry

Throws:

CDFException - CDFException if there is a problem creating an entry

delete

```
public void delete()  
    throws CDFException
```

Deletes this entry.

Specified by:

delete in interface CDFObject

Throws:

CDFException - CDFException if there is a problem deleting this entry

getDataType

```
public long getDataType()
```

Gets the CDF data type of this entry. See the description of the create method for the CDF data types supported by the CDF library.

Returns:

the CDF data type of this entry

getScope

```
public long getScope()
```

Gets the scope of the attribute this entry in in.

Returns:

the scope of this entry

getNumElements

```
public long getNumElements()
```

Gets the number of elements in this entry. For CDF_CHAR, it returns the number of characters stored.

Entry data	Number of elements
-----	-----
10	1
20.8	1
10 20 30	3
20.8 20.9	2
"Upper Limits"	12

Returns:

the number of elements stored in this entry

getNumStrings

```
public long getNumStrings()
```

Gets the number of strings in the data. If the data is not string type, 0 is returned. For global attribute entry, it always returns 1.

Returns:

the string number for this entry

getData

```
public java.lang.Object getData()
                        throws CDFException
```

Gets the data for this entry. Build a new data object so a duplicated variable will have its own copy of the entry data.

Returns:

the data for this entry Note: From CDF V3.7.0, the string typed data of variable entry can return an array of strings. Data from previous versions only returns a single string.

Throws:

CDFException - An exception is thrown if the operation fails

getID

```
public long getID()
```

Gets the ID of this entry.

Returns:

the ID/number of this entry

getName

```
public java.lang.String getName()
```

Gets the name of this entry. Since an entry doesn't have its own name, the string representation of this entry ID is returned.

This method overrides the getName() method defined in the Java Object class. If this method is called explicitly or implicitly (i.e. just

the entry name by itself), it returns the string representation of the entry ID.

Specified by:

`getName` in interface `CDFObject`

Returns:

string representation of this attribute entry ID

rename

```
public void rename(java.lang.String name)
                throws CDFException
```

This method is here as a placeholder since the Entry class implements the CDFObject interface that includes "rename".

Specified by:

`rename` in interface `CDFObject`

Parameters:

name - - not applicable

Throws:

`CDFException` - CDFException - not applicable

updateDataSpec

```
public void updateDataSpec(long dataType,
                           long numElements)
                           throws CDFException
```

Update the data specification (data type and number of elements) of the entry.

Parameters:

dataType - the data type of the entry data

numElements - the number of elements of the entry data

Throws:

`CDFException` - An exception is thrown if the operation fails

putData

```
public void putData(long dataType,
                    java.lang.Object data)
                    throws CDFException
```

Put the entry data into the CDF.

Parameters:

dataType - the data type of the entry data

data - the entry data to write Note: From CDF V3.7.0, the string typed data of variable entry can be an array of strings. Data from previous versions can only be a single string.

Throws:

CDFException - An exception is thrown if the operation fails

Overview

Package

Class

Tree

Deprecated

Index

Help

Prev Class

Next Class

Frames

No Frames

All Classes

Summary: Nested | Field | Constr | Method

Detail: Field | Constr | Method

Overview	Package	Class	Tree	Deprecated	Index	Help
Prev Class	Next Class	Frames	No Frames	All Classes		
Summary: Nested Field Constr Method			Detail: Field Constr Method			

gsfc.nssdc.cdf.util

Class Epoch

java.lang.Object
gsfc.nssdc.cdf.util.EPOCH

All Implemented Interfaces:

CDFConstants

```
public class Epoch
extends java.lang.Object
implements CDFConstants
```

This class contains the handy utility routines (methods) called by the CDF applications to handle epoch data of CDF's CDF_EPOCH data type.

Version:

1.0 Example:

```
// Get the milliseconds to Aug 5, 1990 at 5:00
double ep = Epoch.compute(1990, 8, 5, 5, 0, 0, 0);
//Get the year, month, day, hour, minutes, seconds, milliseconds for ep
long[] times = Epoch.breakdown(ep);
for (int i=0;i<times.length;i++)
    System.out.print(times[i]+" ");
System.out.println();
// Printout the epoch in various formats
System.out.println(EPOCH.encode(ep));
System.out.println(EPOCH.encode1(ep));
System.out.println(EPOCH.encode2(ep));
System.out.println(EPOCH.encode3(ep));
System.out.println(EPOCH.encode4(ep));
// Print out the date using format
String format = "<month> <dom.02>, <year> at <hour>:<min>";
System.out.println(EPOCH.encodeX(ep,format));
```

Field Summary

Fields inherited from interface gsfc.nssdc.cdf.CDFConstants

AHUFF COMPRESSION, ALPHAOSF1 DECODING, ALPHAOSF1 ENCODING, ALPHAVMSd DECODING, ALPHAVMSd ENCODING, ALPHAVMSg DECODING, ALPHAVMSg ENCODING, ALPHAVMSi DECODING, ALPHAVMSi ENCODING, ARM BIG DECODING, ARM BIG ENCODING, ARM LITTLE DECODING, ARM LITTLE ENCODING, ATTR, ATTR EXISTENCE, ATTR EXISTS, ATTR MAXgENTRY, ATTR MAXrENTRY, ATTR MAXzENTRY, ATTR NAME, ATTR NAME TRUNC, ATTR NUMBER, ATTR NUMgENTRIES, ATTR NUMrENTRIES, ATTR NUMzENTRIES, ATTR SCOPE, BACKWARD, BACKWARDFILEoff, BACKWARDFILEon, BAD ALLOCATE RECS, BAD ARGUMENT, BAD ATTR NAME, BAD ATTR NUM, BAD BLOCKING FACTOR, BAD CACHE SIZE, BAD CDF EXTENSION, BAD CDF ID, BAD CDF NAME, BAD CDFSTATUS, BAD CHECKSUM, BAD COMPRESSION PARM, BAD DATA TYPE, BAD DECODING, BAD DIM COUNT, BAD DIM INDEX, BAD DIM INTERVAL, BAD DIM SIZE, BAD ENCODING, BAD ENTRY NUM, BAD FNC OR ITEM, BAD FORMAT, BAD INITIAL RECS, BAD MAJORITY, BAD MALLOC, BAD NEGtoPOSfp0 MODE, BAD NUM DIMS, BAD NUM ELEMS, BAD NUM STRINGS, BAD NUM VARS, BAD READONLY MODE, BAD REC COUNT, BAD REC INTERVAL, BAD REC NUM, BAD SCOPE, BAD SCRATCH DIR, BAD SPARSEARRAYS PARM, BAD VAR NAME, BAD VAR NUM, BAD zMODE, BADDATE LEAPSECOND UPDATED, BeginUnixTimeEPOCH, BeginUnixTimeEPOCH16, BLOCKINGFACTOR TOO LARGE, BLOCKINGFACTOR TOO SMALL, BLOCKINGFACTOR TOO SMALL2, CANNOT ALLOCATE RECORDS, CANNOT CHANGE, CANNOT COMPRESS, CANNOT CONVERT WIDECHAR, CANNOT COPY, CANNOT INSERT RECORDS, CANNOT SPARSEARRAYS, CANNOT SPASERECORDS, CDF, CDF ACCESS, CDF ATTR NAME LEN, CDF ATTR NAME LEN256, CDF BYTE, CDF CACHESIZE, CDF CHAR, CDF CHECKSUM, CDF CLOSE ERROR, CDF COMPRESSION, CDF COPYRIGHT, CDF COPYRIGHT LEN, CDF CREATE ERROR, CDF DECODING, CDF DELETE ERROR, CDF DOUBLE, CDF ENCODING, CDF EPOCH, CDF EPOCH16, CDF EXISTS, CDF FLOAT, CDF FORMAT, CDF INCREMENT, CDF INFO, CDF INT1, CDF INT2, CDF INT4, CDF INT8, CDF INTERNAL ERROR, CDF LEAPSECONDLASTUPDATED, CDF MAJORITY, CDF_MAX_DIMS, CDF_MAX_PARMS, CDF_MIN_DIMS, CDF_NAME, CDF_NAME TRUNC, CDF_NEGtoPOSfp0_MODE,

CDF NUMATTRS , CDF NUMgATTRS , CDF NUMrVARS , CDF NUMvATTRS , CDF NUMzVARS , CDF OK,
CDF_OPEN ERROR, CDF PATHNAME_LEN, CDF READ ERROR, CDF READONLY MODE, CDF REAL4, CDF REAL8,
CDF_RELEASE , CDF SAVE ERROR, CDF SCRATCHDIR , CDF STATUS , CDF STATUSTEXT_LEN, CDF TIME TT2000,
CDF_UCHAR, CDF UINT1, CDF UINT2, CDF UINT4, CDF VAR NAME_LEN, CDF VAR NAME_LEN256, CDF_VERSION_
CDF_WARN, CDF WRITE ERROR, CDF zMODE_, CDFwithSTATS_, CHECKSUM , CHECKSUM ERROR,
CHECKSUM NOT ALLOWED, CLOSE , COLUMN MAJOR, COMPRESS CACHESIZE , COMPRESSION ERROR, CONFIRM_
CORRUPTED V2_CDF, CORRUPTED_V3_CDF, CREATE , CURgENTRY EXISTENCE , CURrENTRY EXISTENCE ,
CURzENTRY EXISTENCE , DATATYPE MISMATCH, DATATYPE SIZE_, DECOMPRESSION ERROR, DECSTATION DECODING,
DECSTATION ENCODING_, DEFAULT BYTE PADVALUE, DEFAULT CHAR PADVALUE, DEFAULT DOUBLE PADVALUE,
DEFAULT EPOCH PADVALUE, DEFAULT EPOCH16 PADVALUE, DEFAULT FLOAT PADVALUE, DEFAULT INT1 PADVALUE,
DEFAULT_INT2 PADVALUE, DEFAULT INT4 PADVALUE, DEFAULT INT8 PADVALUE, DEFAULT REAL4 PADVALUE,
DEFAULT_REAL8 PADVALUE, DEFAULT TT2000 PADVALUE, DEFAULT UCHAR PADVALUE, DEFAULT UNT1 PADVALUE,
DEFAULT_UINT2 PADVALUE, DEFAULT_UINT4 PADVALUE, DELETE ,_DID NOT COMPRESS, EMPTY_COMPRESSED_CDF,
END OF VAR, EPOCH STRING_LEN, EPOCH STRING_LEN EXTEND, EPOCH1 STRING_LEN,
EPOCH1_STRING_LEN_EXTEND, EPOCH2 STRING_LEN, EPOCH2 STRING_LEN EXTEND, EPOCH3 STRING_LEN,
EPOCH3_STRING_LEN_EXTEND, EPOCH4 STRING_LEN, EPOCH4_STRING_LEN_EXTEND, EPOCHx_FORMAT_MAX,
EPOCHx_STRING_MAX, FILLED TT2000_VALUE, FORCED PARAMETER, FUNCTION NOT SUPPORTED, gENTRY ,
gENTRY_DATA , gENTRY DATASPEC , gENTRY DATATYPE , gENTRY EXISTENCE , gENTRY NUMELEMS , GET
GETCDFCHECKSUM , GETCDFFILEBACKWARD , GETCDFVALIDATE , GETLEAPSECONDSENVVAR , GLOBAL_SCOPE ,
GZIP COMPRESSION, HOST DECODING, HOST ENCODING, HP DECODING, HP ENCODING, HUFF COMPRESSION,
IA64VMSd DECODING, IA64VMSd ENCODING, IA64VMSg DECODING, IA64VMSg ENCODING, IA64VMSi_DECODING,
IA64VMSi ENCODING, IBM PC OVERFLOW, IBMPC DECODING, IBMPC ENCODING, IBMRS DECODING,
IBMRS ENCODING, ILLEGAL EPOCH FIELD, ILLEGAL EPOCH VALUE, ILLEGAL FOR SCOPE, ILLEGAL_IN_zMODE,
ILLEGAL ON V1_CDF, ILLEGAL TT2000 VALUE, IS A NETCDF, LIB COPYRIGHT , LIB INCREMENT _
LIB RELEASE ,_LIB subINCREMENT , LIB VERSION _ MAC DECODING, MAC ENCODING_, MD5 CHECKSUM,
MULTI FILE, MULTI FILE FORMAT, NA FOR VARIABLE, NEGATIVE FP ZERO, NEGtoPOSfp0off, NEGtoPOSfp0on,
NETWORK DECODING , NETWORK ENCODING , Next DECODING, Next ENCODING, NO ATTR SELECTED,
NO CDF SELECTED, NO CHECKSUM, NO COMPRESSION, NO DELETE_ACCESS, NO ENTRY SELECTED, NO MORE ACCESS,
NO_PADVALUE SPECIFIED, NO SPARSEARRAYS, NO SPARSERECORDS, NO STATUS SELECTED, NO SUCH_ATTR,
NO SUCH_CDF, NO SUCH ENTRY, NO SUCH RECORD, NO SUCH VAR, NO VAR SELECTED, NO VARS_IN_CDF,
NO_WRITE ACCESS, NONE CHECKSUM, NOT_A_CDF, NOT_A_CDF OR NOT_SUPPORTED, NOVARY, NULL , OPEN _
OPTIMAL ENCODING TREES, OTHER CHECKSUM, PAD SPARSERECORDS, PPC DECODING, PPC ENCODING,
PRECEEDING RECORDS ALLOCATED, PREV SPARSERECORDS, PUT , READ ONLY DISTRIBUTION, READ_ONLY_MODE,
READONLYoff, READONLYon, rENTRY , rENTRY_DATA , rENTRY DATASPEC , rENTRY DATATYPE ,
rENTRY EXISTENCE , rENTRY NAME , rENTRY NUMELEMS , rENTRY NUMSTRINGS , rENTRY STRINGSDATA ,
RLE COMPRESSION, RLE OF ZEROS, ROW MAJOR, rVAR , rVAR ALLOCATEBLOCK , rVAR ALLOCATEDFROM ,
rVAR ALLOCATEDTO , rVAR ALLOCATERECS , rVAR BLOCKINGFACTOR , rVAR CACHESIZE , rVAR COMPRESSION ,
rVAR_DATA , rVAR DATASPEC , rVAR DATATYPE , rVAR DIMVARYS , rVAR EXISTENCE , rVAR HYPERDATA ,
rVAR INITIALRECS , rVAR MAXallocREC , rVAR MAXREC , rVAR NAME , rVAR nINDEXENTRIES ,
rVAR nINDEXLEVELS , rVAR nINDEXRECORDS , rVAR NUMallocRECS , rVAR NUMBER , rVAR NUMELEMS ,
rVAR NUMRECS , rVAR PADVALUE , rVAR RECORDS , rVAR RECORDS_RENUMBER , rVAR RECVAR ,
rVAR RESERVEPERCENT , rVAR SEQDATA , rVAR SEQPOS , rVAR SPARSEARRAYS , rVAR SPARSERECORDS ,
rVARs CACHESIZE , rVARs DIMCOUNTS , rVARs DIMINDICES , rVARs DIMINTERVALS , rVARs DIMSIZES ,
rVARs_MAXREC , rVARs NUMDIMS , rVARs RECCOUNT , rVARs RECDATA , rVARs RECINTERVAL ,
rVARs_RECNUMBER , SAVE , SCRATCH CREATE ERROR, SCRATCH DELETE ERROR, SCRATCH READ ERROR,
SCRATCH WRITE ERROR, SELECT , SGI DECODING, SGI ENCODING, SINGLE FILE, SINGLE FILE FORMAT,
SOME ALREADY ALLOCATED, STAGE CACHESIZE , STATUS TEXT , STRING NOT UTF8 ENCODING, STRINGDELIMITER,
SUN DECODING, SUN ENCODING, TOO MANY PARMS, TOO MANY VARS, TRY TO READ NONSTRING DATA,
TT2000_0 STRING_LEN, TT2000_1 STRING_LEN, TT2000_2 STRING_LEN, TT2000_3 STRING_LEN,
TT2000_4 STRING_LEN, TT2000_CDF MAYNEEDUPDATE, TT2000 TIME ERROR, TT2000 USED OUTDATED TABLE,
UNABLE TO PROCESS CDF, UNKNOWN COMPRESSION, UNKNOWN SPARSENESS, UNSUPPORTED OPERATION, VALIDATE ,
VALIDATEFILEoff, VALIDATEFILEon, VAR ALREADY CLOSED, VAR CLOSE ERROR, VAR CREATE ERROR,
VAR DELETE ERROR, VAR EXISTS, VAR NAME TRUNC, VAR OPEN ERROR, VAR READ ERROR, VAR SAVE_ERROR,
VAR_WRITE ERROR, VARIABLE SCOPE, VARY, VAX DECODING, VAX ENCODING, VIRTUAL RECORD_DATA, zENTRY_
zENTRY_DATA , zENTRY DATASPEC , zENTRY DATATYPE , zENTRY EXISTENCE , zENTRY NAME ,
zENTRY NUMELEMS , zENTRY NUMSTRINGS , zENTRY STRINGSDATA , ZLIB COMPRESS ERROR,
ZLIB_UNCOMPRESS_ERROR, zMODEoff, zMODEon1, zMODEon2, zVAR , zVAR ALLOCATEBLOCK ,
zVAR ALLOCATEDFROM , zVAR ALLOCATEDTO , zVAR ALLOCATERECS , zVAR BLOCKINGFACTOR , zVAR CACHESIZE ,
zVAR COMPRESSION , zVAR_DATA , zVAR DATASPEC , zVAR DATATYPE , zVAR DIMCOUNTS , zVAR DIMINDICES ,
zVAR DIMINTERVALS , zVAR DIMSIZES , zVAR DIMVARYS , zVAR EXISTENCE , zVAR HYPERDATA ,
zVAR_INITIALRECS , zVAR MAXallocREC , zVAR MAXREC , zVAR NAME , zVAR nINDEXENTRIES ,
zVAR nINDEXLEVELS , zVAR nINDEXRECORDS , zVAR NUMallocRECS , zVAR NUMBER , zVAR NUMDIMS ,
zVAR NUMELEMS , zVAR NUMRECS , zVAR PADVALUE , zVAR RECCOUNT , zVAR RECINTERVAL , zVAR RECNUMBER ,
zVAR_RECORDS , zVAR RECORDS_RENUMBER , zVAR RECVAR , zVAR RESERVEPERCENT , zVAR SEQDATA ,
zVAR_SEQPOS , zVAR SPARSEARRAYS , zVAR_SPARSERECORDS , zVARs CACHESIZE , zVARs_MAXREC ,
zVARs_RECDATA , zVARs_RECNUMBER _

Constructor Summary

Constructors
Constructor and Description
Epoch ()

Method Summary

Methods

Modifier and Type	Method and Description
static long[]	breakdown (double epoch) Breaks an EPOCH value down into its component parts.
static long[][]	breakdown (double[] epochs) Breaks an array of EPOCH values down into its component parts.
static double[]	compute (long[] year, long[] month, long[] day) Computes an array of EPOCH values based on their component parts.
static double[]	compute (long[] year, long[] month, long[] day, long[] hour) Computes an array of EPOCH values based on their component parts.
static double[]	compute (long[] year, long[] month, long[] day, long[] hour, long[] minute) Computes an array of EPOCH values based on their component parts.
static double[]	compute (long[] year, long[] month, long[] day, long[] hour, long[] minute, long[] second) Computes an array of EPOCH values based on their component parts.
static double[]	compute (long[] year, long[] month, long[] day, long[] hour, long[] minute, long[] second, long[] msec) Computes an array of EPOCH values based on their component parts.
static double	compute (long year, long month, long day, long hour, long minute, long second, long msec) Computes an EPOCH value based on its component parts.
static java.lang.String	encode (double epoch) Converts an EPOCH value into a readable date/time string.
static java.lang.String[]	encode (double[] epochs) Converts an array of EPOCH values into an array of readable date/time strings.
static java.lang.String	encode1 (double epoch) Converts an EPOCH value into a readable date/time string.
static java.lang.String[]	encode1 (double[] epochs) Converts an array EPOCH values into readable date/time strings.
static java.lang.String	encode2 (double epoch) Converts an EPOCH value into a readable date/time string.
static java.lang.String[]	encode2 (double[] epochs) Converts an array of EPOCH values into readable date/time strings.
static java.lang.String	encode3 (double epoch) Converts an EPOCH value into a readable date/time string.
static java.lang.String[]	encode3 (double[] epochs) Converts an array of EPOCH values into readable date/time strings.
static java.lang.String	encode4 (double epoch) Converts an EPOCH value into a readable date/time, ISO8601 string.
static java.lang.String[]	encode4 (double[] epochs) Converts an array of EPOCH values into readable date/time, ISO8601 strings.
static java.lang.String	encodex (double epoch, java.lang.String formatString) Converts an EPOCH value into a readable date/time string using the specified format.
static double	EpochtoUnixTime (double epoch) Converts an EPOCH value to a unix time of a double value (seconds from 1970-01-01 00:00:00 UTC).
static double[]	EpochtoUnixTime (double[] epoch) Converts an array of EPOCH values to an array of unix time of a double value (seconds from 1970-01-01 00:00:00 UTC).
static double	parse (java.lang.String inString) This function parses an input date/time string and returns an EPOCH value.
static double[]	parse (java.lang.String[] inStrings) This function parses an array of date/time strings and returns an array of EPOCH values.

static double	parse1 (java.lang.String inString) This function parses an input date/time string and returns an EPOCH value.
static double[]	parse1 (java.lang.String[] inStrings) This function parses an array of date/time strings and returns an EPOCH value array.
static double	parse2 (java.lang.String inString) This function parses an input date/time string and returns an EPOCH value.
static double[]	parse2 (java.lang.String[] inStrings) This function parses an array of date/time strings and returns an EPOCH value array.
static double	parse3 (java.lang.String inString) This function parses an input date/time string and returns an EPOCH value.
static double[]	parse3 (java.lang.String[] inStrings) This function parses an array of date/time strings and returns an EPOCH value array.
static double	parse4 (java.lang.String inString) This function parses an input date/time string and returns an EPOCH value.
static double[]	parse4 (java.lang.String[] inStrings) This function parses an array of date/time strings and returns an EPOCH value array.
static java.lang.String	toEncode (double epoch) Converts an EPOCH value into a readable date/time string.
static java.lang.String[]	toEncode (double[] epochs) Converts an array of EPOCH values into readable date/time strings.
static java.lang.String[]	toEncode (double[] epochs, int style) Converts an array of EPOCH values into readable date/time strings.
static java.lang.String	toEncode (double epoch, int style) Converts an EPOCH value into a readable date/time string.
static java.lang.Object	toEncode (java.lang.Object epoch) Converts an EPOCH object into a scalar or array(s) of readable date/time string(s).
static double	toParse (java.lang.String inString) This function parses a date/time string and returns an EPOCH value.
static double[]	toParse (java.lang.String[] inStrings) This function parses an array of date/time strings and returns an array of EPOCH values.
static double	UnixTimeToEpoch (double unixTime) Converts a Unix time value (seconds from 1970-01-01 00:00:00 UTC) to an EPOCH time.
static double[]	UnixTimeToEpoch (double[] unixTimes) Converts an array of Unix time values (seconds from 1970-01-01 00:00:00 UTC) to an array of EPOCH times.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

Epoch

public Epoch()

Method Detail

toParse

```
public static double[] toParse(java.lang.String[] inStrings)
                        throws CDFException
```

This function parses an array of date/time strings and returns an array of EPOCH values. The string format must be exactly as one of the followings (which are made from the corresponding encoding methods).

Style 0 -
Format: dd-mmm-yyyy hh:mm:ss.mmm
Examples: 1-Apr-1990 03:05:02.000
 10-Oct-1993 23:45:49.999

Style 1 -
Format: yyyymmdd.tttttttt
Examples: 19900401.3658893
 19931010.0000000

Style 2 -
Format: yyyymmddhhmmss
Examples: 19900401030502
 19931010234549

Style 3 -
Format: yyyy-mm-ddThh:mm:ss.mmmZ
Examples: 1990-04-01T03:05:02.000Z
 1993-10-10T23:45:49.999Z

Style 4 -
Format: yyyy-mm-ddThh:mm:ss.mmm
Examples: 1990-04-01T03:05:02.000
 1993-10-10T23:45:49.999

Parameters:

inStrings - the epochs in string representation

Returns:

the values of the epoch represented by inStrings or null if null or an empty input array is detected

Throws:

CDFException - if a bad epoch value is passed in inStrings

toParse

```
public static double toParse(java.lang.String inString)
                        throws CDFException
```

This function parses a date/time string and returns an EPOCH value. The string format must be exactly as one of the followings (which are made from the corresponding encoding methods).

Style 0 -
Format: dd-mmm-yyyy hh:mm:ss.mmm
Examples: 1-Apr-1990 03:05:02.000
 10-Oct-1993 23:45:49.999

Style 1 -
Format: yyyymmdd.tttttttt
Examples: 19900401.3658893
 19931010.0000000

Style 2 -
Format: yyyymmddhhmmss
Examples: 19900401030502
 19931010234549

```
Style 3 -
Format:   yyyy-mm-ddThh:mm:ss.mmmZ
Examples: 1990-04-01T03:05:02.000Z
          1993-10-10T23:45:49.999Z

Style 4 -
Format:   yyyy-mm-ddThh:mm:ss.mmm
Examples: 1990-04-01T03:05:02.000
          1993-10-10T23:45:49.999
```

Parameters:

`inString` - the epoch in string representation

Returns:

the value of the epoch represented by `inStrings` or null if null or an empty input array is detected

Throws:

`CDFException` - if a bad epoch value is passed in `inStrings`

parse

```
public static double parse(java.lang.String inString)
                        throws CDFException
```

This function parses an input date/time string and returns an EPOCH value. The string format must be exactly as shown below. Month abbreviations may be in any case and are always the first three letters of the month.

```
Format:   dd-mmm-yyyy hh:mm:ss.mmm
Examples: 1-Apr-1990 03:05:02.000
          10-Oct-1993 23:45:49.999
```

The expected format is the same as that produced by `encode`.

Parameters:

`inString` - the epoch in string representation

Returns:

the value of the epoch represented by `inString`

Throws:

`CDFException` - if a bad epoch value is passed in `inString`

parse

```
public static double[] parse(java.lang.String[] inStrings)
                        throws CDFException
```

This function parses an array of date/time strings and returns an array of EPOCH values. The string format must be exactly as shown below. Month abbreviations may be in any case and are always the first three letters of the month.

```
Format:   dd-mmm-yyyy hh:mm:ss.mmm
Examples: 1-Apr-1990 03:05:02.000
          10-Oct-1993 23:45:49.999
```

The expected format is the same as that produced by `encode`.

Parameters:

`inStrings`

- the epochs in string representation

Returns:

the values of the epoch represented by inStrings or null if null or an empty input array is detected

Throws:

`CDFException` - if a bad epoch value is passed in inStrings

parse1

```
public static double parse1(java.lang.String inString)
    throws CDFException
```

This function parses an input date/time string and returns an EPOCH value. The format must be exactly as shown below. Note that if there are less than 7 digits after the decimal point, zeros (0's) are assumed for the missing digits.

```
Format:      yyyyymmdd.tttttttt
Examples:    19950508.00000000
             19671231.58          (== 19671213.58000000)
```

The expected format is the same as that produced by encode1.

Parameters:

inString - the epoch in string representation

Returns:

the value of the epoch represented by inString

Throws:

`CDFException` - if a bad epoch value is passed in inString

parse1

```
public static double[] parse1(java.lang.String[] inStrings)
    throws CDFException
```

This function parses an array of date/time strings and returns an EPOCH value array. The format must be exactly as shown below. Note that if there are less than 7 digits after the decimal point, zeros (0's) are assumed for the missing digits.

```
Format:      yyyyymmdd.tttttttt
Examples:    19950508.00000000
             19671231.58          (== 19671213.58000000)
```

The expected format is the same as that produced by encode1.

Parameters:

inStrings - the epoch array in string representation

Returns:

the value array of the epoch represented by inString

Throws:

`CDFException` - if a bad epoch value is passed in inString

parse2

```
public static double parse2(java.lang.String inString)
    throws CDFException
```

This function parses an input date/time string and returns an EPOCH value. The format must be exactly as shown below.

```
Format:      yyyyymmddhhmmss
Examples:    199505080000000
            19671231235959
```

The expected format is the same as that produced by encode2.

Parameters:

inString - the epoch in string representation

Returns:

the value of the epoch represented by inString

Throws:

CDFException - if a bad epoch value is passed in inString

parse2

```
public static double[] parse2(java.lang.String[] inStrings)
    throws CDFException
```

This function parses an array of date/time strings and returns an EPOCH value array. The format must be exactly as shown below.

```
Format:      yyyyymmddhhmmss
Examples:    199505080000000
            19671231235959
```

The expected format is the same as that produced by encode2.

Parameters:

inStrings - the epoch array in string representation

Returns:

the value array of the epoch represented by inString

Throws:

CDFException - if a bad epoch value is passed in inString

parse3

```
public static double parse3(java.lang.String inString)
    throws CDFException
```

This function parses an input date/time string and returns an EPOCH value. The format must be exactly as shown below.

```
Format:      yyyy-mm-ddThh:mm:ss.cccZ
Examples:    1990-04-01T03:05:02.000Z
            1993-10-10T23:45:49.999Z
```

The expected format is the same as that produced by encode3.

Parameters:

inString - the epoch in string representation

Returns:

the value of the epoch represented by inString

Throws:

CDFException - if a bad epoch value is passed in inString

parse3

```
public static double[] parse3(java.lang.String[] inStrings)
    throws CDFException
```

This function parses an array of date/time strings and returns an EPOCH value array. The format must be exactly as shown below.

```
Format:      yyyy-mm-ddThh:mm:ss.cccZ
Examples:    1990-04-01T03:05:02.000Z
            1993-10-10T23:45:49.999Z
```

The expected format is the same as that produced by encode3.

Parameters:

inStrings - the epoch array in string representation

Returns:

the value array of the epoch represented by inString

Throws:

CDFException - if a bad epoch value is passed in inString

parse4

```
public static double parse4(java.lang.String inString)
    throws CDFException
```

This function parses an input date/time string and returns an EPOCH value. The format must be an ISO8601 and is exactly as shown below.

```
Format:      yyyy-mm-ddThh:mm:ss.ccc
Examples:    1990-04-01T03:05:02.000
            1993-10-10T23:45:49.999
```

The expected format is the same as that produced by encode3.

Parameters:

inString - the epoch in string representation

Returns:

the value of the epoch represented by inString

Throws:

CDFException - if a bad epoch value is passed in inString

parse4

```
public static double[] parse4(java.lang.String[] inStrings)
    throws CDFException
```

This function parses an array of date/time strings and returns an EPOCH value array. The format must be an ISO8601 and is exactly as shown below.

```
Format:      yyyy-mm-ddThh:mm:ss.ccc
Examples:    1990-04-01T03:05:02.000
              1993-10-10T23:45:49.999
```

The expected format is the same as that produced by encode3.

Parameters:

inStrings - the epoch array in string representation

Returns:

the value array of the epoch represented by inString

Throws:

CDFException - if a bad epoch value is passed in inString

toEncode

```
public static java.lang.String toEncode(double epoch,
                                         int style)
```

Converts an EPOCH value into a readable date/time string. Depending on the encoding style, it can present the string to one of the following forms:

```
For style 0:
Format:      dd-mmm-yyyy hh:mm:ss.ccc
Examples:    01-Apr-1990 03:05:02.000
              10-Oct-1993 23:45:49.999

For style 1:
Format:      yyyymmdd.tttttttt
Examples:    19950508.0000000
              19671231.58          (== 19671213.5800000)

For style 2:
Format:      yyyymmddhhmmss
Examples:    19900401030502
              19931010234549

For style 3:
Format:      yyyymmddThh:mm:ss.cccZ
Examples:    19900401T03:05:02.000Z
              19931010T23:45:49.999Z

For style 4:
Format:      yyyymmddThh:mm:ss.ccc
Examples:    19900401T03:05:02.000
              19931010T23:45:49.999
The default style if the style is invalid.
```

Parameters:

epoch - the epoch value
style - the encoding style

Returns:

A string representation of the epoch

toEncode

```
public static java.lang.String[] toEncode(double[] epochs,
                                     int style)
```

Converts an array of EPOCH values into readable date/time strings. Depending on the encoding style, it can present the string to one of the following forms:

```
For style 0:
Format:    dd-mmm-yyyy hh:mm:ss.ccc
Examples:  01-Apr-1990 03:05:02.000
           10-Oct-1993 23:45:49.999

For style 1:
Format:    yyyyymmdd.tttttttt
Examples:  19950508.0000000
           19671231.58          (== 19671213.58000000)

For style 2:
Format:    yyyyymmddhhmmss
Examples:  19900401030502
           19931010234549

For style 3:
Format:    yyyyymmddThh:mm:ss.cccZ
Examples:  19900401T03:05:02.000Z
           19931010T23:45:49.999Z

For style 4:
Format:    yyyyymmddThh:mm:ss.ccc
Examples:  19900401T03:05:02.000
           19931010T23:45:49.999
```

Parameters:

- epochs - the epoch values
- style - the encoding style

Returns:

An array of strings representation of the epochs If the style is invalid, it will return the string "99991231T23:59:59.999"

toEncode

```
public static java.lang.Object toEncode(java.lang.Object epoch)
```

Converts an EPOCH object into a scalar or array(s) of readable date/time string(s). Each string is presented in the following ISO 8601 form:

```
Format:    yyyyymmddThh:mm:ss.ccc
Examples:  19900401T03:05:02.000
           19931010T23:45:49.999
```

Parameters:

- epoch - the epoch object

Returns:

A string or array(s) of strings representation of the epoch

toEncode

```
public static java.lang.String toEncode(double epoch)
```

Converts an EPOCH value into a readable date/time string. It present the string to the following ISO 8601 form:

Format: yyyyymmddThh:mm:ss.ccc
Examples: 19900401T03:05:02.000
 19931010T23:45:49.999

Parameters:

epoch - the epoch value

Returns:

A string representation of the epoch

toEncode

```
public static java.lang.String[] toEncode(double[] epochs)
```

Converts an array of EPOCH values into readable date/time strings. The strings are of the following ISO 8601 form:

Format: yyyyymmddThh:mm:ss.ccc
Examples: 19900401T03:05:02.000
 19931010T23:45:49.999

Parameters:

epochs - the epoch values

Returns:

A array of strings representation of the epochs

EpochtoUnixTime

```
public static double EpochtoUnixTime(double epoch)
```

Converts an EPOCH value to a unix time of a double value (seconds from 1970-01-01 00:00:00 UTC). Resolution to milliseconds will be made in unix time at its fraction part.

Parameters:

epoch - the epoch value

Returns:

A unix time value

EpochtoUnixTime

```
public static double[] EpochtoUnixTime(double[] epoch)
```

Converts an array of EPOCH values to an array of unix time of a double value (seconds from 1970-01-01 00:00:00 UTC). Resolution to milliseconds will be made in unix time at its fraction part.

Parameters:

epoch - the epoch values

Returns:

Array of unix time values

UnixTimetoEpoch

```
public static double UnixTimetoEpoch(double unixTime)
```

Converts a Unix time value (seconds from 1970-01-01 00:00:00 UTC) to an EPOCH time. The Unix time can have a time resolution of milliseconds (0-999) or microseconds (0-999999) at its fraction part. Only resolution to milliseconds in unix time will be used.

Parameters:

unixTime - the unix time value

Returns:

An epoch value

UnixTimetoEpoch

```
public static double[] UnixTimetoEpoch(double[] unixTimes)
```

Converts an array of Unix time values (seconds from 1970-01-01 00:00:00 UTC) to an array of EPOCH times. The Unix time can have a time resolution of milliseconds (0-999) or microseconds (0-999999) at its fraction part. Only resolution to milliseconds in unix time will be used.

Parameters:

unixTimes - the unix time values

Returns:

An array of epoch values

encode

```
public static java.lang.String encode(double epoch)
```

Converts an EPOCH value into a readable date/time string.

```
Format:      dd-mmm-yyyy hh:mm:ss.ccc
Examples:    01-Apr-1990 03:05:02.000
             10-Oct-1993 23:45:49.999
```

This format is the same as that expected by parse.

Parameters:

epoch - the epoch value

Returns:

A string representation of the epoch

encode

```
public static java.lang.String[] encode(double[] epochs)
```

Converts an array of EPOCH values into an array of readable date/time strings.

Format: dd-mmm-yyyy hh:mm:ss.ccc
Examples: 01-Apr-1990 03:05:02.000
 10-Oct-1993 23:45:49.999

This format is the same as that expected by parse.

Parameters:

epochs - the epoch values

Returns:

Strings representing the epochs or null if null or an empty input array is detected

encode1

```
public static java.lang.String encode1(double epoch)
```

Converts an EPOCH value into a readable date/time string.

Format: yyyyymmdd.ttttttt
Examples: 19900401.3658893
 19611231.0000000

This format is the same as that expected by parse1.

Parameters:

epoch - the epoch value

Returns:

A string representation of the epoch

encode1

```
public static java.lang.String[] encode1(double[] epochs)
```

Converts an array EPOCH values into readable date/time strings.

Format: yyyyymmdd.ttttttt
Examples: 19900401.3658893
 19611231.0000000

This format is the same as that expected by parse1.

Parameters:

epochs - the epoch values

Returns:

Array of strings representation of the epochs

encode2

```
public static java.lang.String encode2(double epoch)
```

Converts an EPOCH value into a readable date/time string.

Format: yyyyymmddhhmmss
Examples: 19900401235959

19611231000000

This format is the same as that expected by parse2.

Parameters:

epoch - the epoch value

Returns:

A string representation of the epoch

encode2

```
public static java.lang.String[] encode2(double[] epochs)
```

Converts an array of EPOCH values into readable date/time strings.

Format: yyyymmddhhmmss
Examples: 19900401235959
 19611231000000

This format is the same as that expected by parse2.

Parameters:

epochs - the epoch values

Returns:

A array of strings representation of the epochs

encode3

```
public static java.lang.String encode3(double epoch)
```

Converts an EPOCH value into a readable date/time string.

Format: yyyy-mm-ddThh:mm:ss.cccZ
Examples: 1990-04-01T03:05:02.000Z
 1993-10-10T23:45:49.999Z

This format is the same as that expected by parse3.

Parameters:

epoch - the epoch value

Returns:

A string representation of the epoch

encode3

```
public static java.lang.String[] encode3(double[] epochs)
```

Converts an array of EPOCH values into readable date/time strings.

Format: yyyy-mm-ddThh:mm:ss.cccZ
Examples: 1990-04-01T03:05:02.000Z
 1993-10-10T23:45:49.999Z

This format is the same as that expected by parse3.

Parameters:

epochs - the epoch values

Returns:

A array of strings representation of the epochs

encode4

```
public static java.lang.String encode4(double epoch)
```

Converts an EPOCH value into a readable date/time, ISO8601 string.

Format: yyyy-mm-ddThh:mm:ss.ccc
Examples: 1990-04-01T03:05:02.000
 1993-10-10T23:45:49.999

This format is the same as that expected by parse3.

Parameters:

epoch - the epoch value

Returns:

A string representation of the epoch

encode4

```
public static java.lang.String[] encode4(double[] epochs)
```

Converts an array of EPOCH values into readable date/time, ISO8601 strings.

Format: yyyy-mm-ddThh:mm:ss.ccc
Examples: 1990-04-01T03:05:02.000
 1993-10-10T23:45:49.999

This format is the same as that expected by parse3.

Parameters:

epochs - the epoch values

Returns:

A array of strings representation of the epochs

encodex

```
public static java.lang.String encodex(double epoch,  
                                       java.lang.String formatString)
```

Converts an EPOCH value into a readable date/time string using the specified format. See the C Reference Manual section 8.7 for details

Parameters:

epoch - the epoch value

`formatString` - a string representing the desired format of the epoch

Returns:

A string representation of the epoch according to `formatString`

compute

```
public static double compute(long year,
                             long month,
                             long day,
                             long hour,
                             long minute,
                             long second,
                             long msec)
    throws CDFException
```

Computes an EPOCH value based on its component parts.

Parameters:

- `year` - the year
- `month` - the month
- `day` - the day
- `hour` - the hour
- `minute` - the minute
- `second` - the second
- `msec` - the millisecond

Returns:

the epoch value

Throws:

`CDFException` - an `ILLEGAL_EPOCH_FIELD` if an illegal component value is detected.

compute

```
public static double[] compute(long[] year,
                               long[] month,
                               long[] day)
    throws CDFException
```

Computes an array of EPOCH values based on their component parts.

Parameters:

- `year` - the year array
- `month` - the month array
- `day` - the day array

Returns:

an array of epoch values or null if an invalid input array(s) is detected.

Throws:

`CDFException` - an `ILLEGAL_EPOCH_FIELD` if an illegal component value is detected.

compute

```
public static double[] compute(long[] year,
                               long[] month,
                               long[] day,
                               long[] hour)
    throws CDFException
```

Computes an array of EPOCH values based on their component parts.

Parameters:

- year - the year array
- month - the month array
- day - the day array
- hour - the hour array

Returns:

an array of epoch values or null if an invalid input array(s) is detected

Throws:

CDFException - an ILLEGAL_EPOCH_FIELD if an illegal component value is detected.

compute

```
public static double[] compute(long[] year,
                               long[] month,
                               long[] day,
                               long[] hour,
                               long[] minute)
    throws CDFException
```

Computes an array of EPOCH values based on their component parts.

Parameters:

- year - the year array
- month - the month array
- day - the day array
- hour - the hour array
- minute - the minute array

Returns:

an array of epoch values or null if an invalid input array(s) is detected

Throws:

CDFException - an ILLEGAL_EPOCH_FIELD if an illegal component value is detected.

compute

```
public static double[] compute(long[] year,
                               long[] month,
                               long[] day,
                               long[] hour,
                               long[] minute,
```

```
long[] second)
    throws CDFException
```

Computes an array of EPOCH values based on their component parts.

Parameters:

- year - the year array
- month - the month array
- day - the day array
- hour - the hour array
- minute - the minute array
- second - the second array

Returns:

an array of epoch values or null if an invalid input array(s) is detected

Throws:

CDFException - an ILLEGAL_EPOCH_FIELD if an illegal component value is detected.

compute

```
public static double[] compute(long[] year,
                               long[] month,
                               long[] day,
                               long[] hour,
                               long[] minute,
                               long[] second,
                               long[] msec)
    throws CDFException
```

Computes an array of EPOCH values based on their component parts.

Parameters:

- year - the year array
- month - the month array
- day - the day array
- hour - the hour array
- minute - the minute array
- second - the second array
- msec - the millisecond array

Returns:

an array of epoch values or null if an invalid input array(s) is detected

Throws:

CDFException - an ILLEGAL_EPOCH_FIELD if an illegal component value is detected.

breakdown

```
public static long[] breakdown(double epoch)
```

Breaks an EPOCH value down into its component parts.

Parameters:

epoch - the epoch value to break down

Returns:

an array containing the epoch parts:

Index	Part
0	year
1	month
2	day
3	hour
4	minute
5	second
6	msec

breakdown

```
public static long[][] breakdown(double[] epochs)
```

Breaks an array of EPOCH values down into its component parts.

Parameters:

epochs - the array of epoch values to break down

Returns:

a 2-dimensional array, the first element being the row, while the second element containing the epoch parts, as follwos:

Index	Part
0	year
1	month
2	day
3	hour
4	minute
5	second
6	msec

or null if null or an empty input array is detected

gsfc.nssdc.cdf.util

Class Epoch16

java.lang.Object
gsfc.nssdc.cdf.util.Epoch16

All Implemented Interfaces:

CDFConstants

```
public class Epoch16
extends java.lang.Object
implements CDFConstants
```

This class contains the handy utility routines (methods) called by the CDF applications to handle epoch data of CDF's CDF_EPOCH16 data type.

Version:

1.0 Example:

```
// Get the time, down to picoseconds, for Aug 5, 1990 at 5:0:0.0.0.0
double[] epoch16 = new double[2];
double ep = Epoch16.compute(1990, 8, 5, 5, 0, 0, 0, 0, 0, 0, epoch16);
//Get the year, month, day, hour, minutes, seconds, milliseconds,
// microseconds, nanoseconds and picoseconds for epoch16
long[] times = Epoch16.breakdown(epoch16);
for (int i=0;i<times.length;i++)
    System.out.print(times[i]+" ");
System.out.println();
// Printout the epoch in various formats
System.out.println(Epoch16.encode(epoch16));
System.out.println(Epoch16.encode1(epoch16));
System.out.println(Epoch16.encode2(epoch16));
System.out.println(Epoch16.encode3(epoch16));
System.out.println(Epoch16.encode4(epoch16));
// Print out the date using format
String format = "<month> <dom.02>, <year> at <hour>:<min>";
System.out.println(Epoch16.encodex(epoch16,format));
```

Field Summary

Fields inherited from interface gsfc.nssdc.cdf.CDFConstants

AHUFF COMPRESSION, ALPHAOSF1 DECODING, ALPHAOSF1 ENCODING, ALPHAVMSd DECODING, ALPHAVMSd ENCODING, ALPHAVMSg DECODING, ALPHAVMSg ENCODING, ALPHAVMSi DECODING, ALPHAVMSi ENCODING, ARM BIG DECODING, ARM BIG ENCODING, ARM LITTLE DECODING, ARM LITTLE ENCODING, ATTR, ATTR EXISTENCE, ATTR EXISTS, ATTR MAXgENTRY, ATTR MAXrENTRY, ATTR MAXZENTRY, ATTR NAME, ATTR NAME TRUNC, ATTR NUMBER, ATTR NUMgENTRIES, ATTR NUMrENTRIES, ATTR NUMzENTRIES, ATTR SCOPE, BACKWARD, BACKWARDFILEoff, BACKWARDFILEon, BAD ALLOCATE RECS, BAD ARGUMENT, BAD ATTR NAME, BAD ATTR NUM, BAD BLOCKING FACTOR, BAD CACHE SIZE, BAD CDF EXTENSION, BAD CDF ID, BAD CDF NAME, BAD CDFSTATUS, BAD CHECKSUM, BAD COMPRESSION PARM, BAD DATA TYPE, BAD DECODING, BAD DIM COUNT, BAD DIM INDEX, BAD DIM INTERVAL, BAD DIM SIZE, BAD ENCODING, BAD ENTRY NUM, BAD FNC OR ITEM, BAD FORMAT, BAD INITIAL RECS, BAD MAJORITY, BAD MALLOC, BAD NEGtoPOSfp0 MODE, BAD NUM DIMS, BAD NUM ELEMS, BAD NUM STRINGS, BAD NUM VARS, BAD READONLY MODE, BAD REC COUNT, BAD REC INTERVAL, BAD REC NUM, BAD SCOPE, BAD SCRATCH DIR, BAD SPARSEARRAYS PARM, BAD VAR NAME, BAD VAR NUM, BAD zMODE, BADDATE LEAPSECOND UPDATED, BeginUnixTimeEPOCH, BeginUnixTimeEPOCH16, BLOCKINGFACTOR TOO LARGE, BLOCKINGFACTOR TOO SMALL, BLOCKINGFACTOR TOO SMALL2, CANNOT ALLOCATE RECORDS, CANNOT CHANGE, CANNOT COMPRESS, CANNOT CONVERT WIDECHAR, CANNOT COPY, CANNOT INSERT RECORDS, CANNOT SPARSEARRAYS, CANNOT SPARSEREORDS, CDF, CDF ACCESS, CDF ATTR NAME LEN, CDF ATTR NAME LEN256, CDF BYTE, CDF CACHESIZE, CDF CHAR, CDF CHECKSUM, CDF CLOSE ERROR, CDF COMPRESSION, CDF COPYRIGHT, CDF COPYRIGHT LEN, CDF CREATE ERROR, CDF DECODING, CDF DELETE ERROR, CDF DOUBLE, CDF ENCODING, CDF EPOCH, CDF EPOCH16, CDF EXISTS, CDF FLOAT, CDF FORMAT, CDF INCREMENT, CDF INFO, CDF INTT,

CDF INT2, CDF INT4, CDF INT8, CDF INTERNAL_ERROR, CDF LEAPSECONDLASTUPDATED, CDF MAJORITY, CDF MAX DIMS, CDF MAX PARMS, CDF MIN DIMS, CDF NAME, CDF NAME TRUNC, CDF NEGtoPOSfp0_MODE, CDF NUMATTRS, CDF NUMgATTRS, CDF NUMrVARS, CDF NUMvATTRS, CDF NUMzVARS, CDF OK, CDF OPEN_ERROR, CDF PATHNAME_LEN, CDF READ_ERROR, CDF READONLY_MODE, CDF REAL4, CDF REAL8, CDF RELEASE, CDF SAVE_ERROR, CDF SCRATCHDIR, CDF STATUS, CDF STATUSTEXT_LEN, CDF TIME TT2000, CDF UCHAR, CDF UINT1, CDF UINT2, CDF UINT4, CDF VAR NAME_LEN, CDF VAR NAME_LEN256, CDF_VERSION, CDF_WARN, CDF WRITE_ERROR, CDF zMODE, CDFwithSTATS, CHECKSUM, CHECKSUM_ERROR, CHECKSUM NOT ALLOWED, CLOSE, COLUMN_MAJOR, COMPRESS_CACHESIZE, COMPRESSION_ERROR, CONFIRM, CORRUPTED V2_CDF, CORRUPTED V3_CDF, CREATE, CURgENTRY_EXISTENCE, CURrENTRY_EXISTENCE, CURzENTRY_EXISTENCE, DATATYPE MISMATCH, DATATYPE SIZE, DECOMPRESSION_ERROR, DECSTATION_DECODING, DECSTATION_ENCODING, DEFAULT_BYTE_PADVALUE, DEFAULT_CHAR_PADVALUE, DEFAULT_DOUBLE_PADVALUE, DEFAULT_EPOCH_PADVALUE, DEFAULT_EPOCH16_PADVALUE, DEFAULT_FLOAT_PADVALUE, DEFAULT_INT1_PADVALUE, DEFAULT_INT2_PADVALUE, DEFAULT_INT4_PADVALUE, DEFAULT_INT8_PADVALUE, DEFAULT_REAL4_PADVALUE, DEFAULT_REAL8_PADVALUE, DEFAULT TT2000_PADVALUE, DEFAULT_UCHAR_PADVALUE, DEFAULT_UINT1_PADVALUE, DEFAULT_UINT2_PADVALUE, DEFAULT_UINT4_PADVALUE, DELETE, DID NOT COMPRESS, EMPTY_COMPRESSED_CDF, END OF VAR, EPOCH_STRING_LEN, EPOCH_STRING_LEN_EXTEND, EPOCH1_STRING_LEN, EPOCH1_STRING_LEN_EXTEND, EPOCH2_STRING_LEN, EPOCH2_STRING_LEN_EXTEND, EPOCH3_STRING_LEN, EPOCH3_STRING_LEN_EXTEND, EPOCH4_STRING_LEN, EPOCH4_STRING_LEN_EXTEND, EPOCHx_FORMAT_MAX, EPOCHx_STRING_MAX, FILLED TT2000_VALUE, FORCED_PARAMETER, FUNCTION NOT SUPPORTED, gENTRY, gENTRY_DATA, gENTRY_DATASPEC, gENTRY_DATATYPE, gENTRY_EXISTENCE, gENTRY_NUMELEMS, GET, GETCDFCHECKSUM, GETCDFFILEBACKWARD, GETCDFVALIDATE, GETLEAPSECONDSENVVAR, GLOBAL_SCOPE, GZIP_COMPRESSION, HOST_DECODING, HOST_ENCODING, HP_DECODING, HP_ENCODING, HUFF_COMPRESSION, IA64VMSd_DECODING, IA64VMSd_ENCODING, IA64VMSg_DECODING, IA64VMSg_ENCODING, IA64VMSi_DECODING, IA64VMSi_ENCODING, IBM_PC_OVERFLOW, IBMPC_DECODING, IBMPC_ENCODING, IBMRs_DECODING, IBMRs_ENCODING, ILLEGAL_EPOCH_FIELD, ILLEGAL_EPOCH_VALUE, ILLEGAL_FOR_SCOPE, ILLEGAL_IN_zMODE, ILLEGAL_ON_V1_CDF, ILLEGAL_TT2000_VALUE, IS_A_NETCDF, LIB_COPYRIGHT, LIB_INCREMENT, LIB_RELEASE, LIB_subINCREMENT, LIB_VERSION, MAC_DECODING, MAC_ENCODING, MD5_CHECKSUM, MULTI_FILE, MULTI_FILE_FORMAT, NA_FOR_VARIABLE, NEGATIVE_FP_ZERO, NEGtoPOSfp0off, NEGtoPOSfp0on, NETWORK_DECODING, NETWORK_ENCODING, Next_DECODING, Next_ENCODING, NO_ATTR_SELECTED, NO_CDF_SELECTED, NO_CHECKSUM, NO_COMPRESSION, NO_DELETE_ACCESS, NO_ENTRY_SELECTED, NO_MORE_ACCESS, NO_PADVALUE_SPECIFIED, NO_SPARSEARRAYS, NO_SPARSERECORDS, NO_STATUS_SELECTED, NO_SUCH_ATTR, NO_SUCH_CDF, NO_SUCH_ENTRY, NO_SUCH_RECORD, NO_SUCH_VAR, NO_VAR_SELECTED, NO_VARS_IN_CDF, NO_WRITE_ACCESS, NONE_CHECKSUM, NOT_A_CDF, NOT_A_CDF_OR_NOT_SUPPORTED, NOVARY, NULL_OPEN, OPTIMAL_ENCODING_TREES, OTHER_CHECKSUM, PAD_SPARSERECORDS, PPC_DECODING, PPC_ENCODING, PRECEDING_RECORDS_ALLOCATED, PREV_SPARSERECORDS, PUT, READ_ONLY_DISTRIBUTION, READ_ONLY_MODE, READONLYoff, READONLYon, rENTRY, rENTRY_DATA, rENTRY_DATASPEC, rENTRY_DATATYPE, rENTRY_EXISTENCE, rENTRY_NAME, rENTRY_NUMELEMS, rENTRY_NUMSTRINGS, rENTRY_STRINGSDATA, RLE_COMPRESSION, RLE_OF_ZEROS, ROW_MAJOR, rVAR, rVAR_ALLOCATEBLOCK, rVAR_ALLOCATEDFROM, rVAR_ALLOCATEDTO, rVAR_ALLOCATERECS, rVAR_BLOCKINGFACTOR, rVAR_CACHESIZE, rVAR_COMPRESSION, rVAR_DATA, rVAR_DATASPEC, rVAR_DATATYPE, rVAR_DIMVARYS, rVAR_EXISTENCE, rVAR_HYPERDATA, rVAR_INITIALRECS, rVAR_MAXallocREC, rVAR_MAXREC, rVAR_NAME, rVAR_nINDEXENTRIES, rVAR_nINDEXLEVELS, rVAR_nINDEXRECORDS, rVAR_NUMallocRECS, rVAR_NUMBER, rVAR_NUMELEMS, rVAR_NUMRECS, rVAR_PADVALUE, rVAR_RECORDS, rVAR_RECORDS_RENUMBER, rVAR_RECVAR, rVAR_RESERVEPERCENT, rVAR_SEQDATA, rVAR_SEQPOS, rVAR_SPARSEARRAYS, rVAR_SPARSERECORDS, rVARs_CACHESIZE, rVARs_DIMCOUNTS, rVARs_DIMINDICES, rVARs_DIMINTERVALS, rVARs_DIMSIZES, rVARs_MAXREC, rVARs_NUMDIMS, rVARs_RECCOUNT, rVARs_RECDATA, rVARs_RECINTERVAL, rVARs_RECNUMBER, SAVE, SCRATCH_CREATE_ERROR, SCRATCH_DELETE_ERROR, SCRATCH_READ_ERROR, SCRATCH_WRITE_ERROR, SELECT, SGI_DECODING, SGI_ENCODING, SINGLE_FILE, SINGLE_FILE_FORMAT, SOME_ALREADY_ALLOCATED, STAGE_CACHESIZE, STATUS_TEXT, STRING_NOT_UTF8_ENCODING, STRINGDELIMITER, SUN_DECODING, SUN_ENCODING, TOO_MANY_PARMS, TOO_MANY_VARS, TRY_TO_READ_NONSTRING_DATA, TT2000_0_STRING_LEN, TT2000_1_STRING_LEN, TT2000_2_STRING_LEN, TT2000_3_STRING_LEN, TT2000_4_STRING_LEN, TT2000_CDF_MAYNEEDUPDATE, TT2000_TIME_ERROR, TT2000_USED_OUTDATED_TABLE, UNABLE_TO_PROCESS_CDF, UNKNOWN_COMPRESSION, UNKNOWN_SPARSENESS, UNSUPPORTED_OPERATION, VALIDATE, VALIDATEFileoff, VALIDATEFileon, VAR_ALREADY_CLOSED, VAR_CLOSE_ERROR, VAR_CREATE_ERROR, VAR_DELETE_ERROR, VAR_EXISTS, VAR_NAME_TRUNC, VAR_OPEN_ERROR, VAR_READ_ERROR, VAR_SAVE_ERROR, VAR_WRITE_ERROR, VARIABLE_SCOPE, VARY, VAX_DECODING, VAX_ENCODING, VIRTUAL_RECORD_DATA, zENTRY, zENTRY_DATA, zENTRY_DATASPEC, zENTRY_DATATYPE, zENTRY_EXISTENCE, zENTRY_NAME, zENTRY_NUMELEMS, zENTRY_NUMSTRINGS, zENTRY_STRINGSDATA, ZLIB_COMPRESS_ERROR, ZLIB_UNCOMPRESS_ERROR, zMODEoff, zMODEon1, zMODEon2, zVAR, zVAR_ALLOCATEBLOCK, zVAR_ALLOCATEDFROM, zVAR_ALLOCATEDTO, zVAR_ALLOCATERECS, zVAR_BLOCKINGFACTOR, zVAR_CACHESIZE, zVAR_COMPRESSION, zVAR_DATA, zVAR_DATASPEC, zVAR_DATATYPE, zVAR_DIMCOUNTS, zVAR_DIMINDICES, zVAR_DIMINTERVALS, zVAR_DIMSIZES, zVAR_DIMVARYS, zVAR_EXISTENCE, zVAR_HYPERDATA, zVAR_INITIALRECS, zVAR_MAXallocREC, zVAR_MAXREC, zVAR_NAME, zVAR_nINDEXENTRIES, zVAR_nINDEXLEVELS, zVAR_nINDEXRECORDS, zVAR_NUMallocRECS, zVAR_NUMBER, zVAR_NUMDIMS, zVAR_NUMELEMS, zVAR_NUMRECS, zVAR_PADVALUE, zVAR_RECCOUNT, zVAR_RECINTERVAL, zVAR_RECNUMBER, zVAR_RECORDS, zVAR_RECORDS_RENUMBER, zVAR_RECVAR, zVAR_RESERVEPERCENT, zVAR_SEQDATA, zVAR_SEQPOS, zVAR_SPARSEARRAYS, zVAR_SPARSERECORDS, zVARs_CACHESIZE, zVARs_MAXREC, zVARs_RECDATA, zVARs_RECNUMBER

Constructor Summary

Constructors
Constructor and Description
Epoch16()

Method Summary

Methods	
Modifier and Type	Method and Description
static long[]	breakdown (java.lang.Object epoch) Breaks an EPOCH16 value down into its component parts.
static double	compute (long year, long month, long day, long hour, long minute, long second, long msec, long usec, long nsec, long psec, java.lang.Object epoch) Computes an EPOCH16 value based on its component parts.
static java.lang.String	encode (java.lang.Object epoch) Converts an EPOCH16 value into a readable date/time string.
static java.lang.String	encode1 (java.lang.Object epoch) Converts an EPOCH16 value into a readable date/time string.
static java.lang.String	encode2 (java.lang.Object epoch) Converts an EPOCH16 value into a readable date/time string.
static java.lang.String	encode3 (java.lang.Object epoch) Converts an EPOCH16 value into a readable date/time string.
static java.lang.String	encode4 (java.lang.Object epoch) Converts an EPOCH16 value into a readable date/time, ISO8601 string.
static java.lang.String	encodex (java.lang.Object epoch, java.lang.String formatString) Converts an EPOCH16 value into a readable date/time string using the specified format.
static double	Epoch16toUnixTime (double[] epoch) Converts an EPOCH16 value to a unix time of a double value (seconds from 1970-01-01 00:00:00 UTC).
static java.lang.Object	parse (java.lang.String inString) This function parses an input date/time string and returns an EPOCH16 value.
static java.lang.Object	parse1 (java.lang.String inString) This function parses an input date/time string and returns an EPOCH16 value.
static java.lang.Object	parse2 (java.lang.String inString) This function parses an input date/time string and returns an EPOCH16 value.
static java.lang.Object	parse3 (java.lang.String inString) This function parses an input date/time string and returns an EPOCH16 value.
static java.lang.Object	parse4 (java.lang.String inString) This function parses an input date/time, ISO8601 string and returns an EPOCH16 value.
static java.lang.String	toEncode (double[] epoch) Converts an EPOCH object into a scalar or array of readable date/time string.
static java.lang.String	toEncode (double[] epoch, int style) Converts an EPOCH16 value into a readable date/time string.
static java.lang.Object	toEncode (java.lang.Object epoch) Converts an EPOCH object into a scalar or array of readable date/time string.
static java.lang.Object	toEncode (java.lang.Object epoch, long size) Converts an EPOCH object into a scalar or array(s) of readable date/time string.
static double[]	toParse (java.lang.String inString) This function parses a date/time string and returns an EPOCH16 value.
static double[]	UnixTimetoEpoch16 (double unixTime) Converts a unix time of a double value (seconds from 1970-01-01 00:00:00 UTC) to an EPOCH16 value.

Methods inherited from class java.lang.Object
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

Epoch16

public Epoch16()

Method Detail

toParse

public static double[] toParse(java.lang.String inString)
throws CDFException

This function parses a date/time string and returns an EPOCH16 value. The string format must be exactly as one of the followings (which are made from the corresponding encoding methods).

Style 0 -
Format: dd-mmm-yyyy hh:mm:ss.mmm.uuu.nnn.ppp
Examples: 1-Apr-1990 03:05:02.000.000.000.000
10-Oct-1993 23:45:49.999.999.999.999

Style 1 -
Format: yyyymmdd.tttttttttttttttt
Examples: 19900401.365889312345678
19931010.0000000000000000

Style 2 -
Format: yyyymmddhhmmss
Examples: 19900401030502
19931010234549

Style 3 -
Format: yyyy-mm-ddThh:mm:ss.mmm.uuu.nnn.pppZ
Examples: 1990-04-01T03:05:02.000.000.000.000Z
1993-10-10T23:45:49.999.999.999.999Z

Style 4 -
Format: yyyy-mm-ddThh:mm:ss.mmmuuunnnppp
Examples: 1990-04-01T03:05:02.000000000000
1993-10-10T23:45:49.999999999999

Parameters:

inString - the epoch in string representation

Returns:

the value of the epoch represented by inString or null if null or an empty string is detected

Throws:

CDFException - if a bad epoch value is passed in inStrings

parse

public static java.lang.Object parse(java.lang.String inString)
throws CDFException

This function parses an input date/time string and returns an EPOCH16 value. The format must be exactly as shown below. Month abbreviations may be in any case and are always the first three letters of the month.

Format: dd-mmm-yyyy hh:mm:ss.ccc.mmm.nnn.ppp
Examples: 1-Apr-1990 03:05:02.000.000.000.000
10-Oct-1993 23:45:49.999.999.999.999

The expected format is the same as that produced by encode.

Parameters:

inString - the epoch in string representation

Returns:

the value of the epoch represented by inString

Throws:

CDFException - if a bad epoch value is passed in inString

parse1

```
public static java.lang.Object parse1(java.lang.String inString)
                                   throws CDFException
```

This function parses an input date/time string and returns an EPOCH16 value. The format must be exactly as shown below. Note that if there are less than 15 digits after the decimal point, zeros (0's) are assumed for the missing digits.

Format: yyyymmdd.tttttttttttttttt
Examples: 19950508.0000000000000000
19671231.58 (== 19671213.5800000000000000)

The expected format is the same as that produced by encode1.

Parameters:

inString - the epoch in string representation

Returns:

the value of the epoch represented by inString

Throws:

CDFException - if a bad epoch value is passed in inString

parse2

```
public static java.lang.Object parse2(java.lang.String inString)
                                   throws CDFException
```

This function parses an input date/time string and returns an EPOCH16 value. The format must be exactly as shown below.

Format: yyyymmddhhmmss
Examples: 19950508000000
19671231235959

The expected format is the same as that produced by encode2.

Parameters:

inString - the epoch in string representation

Returns:

the value of the epoch represented by inString

Throws:

`CDFException` - if a bad epoch value is passed in `inString`

parse3

```
public static java.lang.Object parse3(java.lang.String inString)
                                   throws CDFException
```

This function parses an input date/time string and returns an EPOCH16 value. The format must be exactly as shown below.

```
Format:          yyyy-mm-ddThh:mm:ss.ccc.mmm.nnn.pppZ
Examples:        1990-04-01T03:05:02.000.000.000.000Z
                  1993-10-10T23:45:49.999.999.999.999Z
```

The expected format is the same as that produced by `encode3`.

Parameters:

`inString` - the epoch in string representation

Returns:

the value of the epoch represented by `inString`

Throws:

`CDFException` - if a bad epoch value is passed in `inString`

parse4

```
public static java.lang.Object parse4(java.lang.String inString)
                                   throws CDFException
```

This function parses an input date/time, ISO8601 string and returns an EPOCH16 value. The format must be exactly as shown below.

```
Format:          yyyy-mm-ddThh:mm:ss.cccmmmmnnppp
Examples:        1990-04-01T03:05:02.000000000000
                  1993-10-10T23:45:49.999999999999
```

The expected format is the same as that produced by `encode4`.

Parameters:

`inString` - the epoch in string representation

Returns:

the value of the epoch represented by `inString`

Throws:

`CDFException` - if a bad epoch value is passed in `inString`

toEncode

```
public static java.lang.String toEncode(double[] epoch,
                                       int style)
```

Converts an EPOCH16 value into a readable date/time string. Depending on the encoding style, it can present the string to one of the following forms:

```
For style 0:
Format:      dd-mmm-yyyy hh:mm:ss.ccc.uuu.nnn.ppp
Examples:    01-Apr-1990 03:05:02.000.111.222.333
              10-Oct-1993 23:45:49.999.999.999.999

For style 1:
Format:      yyyymmdd.tttttttt
Examples:    19950508.0000000
              19671231.58          (== 19671213.58000000)

For style 2:
Format:      yyyymmddhhmmss
Examples:    19900401030502
              19931010234549

For style 3:
Format:      yyyymmddThh:mm:ss.ccc.uuu.nnn.pppZ
Examples:    19900401T03:05:02.000.111.222.333Z
              19931010T23:45:49.999.999.999.999Z

For style 4:
Format:      yyyymmddThh:mm:ss.cccuuunnnppp
Examples:    19900401T03:05:02.000111222333
              19931010T23:45:49.999999999999999
The default style, if the style is invalid.
```

Parameters:

- epoch - the epoch value
- style - the encoding style

Returns:

A string representation of the epoch

toEncode

```
public static java.lang.Object toEncode(java.lang.Object epoch)
```

Converts an EPOCH object into a scalar or array of readable date/time string. Each string is presented in the following ISO 8601 form:

```
Format:      yyyymmddThh:mm:ss.cccuuunnnppp
Examples:    19900401T03:05:02.000111222333
              19931010T23:45:49.999999999999999
```

Parameters:

- epoch - the epoch object

Returns:

A string or array of strings representation of the epoch

toEncode

```
public static java.lang.String toEncode(double[] epoch)
```

Converts an EPOCH object into a scalar or array of readable date/time string. Each string is presented in the following ISO 8601 form:

```
Format:      yyyymmddThh:mm:ss.cccuuunnnppp
Examples:    19900401T03:05:02.000111222333
```

19931010T23:45:49.999999999999

Parameters:

epoch - the epoch object

Returns:

A string or array of strings representation of the epoch

toEncode

```
public static java.lang.Object toEncode(java.lang.Object epoch,
                                       long size)
```

Converts an EPOCH object into a scalar or array(s) of readable date/time string. Each string is presented in the following ISO 8601 form:

```
Format:      yyyyymmddThh:mm:ss.cccuuunnnppp
Examples:    19900401T03:05:02.000111222333
             19931010T23:45:49.999999999999
```

Parameters:

- epoch - the epoch object
- size - the number of CDF_EPOCH16 data

Returns:

A string or array(s) of strings representation of the epoch

Epoch16toUnixTime

```
public static double Epoch16toUnixTime(double[] epoch)
```

Converts an EPOCH16 value to a unix time of a double value (seconds from 1970-01-01 00:00:00 UTC). The unix time will have a time resolution of microseconds at its fraction part. Note: As EPOCH16 have a higher time resolution than the unix time. The conversion might not precisely preserve the microseconds due to the floating point presentation.

Parameters:

epoch - the epoch16 value (2-double)

Returns:

A unix time value

UnixTimetoEpoch16

```
public static double[] UnixTimetoEpoch16(double unixTime)
```

Converts a unix time of a double value (seconds from 1970-01-01 00:00:00 UTC) to an EPOCH16 value. The unix time can have a time resolution in microseconds at its fraction part. Note: As EPOCH16 have a higher time resolution than the unix time. The conversion might not precisely preserve the microseconds due to the floating point presentation.

Parameters:

unixTime - the unix time value

Returns:

An EPOCH16 value (2-double)

encode

```
public static java.lang.String encode(java.lang.Object epoch)
```

Converts an EPOCH16 value into a readable date/time string.

Format: dd-mmm-yyyy hh:mm:ss.ccc.mmm.nnn.ppp
Examples: 01-Apr-1990 03:05:02.000.000.000.000
10-Oct-1993 23:45:49.999.999.999.999

This format is the same as that expected by parse.

Parameters:

epoch - the epoch value

Returns:

A string representation of the epoch

encode1

```
public static java.lang.String encode1(java.lang.Object epoch)
```

Converts an EPOCH16 value into a readable date/time string.

Format: yyyyymmdd.tttttttttttttttt
Examples: 19900401.365889312341234
19611231.0000000000000000

This format is the same as that expected by parse1.

Parameters:

epoch - the epoch value

Returns:

A string representation of the epoch

encode2

```
public static java.lang.String encode2(java.lang.Object epoch)
```

Converts an EPOCH16 value into a readable date/time string.

Format: yyyyymmddhhmmss
Examples: 19900401235959
19611231000000

This format is the same as that expected by parse2.

Parameters:

epoch - the epoch value

Returns:

A string representation of the epoch

encode3

```
public static java.lang.String encode3(java.lang.Object epoch)
```

Converts an EPOCH16 value into a readable date/time string.

Format: yyyy-mm-ddThh:mm:ss.ccc.mmm.nnn.pppZ
Examples: 1990-04-01T03:05:02.000.000.000.000Z
 1993-10-10T23:45:49.999.999.999.999Z

This format is the same as that expected by parse3.

Parameters:

epoch - the epoch value

Returns:

A string representation of the epoch

encode4

```
public static java.lang.String encode4(java.lang.Object epoch)
```

Converts an EPOCH16 value into a readable date/time, ISO8601 string.

Format: yyyy-mm-ddThh:mm:ss.cccmmmmnnppp
Examples: 1990-04-01T03:05:02.000000000000
 1993-10-10T23:45:49.999999999999

This format is the same as that expected by parse4.

Parameters:

epoch - the epoch value

Returns:

A string representation of the epoch

encodex

```
public static java.lang.String encodex(java.lang.Object epoch,  
                                       java.lang.String formatString)
```

Converts an EPOCH16 value into a readable date/time string using the specified format. See the C Reference Manual section 8.7 for details

Parameters:

- epoch - the epoch value
- formatString - a string representing the desired format of the epoch

Returns:

A string representation of the epoch according to formatString

compute

```
public static double compute(long year,
                             long month,
                             long day,
                             long hour,
                             long minute,
                             long second,
                             long msec,
                             long usec,
                             long nsec,
                             long psec,
                             java.lang.Object epoch)
    throws CDFException
```

Computes an EPOCH16 value based on its component parts.

Parameters:

- year - the year
- month - the month
- day - the day
- hour - the hour
- minute - the minute
- second - the second
- msec - the milliseconds
- usec - the microseconds
- nsec - the nanoseconds
- psec - the picoseconds
- epoch - returned epoch value

Returns:

a double value which indicates whether the operation is successful

Throws:

CDFException - an ILLEGAL_EPOCH_FIELD if an illegal component value is detected.

breakdown

```
public static long[] breakdown(java.lang.Object epoch)
```

Breaks an EPOCH16 value down into its component parts.

Parameters:

- epoch - the epoch value to break down

Returns:

an array containing the epoch parts:

Index	Part
0	year
1	month
2	day
3	hour

4	minute
5	second
6	msec
7	usec
8	nsec
9	psec

Overview

Package

Class

Tree

Deprecated

Index

Help

Prev Class

Next Class

Frames

No Frames

All Classes

Summary: Nested | Field | Constr | Method

Detail: Field | Constr | Method

gsfc.nssdc.cdf.util

Class EpochNative

java.lang.Object
gsfc.nssdc.cdf.util.EpochNative

```
public class EpochNative
extends java.lang.Object
```

The Epoch class is a Java wrapper to the CDF epoch handling routines. See Chapter 8 of the CDF C Reference Manual Version 2.6 for details **Example:**

```
// Get the milliseconds to Aug 5, 1990 at 5:00
double ep = Epoch.compute(1990, 8, 5, 5, 0, 0, 0);
//Get the year, month, day, hour, minutes, seconds, milliseconds for ep
long times[] = Epoch.breakdown(ep);
for (int i=0;i<times.length;i++)
    System.out.print(times[i]+" ");
System.out.println();
// Printout the epoch in various formats
System.out.println(Epoch.encode(ep));
System.out.println(Epoch.encode1(ep));
System.out.println(Epoch.encode2(ep));
System.out.println(Epoch.encode3(ep));
// Print out the date using format
String format = "<month> <dom.02>, <year> at <hour>:<min>";
System.out.println(Epoch.encodedx(ep,format));
```

Constructor Summary

Constructors
Constructor and Description
EpochNative()

Method Summary

Methods

Modifier and Type	Method and Description
static long[]	breakdown (double epoch) Mirrors EPOCHbreakdown from the CDF library.
static double	compute (long year, long month, long day, long hour, long minute, long second, long msec) Mirrors computeEPOCH from the CDF library.
static java.lang.String	encode (double epoch) Mirrors encodeEPOCH from the CDF library.
static java.lang.String	encode1 (double epoch) Mirrors encodeEPOCH1 from the CDF library.

static java.lang.String	encode2 (double epoch) Mirrors encodeEPOCH2 from the CDF library.
static java.lang.String	encode3 (double epoch) Mirrors encodeEPOCH3 from the CDF library.
static java.lang.String	encode4 (double epoch) Mirrors encodeEPOCH4 from the CDF library.
static java.lang.String	encodeX (double epoch, java.lang.String format) Mirrors encodeEPOCHx from the CDF library.
static double	parse (java.lang.String sEpoch) Mirrors parseEPOCH from CDF library.
static double	parse1 (java.lang.String sEpoch) Mirrors parseEPOCH from CDF library.
static double	parse2 (java.lang.String sEpoch) Mirrors parseEPOCH from CDF library.
static double	parse3 (java.lang.String sEpoch) Mirrors parseEPOCH from CDF library.
static double	parse4 (java.lang.String sEpoch) Mirrors parseEPOCH from CDF library.

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

EpochNative

public EpochNative()

Method Detail

compute

```
public static double compute(long year,
                             long month,
                             long day,
                             long hour,
                             long minute,
                             long second,
                             long msec)
```

Mirrors computeEPOCH from the CDF library. See Section 8.1 of the CDF C Reference Manual Version 2.6 for details

Parameters:

- year - the year component
- month - the month component
- day - the day component
- hour - the hour component

`minute` - the minute component

`second` - the second component

`msec` - the millisecond component

Returns:

a epoch value

breakdown

```
public static long[] breakdown(double epoch)
```

Mirrors EPOCHbreakdown from the CDF library. See Section 8.2 of the CDF C Reference Manual Version 2.6 for details

Parameters:

`epoch` - the epoch, milliseconds since 0AD

Returns:

the day-time components

encode

```
public static java.lang.String encode(double epoch)
```

Mirrors encodeEPOCH from the CDF library. See Section 8.3 of the CDF C Reference Manual Version 2.6 for details

Parameters:

`epoch` - the epoch, milliseconds since 0AD

Returns:

the epoch in UTC string

encode1

```
public static java.lang.String encode1(double epoch)
```

Mirrors encodeEPOCH1 from the CDF library. See Section 8.4 of the CDF C Reference Manual Version 2.6 for details

Parameters:

`epoch` - the epoch, milliseconds since 0AD

Returns:

the epoch in UTC string

encode2

```
public static java.lang.String encode2(double epoch)
```

Mirrors encodeEPOCH2 from the CDF library. See Section 8.5 of the CDF C Reference Manual Version 2.6 for details

Parameters:

`epoch`

- the epoch, milliseconds since 0AD

Returns:

the epoch in UTC string

encode3

```
public static java.lang.String encode3(double epoch)
```

Mirrors encodeEPOCH3 from the CDF library. See Section 8.6 of the CDF C Reference Manual Version 2.6 for details

Parameters:

epoch - the epoch, milliseconds since 0AD

Returns:

the epoch in UTC string

encode4

```
public static java.lang.String encode4(double epoch)
```

Mirrors encodeEPOCH4 from the CDF library. See Section 8.6 of the CDF C Reference Manual Version 2.6 for details

Parameters:

epoch - the epoch, milliseconds since 0AD

Returns:

the epoch in UTC string

encodex

```
public static java.lang.String encodex(double epoch,
                                     java.lang.String format)
```

Mirrors encodeEPOCHx from the CDF library. See Section 8.7 of the CDF C Reference Manual Version 2.6 for details

Parameters:

epoch - the epoch, milliseconds since 0AD

format - the format to encode the string

Returns:

the epoch in UTC string

parse

```
public static double parse(java.lang.String sEpoch)
```

Mirrors parseEPOCH from CDF library. See Section 8.8 of the CDF C Reference Manual Version 2.6 for details

Parameters:

sEpoch - the epoch string

Returns:

the epoch

parse1

```
public static double parse1(java.lang.String sEpoch)
```

Mirrors parseEPOCH from CDF library. See Section 8.9 of the CDF C Reference Manual Version 2.6 for details

Parameters:

sEpoch - the epoch string

Returns:

the epoch

parse2

```
public static double parse2(java.lang.String sEpoch)
```

Mirrors parseEPOCH from CDF library. See Section 8.10 of the CDF C Reference Manual Version 2.6 for details

Parameters:

sEpoch - the epoch string

Returns:

the epoch

parse3

```
public static double parse3(java.lang.String sEpoch)
```

Mirrors parseEPOCH from CDF library. See Section 8.11 of the CDF C Reference Manual Version 2.6 for details

Parameters:

sEpoch - the epoch string

Returns:

the epoch

parse4

```
public static double parse4(java.lang.String sEpoch)
```

Mirrors parseEPOCH from CDF library. See Section 8.11 of the CDF C Reference Manual Version 2.6 for details

Parameters:

sEpoch - the epoch string

Returns:

the epoch

Overview	Package	Class	Tree	Deprecated	Index	Help
Prev Class	Next Class	Frames	No Frames	All Classes		
Summary: Nested Field Constr Method Detail: Field Constr Method						

gsfc.nssdc.cdf

Class Variable

java.lang.Object
gsfc.nssdc.cdf.Variable

All Implemented Interfaces:

CDFConstants, CDFObject

```
public class Variable
extends java.lang.Object
implements CDFObject, CDFConstants
```

The **Variable** class defines a CDF variable.

Notes: Since the CDF JavaAPI always uses `zMODE = 2`, all variables are by default, `zVariables`.

Version:

1.0, 2.0 03/18/05 Selection of current CDF and variable are done as part of operations passed to JNI. JNI call is synchronized so only one process is allowed in a JVM, due to multi-thread safety. The select method will never be called.

See Also:

Attribute, Entry

Field Summary

Fields inherited from interface gsfc.nssdc.cdf.CDFConstants

AHUFF COMPRESSION, ALPHAOSf1 DECODING, ALPHAOSf1 ENCODING, ALPHAVMSd DECODING, ALPHAVMSd ENCODING, ALPHAVMSg DECODING, ALPHAVMSg ENCODING, ALPHAVMSI DECODING, ALPHAVMSI ENCODING, ARM BIG DECODING, ARM BIG ENCODING, ARM LITTLE DECODING, ARM LITTLE ENCODING, ATTR, ATTR EXISTENCE, ATTR EXISTS, ATTR MAXgENTRY, ATTR MAXrENTRY, ATTR MAXzENTRY, ATTR NAME, ATTR NAME TRUNC, ATTR NUMBER, ATTR NUMgENTRIES, ATTR NUMrENTRIES, ATTR NUMzENTRIES, ATTR SCOPE, BACKWARD, BACKWARDFILEoff, BACKWARDFILEon, BAD ALLOCATE RECS, BAD ARGUMENT, BAD ATTR NAME, BAD ATTR NUM, BAD BLOCKING FACTOR, BAD CACHE SIZE, BAD CDF EXTENSION, BAD CDF ID, BAD CDF NAME, BAD CDFSTATUS, BAD CHECKSUM, BAD COMPRESSION PARM, BAD DATA TYPE, BAD DECODING, BAD DIM COUNT, BAD DIM INDEX, BAD DIM INTERVAL, BAD DIM SIZE, BAD ENCODING, BAD ENTRY NUM, BAD FNC OR ITEM, BAD FORMAT, BAD INITIAL RECS, BAD MAJORITY, BAD MALLOC, BAD NEGtoPOSfp0 MODE, BAD NUM DIMS, BAD NUM ELEMS, BAD NUM STRINGS, BAD NUM VARS, BAD READONLY MODE, BAD REC COUNT, BAD REC INTERVAL, BAD REC NUM, BAD SCOPE, BAD SCRATCH DIR, BAD SPARSEARRAYS PARM, BAD VAR NAME, BAD VAR NUM, BAD zMODE, BADDATE LEAPSECOND UPDATED, BeginUnixTimeEPOCH, BeginUnixTimeEPOCH16, BLOCKINGFACTOR TOO LARGE, BLOCKINGFACTOR TOO SMALL, BLOCKINGFACTOR TOO SMALL2, CANNOT ALLOCATE RECORDS, CANNOT CHANGE, CANNOT COMPRESS, CANNOT CONVERT WIDECCHAR, CANNOT COPY, CANNOT INSERT RECORDS, CANNOT SPARSEARRAYS, CANNOT SPARSERECORDS, CDF, CDF ACCESS, CDF ATTR NAME LEN, CDF ATTR NAME LEN256, CDF BYTE, CDF CACHESIZE, CDF CHAR, CDF CHECKSUM, CDF CLOSE ERROR, CDF COMPRESSION, CDF COPYRIGHT, CDF COPYRIGHT LEN, CDF CREATE ERROR, CDF DECODING, CDF DELETE ERROR, CDF DOUBLE, CDF ENCODING, CDF EPOCH, CDF EPOCH16, CDF EXISTS, CDF FLOAT, CDF FORMAT, CDF INCREMENT, CDF INFO, CDF INT1, CDF INT2, CDF INT4, CDF INT8, CDF INTERNAL ERROR, CDF LEAPSECONDLASTUPDATED, CDF MAJORITY, CDF MAX DIMS, CDF MAX PARMS, CDF MIN DIMS, CDF NAME, CDF NAME TRUNC, CDF NEGtoPOSfp0 MODE, CDF NUMATTRS, CDF NUMgATTRS, CDF NUMrVARS, CDF NUMvATTRS, CDF NUMzVARS, CDF OK, CDF OPEN ERROR, CDF PATHNAME LEN, CDF READ ERROR, CDF READONLY MODE, CDF REAL4, CDF REAL8, CDF RELEASE, CDF SAVE ERROR, CDF SCRATCHDIR, CDF STATUS, CDF STATUSTEXT LEN, CDF TIME TT2000, CDF UCHAR, CDF UINT1, CDF UINT2, CDF UINT4, CDF VAR NAME LEN, CDF VAR NAME LEN256, CDF VERSION, CDF WARN, CDF WRITE ERROR, CDF zMODE, CDFwithSTATS, CHECKSUM, CHECKSUM ERROR, CHECKSUM NOT ALLOWED, CLOSE, COLUMN MAJOR, COMPRESS CACHESIZE, COMPRESSION ERROR, CONFIRM, CORRUPTED V2 CDF, CORRUPTED V3 CDF, CREATE, CURENTRY EXISTENCE, CURENTRY EXISTENCE, CURrENTRY EXISTENCE, DATATYPE MISMATCH, DATATYPE SIZE, DECOMPRESSION ERROR, DECSTATION DECODING, DECSTATION ENCODING, DEFAULT BYTE PADVALUE, DEFAULT CHAR PADVALUE, DEFAULT DOUBLE PADVALUE, DEFAULT EPOCH PADVALUE, DEFAULT EPOCH16 PADVALUE, DEFAULT FLOAT PADVALUE, DEFAULT INT1 PADVALUE, DEFAULT INT2 PADVALUE, DEFAULT INT4 PADVALUE, DEFAULT INT8 PADVALUE, DEFAULT REAL4 PADVALUE, DEFAULT REAL8 PADVALUE, DEFAULT TT2000 PADVALUE, DEFAULT UCHAR PADVALUE, DEFAULT UINT1 PADVALUE, DEFAULT UINT2 PADVALUE, DEFAULT UINT4 PADVALUE, DELETE, DID NOT COMPRESS, EMPTY COMPRESSED CDF, END OF VAR, EPOCH STRING LEN, EPOCH STRING LEN EXTEND, EPOCH1 STRING LEN,

EPOCH1 STRING LEN EXTEND, EPOCH2 STRING LEN, EPOCH2 STRING LEN EXTEND, EPOCH3 STRING LEN, EPOCH3 STRING LEN EXTEND, EPOCH4 STRING LEN, EPOCH4 STRING LEN EXTEND, EPOCHx FORMAT MAX, EPOCHx STRING MAX, FILLED TT2000 VALUE, FORCED PARAMETER, FUNCTION NOT SUPPORTED, gENTRY, gENTRY DATA, gENTRY DATASPEC, gENTRY DATATYPE, gENTRY EXISTENCE, gENTRY NUMELEMS, GET, GETCDFCHECKSUM, GETCDFFILEBACKWARD, GETCDFVALIDATE, GETLEAPSECONDSENVVAR, GLOBAL SCOPE, GZIP COMPRESSION, HOST DECODING, HOST ENCODING, HP DECODING, HP ENCODING, HUFF COMPRESSION, IA64VMSd DECODING, IA64VMSd ENCODING, IA64VMSg DECODING, IA64VMSg ENCODING, IA64VMSi DECODING, IA64VMSi ENCODING, IBM PC OVERFLOW, IBMPC DECODING, IBMPC ENCODING, IBMRS DECODING, IBMRS ENCODING, ILLEGAL EPOCH FIELD, ILLEGAL EPOCH VALUE, ILLEGAL FOR SCOPE, ILLEGAL IN zMODE, ILLEGAL ON V1 CDF, ILLEGAL TT2000 VALUE, IS A NETCDF, LIB COPYRIGHT, LIB INCREMENT, LIB RELEASE, LIB subINCREMENT, LIB VERSION, MAC DECODING, MAC ENCODING, MD5 CHECKSUM, MULTI FILE, MULTI FILE FORMAT, NA FOR VARIABLE, NEGATIVE FP ZERO, NEGtoPOSfp0off, NEGtoPOSfp0on, NETWORK DECODING, NETWORK ENCODING, Next DECODING, Next ENCODING, NO ATTR SELECTED, NO CDF SELECTED, NO CHECKSUM, NO COMPRESSION, NO DELETE ACCESS, NO ENTRY SELECTED, NO MORE ACCESS, NO PADVALUE SPECIFIED, NO SPARSEARRAYS, NO SPARSERECORDS, NO STATUS SELECTED, NO SUCH ATTR, NO SUCH CDF, NO SUCH ENTRY, NO SUCH RECORD, NO SUCH VAR, NO VAR SELECTED, NO VARS IN CDF, NO WRITE ACCESS, NONE CHECKSUM, NOT A CDF, NOT A CDF OR NOT SUPPORTED, NOVARY, NULL OPEN, OPTIMAL ENCODING TREES, OTHER CHECKSUM, PAD SPARSERECORDS, PPC DECODING, PPC ENCODING, PRECEDING RECORDS ALLOCATED, PREV SPARSERECORDS, PUT, READ ONLY DISTRIBUTION, READ_ONLY_MODE, READONLYoff, READONLYon, rENTRY, rENTRY DATA, rENTRY DATASPEC, rENTRY DATATYPE, rENTRY EXISTENCE, rENTRY NAME, rENTRY NUMELEMS, rENTRY NUMSTRINGS, rENTRY STRINGSDATA, RLE COMPRESSION, RLE OF ZEROS, ROW MAJOR, rVAR, rVAR ALLOCATEBLOCK, rVAR ALLOCATEDFROM, rVAR ALLOCATEDTO, rVAR ALLOCATERECS, rVAR BLOCKINGFACTOR, rVAR CACHESIZE, rVAR COMPRESSION, rVAR DATA, rVAR DATASPEC, rVAR DATATYPE, rVAR DIMVARYS, rVAR EXISTENCE, rVAR HYPERDATA, rVAR INITIALRECS, rVAR MAXallocREC, rVAR MAXREC, rVAR NAME, rVAR nINDEXENTRIES, rVAR nINDEXLEVELS, rVAR nINDEXRECORDS, rVAR NUMallocRECS, rVAR NUMBER, rVAR NUMELEMS, rVAR NUMRECS, rVAR PADVALUE, rVAR RECORDS, rVAR RECORDS RENUMBER, rVAR RECVAR, rVAR RESERVEPERCENT, rVAR SEQDATA, rVAR SEQPOS, rVAR SPARSEARRAYS, rVAR SPARSERECORDS, rVARs CACHESIZE, rVARs DIMCOUNTS, rVARs DIMINDICES, rVARs DIMINTERVALS, rVARs DIMSIZES, rVARs MAXREC, rVARs NUMDIMS, rVARs RECCOUNT, rVARs RECDATA, rVARs RECINTERVAL, rVARs RECNUMBER, SAVE, SCRATCH CREATE ERROR, SCRATCH DELETE ERROR, SCRATCH READ ERROR, SCRATCH WRITE ERROR, SELECT, SGI DECODING, SGI ENCODING, SINGLE FILE, SINGLE FILE FORMAT, SOME ALREADY ALLOCATED, STAGE CACHESIZE, STATUS TEXT, STRING NOT UTF8 ENCODING, STRINGDELIMITER, SUN DECODING, SUN ENCODING, TOO MANY PARMS, TOO MANY VARS, TRY TO READ NONSTRING DATA, TT2000 0 STRING LEN, TT2000 1 STRING LEN, TT2000 2 STRING LEN, TT2000 3 STRING LEN, TT2000 4 STRING LEN, TT2000 CDF MAYNEEDUPDATE, TT2000 TIME ERROR, TT2000 USED OUTDATED TABLE, UNABLE TO PROCESS CDF, UNKNOWN COMPRESSION, UNKNOWN SPARSENESS, UNSUPPORTED OPERATION, VALIDATE, VALIDATEFILEoff, VALIDATEFILEon, VAR ALREADY CLOSED, VAR CLOSE ERROR, VAR CREATE ERROR, VAR DELETE ERROR, VAR EXISTS, VAR NAME TRUNC, VAR OPEN ERROR, VAR READ ERROR, VAR SAVE ERROR, VAR WRITE ERROR, VARIABLE SCOPE, VARY, VAX DECODING, VAX ENCODING, VIRTUAL RECORD DATA, zENTRY, zENTRY DATA, zENTRY DATASPEC, zENTRY DATATYPE, zENTRY EXISTENCE, zENTRY NAME, zENTRY NUMELEMS, zENTRY NUMSTRINGS, zENTRY STRINGSDATA, ZLIB COMPRESS ERROR, ZLIB UNCOMPRESS ERROR, zMODEoff, zMODEon1, zMODEon2, zVAR, zVAR ALLOCATEBLOCK, zVAR ALLOCATEDFROM, zVAR ALLOCATEDTO, zVAR ALLOCATERECS, zVAR BLOCKINGFACTOR, zVAR CACHESIZE, zVAR COMPRESSION, zVAR DATA, zVAR DATASPEC, zVAR DATATYPE, zVAR DIMCOUNTS, zVAR DIMINDICES, zVAR DIMINTERVALS, zVAR DIMSIZES, zVAR DIMVARYS, zVAR EXISTENCE, zVAR HYPERDATA, zVAR INITIALRECS, zVAR MAXallocREC, zVAR MAXREC, zVAR NAME, zVAR nINDEXENTRIES, zVAR nINDEXLEVELS, zVAR nINDEXRECORDS, zVAR NUMallocRECS, zVAR NUMBER, zVAR NUMDIMS, zVAR NUMELEMS, zVAR NUMRECS, zVAR PADVALUE, zVAR RECCOUNT, zVAR RECINTERVAL, zVAR RECNUMBER, zVAR RECORDS, zVAR RECORDS RENUMBER, zVAR RECVAR, zVAR RESERVEPERCENT, zVAR SEQDATA, zVAR SEQPOS, zVAR SPARSEARRAYS, zVAR SPARSERECORDS, zVARs CACHESIZE, zVARs MAXREC, zVARs RECDATA, zVARs RECNUMBER

Method Summary

Methods	
Modifier and Type	Method and Description
void	allocateBlock (long firstRec, long lastRec) Allocates a range of records for this variable.
void	allocateRecords (long num0toRecords) Allocates a number of records, starting from record number 0.
boolean	checkPadValueExistence () Checks if the pad value has been defined for this variable.
void	concatenateDataRecords (Variable destVar) Concatenates this variable's data records to the destination variable.
long	confirmCacheSize () Gets the number of 512-byte cache buffers defined for this variable.
long	confirmPadValue () Checks the existence of an explicitly specified pad value for the current z variable.
long	confirmReservePercent () Gets the reserve percentage set for this variable.
Variable	copy (CDF destCDF, java.lang.String varName)

	Copies this variable into a new variable and puts it into the designated CDF file.
Variable	copy (java.lang.String varName) Copies this variable to a new variable.
void	copyDataRecords (Variable destVar) Copies this variable's data to the destination variable.
static Variable	create (CDF myCDF, java.lang.String varName, long dataType, long numElements, long numDims, long[] dimSizes, long recVary, long[] dimVarys) Creates a variable.
void	delete () Deletes this variable.
void	deleteRecords (long firstRec, long lastRec) Deletes a range of records from this variable.
void	deleteRecordsRenum (long firstRec, long lastRec) Deletes a range of records from this variable.
void	dumpDataWithFormat (CDFData data) Dump the data, either the variable value or metadata, with the format.
void	dumpDataWithFormat (java.lang.Object data) Dump the data, either the variable value or metadata, with or without the format.
void	dumpDataWithFormat (java.lang.Object data, java.io.PrintWriter outWriter) Dump the data, either the variable value or metadata, with or without the format.
Variable	duplicate (CDF destCDF, java.lang.String varName) Duplicates this variable and put it into the designated CDF file.
Variable	duplicate (java.lang.String varName) Duplicates this variable to a new variable.
long	getAllocatedFrom (long recNum) Inquires the next allocated record at or after a given record for this variable.
long	getAllocatedTo (long firstRec) Inquires the last allocated record (before the next unallocated record) at or after a given record for this variable.
java.lang.Object	getAllRecords () Get all written records, from record number 0 till the last written record number, from this variable.
CDFData	getAllRecordsObject () Get all written records, from record number 0 till the last written record number, from this variable.
java.util.Vector	getAttributes () Returns the variable attributes that are associated with this variable.
java.util.Map	getAttributesandEntries () Returns the variable attributes and their entries that are associated with this variable.
java.util.Map	getAttributesandEntries (boolean encoding) Returns the variable attributes and their entries that are associated with this variable.
long	getBlockingFactor () Gets the blocking factor for this variable.
java.lang.String	getCompression () Gets the string representation of the compression type and parameters set for this variable.
long[]	getCompressionParms () Sets the compression parameters of this variable.
long	getCompressionPct () Gets the compression percentage rate of this variable.
long	getCompressionType () Gets the compression type of this variable.
long	getDataType () Gets the CDF data type of this variable.

long[]	getDimSizes() Gets the dimensions size of this variable.
long[]	getDimVariances() Gets the dimension variances for this variable.
java.lang.Object	getEntryData (java.lang.String attrName) Gets the attribute entry data for this variable.
java.lang.Object	getHyperData (long recNum, long recCount, long recInterval, long[] dimIndices, long[] dimCounts, long[] dimIntervals) Reads one or more values from the current z variable.
CDFData	getHyperDataObject (long recNum, long recCount, long recInterval, long[] dimIndices, long[] dimCounts, long[] dimIntervals) Reads one or more values from the current z variable.
long	getID() Gets the ID of this variable.
long	getMaxAllocatedRecord() Gets the maximum allocated record number for this variable.
long	getMaxWrittenRecord() Gets the last written record number, beginning with 0.
CDF	getMyCDF() Gets the CDF object to which this variable belongs.
java.lang.String	getName() Gets the name of this variable.
long	getNumAllocatedRecords() Gets the number of records allocated for this variable.
long	getNumDims() Gets the number of dimensions for this variable.
long	getNumElements() Gets the number of elements for this variable.
long	getNumWrittenRecords() Gets the number of records physically written (not allocated) for this variable.
java.lang.Object	getPadValue() Gets the pad value for this variable.
java.lang.Object	getRecord (long recNum) Gets a single record from this variable.
CDFData	getRecordObject (long recNum) Get a single record of data from this variable.
CDFData	getRecordsObject (long recNum, long numRecs) Get a number of records of data from this variable.
boolean	getRecVariance() Gets the value of record variance.
java.lang.Object	getScalarData() Gets the scalar data from a non-record varying 0-dimensional variable.
java.lang.Object	getScalarData (long recNum) Get the scalar data from a record varying 0-dimensional variable.
CDFData	getScalarDataObject() Get the scalar data from a non-record varying 0-dimensional variable.
CDFData	getScalarDataObject (long recNum) Get the scalar data from this record varying 0-dimensional variable.
java.lang.Object	getSingleData (long recNum, long[] indices) Gets a single data value.
CDFData	getSingleDataObject (long recNum, long[] indices) Gets a single data object from this variable.

long	getSparseRecords() Gets the sparse record type for this variable.
void	putEntry (Attribute attr, long dataType, java.lang.Object data) Creates an attribute entry for this variable.
void	putEntry (java.lang.String attrName, long dataType, java.lang.Object data) Creates an attribute entry for this variable.
CDFData	putHyperData (long recNum, long recCount, long recInterval, long[] dimIndices, long[] dimCounts, long[] dimIntervals, java.lang.Object data) Writes one or more values from the current z variable.
CDFData	putRecord (long recNum, java.lang.Object data) Adds a single record to a record-varying variable.
CDFData	putRecord (java.lang.Object data) Adds a single record to a non-record-varying variable.
CDFData	putRecords (long startRec, long recCount, java.lang.Object data) Writes a number of records from the current z variable.
CDFData	putScalarData (long recNum, java.lang.Object data) Adds a scalar data to this variable (of 0 dimensional).
CDFData	putScalarData (java.lang.Object data) Adds a scalar data to this variable (of 0 dimensional).
CDFData	putSingleData (long recNum, long[] indices, java.lang.Object data) Adds a single data value to this variable.
java.util.Map	readVariable() Gets the full variable information, its specification, metadata and data.
java.util.Map	readVariable (boolean encoding, boolean basic, boolean metadata, boolean vardata) Gets the specified variable information: its specification, metadata and data.
java.util.Map	readVariableData() Gets the variable's data.
java.util.Map	readVariableMetaData() Gets the variable's metadata.
java.util.Map	readVariableSpec() Gets the variable's specification.
void	rename (java.lang.String newName) Renames the current variable.
void	selectCacheSize (long cacheSize) Sets the number of 512-byte cache buffers to be used.
void	selectReservePercent (long reservePercent) Sets the reserve percentage to be used for this variable.
void	setBlockingFactor (long blockingFactor) Sets the blocking factor for this variable.
void	setCompression (long cType, long[] cParms) Sets the compression type and parameters for this variable.
void	setDimVariances (long[] dimVariances) Sets the dimension variances for this variable.
void	setInitialRecords (long nRecords) Sets the number of records to be written initially for this variable.
void	setPadValue (java.lang.Object padValue) Sets the pad value for this variable.
void	setRecVariance (long recVariance) Sets the record variance for this variable.
void	setSparseRecords (long sparseRecords)

	Sets the sparse record type for this variable.
java.lang.String	<code>toString()</code> Gets the name of this variable.
void	<code>updateDataSpec(long dataType, long numElements)</code> Update the data specification (data type and number of elements) of the variable.

Methods inherited from class java.lang.Object

`equals, getClass, hashCode, notify, notifyAll, wait, wait, wait`

Method Detail

create

```
public static Variable create(CDF myCDF,
                             java.lang.String varName,
                             long dataType,
                             long numElements,
                             long numDims,
                             long[] dimSizes,
                             long recVary,
                             long[] dimVarys)
    throws CDFException
```

Creates a variable.

The following example creates a variable called "Longitude" that is scalar (non-array) and record-varying:

```
longitude = Variable.create(cdf, "Longitude", CDF_INT2,
                           1L, 0L, new long [] {1},
                           VARY,
                           new long [] {NOVARY});
```

The following example creates a variable called "TestData" whose data is 2-dimensional (3 x 2), record variance is TURE, and dimension variances are TRUE.

```
data = Variable.create(cdf, "TestData", CDF_INT2,
                      1L, 2L, new long [] {3,2},
                      VARY,
                      new long [] {VARY, VARY});
```

Parameters:

- myCDF - the CDF to which this variable belongs
- varName - the name of the variable to create
- dataType - the CDF data type for this variable that should be one of the following:
 - CDF_BYTE - 1-byte, signed integer
 - CDF_CHAR - 1-byte, signed character
 - CDF_INT1 - 1-byte, signed integer
 - CDF_UCHAR - 1-byte, unsigned character
 - CDF_UINT1 - 1-byte, unsigned integer
 - CDF_INT2 - 2-byte, signed integer
 - CDF_UINT2 - 2-byte, unsigned integer
 - CDF_INT4 - 4-byte, signed integer
 - CDF_UINT4 - 4-byte, unsigned integer
 - CDF_INT8 - 8-byte, signed integer
 - CDF_REAL4 - 4-byte, floating point
 - CDF_FLOAT - 4-byte, floating point
 - CDF_REAL8 - 8-byte, floating point

- CDF_DOUBLE - 8-byte, floating point
- CDF_EPOCH - 8-byte, floating point
- CDF_EPOCH16 - 2*8-byte, floating point
- CDF_TIME_TT2000 - 8-byte, signed integer

numElements - for CDF_CHAR and CDF_UCHAR this is the string length, 1 otherwise

numDims - the dimensionality

dimSizes - The dimension sizes. An array of length numDims indicating the size of each dimension

recVary - the record variance that should be either VARY or NOVARY

dimVarys - The dimension variance(s). Each dimension variance should be either VARY or NOVARY.

Returns:

newly created Variable object

Throws:

CDFException - if there is a problem creating a variable

delete

```
public void delete()  
    throws CDFException
```

Deletes this variable.

Specified by:

delete in interface CDFObject

Throws:

CDFException - if there was an error deleting this variable

rename

```
public void rename(java.lang.String newName)  
    throws CDFException
```

Renames the current variable.

Specified by:

rename in interface CDFObject

Parameters:

newName - the new variable name

Throws:

CDFException - if there was a problem renaming this variable

copy

```
public Variable copy(java.lang.String varName)  
    throws CDFException
```

Copies this variable to a new variable. This method only copies the metadata associated with this variable. The duplicate method in

this class should be used if the user wants to copy a variable with data and metadata.

Parameters:

varName - the name of the variable to copy this variable into

Returns:

newly copied variable

Throws:

CDFException - if there was a problem copying a variable

copy

```
public Variable copy(CDF destCDF,
                    java.lang.String varName)
    throws CDFException
```

Copies this variable into a new variable and puts it into the designated CDF file. This method only copies the metadata associated with this variable. The duplicate method in this class should be used if the user wants to copy a variable with data and metadata.

Parameters:

destCDF - the destination CDF into which copy this variable

varName - the new variable name

Returns:

newly copied variable

Throws:

CDFException - if there was a problem copying a variable

duplicate

```
public Variable duplicate(java.lang.String varName)
    throws CDFException
```

Duplicates this variable to a new variable.

Note: This copies everything from the existing variable to a new variable. It includes the metadata associated with this variable, all data records as well as other information such as blocking factor/compression/sparseness/pad value.

Parameters:

varName - the name of the variable to duplicate this variable into

Returns:

newly duplicated variable

Throws:

CDFException - if there was a problem duplicating a variable

duplicate

```
public Variable duplicate(CDF destCDF,
                        java.lang.String varName)
```

throws `CDFException`

Duplicates this variable and put it into the designated CDF file.

Note: This copies everything from the current variable to a new variable. It includes the metadata associated with this variable, all data records as well as other information such as blocking factor/compression/sparseness/pad value.

Parameters:

`destCDF` - the destination CDF to duplicate this variable into

`varName` - the name of the variable to duplicate this variable into

Returns:

newly duplicated variable

Throws:

`CDFException` - if there was a problem duplicating a variable

copyDataRecords

```
public void copyDataRecords(Variable destVar)
    throws CDFException
```

Copies this variable's data to the destination variable.

Parameters:

`destVar` - the destination variable to copy data into

Throws:

`CDFException` - if there was a problem copying data records **Note:** This copies data records from the current variable to the destination variable. The metadata associated with the destination variable will be not changed.

The current CDF file MUST be saved first (by calling the `save()` method) before 'copying/duplicating data records' operation is performed. Otherwise the program will either fail or produce undesired results.

concatenateDataRecords

```
public void concatenateDataRecords(Variable destVar)
    throws CDFException
```

Concatenates this variable's data records to the destination variable.

Parameters:

`destVar` - the destination variable to copy data records into

Throws:

`CDFException` - if there was a problem copying data records **Note:** This copies only the data records from the current variable to the destination variable. The metadata associated with the destination variable will be not changed.

getEntryData

```
public java.lang.Object getEntryData(java.lang.String attrName)
    throws CDFException
```

Gets the attribute entry data for this variable.

The following examples retrieves the 'Longitude' variable entry for the attribute VALIDMIN:

```
Variable var = cdf.getVariable("Longitude");
float longitude = (float) var.getEntryData("VALIDMIN");
```

Parameters:

`attrName` - the name of the attribute to get entry data from

Returns:

the attribute entry data for this variable

Throws:

`CDFException` - if there was a problem getting entry data

getSingleData

```
public java.lang.Object getSingleData(long recNum,
                                     long[] indices)
    throws CDFException
```

Gets a single data value. This method is useful for extracting a specific item among many items.

Let's assume that variable `TestData` is defined to be 1-dimensional array that has 3 elements in it. The following example extracts the last element from the second record:

```
Variable var = cdf.getVariable("TestData");
int data = (int) var.getSingleData(1L, new long [] {2});
```

Let's assume that variable `TestData` is defined to be 2-dimensional (3x2 - 3 rows and 2 columns) array. The following example extracts the first element of the second row from the first record:

```
Variable var = cdf.getVariable("TestData");
int data = (int) var.getSingleData(0L, new long [] {1,0});
```

Parameters:

`recNum` - the record number to retrieve data from

`indices` - the index, within a record, to extract data from

Returns:

extracted single data value

Throws:

`CDFException` - if there was a problem extracting data

getSingleDataObject

```
public CDFData getSingleDataObject(long recNum,
                                    long[] indices)
    throws CDFException
```

Gets a single data object from this variable. The value read is put into an `CDFData` object. This method is identical to the `getSingleData` method except that the extracted data is encapsulated inside the `CDFData` object along with other information such as record number, record count, record interval, dimension indices, dimension counts, and dimension intervals.

Parameters:

`recNum` - the record number to retrieve data from

`indices` - the index, within a record, to extract data from

Returns:

CDFData object containing the requested data

Throws:

`CDFException` - if there was a problem extracting data

getRecord

```
public java.lang.Object getRecord(long recNum)
                           throws CDFException
```

Gets a single record from this variable.

Let's assume that variable `TestData` is defined to be 2-dimensional (3x2 - 3 rows and 2 columns). The following example extracts an entire record (containing 6 elements) from the first record from a variable of data type `CDF_INT4`:

```
Variable var = cdf.getVariable("TestData");
int[][] data = (int [][]) var.getRecord(0L);
```

However, if a dimensional variable with all indices being invariant, e.g., 2-dimensional (1x1), the retrieved object will be different. (Since the variable has only one data value per record, it is preferred to be defined as an 0-dim, rather.). The object is not an array, instead, a single Java class item, e.g., Integer, Double, Short, etc. The following example extracts an record from the first record of a variable, 2-dim (1x1), with data type `CDF_INT2`:

```
Variable var = cdf.getVariable("TestVar");
short data = ((Short) var.getRecord(0L)).shortValue();
```

Parameters:

`recNum` - the record number to retrieve data from

Returns:

the requested data record

Throws:

`CDFException` - if there was a problem getting a record

getRecordObject

```
public CDFData getRecordObject(long recNum)
                           throws CDFException
```

Get a single record of data from this variable. The values read are put into an `CDFData` object. This method is identical to the `getRecord` method except that the extracted data is encapsulated inside the `CDFData` object along with other information such as record number, record count, record interval, dimension indices, dimension counts, and dimension intervals.

Parameters:

`recNum` - the record number to retrieve data from

Returns:

CDFData object containing the requested data record

Throws:

`CDFException` - if there was a problem getting a record

getRecordsObject

```
public CDFData getRecordsObject(long recNum,  
                                long numRecs)  
    throws CDFException
```

Get a number of records of data from this variable. The values read are put into an CDFData object.

Parameters:

recNum - the record number to start to retrieve data from

numRecs - the number of records to retrieve

Returns:

CDFData object containing the requested data record(s)

Throws:

CDFException - if there was a problem getting the record(s)

getAllRecordsObject

```
public CDFData getAllRecordsObject()  
    throws CDFException
```

Get all written records, from record number 0 till the last written record number, from this variable. The data values read are put into an CDFData object. Note: If this variable has sparse records, then the missing record(s) is filled with FILLVAL (or PAD if FILLVAL does not exist) value.

Returns:

CDFData object containing all data record(s)

Throws:

CDFException - if there was a problem getting the record(s)

getAllRecords

```
public java.lang.Object getAllRecords()  
    throws CDFException
```

Get all written records, from record number 0 till the last written record number, from this variable. The data values read are put into an Object. Note: If this variable has sparse records, then the missing record(s) is filled with FILLVAL (or PAD if FILLVAL does not exist) value.

Returns:

Object containing all data record(s)

Throws:

CDFException - if there was a problem getting the record(s)

getScalarData

```
public java.lang.Object getScalarData()
```

throws `CDFException`

Gets the scalar data from a non-record varying 0-dimensional variable.

Returns:

the variable data from this variable

Throws:

`CDFException` - if there was a problem getting data

getScalarData

```
public java.lang.Object getScalarData(long recNum)
                               throws CDFException
```

Get the scalar data from a record varying 0-dimensional variable.

Parameters:

`recNum` - The record number to retrieve data from

Returns:

the variable data from this variable

Throws:

`CDFException` - if there was a problem getting data

getScalarDataObject

```
public CDFData getScalarDataObject()
                               throws CDFException
```

Get the scalar data from a non-record varying 0-dimensional variable. This method is identical to the `getScalarData` method except that the extracted data is encapsulated inside the `CDFData` object along with other information such as record number, record count, record interval, dimension indices, dimension counts, and dimension intervals.

Returns:

the variable data from this variable

Throws:

`CDFException` - if there was a problem getting data

getScalarDataObject

```
public CDFData getScalarDataObject(long recNum)
                               throws CDFException
```

Get the scalar data from this record varying 0-dimensional variable. This method is identical to the `getScalarData` method except that the extracted data is encapsulated inside the `CDFData` object along with other information such as record number, record count, record interval, dimension indices, dimension counts, and dimension intervals.

Parameters:

`recNum` - the record number to retrieve data from

Returns:

the variable data from this variable

Throws:

`CDFException` - if there was a problem getting data

getHyperData

```
public java.lang.Object getHyperData(long recNum,
                                     long recCount,
                                     long recInterval,
                                     long[] dimIndices,
                                     long[] dimCounts,
                                     long[] dimIntervals)
    throws CDFException
```

Reads one or more values from the current z variable. The values are based on the current record number, current record count, current record interval, current dimension indices, current dimension counts, and current dimension intervals.

Let's assume that variable `TestData` is defined to be 2-dimensional (3x2 - 3 rows and 2 columns). The following example extracts the entire record (containing 6 elements) from the first, second, and third records:

```
Variable var = cdf.getVariable("TestData");
int[][] data = (int [][]) var.getHyperData (0L, 3L, 1L,
                                             new long[] {0, 0},
                                             new long[] {3, 2},
                                             new long[] {1, 1});
```

The following example will extract the entire record from the first record:

```
Variable var = cdf.getVariable("TestData");
int[][] data = (int [][]) var.getHyperData (0L, 1L, 1L,
                                             new long[] {0, 0},
                                             new long[] {3, 2},
                                             new long[] {1, 1});
```

Note: it returns a 2-dimensional object as only one record is involved. The following example will extract the second row from the first, and third records:

```
Variable var = cdf.getVariable("TestData");
int[][] data = (int [][]) var.getHyperData (0L, 3L, 2L,
                                             new long[] {1, 0},
                                             new long[] {1, 2},
                                             new long[] {1, 1});
```

The following example will extract the first column from the first and second records:

```
Variable var = cdf.getVariable("TestData");
int[][] data = (int [][]) var.getHyperData (0L, 2L, 1L,
                                             new long[] {0, 0},
                                             new long[] {3, 1},
                                             new long[] {1, 1});
```

Parameters:

`recNum` - the record number at which data search begins

`recCount` - the number of records to read

`recInterval` - the number of records to skip between reads

`dimIndices` - the dimension index within a record at which data search begins

`dimCounts` - the number of elements to read from `dimIndices`

`dimIntervals` - the number of elements to skip between reads

Returns:

the variable data specified by `recNum`, `recCount`, `recInterval`, `dimIndices`, `dimCounts`, and `dimIntervals`

Throws:

`CDFException` - if there was a problem getting data

getHyperDataObject

```
public CDFData getHyperDataObject(long recNum,
                                   long recCount,
                                   long recInterval,
                                   long[] dimIndices,
                                   long[] dimCounts,
                                   long[] dimIntervals)
    throws CDFException
```

Reads one or more values from the current `z` variable. The values are read based on the current record number, current record count, current record interval, current dimension indices, current dimension counts, and current dimension intervals. The values read are put into an `CDFData` object.

Parameters:

- `recNum` - the record number at which data search begins
- `recCount` - the number of records to read
- `recInterval` - the number of records to skip between reads
- `dimIndices` - the dimension index within a record at which data search begins
- `dimCounts` - the number of elements to read from `dimIndices`
- `dimIntervals` - the number of elements to skip between reads

Returns:

`CDFData` object that contains the variable data specified by `recNum`, `recCount`, `recInterval`, `dimIndices`, `dimCounts`, and `dimIntervals` as well as the information passed to this method plus the number of dimensions and the number of elements for this variable.

Throws:

`CDFException` - if there was a problem getting data

readVariable

```
public java.util.Map readVariable()
```

Gets the full variable information, its specification, metadata and data. Note: Each metadata/data of epoch type data will be encoded in date/time string.

```
Variable v = cdf.getVariable("var1");
Map var = v.readVariable();
// Three key-value pairs will be included with keys of as
// "VarSpec", "VarMetaData", "VarData"

// Key: "VarSpec" contains variable specification - another Map object
// These include: keys of "DataType", "NumElements", "NumDims",
// "DimSizes" and "PadValue".
System.out.println("  specification: "+var.get("VarSpec"));

// Key: "VarMetaData" contains variable attributes - another Map object
// These include variable attribute name (key) and its entry (value)
System.out.println("  meta: "+var.get("VarMetaData"));
```

```
// Key: "VarData" has variable data - an object
System.out.println("  data:");
CDFUtils.printData(var.get("VarData"));
```

Returns:

A Map object that contains the full variable information.

readVariableSpec

```
public java.util.Map readVariableSpec()
```

Gets the variable's specification.

Returns:

A Map object that contains the variable's specification with the key "VarSpec". The value is another Map object.

readVariableMetaData

```
public java.util.Map readVariableMetaData()
```

Gets the variable's metadata.

Returns:

A Map object that contains the variable's metadata with the key "VarMetaData". The value is another Map object if it has metadata.

readVariableData

```
public java.util.Map readVariableData()
```

Gets the variable's data.

Returns:

A Map object that contains the variable's specification with the key "VarData".

readVariable

```
public java.util.Map readVariable(boolean encoding,
                                boolean basic,
                                boolean metadata,
                                boolean vardata)
```

Gets the specified variable information: its specification, metadata and data.

```
Variable v = cdf.getVariable("var1");
Map var = v.readVariable(true, true, true, true);
// Three key-value pairs might be included with keys of as
// "VarSpec" and "VarMetaData" and/or "VarData" if there are data.

// Key: "VarSpec" contains variable specification - another Map object
// These include: keys of "DataType", "NumElements", "NumDims",
// "DimSizes" and "PadValue".
System.out.println("  specification: "+var.get("VarSpec"));

// Key: "VarMetaData" contains variable attributes - another Map object
```

```
// These include variable attribute name (key) and its entry (value)
System.out.println("  meta: "+var.get("VarMetaData"));

// Key: "VarData" has variable data - an object
System.out.println("  data:");
CDFUtils.printData(var.get("VarData"));
```

Parameters:

- encoding - A true/false flag indicates whether to encode epoch data type from metadata to date/time string.
- basic - A true/false flag indicates whether to return the specification of the variable
- metadata - A true/false flag indicates whether to return the metadata from the variable
- vardata - true/false flag indicates whether to return the data from the variable

Returns:

A Map object that contains the requested variable information.

putEntry

```
public void putEntry(java.lang.String attrName,
                    long dataType,
                    java.lang.Object data)
    throws CDFException
```

Creates an attribute entry for this variable.

The following example creates a variable entry for the variable "Longitude" associated with the attribute "VALIDMIN":

```
Variable longitude = cdf.getVariable("Longitude");
longitude.putEntry("VALIDMIN", CDF_INT2, new Short((short)180));
```

Parameters:

- attrName - the attribute to which this attribute entry is attached
- dataType - the CDF data type of the entry data - see the description of the create method in this class for a list of the CDF data types supported
- data - the attribute entry data to be added

Throws:

CDFException - if a problem occurs putting an entry

See Also:

Attribute, Entry

putEntry

```
public void putEntry(Attribute attr,
                    long dataType,
                    java.lang.Object data)
    throws CDFException
```

Creates an attribute entry for this variable. The following example creates a variable entry for the variable "Longitude" associated with the attribute "VALIDMIN":

```
Variable longitude = cdf.getVariable("Longitude");
Attribute validMin = Attribute.create(cdf, "VALIDMIN",
                                   VARIABLE_SCOPE);
Entry.create(validMin, longitude.getID(), CDF_INT2,
```

```
new Short((short)10));
OR
longitude.putEntry(validMin, CDF_INT2, new Short((short)180));
```

Parameters:

- attr - the attribute to which this attribute entry is attached
- dataType - the CDF data type of the entry data - see the description of the create method in this class for a list of the CDF data types supported
- data - the attribute entry data to be added

Throws:

- CDFException - if a problem occurs putting an entry

See Also:

Attribute, Entry

putSingleData

```
public CDFData putSingleData(long recNum,
                             long[] indices,
                             java.lang.Object data)
    throws CDFException
```

Adds a single data value to this variable. This method is used to specify a particular element in a record (if a record is comprised of multiple elements). If a record contains 3 elements, the following example will write the second element to record number 0, leaving the first and third elements unwritten.

```
longitude = cdf.getVariable("Longitude");
longitude.putSingleData(0L, new long[] {1}, new Short((short)200));
or
longitude.putSingleData(0L, new long[] {1}, longitudeData[1]);
```

Parameters:

- recNum - the record number to which this data belongs
- indices - the index (location) in the specified record
- data - the data to be added

Returns:

CDFData object containing the user specified data

Throws:

- CDFException - if there was an error writing data

putScalarData

```
public CDFData putScalarData(long recNum,
                             java.lang.Object data)
    throws CDFException
```

Adds a scalar data to this variable (of 0 dimensional). This method should be used if a variable is defined as record-varying and non-array. The following example will write data to record number 0.

```
longitude = cdf.getVariable("Longitude");
longitude.putScalarData(0L, new Short((short)200));
or
```

```
longitude.putScalarData(0L, longitudeData[0]);
```

Parameters:

recNum - the record number to which this data belongs

data - the data to be added

Returns:

CDFData object containing the user specified data

Throws:

CDFException - if there was an error writing data

putScalarData

```
public CDFData putScalarData(java.lang.Object data)
                           throws CDFException
```

Adds a scalar data to this variable (of 0 dimensional). This method should be used if a variable is defined as non-record-varying and non-array. Note that there'll be only one record exist if a variable is defined as non-record-varying. The following example will write data to record number 0.

```
longitude = cdf.getVariable("Longitude");
longitude.putScalarData(new Short((short)200));
    or
longitude.putScalarData(longitudeData[0]);
```

Parameters:

data - the data to be added

Returns:

CDFData object containing the user specified data

Throws:

CDFException - if there was an error writing data

putRecord

```
public CDFData putRecord(long recNum,
                        java.lang.Object data)
                        throws CDFException
```

Adds a single record to a record-varying variable. This method should be used if a record contains one or more elements.

The following example adds a scalar data to record number 0:

```
longitude = cdf.getVariable("Longitude");
longitude.putRecord(0L, new Short((short)200));
```

The following example adds multiple elements (array) to record number 0:

```
short [] longitudeData = {10, 20, 30};
longitude = cdf.getVariable("Longitude");
longitude.putRecord(0L, longitudeData);
```

Parameters:

recNum - the record number to which this data belongs

data - the data to be added

Returns:

CDFData object containing the user specified data

Throws:

`CDFException` - if there was a problem writing data

putRecord

```
public CDFData putRecord(java.lang.Object data)
    throws CDFException
```

Adds a single record to a non-record-varying variable. This method should be used if a record contains one element or multiple elements.

The following example adds a scalar data to record number 0:

```
longitude = cdf.getVariable("Longitude");
longitude.putRecord(new Short((short)200));
```

The following example adds multiple elements (array) to record number 0:

```
short [] longitudeData = {10, 20, 30};
longitude = cdf.getVariable("Longitude");
longitude.putRecord(longitudeData);
```

Parameters:

data - the data to be added

Returns:

CDFData object containing the user specified data

Throws:

`CDFException` - if there was a problem writing data

putHyperData

```
public CDFData putHyperData(long recNum,
    long recCount,
    long recInterval,
    long[] dimIndices,
    long[] dimCounts,
    long[] dimIntervals,
    java.lang.Object data)
    throws CDFException
```

Writes one or more values from the current z variable. The values are written based on the current record number, current record count, current record interval, current dimension indices, current dimension counts, and current dimension intervals. The values read are put into an CDFData object. Although this method returns a CDFData object, it is not necessary to capture the return value to a CDFData variable.

Let's assume that variable TestData is defined to be 2-dimensional (3x2 - 3 rows and 2 columns). The following example writes the entire record (containing 6 elements) to the first, second, and third records:

```
long [][][] testData = {{{10,20},{30,40},{50, 60}},
    {{15,25},{45,55},{75, 85}}
    {{90,95},{96,97},{2147483648L,4294967295L}}
    };
testData.putHyperData (0L, 3L, 1L,
    new long[] {0, 0},
    new long[] {3, 2},
    new long[] {1, 1}, testData);
```

The following example will write the first two rows of testData to the first, third, and fifth records:

```
testData.putHyperData (0L, 3L, 2L,
                        new long[] {0, 0},
                        new long[] {2, 2},
                        new long[] {1, 1}, testData);
```

Parameters:

- recNum - the record number at which data write begins
- recCount - the number of records to write
- recInterval - the number of records to skip between writes
- dimIndices - the dimension index within a record at which data write begins
- dimCounts - the number of elements to write from dimIndices
- dimIntervals - the number of elements to skip between writes
- data - the data to be written

Returns:

CDFData object that contains the variable data specified by recNum, recCount, recInterval, dimIndices, dimCounts, and dimIntervals as well as the information passed to this method plus the number of dimensions and the number of elements for this variable.

Throws:

- CDFException - if there was a problem writing data

putRecords

```
public CDFData putRecords(long startRec,
                          long recCount,
                          java.lang.Object data)
    throws CDFException
```

Writes a number of records from the current z variable. The values are written from the starting record number. Although this method returns a CDFData object, it is not necessary to capture the return value to a CDFData variable.

Let's assume that variable TestData is defined to be 2-dimensional (3x2 - 3 rows and 2 columns). The following example writes three records to the variable as the first, second, and third record:

```
long [][][] testData = {{{10,20},{30,40},{50, 60}},
                        {{15,25},{45,55},{75, 85}},
                        {{90,95},{96,97},{2147483648L,4294967295L}}
                        };
testData.putRecords (0L, 3L, testData);
```

Parameters:

- startRec - the starting record number at which data write begins
- recCount - the number of records to write
- data - the data to be written

Returns:

CDFData object that contains the variable data specified by recNum, recCount, recInterval, dimIndices, dimCounts, and dimIntervals as well as the information passed to this method plus the number of dimensions and the number of elements for this variable.

Throws:

`CDFException` - if there was a problem writing data

getMyCDF

```
public CDF getMyCDF()
```

Gets the CDF object to which this variable belongs.

Returns:

the CDF object to which this variable belongs

getCompressionType

```
public long getCompressionType()
```

Gets the compression type of this variable.

Returns:

the compression type of this variable

getCompressionPct

```
public long getCompressionPct()
```

Gets the compression percentage rate of this variable.

Returns:

the compression percentage rate of this variable

getCompressionParms

```
public long[] getCompressionParms()
```

Sets the compression parameters of this variable. This is only applicable for the GZIP compression method.

Returns:

the compression parameters of this variable

setCompression

```
public void setCompression(long cType,
                           long[] cParms)
    throws CDFException
```

Sets the compression type and parameters for this variable.

Parameters:

`cType` - the compression type

`cParms` - the compression parameters that go with `cType`

Throws:

`CDFException` - if a problem occurs setting compression type and parameters

getCompression

```
public java.lang.String getCompression()  
                        throws CDFException
```

Gets the string representation of the compression type and parameters set for this variable.

Returns:

the string representation of the compression type and parameters for this variable

Throws:

`CDFException` - if a problem occurs getting the compression type and parameters

getNumDims

```
public long getNumDims()
```

Gets the number of dimensions for this variable.

Returns:

the number of dimensions for this variable

getDimSizes

```
public long[] getDimSizes()
```

Gets the dimensions size of this variable.

Returns:

the dimension size of this variable

getNumElements

```
public long getNumElements()
```

Gets the number of elements for this variable. For `CDF_CHAR` and `CDF_UCHAR` this is the number of characters in the string. For all other types this defaults to 1.

Returns:

the number of elements for this variable

getName

```
public java.lang.String getName()
```

Gets the name of this variable.

Specified by:

`getName` in interface `CDFObject`

Returns:

the name of this variable

getID

`public long getID()`

Gets the ID of this variable.

Returns:

the ID of this variable

toString

`public java.lang.String toString()`

Gets the name of this variable.

Overrides:

`toString` in class `java.lang.Object`

Returns:

the name of this variable

setRecVariance

`public void setRecVariance(long recVariance)
throws CDFException`

Sets the record variance for this variable.

Parameters:

`recVariance` - the record variance that should be either VARY or NOVARY.

Throws:

`CDFException` - if a problem occurs setting the record variance

getRecVariance

`public boolean getRecVariance()`

Gets the value of record variance.

Returns:

True if this variable is record varying, False otherwise

setDimVariances

```
public void setDimVariances(long[] dimVariances)
    throws CDFException
```

Sets the dimension variances for this variable.

Parameters:

dimVariances - the dimension variances for this variable

Throws:

CDFException - if a problem occurs setting the dimension variances

getDimVariances

```
public long[] getDimVariances()
```

Gets the dimension variances for this variable.

Returns:

the dimension variances for this variable

getDataType

```
public long getDataType()
```

Gets the CDF data type of this variable.

Returns:

the CDF data type of this variable

deleteRecords

```
public void deleteRecords(long firstRec,
    long lastRec)
    throws CDFException
```

Deletes a range of records from this variable. While non-sparse variable records after the last deleted record will be renumbered, the sparse variable records will not.

Parameters:

firstRec - the first record to be deleted

lastRec - the last record to be deleted

Throws:

CDFException - if a problem occurs deleting records

deleteRecordsRenumber

```
public void deleteRecordsRenumber(long firstRec,
    long lastRec)
    throws CDFException
```

Deletes a range of records from this variable. All records after the last deleted record are renumbered for both the sparse or non-sparse variable after the deletion.

Parameters:

firstRec - the first record to be deleted

lastRec - the last record to be deleted

Throws:

CDFException - if a problem occurs deleting records

allocateBlock

```
public void allocateBlock(long firstRec,
                        long lastRec)
    throws CDFException
```

Allocates a range of records for this variable.

Parameters:

firstRec - the first record to be allocated

lastRec - the last record to be allocated

Throws:

CDFException - if a problem occurs allocating records

allocateRecords

```
public void allocateRecords(long num0toRecords)
    throws CDFException
```

Allocates a number of records, starting from record number 0.

Parameters:

num0toRecords - the number of records to be allocated

Throws:

CDFException - if a problem occurs allocating records

getNumWrittenRecords

```
public long getNumWrittenRecords()
    throws CDFException
```

Gets the number of records physically written (not allocated) for this variable.

Returns:

the number of records written physically

Throws:

CDFException - if a problem occurs getting the number of records written physically

getMaxWrittenRecord

```
public long getMaxWrittenRecord()  
    throws CDFException
```

Gets the last written record number, beginning with 0.

Returns:

the last written record number

Throws:

CDFException - if a problem occurs getting the last written record number

getNumAllocatedRecords

```
public long getNumAllocatedRecords()  
    throws CDFException
```

Gets the number of records allocated for this variable.

Returns:

the number of records allocated

Throws:

CDFException - if a problem occurs getting the number of records allocated

getMaxAllocatedRecord

```
public long getMaxAllocatedRecord()  
    throws CDFException
```

Gets the maximum allocated record number for this variable.

Returns:

the maximum allocated record number

Throws:

CDFException - if a problem occurs getting the maximum allocated record number

setPadValue

```
public void setPadValue(java.lang.Object padValue)  
    throws CDFException
```

Sets the pad value for this variable. This pad value is used, when storing data, for undefined values.

Parameters:

padValue - the pad value to be used for undefined values

Throws:

CDFException - if a problem occurs setting the pad value

checkPadValueExistence

```
public boolean checkPadValueExistence()
```

throws `CDFException`

Checks if the pad value has been defined for this variable.

Returns:

Whether the user-defined pad value exists. It is either true or false.

- true - pad value has been specified.
- false - pad value is not specified.

Throws:

`CDFException` - if a problem occurs checking the existence of the pad value Note: The `getPadValue()` method will return a pad value, whether it is the user defined or the default.

getPadValue

```
public java.lang.Object getPadValue()  
                        throws CDFException
```

Gets the pad value for this variable.

Returns:

the pad value set for this variable

Throws:

`CDFException` - if a problem occurs reading the pad value

setSparseRecords

```
public void setSparseRecords(long sparseRecords)  
                        throws CDFException
```

Sets the sparse record type for this variable.

Parameters:

`sparseRecords` - sparse record type that should be one of the following types:

- NO_SPARSERECORDS - The variable doesn't have sparse records.
- PAD_SPARSERECORDS - The variable has pad-missing records.
- PREV_SPARSERECORDS - The variable has previous-missing records.

Throws:

`CDFException` - if a problem occurs setting the sparse record type

getSparseRecords

```
public long getSparseRecords()
```

Gets the sparse record type for this variable.

Returns:

one of the following sparse record type is returned:

- NO_SPARSERECORDS - means that no sparse records are defined
- PAD_SPARSERECORDS - means that the variable's pad value is used when reading values from a missing record
- PREV_SPARSERECORDS - means that values from the previous existing records are used when reading values from a missing record

setBlockingFactor

```
public void setBlockingFactor(long blockingFactor)
    throws CDFException
```

Sets the blocking factor for this variable. The blocking factor has no effect for Non-Record varying (NRV) variables or multi-file CDFs.

Parameters:

blockingFactor - the blocking factor - a value of zero (0) indicates that the default blocking factor should be used

Throws:

CDFException - if a problem occurs setting the blocking factor

getBlockingFactor

```
public long getBlockingFactor()
    throws CDFException
```

Gets the blocking factor for this variable.

Returns:

the blocking factor set this variable

Throws:

CDFException - if a problem occurs getting the blocking factor set for this variable

setInitialRecords

```
public void setInitialRecords(long nRecords)
    throws CDFException
```

Sets the number of records to be written initially for this variable.

Parameters:

nRecords - the number of records to be written initially

Throws:

CDFException - if a problem occurs writing initial records

selectCacheSize

```
public void selectCacheSize(long cacheSize)
    throws CDFException
```

Sets the number of 512-byte cache buffers to be used. This operation is not applicable for a single-file CDF.

Parameters:

cacheSize - the number of 512-byte cache buffers

Throws:

CDFException - if a problem occurs allocating cache buffers

confirmCacheSize

```
public long confirmCacheSize()  
    throws CDFException
```

Gets the number of 512-byte cache buffers defined for this variable.

Returns:

the number of 512-byte cache buffers set for this variable

Throws:

`CDFException` - if a problem occurs getting the number of cache buffers set for this variable

selectReservePercent

```
public void selectReservePercent(long reservePercent)  
    throws CDFException
```

Sets the reserve percentage to be used for this variable. This operation is only applicable to compressed z Variables. The Concepts chapter in the CDF User's Guide describes the reserve percentage scheme used by the CDF library.

Parameters:

`reservePercent` - the reserve percentage to be used

Throws:

`CDFException` - if a problem occurs setting a reserve percentage

confirmReservePercent

```
public long confirmReservePercent()  
    throws CDFException
```

Gets the reserve percentage set for this variable. This operation is only applicable to compressed z Variables.

Returns:

the reserve percentage set for this variable

Throws:

`CDFException` - if a problem occurs getting the reserve percentage

confirmPadValue

```
public long confirmPadValue()  
    throws CDFException
```

Checks the existence of an explicitly specified pad value for the current z variable. If an explicit pad value has not been specified, the informational status code `NO_PADVALUE_SPECIFIED` is returned. Otherwise, `CDF_OK` is returned.

Returns:

Existence of pad value. If no pad value is specified for this variable, `NO_PADVALUE_SPECIFIED` is returned. If a pad value has been specified, then `CDF_OK` is returned.

Throws:

`CDFException` - if a problem occurs checking the existence of pad value. Note: for `NO_PADVALUE_SPECIFIED`, `getPadValue` method will return the default pad value.

getAllocatedFrom

```
public long getAllocatedFrom(long recNum)
                        throws CDFException
```

Inquires the next allocated record at or after a given record for this variable.

Parameters:

`recNum` - The record number at which to begin searching for the next allocated record. If this record exists, it will be considered the next allocated record.

Returns:

the number of the next allocated record

Throws:

`CDFException` - if a problem occurs getting the number of the next allocated record

getAllocatedTo

```
public long getAllocatedTo(long firstRec)
                        throws CDFException
```

Inquires the last allocated record (before the next unallocated record) at or after a given record for this variable.

Parameters:

`firstRec` - the record number at which to begin searching for the last allocated record

Returns:

the number of the last allocated record

Throws:

`CDFException` - if a problem occurs getting the number of the last allocated record

updateDataSpec

```
public void updateDataSpec(long dataType,
                          long numElements)
                        throws CDFException
```

Update the data specification (data type and number of elements) of the variable.

Parameters:

`dataType` - the data type of the entry data
`numElements` - the number of elements fo the entry data

Throws:

`CDFException` - An exception is thrown if the operation fails

getAttributes

```
public java.util.Vector getAttributes()
```

Returns the variable attributes that are associated with this variable.

The following example describes how to retrieve all the variable attributes that are associated with a particular variable.

```
Variable v = cdf.getVariable("myVariable");
Vector attrs = v.getAttributes();
if (attrs.size() > 0) {
    for (Enumeration e=attrs.elements(); e.hasMoreElements();) {
        Attribute a = (Attribute) e.nextElement();
        // manipulate the attribute
    }
}
```

Returns:

Returns the variable attributes that are associated with this variable.

getAttributesandEntries

```
public java.util.Map getAttributesandEntries()
```

Returns the variable attributes and their entries that are associated with this variable.

The following example describes how to retrieve all the variable attributes and their entries that are associated with a particular variable.

```
Variable v = cdf.getVariable("myVariable");
Map vaes = v.getAttributesandEntries();
if (vaes != null) {
    for (Object key : vaes.keySet()) {
        System.out.println("Attribute:"+key+" entry:"+vaes.get(key));
    }
}
```

Note: Each attribute's entry, an object, can be a single data or an array of values. CDF Epoch type data will be encoded in date/time string.

Returns:

Returns a Map object that contains variable attribute names as keys and entries as values that are associated with this variable. All keys and values are in object type. If there is no attribute, then null is returned;

getAttributesandEntries

```
public java.util.Map getAttributesandEntries(boolean encoding)
```

Returns the variable attributes and their entries that are associated with this variable.

The following example describes how to retrieve all the variable attributes and their entries that are associated with a particular variable.

```
Variable v = cdf.getVariable("myVariable");
Map vaes = v.getAttributesandEntries(true);
if (vaes != null) {
    for (Object key : vaes.keySet()) {
        System.out.println("Attribute:"+key+" entry:"+vaes.get(key));
    }
}
```

Note: Each attribute's entry, an object, can be a single data or an array of values.

Parameters:

`encoding` - A true/false flag indicates whether to encode epoch type data to date/time string.

Returns:

Returns a Map object that contains variable attribute names as keys and entries as values that are associated with this variable. All keys and values are in object type. If there is no attribute, then null is returned;

dumpDataWithFormat

```
public void dumpDataWithFormat(java.lang.Object data)
```

Dump the data, either the variable value or metadata, with or without the format. The format comes from the FORMAT variable attribute.

Parameters:

`data` - An object, likely an attribute entry, for output

dumpDataWithFormat

```
public void dumpDataWithFormat(java.lang.Object data,
                               java.io.PrintWriter outWriter)
```

Dump the data, either the variable value or metadata, with or without the format. The format comes from the FORMAT variable attribute.

Parameters:

`data` - An object, likely an attribute entry, for output
`outWriter` - the print writer to which formatted representations of the object/data is printed as a text-output stream

dumpDataWithFormat

```
public void dumpDataWithFormat(CDFData data)
```

Dump the data, either the variable value or metadata, with the format. The format comes from the FORMAT variable attribute.

Parameters:

`data` - A CDFData object, likely variable data, for output

Overview	Package	Class	Tree	Deprecated	Index	Help		
Prev	Next	Frames	No Frames	All Classes				

Hierarchy For All Packages

Package Hierarchies:
gsfc.nssdc.cdf, gsfc.nssdc.cdf.util

Class Hierarchy

- java.lang.Object
 - gsfc.nssdc.cdf.Attribute (implements gsfc.nssdc.cdf.CDFConstants, gsfc.nssdc.cdf.CDFObject)
 - gsfc.nssdc.cdf.CDF (implements gsfc.nssdc.cdf.CDFConstants, gsfc.nssdc.cdf.CDFObject)
 - gsfc.nssdc.cdf.CDFData (implements gsfc.nssdc.cdf.CDFConstants, gsfc.nssdc.cdf.CDFObject)
 - gsfc.nssdc.cdf.CDFNativeLibrary (implements gsfc.nssdc.cdf.CDFDelegate)
 - gsfc.nssdc.cdf.CDFTools (implements gsfc.nssdc.cdf.CDFConstants)
 - gsfc.nssdc.cdf.util.CDFTT2000 (implements gsfc.nssdc.cdf.CDFConstants)
 - gsfc.nssdc.cdf.util.CDFUtils (implements gsfc.nssdc.cdf.CDFConstants)
 - gsfc.nssdc.cdf.Entry (implements gsfc.nssdc.cdf.CDFConstants, gsfc.nssdc.cdf.CDFObject)
 - gsfc.nssdc.cdf.util.Epoch (implements gsfc.nssdc.cdf.CDFConstants)
 - gsfc.nssdc.cdf.util.Epoch16 (implements gsfc.nssdc.cdf.CDFConstants)
 - gsfc.nssdc.cdf.util.EpochNative
 - java.lang.Throwable (implements java.io.Serializable)
 - java.lang.Exception
 - gsfc.nssdc.cdf.CDFException (implements gsfc.nssdc.cdf.CDFConstants)
 - gsfc.nssdc.cdf.Variable (implements gsfc.nssdc.cdf.CDFConstants, gsfc.nssdc.cdf.CDFObject)

Interface Hierarchy

- gsfc.nssdc.cdf.CDFConstants
- gsfc.nssdc.cdf.CDFDelegate
- gsfc.nssdc.cdf.CDFObject

Overview	Package	Class	Tree	Deprecated	Index	Help		
Prev	Next	Frames	No Frames	All Classes				

Overview	Package	Class	Tree	Deprecated	Index	Help		
Prev	Next	Frames	No Frames	All Classes				

Deprecated API

Contents

Deprecated Methods

Deprecated Methods
Method and Description
gsfc.nssdc.cdf.CDF.create(String, int) <i>Use setFileBackward(long) method to set the file backward flag and create(String) to create file instead.</i>

Overview	Package	Class	Tree	Deprecated	Index	Help		
Prev	Next	Frames	No Frames	All Classes				

A B C D E F G H I L M N O P R S T U V Z

A

AHUFF_COMPRESSION - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ALL_VALUES - Static variable in class [gsfc.nssdc.cdf.CDFTools](#)

allocateBlock(long, long) - Method in class [gsfc.nssdc.cdf.Variable](#)

Allocates a range of records for this variable.

allocateRecords(long) - Method in class [gsfc.nssdc.cdf.Variable](#)

Allocates a number of records, starting from record number 0.

ALPHAOSF1_DECODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ALPHAOSF1_ENCODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ALPHAVMSd_DECODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ALPHAVMSd_ENCODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ALPHAVMSg_DECODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ALPHAVMSg_ENCODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ALPHAVMSi_DECODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ALPHAVMSi_ENCODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ARM_BIG_DECODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ARM_BIG_ENCODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ARM_LITTLE_DECODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ARM_LITTLE_ENCODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ATTR_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ATTR_EXISTENCE_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ATTR_EXISTS - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ATTR_MAXgENTRY_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ATTR_MAXrENTRY_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ATTR_MAXzENTRY_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ATTR_NAME_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ATTR_NAME_TRUNC - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ATTR_NUMBER_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ATTR_NUMgENTRIES_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ATTR_NUMrENTRIES_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ATTR_NUMzENTRIES_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

ATTR_SCOPE_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

Attribute - Class in [gsfc.nssdc.cdf](#)

This class contains the methods that are associated with either global or variable attributes.

B

BACKWARD_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BACKWARDFILEoff - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BACKWARDFILEon - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_ALLOCATE_RECS - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_ARGUMENT - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_ATTR_NAME - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_ATTR_NUM - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_BLOCKING_FACTOR - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_CACHE_SIZE - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_CDF_EXTENSION - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_CDF_ID - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_CDF_NAME - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_CDFSTATUS - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_CHECKSUM - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_COMPRESSION_PARM - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_DATA_TYPE - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_DECODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_DIM_COUNT - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_DIM_INDEX - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_DIM_INTERVAL - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_DIM_SIZE - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_ENCODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_ENTRY_NUM - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

BAD_FNC_OR_ITEM - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

- BAD_FORMAT** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_INITIAL_RECS** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_MAJORITY** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_MALLOC** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_NEGtoPOSfp0_MODE** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_NUM_DIMS** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_NUM_ELEMS** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_NUM_STRINGS** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_NUM_VARS** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_READONLY_MODE** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_REC_COUNT** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_REC_INTERVAL** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_REC_NUM** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_SCOPE** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_SCRATCH_DIR** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_SPARSEARRAYS_PARM** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_VAR_NAME** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_VAR_NUM** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BAD_zMODE** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BADDATE_LEAPSECOND_UPDATED** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BeginUnixTimeEPOCH** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BeginUnixTimeEPOCH16** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BLOCKINGFACTOR_TOO_LARGE** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BLOCKINGFACTOR_TOO_SMALL** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- BLOCKINGFACTOR_TOO_SMALL2** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- breakdown(long)** - Static method in class `gsfc.nssdc.cdf.util.CDFTT2000`
 - Breaks a TT2000 epoch value down into its full, UTC-based date/time component parts.
- breakdown(long[])** - Static method in class `gsfc.nssdc.cdf.util.CDFTT2000`
 - Breaks an array of TT2000 epoch values down into two dimensional array, the first dimension being the count of the epoch values, and the second dimension being their full, UTC-based date/time component parts for each value.
- breakdown(double)** - Static method in class `gsfc.nssdc.cdf.util.Epoch`
 - Breaks an EPOCH value down into its component parts.
- breakdown(double[])** - Static method in class `gsfc.nssdc.cdf.util.Epoch`
 - Breaks an array of EPOCH values down into its component parts.
- breakdown(Object)** - Static method in class `gsfc.nssdc.cdf.util.Epoch16`

Breaks an EPOCH16 value down into its component parts.

breakdown(double) - Static method in class [gsfc.nssdc.cdf.util.EpochNative](#)

Mirrors EPOCHbreakdown from the CDF library.

breakdownTT2000(long) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Breaks a TT2000 epoch value down into its full, UTC-based date/time component parts - new name as toUTCparts.

breakdownTT2000withBasedLeapDay(long, int) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

breakdownTT2000withBasedLeapDay.

breakIntoStrings(String) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Break down a merged string into their original array of strings.

C

CANNOT_ALLOCATE_RECORDS - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CANNOT_CHANGE - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CANNOT_COMPRESS - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CANNOT_CONVERT_WIDECHAR - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CANNOT_COPY - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CANNOT_INSERT_RECORDS - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CANNOT_SPARSEARRAYS - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CANNOT_SPARSERECORDS - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF - Class in [gsfc.nssdc.cdf](#)

The CDF class is the main class used to interact with a CDF file.

CDF_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_ACCESS_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_ATTR_NAME_LEN - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_ATTR_NAME_LEN256 - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_BYTE - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_CACHESIZE_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_CHAR - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_CHECKSUM_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_CLOSE_ERROR - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_COMPRESSION_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_COPYRIGHT_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_COPYRIGHT_LEN - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_CREATE_ERROR - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_DECODING_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_DELETE_ERROR - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

- CDF_DOUBLE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_ENCODING_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_EPOCH** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_EPOCH16** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_EXISTS** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_FLOAT** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_FORMAT_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_INCREMENT_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_INFO_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_INT1** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_INT2** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_INT4** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_INT8** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_INTERNAL_ERROR** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_LEAPSECONDLASTUPDATED_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_MAJORITY_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_MAX_DIMS** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_MAX_PARMS** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_MIN_DIMS** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_NAME_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_NAME_TRUNC** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_NEGtoPOSfp0_MODE_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_NUMATTRS_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_NUMgATTRS_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_NUMrVARS_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_NUMvATTRS_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_NUMzVARS_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_OK** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_OPEN_ERROR** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- CDF_PATHNAME_LEN** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_READ_ERROR - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_READONLY_MODE_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_REAL4 - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_REAL8 - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_RELEASE_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_SAVE_ERROR - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_SCRATCHDIR_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_STATUS_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_STATUSTEXT_LEN - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_TIME_TT2000 - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_UCHAR - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_UINT1 - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_UINT2 - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_UINT4 - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_VAR_NAME_LEN - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_VAR_NAME_LEN256 - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_VERSION_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_WARN - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_WRITE_ERROR - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDF_zMODE_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CDFConstants - Interface in [gsfc.nssdc.cdf](#)

This class defines the constants used by the CDF library and CDF Java APIs, and it mimics the `cdf.h` include file from the cdf distribution.

CDFData - Class in [gsfc.nssdc.cdf](#)

This class acts as the glue between the Java code and the Java Native Interface (JNI) code.

CDFDelegate - Interface in [gsfc.nssdc.cdf](#)

This class defines the method that is responsible for acting as the gateway between the CDF Java code and the CDF library.

CDFException - Exception in [gsfc.nssdc.cdf](#)

This class defines the informational, warning, and error messages that can arise from CDF operations.

CDFException(String) - Constructor for exception [gsfc.nssdc.cdf.CDFException](#)

Takes a text message from the calling program and throws a CDFException.

CDFException(long) - Constructor for exception [gsfc.nssdc.cdf.CDFException](#)

Takes a status code and throws a CDFException with the message that corresponds to the status code that is passed in.

CDFException(long, String) - Constructor for exception [gsfc.nssdc.cdf.CDFException](#)

Takes a status code and throws a CDFException with the message that corresponds to the status code that is passed in.

cdfFileExists(String) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Checks the existence of the given CDF file name.

CDFgetLastDateInLeapSecondsTable() - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

/** This method returns the last UTC date that a leap second was added in the leap second table used in the class.

CDFgetLeapSecondsTable() - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

This method returns the leap seconds table.

CDFgetLeapSecondsTableStatus() - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

This method returns the status code reflecting whether the leap seconds are from a external file, defined by an environment variable, or the leap seconds are based on the hard-coded table in the class.

CDFgetRowsinLeapSecondsTable() - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

This method returns the number of entries in the leap seconds table.

cdflib(CDF, CDFObject, Vector) - Method in interface [gsfc.nssdc.cdf.CDFDelegate](#)

Defines the method that is responsible for acting as the gateway between the CDF Java code and the CDF library.

cdflib(CDF, CDFObject, Vector) - Method in class [gsfc.nssdc.cdf.CDFNativeLibrary](#)

Calls the Java Native Interface (JNI) program, [cdfNativeLibrary.c](#).

CDFNativeLibrary - Class in [gsfc.nssdc.cdf](#)

This class implements the method that act as the gateway between the CDF Java APIs and the CDF library.

CDFNativeLibrary() - Constructor for class [gsfc.nssdc.cdf.CDFNativeLibrary](#)

CDFObject - Interface in [gsfc.nssdc.cdf](#)

CDFObject provides the base interface for all CDF objects.

CDFTools - Class in [gsfc.nssdc.cdf](#)

CDFTools.java Created: Tue Nov 24 16:14:50 1998

CDFTools() - Constructor for class [gsfc.nssdc.cdf.CDFTools](#)

CDFTT2000 - Class in [gsfc.nssdc.cdf.util](#)

This class contains the handy utility routines (methods) called by the CDF applications to handle epoch data of CDF's CDF_TIME_TT2000 data type.

CDFTT2000() - Constructor for class [gsfc.nssdc.cdf.util.CDFTT2000](#)

CDFUtils - Class in [gsfc.nssdc.cdf.util](#)

This class contains the handy utility routines (methods) called by the core CDF Java APIs.

CDFUtils() - Constructor for class [gsfc.nssdc.cdf.util.CDFUtils](#)

CDFwithSTATS_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CFtoJformat(String) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Convert a C/Fortran-based print format to a corresponding Java style format for numerical data.

checkPadValueExistence() - Method in class [gsfc.nssdc.cdf.Variable](#)

Checks if the pad value has been defined for this variable.

CHECKSUM_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CHECKSUM_ERROR - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CHECKSUM_NOT_ALLOWED - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

close() - Method in class [gsfc.nssdc.cdf.CDF](#)

Closes this CDF file.

CLOSE_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

COLUMN_MAJOR - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

COMPRESS_CACHESIZE_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

COMPRESSION_ERROR - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

compute(long, long, long, long, long, long, long, long, long, long) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.

compute(long[], long[], long[]) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Computes an array of TT2000 epochs, nanoseconds since J2000, based on its UTC-based date/time component parts.

compute(long[], long[], long[], long[]) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Computes an array of TT2000 epochs, nanoseconds since J2000, based on its UTC-based date/time component parts.
compute(long[], long[], long[], long[], long[]) - Static method in class gsfc.nssdc.cdf.util.CDFTT2000

Computes an array of TT2000 epochs, nanoseconds since J2000, based on its * UTC-based date/time component parts.
compute(long[], long[], long[], long[], long[], long[]) - Static method in class gsfc.nssdc.cdf.util.CDFTT2000

Computes an array of TT2000 epochs, nanoseconds since J2000, based on its * UTC-based date/time component parts.
compute(long[], long[], long[], long[], long[], long[], long[]) - Static method in class gsfc.nssdc.cdf.util.CDFTT2000

Computes an array of TT2000 epochs, nanoseconds since J2000, based on its * UTC-based date/time component parts.
compute(long[], long[], long[], long[], long[], long[], long[], long[]) - Static method in class gsfc.nssdc.cdf.util.CDFTT2000

Computes an array of TT2000 epochs, nanoseconds since J2000, based on its * UTC-based date/time component parts.
compute(long[], long[], long[], long[], long[], long[], long[], long[], long[], long[]) - Static method in class gsfc.nssdc.cdf.util.CDFTT2000

Computes an array of TT2000 epochs, nanoseconds since J2000, based on its * UTC-based date/time component parts.
compute(long, long, long, long, long, long, long, long) - Static method in class gsfc.nssdc.cdf.util.Epoch

Computes an EPOCH value based on its component parts.
compute(long[], long[], long[]) - Static method in class gsfc.nssdc.cdf.util.Epoch

Computes an array of EPOCH values based on their component parts.
compute(long[], long[], long[], long[]) - Static method in class gsfc.nssdc.cdf.util.Epoch

Computes an array of EPOCH values based on their component parts.
compute(long[], long[], long[], long[], long[]) - Static method in class gsfc.nssdc.cdf.util.Epoch

Computes an array of EPOCH values based on their component parts.
compute(long[], long[], long[], long[], long[], long[]) - Static method in class gsfc.nssdc.cdf.util.Epoch

Computes an array of EPOCH values based on their component parts.
compute(long[], long[], long[], long[], long[], long[], long[]) - Static method in class gsfc.nssdc.cdf.util.Epoch

Computes an array of EPOCH values based on their component parts.
compute(long[], long[], long[], long[], long[], long[], long[], long[]) - Static method in class gsfc.nssdc.cdf.util.Epoch

Computes an array of EPOCH values based on their component parts.
compute(long, long, long, long, long, long, long, long, long, long, long, Object) - Static method in class gsfc.nssdc.cdf.util.Epoch16

Computes an EPOCH16 value based on its component parts.
compute(long, long, long, long, long, long, long, long) - Static method in class gsfc.nssdc.cdf.util.EpochNative

Mirrors computeEPOCH from the CDF library.
computeTT2000(double, double, double) - Static method in class gsfc.nssdc.cdf.util.CDFTT2000

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
computeTT2000(double, double, double, double) - Static method in class gsfc.nssdc.cdf.util.CDFTT2000

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
computeTT2000(double, double, double, double, double) - Static method in class gsfc.nssdc.cdf.util.CDFTT2000

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
computeTT2000(double, double, double, double, double, double) - Static method in class gsfc.nssdc.cdf.util.CDFTT2000

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
computeTT2000(double, double, double, double, double, double, double) - Static method in class gsfc.nssdc.cdf.util.CDFTT2000

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
computeTT2000(double, double, double, double, double, double, double, double) - Static method in class gsfc.nssdc.cdf.util.CDFTT2000

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
computeTT2000(double, double, double, double, double, double, double, double, double) - Static method in class gsfc.nssdc.cdf.util.CDFTT2000

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.
computeTT2000(double, double, double, double, double, double, double, double, double, double) - Static method in class gsfc.nssdc.cdf.util.CDFTT2000

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts - a new name from fromUTCparts.
computeTT2000withBasedLeapDay(long, long, long, long, long, long, long, long, long, long, long, int) - Static method in class gsfc.nssdc.cdf.util.CDFTT2000

This method returns the TT2000 time in nanoseconds based on the last leap second day.
computeTT2000withBasedLeapDay(double, double, double, double, double, double, double, double, double, double, int) - Static method in class gsfc.nssdc.cdf.util.CDFTT2000

This method returns the TT2000 time in nanoseconds based on the last leap second day.
concatenateDataRecords(Variable) - Method in class gsfc.nssdc.cdf.Variable

Concatenates this variable's data records to the destination variable.
CONFIRM_ - Static variable in interface gsfc.nssdc.cdf.CDFConstants

confirmCacheSize() - Method in class gsfc.nssdc.cdf.Variable

Gets the number of 512-byte cache buffers defined for this variable.

confirmCDFCacheSize() - Method in class [gsfc.nssdc.cdf.CDF](#)

Gets the CDF cache size (the number of 512-byte cache buffers) set for this CDF.

confirmCompressCacheSize() - Method in class [gsfc.nssdc.cdf.CDF](#)

Gets the number of 512-byte cache buffers being used for the compression scratch file (for the current CDF).

confirmDecoding() - Method in class [gsfc.nssdc.cdf.CDF](#)

Gets the CDF decoding method defined for this CDF.

confirmNegtoPosfp0() - Method in class [gsfc.nssdc.cdf.CDF](#)

Gets the -0.0 to 0.0 translation flag set for this CDF.

confirmPadValue() - Method in class [gsfc.nssdc.cdf.Variable](#)

Checks the existence of an explicitly specified pad value for the current z variable.

confirmReadOnlyMode() - Method in class [gsfc.nssdc.cdf.CDF](#)

Gets the value of the read-only mode flag set for this CDF file.

confirmReservePercent() - Method in class [gsfc.nssdc.cdf.Variable](#)

Gets the reserve percentage set for this variable.

confirmStageCacheSize() - Method in class [gsfc.nssdc.cdf.CDF](#)

Gets the number of 512-byte cache buffers defined for the staging scratch file.

confirmzMode() - Method in class [gsfc.nssdc.cdf.CDF](#)

Gets the zMode set for this CDF.

copy(String) - Method in class [gsfc.nssdc.cdf.Variable](#)

Copies this variable to a new variable.

copy(CDF, String) - Method in class [gsfc.nssdc.cdf.Variable](#)

Copies this variable into a new variable and puts it into the designated CDF file.

copyDataRecords(Variable) - Method in class [gsfc.nssdc.cdf.Variable](#)

Copies this variable's data to the destination variable.

CORRUPTED_V2_CDF - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CORRUPTED_V3_CDF - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

Cp1252toUTF8(Object) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

create(CDF, String, long) - Static method in class [gsfc.nssdc.cdf.Attribute](#)

Creates a new attribute in the given CDF.

create(String) - Static method in class [gsfc.nssdc.cdf.CDF](#)

Creates a CDF file in the current directory.

create(String, int) - Static method in class [gsfc.nssdc.cdf.CDF](#)

Deprecated.

Use [setFileBackward\(long\)](#) method to set the file backward flag and [create\(String\)](#) to create file instead.

create(Attribute, long, long, Object) - Static method in class [gsfc.nssdc.cdf.Entry](#)

Creates a new global or variable attribute entry.

create(CDF, String, long, long, long[], long, long[]) - Static method in class [gsfc.nssdc.cdf.Variable](#)

Creates a variable.

CREATE_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CtoJformat(String) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Convert a C-based print format to a corresponding Java style format for numerical data.

CURgENTRY_EXISTENCE_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CURrENTRY_EXISTENCE_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

CURzENTRY_EXISTENCE_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

D

DATATYPE_MISMATCH - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

DATATYPE_SIZE_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

- DECOMPRESSION_ERROR** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DECSTATION_DECODING** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DECSTATION_ENCODING** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_BYTE_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_CHAR_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_DOUBLE_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_EPOCH16_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_EPOCH_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_FLOAT_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_INT1_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_INT2_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_INT4_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_INT8_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_REAL4_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_REAL8_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_TT2000_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_UCHAR_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_UINT1_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_UINT2_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- DEFAULT_UINT4_PADVALUE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- delete()** - Method in class [gsfc.nssdc.cdf.Attribute](#)
 - Deletes this attribute.
- delete()** - Method in class [gsfc.nssdc.cdf.CDF](#)
 - Deletes this CDF file.
- delete()** - Method in class [gsfc.nssdc.cdf.CDFData](#)
 - See the description of the [getName\(\)](#) method in this class.
- delete()** - Method in interface [gsfc.nssdc.cdf.CDFObject](#)
 - Deletes the current object.
- delete()** - Method in class [gsfc.nssdc.cdf.Entry](#)
 - Deletes this entry.
- delete()** - Method in class [gsfc.nssdc.cdf.Variable](#)
 - Deletes this variable.
- DELETE_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- deleteEntry(long)** - Method in class [gsfc.nssdc.cdf.Attribute](#)
 - Deletes an attribute entry for the given entry number.
- deleteEntry(Variable)** - Method in class [gsfc.nssdc.cdf.Attribute](#)
 - Deletes the attribute entry for the given variable.

deleteRecords(long, long) - Method in class [gsfc.nssdc.cdf.Variable](#)

Deletes a range of records from this variable.

deleteRecordsRenummer(long, long) - Method in class [gsfc.nssdc.cdf.Variable](#)

Deletes a range of records from this variable.

DID_NOT_COMPRESS - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

dump() - Method in class [gsfc.nssdc.cdf.CDFData](#)

Dump data information and values, one row at a time, to the stderr.

dumpData() - Method in class [gsfc.nssdc.cdf.CDFData](#)

Dumps variable data, one row at a time per record.

dumpDataWithFormat(String) - Method in class [gsfc.nssdc.cdf.CDFData](#)

Dumps variable data, one row at a time per record, with format.

dumpDataWithFormat(Object) - Method in class [gsfc.nssdc.cdf.Variable](#)

Dump the data, either the variable value or metadata, with or without the format.

dumpDataWithFormat(Object, PrintWriter) - Method in class [gsfc.nssdc.cdf.Variable](#)

Dump the data, either the variable value or metadata, with or without the format.

dumpDataWithFormat(CDFData) - Method in class [gsfc.nssdc.cdf.Variable](#)

Dump the data, either the variable value or metadata, with the format.

duplicate(String) - Method in class [gsfc.nssdc.cdf.Variable](#)

Duplicates this variable to a new variable.

duplicate(CDF, String) - Method in class [gsfc.nssdc.cdf.Variable](#)

Duplicates this variable and put it into the designated CDF file.

E

EMPTY_COMPRESSED_CDF - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

encode(long[], int) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Converts an array of epoch values in TT2000 type into readable, UTC-based date/time strings of chosen style.

encode(long) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Converts an epoch value in TT2000 type into a readable, UTC-based date/time string in ISO 8601 style.

encode(long[]) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Converts an array of epoch values in TT2000 type into an array of readable, UTC-based date/time strings in ISO 8601 style.

encode(long, int) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of chosen style.

encode(double) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an EPOCH value into a readable date/time string.

encode(double[]) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an array of EPOCH values into an array of readable date/time strings.

encode(Object) - Static method in class [gsfc.nssdc.cdf.util.Epoch16](#)

Converts an EPOCH16 value into a readable date/time string.

encode(double) - Static method in class [gsfc.nssdc.cdf.util.EpochNative](#)

Mirrors encodeEPOCH from the CDF library.

encode1(double) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an EPOCH value into a readable date/time string.

encode1(double[]) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an array EPOCH values into readable date/time strings.

encode1(Object) - Static method in class [gsfc.nssdc.cdf.util.Epoch16](#)

Converts an EPOCH16 value into a readable date/time string.

encode1(double) - Static method in class [gsfc.nssdc.cdf.util.EpochNative](#)

Mirrors encodeEPOCH1 from the CDF library.

encode2(double) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an EPOCH value into a readable date/time string.

encode2(double[]) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an array of EPOCH values into readable date/time strings.

encode2(Object) - Static method in class [gsfc.nssdc.cdf.util.Epoch16](#)

Converts an EPOCH16 value into a readable date/time string.

encode2(double) - Static method in class [gsfc.nssdc.cdf.util.EpochNative](#)

Mirrors encodeEPOCH2 from the CDF library.

encode3(double) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an EPOCH value into a readable date/time string.

encode3(double[]) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an array of EPOCH values into readable date/time strings.

encode3(Object) - Static method in class [gsfc.nssdc.cdf.util.Epoch16](#)

Converts an EPOCH16 value into a readable date/time string.

encode3(double) - Static method in class [gsfc.nssdc.cdf.util.EpochNative](#)

Mirrors encodeEPOCH3 from the CDF library.

encode4(double) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an EPOCH value into a readable date/time, ISO8601 string.

encode4(double[]) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an array of EPOCH values into readable date/time, ISO8601 strings.

encode4(Object) - Static method in class [gsfc.nssdc.cdf.util.Epoch16](#)

Converts an EPOCH16 value into a readable date/time, ISO8601 string.

encode4(double) - Static method in class [gsfc.nssdc.cdf.util.EpochNative](#)

Mirrors encodeEPOCH4 from the CDF library.

encodeTT2000withBasedLeapDay(long, int) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

encodeTT2000withBasedLeapDay.

encodex(double, String) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an EPOCH value into a readable date/time string using the specified format.

encodex(Object, String) - Static method in class [gsfc.nssdc.cdf.util.Epoch16](#)

Converts an EPOCH16 value into a readable date/time string using the specified format.

encodex(double, String) - Static method in class [gsfc.nssdc.cdf.util.EpochNative](#)

Mirrors encodeEPOCHx from the CDF library.

END_OF_VAR - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

Entry - Class in [gsfc.nssdc.cdf](#)

This class describes a CDF global or variable attribute entry.

Epoch - Class in [gsfc.nssdc.cdf.util](#)

This class contains the handy utility routines (methods) called by the CDF applications to handle epoch data of CDF's CDF_EPOCH data type.

Epoch() - Constructor for class [gsfc.nssdc.cdf.util.Epoch](#)

Epoch16 - Class in [gsfc.nssdc.cdf.util](#)

This class contains the handy utility routines (methods) called by the CDF applications to handle epoch data of CDF's CDF_EPOCH16 data type.

Epoch16() - Constructor for class [gsfc.nssdc.cdf.util.Epoch16](#)

Epoch16toUnixTime(double[]) - Static method in class [gsfc.nssdc.cdf.util.Epoch16](#)

Converts an EPOCH16 value to a unix time of a double value (seconds from 1970-01-01 00:00:00 UTC).

EPOCH1_STRING_LEN - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

EPOCH1_STRING_LEN_EXTEND - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

EPOCH2_STRING_LEN - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

EPOCH2_STRING_LEN_EXTEND - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

EPOCH3_STRING_LEN - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

EPOCH3_STRING_LEN_EXTEND - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

EPOCH4_STRING_LEN - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

EPOCH4_STRING_LEN_EXTEND - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

EPOCH_STRING_LEN - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

EPOCH_STRING_LEN_EXTEND - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

EpochNative - Class in [gsfc.nssdc.cdf.util](#)

The Epoch class is a Java wrapper to the CDF epoch handling routines.

EpochNative() - Constructor for class [gsfc.nssdc.cdf.util.EpochNative](#)

EpochtoUnixTime(double) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an EPOCH value to a unix time of a double value (seconds from 1970-01-01 00:00:00 UTC).

EpochtoUnixTime(double[]) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an array of EPOCH values to an array of unix time of a double value (seconds from 1970-01-01 00:00:00 UTC).

EPOCHx_FORMAT_MAX - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

EPOCHx_STRING_MAX - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

F

FILLED_TT2000_VALUE - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

finalize() - Method in class [gsfc.nssdc.cdf.CDF](#)

Do the necessary cleanup when garbage collector reaps it.

FORCED_PARAMETER - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

fromGregorianTime(GregorianCalendar) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

This method converts the UTC-based date/time in a [GregorianCalendar](#) class object to TT2000 time.

fromUTCEPOCH(double) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Convert an epoch value in CDF_EPOCH type to TT2000 type.

fromUTCEPOCH16(double[]) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Convert an epoch data in CDF_EPOCH16 type to TT2000 type.

fromUTCISO8601string(String) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

This method parses an input, UTC-based, date/time string in ISO 8601 and returns their date/time components.

fromUTCparts(double, double, double) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.

fromUTCparts(double, double, double, double) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.

fromUTCparts(double, double, double, double, double) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.

fromUTCparts(double, double, double, double, double, double) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.

fromUTCparts(double, double, double, double, double, double, double) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.

fromUTCparts(double, double, double, double, double, double, double, double) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.

fromUTCparts(double, double, double, double, double, double, double, double, double) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Computes a TT2000 epoch, nanoseconds since J2000, based on its UTC-based date/time component parts.

fromUTCstring(String) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

This method parses an input, UTC-based, date/time string and returns a TT2000 epoch value, nanoseconds since J2000.

FtoJformat(String) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Convert a Fortran-based print format to a corresponding Java style format for numerical data.

FUNCTION_NOT_SUPPORTED - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

G

gENTRY_ - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

gENTRY_DATA_ - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

gENTRY_DATASPEC_ - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

gENTRY_DATATYPE_ - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

gENTRY_EXISTENCE_ - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

gENTRY_NUMELEMS_ - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

GET_ - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

getAllocatedFrom(long) - Method in class `gsfc.nssdc.cdf.Variable`

Inquires the next allocated record at or after a given record for this variable.

getAllocatedTo(long) - Method in class `gsfc.nssdc.cdf.Variable`

Inquires the last allocated record (before the next unallocated record) at or after a given record for this variable.

getAllRecords() - Method in class `gsfc.nssdc.cdf.Variable`

Get all written records, from record number 0 till the last written record number, from this variable.

getAllRecordsObject() - Method in class `gsfc.nssdc.cdf.Variable`

Get all written records, from record number 0 till the last written record number, from this variable.

getAttribute(long) - Method in class `gsfc.nssdc.cdf.CDF`

Gets the attribute for the given attribute number.

getAttribute(String) - Method in class `gsfc.nssdc.cdf.CDF`

Gets the attribute for the given attribute name.

getAttributeID(String) - Method in class `gsfc.nssdc.cdf.CDF`

Gets the id of the given attribute.

getAttributes() - Method in class `gsfc.nssdc.cdf.CDF`

Gets all the global and variable attributes defined for this CDF.

getAttributes() - Method in class `gsfc.nssdc.cdf.Variable`

Returns the variable attributes that are associated with this variable.

getAttributesandEntries() - Method in class `gsfc.nssdc.cdf.Variable`

Returns the variable attributes and their entries that are associated with this variable.

getAttributesandEntries(boolean) - Method in class `gsfc.nssdc.cdf.Variable`

Returns the variable attributes and their entries that are associated with this variable.

getBlockingFactor() - Method in class `gsfc.nssdc.cdf.Variable`

Gets the blocking factor for this variable.

GETCDFCHECKSUM_ - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

GETCDFFILEBACKWARD_ - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

GETCDFVALIDATE_ - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

getChecksum() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the checksum method, if any, applied to the CDF.

getChecksumEnvVar() - Static method in class `gsfc.nssdc.cdf.CDF`

Gets the value of the CDF_CHECKSUM environment variable.

getCompression() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the string representation of the compression type and parameters defined for this CDF.

getCompression() - Method in class `gsfc.nssdc.cdf.Variable`

Gets the string representation of the compression type and parameters set for this variable.

getCompressionParms() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the compression parameters set for this CDF.

getCompressionParms() - Method in class `gsfc.nssdc.cdf.Variable`

Sets the compression parameters of this variable.

getCompressionPct() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the compression percentage set for this CDF.

getCompressionPct() - Method in class `gsfc.nssdc.cdf.Variable`

Gets the compression percentage rate of this variable.

getCompressionType() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the compression type set for this CDF.

getCompressionType() - Method in class `gsfc.nssdc.cdf.Variable`

Gets the compression type of this variable.

getCopyright() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the CDF copyright statement for this CDF.

getCurrentStatus() - Method in exception `gsfc.nssdc.cdf.CDFException`

Gets the status code that caused `CDFException`.

getData() - Method in class `gsfc.nssdc.cdf.CDFData`

Returns an object that is properly dimensioned.

getData() - Method in class `gsfc.nssdc.cdf.Entry`

Gets the data for this entry.

getDataType() - Method in class `gsfc.nssdc.cdf.Entry`

Gets the CDF data type of this entry.

getDataType() - Method in class `gsfc.nssdc.cdf.Variable`

Gets the CDF data type of this variable.

getDataTypeValue(String) - Static method in class `gsfc.nssdc.cdf.util.CDFUtils`

Gets the long value of the given CDF data type in string.

getDelegate() - Method in class `gsfc.nssdc.cdf.CDF`

This is a placeholder for future expansions/extensions.

getDimCounts() - Method in class `gsfc.nssdc.cdf.CDFData`

Gets the value of the dimension counts that represents the number of elements read or write starting at the location <dimension index> for a hyper get/put function.

getDimensionSizes(Object) - Static method in class `gsfc.nssdc.cdf.util.CDFUtils`

getDimIndices() - Method in class `gsfc.nssdc.cdf.CDFData`

Gets the starting dimension index within a record for a hyper get/put function.

getDimIntervals() - Method in class `gsfc.nssdc.cdf.CDFData`

Gets the value of the dimension intervals that represent the number of elements to skip between reads or writes for a hyper get/put function.

getDimSizes() - Method in class `gsfc.nssdc.cdf.CDFData`

Gets the dimension sizes of this variable.

getDimSizes() - Method in class `gsfc.nssdc.cdf.Variable`

Gets the dimensions size of this variable.

getDimVariances() - Method in class `gsfc.nssdc.cdf.Variable`

Gets the dimension variances for this variable.

getEncoding() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the encoding method defined for this CDF.

getEntries() - Method in class `gsfc.nssdc.cdf.Attribute`

Gets all the entries defined for this attribute.

getEntry(long) - Method in class `gsfc.nssdc.cdf.Attribute`

Gets the attribute entry for the given entry number.

getEntry(Variable) - Method in class `gsfc.nssdc.cdf.Attribute`

Gets the attribute entry for the given variable.

getEntryData(String) - Method in class `gsfc.nssdc.cdf.Variable`

Gets the attribute entry data for this variable.

getEntryID(Entry) - Method in class `gsfc.nssdc.cdf.Attribute`

Gets the entry id for the given entry.

getFileBackward() - Static method in class `gsfc.nssdc.cdf.CDF`

Gets the file backward flag.

getFileBackwardEnvVar() - Static method in class `gsfc.nssdc.cdf.CDF`

Gets the value of the CDF_FILEBACKWARD environment variable.

getFormat() - Method in class gsfc.nssdc.cdf.CDF

Gets the CDF format defined for this CDF.

getGlobalAttributes() - Method in class gsfc.nssdc.cdf.CDF

Gets the global attributes defined for this CDF.

getHyperData(long, long, long, long[], long[], long[]) - Method in class gsfc.nssdc.cdf.Variable

Reads one or more values from the current z variable.

getHyperDataObject(long, long, long, long[], long[], long[]) - Method in class gsfc.nssdc.cdf.Variable

Reads one or more values from the current z variable.

getID() - Method in class gsfc.nssdc.cdf.Attribute

Gets the attribute ID of this attribute.

getID() - Method in class gsfc.nssdc.cdf.CDF

Gets the id of this CDF file.

getID() - Method in class gsfc.nssdc.cdf.Entry

Gets the ID of this entry.

getID() - Method in class gsfc.nssdc.cdf.Variable

Gets the ID of this variable.

getLeapSecondLastUpdated() - Method in class gsfc.nssdc.cdf.CDF

Gets the date that the CDF has the last leap second updated.

getLeapSecondLastUpdated(CDF) - Static method in class gsfc.nssdc.cdf.util.CDFUtils

Gets the date of the given CDF's last updated for the leap second.

GETLEAPSECONDSENVVAR_ - Static variable in interface gsfc.nssdc.cdf.CDFConstants

getLeapSecondsTableEnvVar() - Static method in class gsfc.nssdc.cdf.CDF

Gets the the CDF_LEAPSECONDSTABLE (or CDF\$LEAPSECONDSTABLE on VMS) environment variable.

getLeapSecondsTableEnvVar() - Static method in class gsfc.nssdc.cdf.util.CDFTT2000

Find the environment variable "CDF_LEAPSECONDSTABLE" that is defined for the leap seconds table for CDF.

getLibraryCopyright() - Static method in class gsfc.nssdc.cdf.CDF

Retrieve library copyright information associated with the CDF library.

getLibraryVersion() - Static method in class gsfc.nssdc.cdf.CDF

Retrieve library version/release/increment/sub_increment information associated with the CDF library.

getLongChecksum(String) - Static method in class gsfc.nssdc.cdf.util.CDFUtils

Gets the long value of the given CDF's checksum in string.

getLongCompressionType(String) - Static method in class gsfc.nssdc.cdf.util.CDFUtils

Gets the long representation of the given CDF compression type in string.

getLongEncoding(String) - Static method in class gsfc.nssdc.cdf.util.CDFUtils

Gets the long value of the given CDF encoding type in string.

getLongFormat(String) - Static method in class gsfc.nssdc.cdf.util.CDFUtils

Gets the long value of the given CDF file format in string.

getLongMajority(String) - Static method in class gsfc.nssdc.cdf.util.CDFUtils

Gets the long value of the given CDF majority.

getLongSparseRecord(String) - Static method in class gsfc.nssdc.cdf.util.CDFUtils

Gets the long value of the given sparse record type in string.

getMajority() - Method in class gsfc.nssdc.cdf.CDF

Gets the variable majority defined for this CDF.

getMaxAllocatedRecord() - Method in class gsfc.nssdc.cdf.Variable

Gets the maximum allocated record number for this variable.

getMaxEntryNumber() - Method in class gsfc.nssdc.cdf.Attribute

Gets the largest Entry number for this attribute.

getMaxWrittenRecord() - Method in class gsfc.nssdc.cdf.Variable

Gets the last written record number, beginning with 0.

getMyCDF() - Method in class gsfc.nssdc.cdf.Attribute

Gets the CDF object to which this attribute belongs.

getMyCDF() - Method in class gsfc.nssdc.cdf.Variable

Gets the CDF object to which this variable belongs.

getName() - Method in class `gsfc.nssdc.cdf.Attribute`

Gets the name of this attribute.

getName() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the name of this CDF.

getName() - Method in class `gsfc.nssdc.cdf.CDFData`

CDFData implements CDFObject to enable CDFDelegate calls.

getName() - Method in interface `gsfc.nssdc.cdf.CDFObject`

Returns the name of the current object.

getName() - Method in class `gsfc.nssdc.cdf.Entry`

Gets the name of this entry.

getName() - Method in class `gsfc.nssdc.cdf.Variable`

Gets the name of this variable.

getnDims() - Method in class `gsfc.nssdc.cdf.CDFData`

Gets the dimensionality of this variable.

getNumAllocatedRecords() - Method in class `gsfc.nssdc.cdf.Variable`

Gets the number of records allocated for this variable.

getNumAttrs() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the total number of global and variable attributes in this CDF.

getNumDimensions(Object) - Static method in class `gsfc.nssdc.cdf.util.CDFUtils`

getNumDims() - Method in class `gsfc.nssdc.cdf.Variable`

Gets the number of dimensions for this variable.

getNumElements() - Method in class `gsfc.nssdc.cdf.Entry`

Gets the number of elements in this entry.

getNumElements(long, Object) - Static method in class `gsfc.nssdc.cdf.util.CDFUtils`

Gets the number of elements contained in the given data object.

getNumElements() - Method in class `gsfc.nssdc.cdf.Variable`

Gets the number of elements for this variable.

getNumEntries() - Method in class `gsfc.nssdc.cdf.Attribute`

Gets the number of entries in this attribute.

getNumGattrs() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the number of global attributes in this CDF.

getNumRvars() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the number of r variables.

getNumStrings() - Method in class `gsfc.nssdc.cdf.Entry`

Gets the number of strings in the data.

getNumStrings(Object) - Static method in class `gsfc.nssdc.cdf.util.CDFUtils`

Gets the number of strings contained in the given data object.

getNumVars() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the number of Z variables defined for this CDF.

getNumVattrs() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the number of variable attributes in this CDF.

getNumWrittenRecords() - Method in class `gsfc.nssdc.cdf.Variable`

Gets the number of records physically written (not allocated) for this variable.

getNumZvars() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the number of z variables in this CDF file.

getOrphanAttributes() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the variable attributes defined for this CDF that are not associated with any variables.

getPadValue() - Method in class `gsfc.nssdc.cdf.Variable`

Gets the pad value for this variable.

getRawData() - Method in class `gsfc.nssdc.cdf.CDFData`

Returns an object of a 1-dimensional array, which presents a sequence of raw data values retrieved and presented by JNI from a CDF file.

getRecCount() - Method in class `gsfc.nssdc.cdf.CDFData`

Gets the number of records to read or write for a hyper get/put function.

getRecInterval() - Method in class `gsfc.nssdc.cdf.CDFData`

Gets the number of records to skip for a hyper get/put function.
getRecord(long, String[]) - Method in class gsfc.nssdc.cdf.CDF

Retrieves a logical record that consists of single variable record(s) from an arbitrary number of CDF variables.
getRecord(long, String[], long[]) - Method in class gsfc.nssdc.cdf.CDF

Retrieves a logical record that consists of single variable record(s) from an arbitrary number of CDF variables.
getRecord(long, long[]) - Method in class gsfc.nssdc.cdf.CDF

Retrieves a logical record that consists of single variable record(s) from an arbitrary number of CDF variables.
getRecord(long, long[], long[]) - Method in class gsfc.nssdc.cdf.CDF

Retrieves a logical record that consists of single variable record(s) from an arbitrary number of CDF variables.
getRecord(long) - Method in class gsfc.nssdc.cdf.Variable

Gets a single record from this variable.
getRecordObject(long) - Method in class gsfc.nssdc.cdf.Variable

Get a single record of data from this variable.
getRecordsObject(long, long) - Method in class gsfc.nssdc.cdf.Variable

Get a number of records of data from this variable.
getRecStart() - Method in class gsfc.nssdc.cdf.CDFData

Gets the record number at which a hyper get/put function starts.
getRecVariance() - Method in class gsfc.nssdc.cdf.Variable

Gets the value of record variance.
getScalarData() - Method in class gsfc.nssdc.cdf.Variable

Gets the scalar data from a non-record varying 0-dimensional variable.
getScalarData(long) - Method in class gsfc.nssdc.cdf.Variable

Get the scalar data from a record varying 0-dimensional variable.
getScalarDataObject() - Method in class gsfc.nssdc.cdf.Variable

Get the scalar data from a non-record varying 0-dimensional variable.
getScalarDataObject(long) - Method in class gsfc.nssdc.cdf.Variable

Get the scalar data from this record varying 0-dimensional variable.
getScope() - Method in class gsfc.nssdc.cdf.Attribute

Gets the scope of this attribute.
getScope() - Method in class gsfc.nssdc.cdf.Entry

Gets the scope of the attribute this entry in in.
getSignature(Object) - Static method in class gsfc.nssdc.cdf.util.CDFUtils

Gets the java signature of the given object.
getSingleData(long, long[]) - Method in class gsfc.nssdc.cdf.Variable

Gets a single data value.
getSingleDataObject(long, long[]) - Method in class gsfc.nssdc.cdf.Variable

Gets a single data object from this variable.
getSparseRecords() - Method in class gsfc.nssdc.cdf.Variable

Gets the sparse record type for this variable.
getStatus() - Method in class gsfc.nssdc.cdf.CDF

Gets the status of the most recent CDF JNI/library function call.
getStatusMsg(long) - Static method in exception gsfc.nssdc.cdf.CDFException

Get the status text message for the given status code.
getStatusText(long) - Static method in class gsfc.nssdc.cdf.CDF

Gets the status text of the most recent CDF JNI/library function call.
getStringChecksum(CDF) - Static method in class gsfc.nssdc.cdf.util.CDFUtils

Gets the string value of the given CDF's checksum.
getStringChecksum(long) - Static method in class gsfc.nssdc.cdf.util.CDFUtils

Gets the string value of the given CDF's checksum.
getStringCompressionType(long) - Static method in class gsfc.nssdc.cdf.util.CDFUtils

Gets the string representation of the given CDF compression type.
getStringCompressionType(Variable) - Static method in class gsfc.nssdc.cdf.util.CDFUtils

Gets the string representation of the given variable's compression type.
getStringCompressionType(CDF) - Static method in class gsfc.nssdc.cdf.util.CDFUtils

Gets the string representation of the given CDF file's compression type.

- getStringData(Object)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Returns the string value of the given data.
- getStringData(Object, int)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Returns the string value of the given data.
- getStringData(Object, String)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Returns the string of the value of the given data.
- getStringData(Object, String, int)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Returns the string of the value of the given data.
- getStringData(Object, String, int, String)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Returns the string of the value of the given data.
- getStringDataType(Variable)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Gets the string value of the CDF data type for the given variable.
- getStringDataType(Entry)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Gets the string value of the CDF data type for the given entry.
- getStringDataType(long)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Gets the string representation of the given CDF data type.
- getStringDecoding(long)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Gets the string value of the given CDF decoding type .
- getStringDecoding(CDF)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Gets the string value of the given CDF file's decoding type.
- getStringEncoding(long)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Gets the string value of the given CDF encoding type.
- getStringEncoding(CDF)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Get the string value of the given CDF's encoding type.
- getStringFloatingData(Object, String, String)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Returns the string of the value of the given data.
- getStringFormat(long)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Gets the string value of the given CDF's file format.
- getStringFormat(CDF)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Gets the string value of the given CDF's file format.
- getStringMajority(long)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Gets the string value of the given CDF majority.
- getStringMajority(CDF)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Gets the string value of the given CDF file's majority.
- getStringSparseRecord(long)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Gets the string value of the given sparse record type.
- getStringSparseRecord(Variable)** - Static method in class gsfc.nssdc.cdf.util.CDFUtils
Gets the string value of the given variable's sparse record type.
- getValidate()** - Static method in class gsfc.nssdc.cdf.CDF
Gets the file validation mode.
- getVariable(long)** - Method in class gsfc.nssdc.cdf.CDF
Gets the variable object for the given variable number.
- getVariable(String)** - Method in class gsfc.nssdc.cdf.CDF
Gets the variable object for the given variable name.
- getVariableAttributes()** - Method in class gsfc.nssdc.cdf.CDF
Gets the variable attributes defined for this CDF.
- getVariableID(String)** - Method in class gsfc.nssdc.cdf.CDF
Gets the ID of the given variable.
- getVariables()** - Method in class gsfc.nssdc.cdf.CDF
Gets the z variables defined for this CDF.
- getVersion()** - Method in class gsfc.nssdc.cdf.CDF
Gets the CDF library version that was used to create this CDF (e.g. 2.6.7, etc.).
- GLOBAL_SCOPE** - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- gsfc.nssdc.cdf** - package gsfc.nssdc.cdf

[gsfc.nssdc.cdf.util](#) - package [gsfc.nssdc.cdf.util](#)

[GZIP_COMPRESSION](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

H

[HOST_DECODING](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[HOST_ENCODING](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[HP_DECODING](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[HP_ENCODING](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[HUFF_COMPRESSION](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

I

[IA64VMSd_DECODING](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[IA64VMSd_ENCODING](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[IA64VMSg_DECODING](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[IA64VMSg_ENCODING](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[IA64VMSi_DECODING](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[IA64VMSi_ENCODING](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[IBM_PC_OVERFLOW](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[IBMPC_DECODING](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[IBMPC_ENCODING](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[IBMRS_DECODING](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[IBMRS_ENCODING](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[ILLEGAL_EPOCH_FIELD](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[ILLEGAL_EPOCH_VALUE](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[ILLEGAL_FOR_SCOPE](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[ILLEGAL_IN_zMODE](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[ILLEGAL_ON_V1_CDF](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[ILLEGAL_TT2000_VALUE](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[IS_A_NETCDF](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

[isEpochDataType\(long\)](#) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Returns whether a CDF data type is an epoch related type.

[isFloatingPadValue\(long, Object\)](#) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Check if a data is a floating point and its value is a pad value.

isFloatingPadValue(Object) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Check if a data is a floating point and its value is a pad value.

isFloatingPadValue(long, float) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Check if a data is a floating point and its value is a pad value.

isFloatingPadValue(long, double) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Check if a data is a floating point and its value is a pad value.

isFloatingPadValue(float) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Check if a float data is a pad value.

isFloatingPadValue(double) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Check if a double data is a pad value.

isStringDataType(long) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Returns whether a CDF data type is a string type.

L

LeapSecondsfromYMD(long, long, long) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Find the leap seconds from a given, UTC-based year/month/day.

LIB_COPYRIGHT_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

LIB_INCREMENT_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

LIB_RELEASE_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

LIB_subINCREMENT_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

LIB_VERSION_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

M

MAC_DECODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

MAC_ENCODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

MD5_CHECKSUM - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

mergeFromStrings(Object) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Merge an array of strings into a single string with "\ N ", a 3-char separator.

MULTI_FILE - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

MULTI_FILE_FORMAT - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

N

NA_FOR_VARIABLE - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

NAMED_VALUES - Static variable in class [gsfc.nssdc.cdf.CDFTools](#)

NEGATIVE_FP_ZERO - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

NEGtoPOSfp0off - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

NEGtoPOSfp0on - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

NETWORK_DECODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

NETWORK_ENCODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

- NeXT_DECODING** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NeXT_ENCODING** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_ATTR_SELECTED** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_CDF_SELECTED** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_CHECKSUM** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_COMPRESSION** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_DELETE_ACCESS** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_ENTRY_SELECTED** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_MORE_ACCESS** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_PADVALUE_SPECIFIED** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_REPORTS** - Static variable in class [gsfc.nssdc.cdf.CDFTools](#)
- NO_SPARSEARRAYS** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_SPARSERECORDS** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_STATUS_SELECTED** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_SUCH_ATTR** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_SUCH_CDF** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_SUCH_ENTRY** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_SUCH_RECORD** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_SUCH_VAR** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_VALUES** - Static variable in class [gsfc.nssdc.cdf.CDFTools](#)
- NO_VAR_SELECTED** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_VARS_IN_CDF** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NO_WRITE_ACCESS** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NONE_CHECKSUM** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NOT_A_CDF** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NOT_A_CDF_OR_NOT_SUPPORTED** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NOVARY** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- NRV_VALUES** - Static variable in class [gsfc.nssdc.cdf.CDFTools](#)
- NULL_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

O

open(String) - Static method in class `gsfc.nssdc.cdf.CDF`

Open a CDF file for read/write, the default mode for opening a CDF.

open(String, long) - Static method in class `gsfc.nssdc.cdf.CDF`

Open a CDF file.

OPEN_ - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

OPTIMAL_ENCODING_TREES - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

OTHER_CHECKSUM - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

P

PAD_SPARSERECORDS - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

parse(String) - Static method in class `gsfc.nssdc.cdf.util.CDFTT2000`

This method parses an input date/time string and returns a TT2000 epoch value, nanoseconds since J2000.

parse(String[]) - Static method in class `gsfc.nssdc.cdf.util.CDFTT2000`

This method parses an array of input date/time strings and returns an array of TT2000 epoch values, nanoseconds since J2000.

parse(String) - Static method in class `gsfc.nssdc.cdf.util.Epoch`

This function parses an input date/time string and returns an EPOCH value.

parse(String[]) - Static method in class `gsfc.nssdc.cdf.util.Epoch`

This function parses an array of date/time strings and returns an array of EPOCH values.

parse(String) - Static method in class `gsfc.nssdc.cdf.util.Epoch16`

This function parses an input date/time string and returns an EPOCH16 value.

parse(String) - Static method in class `gsfc.nssdc.cdf.util.EpochNative`

Mirrors `parseEPOCH` from CDF library.

parse1(String) - Static method in class `gsfc.nssdc.cdf.util.Epoch`

This function parses an input date/time string and returns an EPOCH value.

parse1(String[]) - Static method in class `gsfc.nssdc.cdf.util.Epoch`

This function parses an array of date/time strings and returns an EPOCH value array.

parse1(String) - Static method in class `gsfc.nssdc.cdf.util.Epoch16`

This function parses an input date/time string and returns an EPOCH16 value.

parse1(String) - Static method in class `gsfc.nssdc.cdf.util.EpochNative`

Mirrors `parseEPOCH` from CDF library.

parse2(String) - Static method in class `gsfc.nssdc.cdf.util.Epoch`

This function parses an input date/time string and returns an EPOCH value.

parse2(String[]) - Static method in class `gsfc.nssdc.cdf.util.Epoch`

This function parses an array of date/time strings and returns an EPOCH value array.

parse2(String) - Static method in class `gsfc.nssdc.cdf.util.Epoch16`

This function parses an input date/time string and returns an EPOCH16 value.

parse2(String) - Static method in class `gsfc.nssdc.cdf.util.EpochNative`

Mirrors `parseEPOCH` from CDF library.

parse3(String) - Static method in class `gsfc.nssdc.cdf.util.Epoch`

This function parses an input date/time string and returns an EPOCH value.

parse3(String[]) - Static method in class `gsfc.nssdc.cdf.util.Epoch`

This function parses an array of date/time strings and returns an EPOCH value array.

parse3(String) - Static method in class `gsfc.nssdc.cdf.util.Epoch16`

This function parses an input date/time string and returns an EPOCH16 value.

parse3(String) - Static method in class `gsfc.nssdc.cdf.util.EpochNative`

Mirrors `parseEPOCH` from CDF library.

parse4(String) - Static method in class `gsfc.nssdc.cdf.util.Epoch`

This function parses an input date/time string and returns an EPOCH value.

parse4(String[]) - Static method in class `gsfc.nssdc.cdf.util.Epoch`

This function parses an array of date/time strings and returns an EPOCH value array.

parse4(String) - Static method in class `gsfc.nssdc.cdf.util.Epoch16`

This function parses an input date/time, ISO8601 string and returns an EPOCH16 value.

parse4(String) - Static method in class [gsfc.nssdc.cdf.util.EpochNative](#)

Mirrors parseEPOCH from CDF library.

parseTT2000(String) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

This method parses an input, UTC-based, date/time string and returns a TT2000 epoch value, nanoseconds since J2000.

parseTT2000(String[]) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

This method parses an input, UTC-based, date/time strings and returns a TT2000 epoch value array, nanoseconds since J2000.

parseTT2000withBasedLeapDay(String, int) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

parseTT2000withBasedLeapDay.

PPC_DECODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

PPC_ENCODING - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

PRECEEDING_RECORDS_ALLOCATED - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

PREV_SPARSERECORDS - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

printData(Object) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data on the screen.

printData(Object, int, boolean) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data on the screen.

printData(Object, int, boolean, String) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data on the screen.

printData(Object, int) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data on the screen.

printData(Object, long) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data on the screen.

printData(Object, PrintWriter) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc.

printData(Object, PrintWriter, int) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc.

printData(Object, PrintWriter, int, boolean) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc.

printData(Object, PrintWriter, int, boolean, String) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc.

printDataWithFormat(Object, String) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data on the screen.

printDataWithFormat(Object, String, int, boolean) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data on the screen.

printDataWithFormat(Object, String, int, boolean, String) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data on the screen.

printDataWithFormat(Object, String, int) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data on the screen.

printDataWithFormat(Object, String, PrintWriter) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc.

printDataWithFormat(Object, String, PrintWriter, int) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc.

printDataWithFormat(Object, String, PrintWriter, int, boolean) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc.

printDataWithFormat(Object, String, PrintWriter, int, boolean, String) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

Prints the value of the given data to the place designated by PrintWriter that can be a file, Sysem.out, System.err, and etc.

PUT_ - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

putData(long, Object) - Method in class [gsfc.nssdc.cdf.Entry](#)

Put the entry data into the CDF.

putEntry(String, long, Object) - Method in class [gsfc.nssdc.cdf.Variable](#)

Creates an attribute entry for this variable.

putEntry(Attribute, long, Object) - Method in class `gsfc.nssdc.cdf.Variable`

Creates an attribute entry for this variable.

putHyperData(long, long, long, long[], long[], long[], Object) - Method in class `gsfc.nssdc.cdf.Variable`

Writes one or more values from the current z variable.

putRecord(long, String[], Vector) - Method in class `gsfc.nssdc.cdf.CDF`

Writes a logical record that consists of single variable record(s) from an arbitrary number of CDF variables.

putRecord(long, String[], Vector, long[]) - Method in class `gsfc.nssdc.cdf.CDF`

Writes a logical record that consists of single variable record(s) from an arbitrary number of CDF variables.

putRecord(long, long[], Vector) - Method in class `gsfc.nssdc.cdf.CDF`

Writes a logical record that consists of single variable record(s) from an arbitrary number of CDF variables.

putRecord(long, long[], Vector, long[]) - Method in class `gsfc.nssdc.cdf.CDF`

Writes a logical record that consists of single variable record(s) from an arbitrary number of CDF variables.

putRecord(long, Object) - Method in class `gsfc.nssdc.cdf.Variable`

Adds a single record to a record-varying variable.

putRecord(Object) - Method in class `gsfc.nssdc.cdf.Variable`

Adds a single record to a non-record-varying variable.

putRecords(long, long, Object) - Method in class `gsfc.nssdc.cdf.Variable`

Writes a number of records from the current z variable.

putScalarData(long, Object) - Method in class `gsfc.nssdc.cdf.Variable`

Adds a scalar data to this variable (of 0 dimensional).

putScalarData(Object) - Method in class `gsfc.nssdc.cdf.Variable`

Adds a scalar data to this variable (of 0 dimensional).

putSingleData(long, long[], Object) - Method in class `gsfc.nssdc.cdf.Variable`

Adds a single data value to this variable.

R

READ_ONLY_DISTRIBUTION - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

READ_ONLY_MODE - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

readCDF() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the full CDF information.

readCDF(boolean) - Method in class `gsfc.nssdc.cdf.CDF`

Gets the full CDF information.

readCDF(boolean, boolean, boolean, boolean) - Method in class `gsfc.nssdc.cdf.CDF`

Gets the specified information from a CDF.

readCDF(boolean, boolean, boolean, boolean, boolean, boolean) - Method in class `gsfc.nssdc.cdf.CDF`

Gets the specified information from a CDF.

readCDF(boolean, boolean, boolean, boolean, boolean, boolean, boolean) - Method in class `gsfc.nssdc.cdf.CDF`

Gets the specified information from a CDF.

readCDFGlobalAttributes() - Method in class `gsfc.nssdc.cdf.CDF`

Gets the global attributes and their entries defined for this CDF.

readCDFGlobalAttributes(boolean) - Method in class `gsfc.nssdc.cdf.CDF`

Gets the global attributes and their entries defined for this CDF.

readCDFGlobalAttributes(String) - Method in class `gsfc.nssdc.cdf.CDF`

Gets a specified global attribute's entry(ies) defined for this CDF.

readCDFGlobalAttributes(String[]) - Method in class `gsfc.nssdc.cdf.CDF`

Gets a specified list of global attributes and their entries defined for this CDF.

readCDFGlobalAttributes(long) - Method in class `gsfc.nssdc.cdf.CDF`

Gets a specified global attribute's entry(ies) defined for this CDF.

readCDFGlobalAttributes(long[]) - Method in class `gsfc.nssdc.cdf.CDF`

Gets a specified list of global attributes and their entries defined for this CDF.

readCDFGlobalAttributes(Object, boolean) - Method in class `gsfc.nssdc.cdf.CDF`

Gets a list of specified global attributes and their entries defined for this CDF.

- readCDFInfo()** - Method in class `gsfc.nssdc.cdf.CDF`
Gets the basic information about this CDF.
- readCDFNoEntryAttributes()** - Method in class `gsfc.nssdc.cdf.CDF`
Gets a map of global attributes and variable attributes with no entry data.
- readCDFVariables()** - Method in class `gsfc.nssdc.cdf.CDF`
Reads all variables' information in the CDF.
- readCDFVariablesData()** - Method in class `gsfc.nssdc.cdf.CDF`
Reads all variables' data in the CDF.
- readCDFVariablesMetaData()** - Method in class `gsfc.nssdc.cdf.CDF`
Reads all variables' metadata in the CDF.
- readCDFVariablesSpec()** - Method in class `gsfc.nssdc.cdf.CDF`
Reads all variables' specifications in the CDF.
- READONLYoff** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- READONLYon** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- readVariable()** - Method in class `gsfc.nssdc.cdf.Variable`
Gets the full variable information, its specification, metadata and data.
- readVariable(boolean, boolean, boolean, boolean)** - Method in class `gsfc.nssdc.cdf.Variable`
Gets the specified variable information: its specification, metadata and data.
- readVariableData()** - Method in class `gsfc.nssdc.cdf.Variable`
Gets the variable's data.
- readVariableMetaData()** - Method in class `gsfc.nssdc.cdf.Variable`
Gets the variable's metadata.
- readVariableSpec()** - Method in class `gsfc.nssdc.cdf.Variable`
Gets the variable's specification.
- rename(String)** - Method in class `gsfc.nssdc.cdf.Attribute`
Renames the current attribute.
- rename(String)** - Method in class `gsfc.nssdc.cdf.CDF`
Renames the current CDF.
- rename(String)** - Method in class `gsfc.nssdc.cdf.CDFData`
See the description of the `getName()` method in this class.
- rename(String)** - Method in interface `gsfc.nssdc.cdf.CDFObject`
Renames the current object.
- rename(String)** - Method in class `gsfc.nssdc.cdf.Entry`
This method is here as a placeholder since the `Entry` class implements the `CDFObject` interface that includes "rename".
- rename(String)** - Method in class `gsfc.nssdc.cdf.Variable`
Renames the current variable.
- rENTRY_** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- rENTRY_DATA_** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- rENTRY_DATASPEC_** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- rENTRY_DATATYPE_** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- rENTRY_EXISTENCE_** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- rENTRY_NAME_** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- rENTRY_NUMELEMS_** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- rENTRY_NUMSTRINGS_** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- rENTRY_STRINGSDATA_** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- REPORT_ERRORS** - Static variable in class `gsfc.nssdc.cdf.CDFTools`

- [REPORT_INFORMATION](#) - Static variable in class `gsfc.nssdc.cdf.CDFTools`
- [REPORT_WARNINGS](#) - Static variable in class `gsfc.nssdc.cdf.CDFTools`
- [RLE_COMPRESSION](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [RLE_OF_ZEROS](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [ROW_MAJOR](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [RV_VALUES](#) - Static variable in class `gsfc.nssdc.cdf.CDFTools`
- [rVAR_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_ALLOCATEBLOCK_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_ALLOCATEDFROM_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_ALLOCATEDTO_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_ALLOCATERECS_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_BLOCKINGFACTOR_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_CACHESIZE_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_COMPRESSION_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_DATA_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_DATASPEC_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_DATATYPE_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_DIMVARYS_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_EXISTENCE_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_HYPERDATA_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_INITIALRECS_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_MAXallocREC_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_MAXREC_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_NAME_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_nINDEXENTRIES_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_nINDEXLEVELS_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_nINDEXRECORDS_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_NUMallocRECS_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_NUMBER_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- [rVAR_NUMELEMS_](#) - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

- rVAR_NUMRECS_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVAR_PADVALUE_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVAR_RECORDS_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVAR_RECORDS_RENUMBER_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVAR_RECVAR_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVAR_RESERVEPERCENT_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVAR_SEQDATA_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVAR_SEQPOS_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVAR_SPARSEARRAYS_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVAR_SPARSERECORDS_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVARs_CACHESIZE_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVARs_DIMCOUNTS_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVARs_DIMINDICES_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVARs_DIMINTERVALS_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVARs_DIMSIZES_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVARs_MAXREC_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVARs_NUMDIMS_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVARs_RECCOUNT_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVARs_RECDATA_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVARs_RECINTERVAL_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- rVARs_RECNUMBER_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

S

- save()** - Method in class [gsfc.nssdc.cdf.CDF](#)
Saves this CDF file without closing.
- SAVE_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- SCRATCH_CREATE_ERROR** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- SCRATCH_DELETE_ERROR** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- SCRATCH_READ_ERROR** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- SCRATCH_WRITE_ERROR** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- SELECT_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

selectCacheSize(long) - Method in class `gsfc.nssdc.cdf.Variable`

Sets the number of 512-byte cache buffers to be used.

selectCDFCacheSize(long) - Method in class `gsfc.nssdc.cdf.CDF`

Defines the number of 512-byte cache buffers to be used for the dotCDF file (for the current CDF).

selectCompressCacheSize(long) - Method in class `gsfc.nssdc.cdf.CDF`

Sets the number of 512-byte cache buffers to be used for the compression scratch file (for the current CDF).

selectDecoding(long) - Method in class `gsfc.nssdc.cdf.CDF`

Defines the CDF decoding method to be used for this CDF.

selectNegtoPosfp0(long) - Method in class `gsfc.nssdc.cdf.CDF`

Defines whether to translate -0.0 to 0.0 for reading or writing.

selectReadOnlyMode(long) - Method in class `gsfc.nssdc.cdf.CDF`

Sets the desired read-only mode.

selectReservePercent(long) - Method in class `gsfc.nssdc.cdf.Variable`

Sets the reserve percentage to be used for this variable.

selectStageCacheSize(long) - Method in class `gsfc.nssdc.cdf.CDF`

Sets the number of 512-byte cache buffers to be used for the staging scratch file (for the current CDF).

setBlockingFactor(long) - Method in class `gsfc.nssdc.cdf.Variable`

Sets the blocking factor for this variable.

setChecksum(long) - Method in class `gsfc.nssdc.cdf.CDF`

Specifies the checksum option applied to the CDF.

setCompression(long, long[]) - Method in class `gsfc.nssdc.cdf.CDF`

Sets the compression type and parameters for this CDF.

setCompression(long, long[]) - Method in class `gsfc.nssdc.cdf.Variable`

Sets the compression type and parameters for this variable.

setDelegate(CDFDelegate) - Method in class `gsfc.nssdc.cdf.CDF`

This is a placeholder for future expansions/extensions.

setDimVariances(long[]) - Method in class `gsfc.nssdc.cdf.Variable`

Sets the dimension variances for this variable.

setEncoding(long) - Method in class `gsfc.nssdc.cdf.CDF`

Defines the encoding method to be used for this CDF.

setFileBackward(long) - Static method in class `gsfc.nssdc.cdf.CDF`

Sets the file backward flag so that when a new CDF file is created, it will be created in either in the older V2.7 version or the current library version, i.e., V3.*.

setFormat(long) - Method in class `gsfc.nssdc.cdf.CDF`

Specifies the format of this CDF.

setInfoWarningOff() - Method in class `gsfc.nssdc.cdf.CDF`

Sets the informational (status code < 0) or warning messages (status code between -1 and -2000) coming from the CDF JNI/library function off.

setInfoWarningOn() - Method in class `gsfc.nssdc.cdf.CDF`

Sets the informational (status code < 0) or warning messages (status code between -1 and -2000) coming from the CDF JNI/library function on.

setInitialRecords(long) - Method in class `gsfc.nssdc.cdf.Variable`

Sets the number of records to be written initially for this variable.

setLeapSecondLastUpdated(long) - Method in class `gsfc.nssdc.cdf.CDF`

Set the leap second last updated for this CDF.

setMajority(long) - Method in class `gsfc.nssdc.cdf.CDF`

Sets the variable majority for this CDF.

setPadValue(Object) - Method in class `gsfc.nssdc.cdf.Variable`

Sets the pad value for this variable.

setRecVariance(long) - Method in class `gsfc.nssdc.cdf.Variable`

Sets the record variance for this variable.

setSparseRecords(long) - Method in class `gsfc.nssdc.cdf.Variable`

Sets the sparse record type for this variable.

setValidate(long) - Static method in class `gsfc.nssdc.cdf.CDF`

Sets the file validation mode so that when a CDF file is open, it will be validated accordingly.

SGI_DECODING - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

SGI_ENCODING - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

SINGLE_FILE - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

SINGLE_FILE_FORMAT - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

- skeletonCDF(String, String, boolean, boolean, boolean, boolean, int, int, int)** - Static method in class `gsfc.nssdc.cdf.CDFTools`
 skeletonCDF produces a CDF file from a skeleton table.
- skeletonCDF(String, String, boolean, boolean, boolean, boolean, int, int, int, int)** - Static method in class `gsfc.nssdc.cdf.CDFTools`
 skeletonCDF produces a CDF file from a skeleton table.
- skeletonCDF(String, String, boolean, boolean, boolean, boolean, int, int, int, int, int)** - Static method in class `gsfc.nssdc.cdf.CDFTools`
 skeletonCDF produces a CDF file from a skeleton table.
- skeletonCDF(String, String, boolean, boolean, boolean, boolean, int, int, String)** - Static method in class `gsfc.nssdc.cdf.CDFTools`
 skeletonCDF produces a CDF file from a skeleton table.
- skeletonTable(String, String, boolean, boolean, boolean, boolean, boolean, boolean, int, String[], int, int, int)** - Static method in class `gsfc.nssdc.cdf.CDFTools`
 skeletonTable produces a skeleton table from a CDF.
- skeletonTable(String, String, boolean, boolean, boolean, boolean, boolean, boolean, int, String[], int, int, int, int)** - Static method in class `gsfc.nssdc.cdf.CDFTools`
 skeletonTable produces a skeleton table from a CDF.
- skeletonTable(String, String, boolean, boolean, boolean, boolean, boolean, boolean, int, String[], int, int, int, int, int)** - Static method in class `gsfc.nssdc.cdf.CDFTools`
 skeletonTable produces a skeleton table from a CDF.
- skeletonTable(String, String, boolean, boolean, boolean, boolean, boolean, boolean, int, String[], int, int, String)** - Static method in class `gsfc.nssdc.cdf.CDFTools`
 skeletonTable produces a skeleton table from a CDF.
- skeletonTable(String, String, boolean, boolean, boolean, boolean, boolean, boolean, int, String[], int, int, String, String)** - Static method in class `gsfc.nssdc.cdf.CDFTools`
 skeletonTable produces a skeleton table from a CDF.
- SOME_ALREADY_ALLOCATED** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- STAGE_CACHESIZE_** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- STATUS_TEXT_** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- STRING_NOT_UTF8_ENCODING** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- STRINGDELIMITER** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- SUN_DECODING** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`
- SUN_ENCODING** - Static variable in interface `gsfc.nssdc.cdf.CDFConstants`

T

- toEncode(Long, int)** - Static method in class `gsfc.nssdc.cdf.util.CDFTT2000`
 Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of chosen style.
- toEncode(long)** - Static method in class `gsfc.nssdc.cdf.util.CDFTT2000`
 Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of ISO 8601 forme.
- toEncode(long, int)** - Static method in class `gsfc.nssdc.cdf.util.CDFTT2000`
 Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of chosen style.
- toEncode(Object)** - Static method in class `gsfc.nssdc.cdf.util.CDFTT2000`
 Converts an epoch object in TT2000 type into a scalar or array(s) of readable, UTC-based date/time string of ISO8601 style (style 3).
- toEncode(long[])** - Static method in class `gsfc.nssdc.cdf.util.CDFTT2000`
 Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of ISO8601 style (style 3).
- toEncode(long[], int)** - Static method in class `gsfc.nssdc.cdf.util.CDFTT2000`

Converts an array of epoch values in TT2000 type into readable, UTC-based date/time strings of chosen style.

toEncode(double, int) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an EPOCH value into a readable date/time string.

toEncode(double[], int) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an array of EPOCH values into readable date/time strings.

toEncode(Object) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an EPOCH object into a scalar or array(s) of readable date/time string(s).

toEncode(double) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an EPOCH value into a readable date/time string.

toEncode(double[]) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an array of EPOCH values into readable date/time strings.

toEncode(double[], int) - Static method in class [gsfc.nssdc.cdf.util.Epoch16](#)

Converts an EPOCH16 value into a readable date/time string.

toEncode(Object) - Static method in class [gsfc.nssdc.cdf.util.Epoch16](#)

Converts an EPOCH object into a scalar or array of readable date/time string.

toEncode(double[]) - Static method in class [gsfc.nssdc.cdf.util.Epoch16](#)

Converts an EPOCH object into a scalar or array of readable date/time string.

toEncode(Object, long) - Static method in class [gsfc.nssdc.cdf.util.Epoch16](#)

Converts an EPOCH object into a scalar or array(s) of readable date/time string.

toGregorianTime(long) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

This method converts the UTC-based date/time in TT2000 type to a [GregorianCalendar](#) class object in default, local time zone.

toGregorianTime(long, TimeZone) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

This method converts the UTC-based date/time in TT2000 type to a [GregorianCalendar](#) class object in specified time zone.

TOO_MANY_PARMS - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

TOO_MANY_VARS - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

toParse(String) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

This method parses an input, UTC-based, date/time string and returns a TT2000 epoch value, nanoseconds since J2000.

toParse(String[]) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

This method parses an input, UTC-based, date/time strings and returns a TT2000 epoch value array, nanoseconds since J2000.

toParse(String[]) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

This function parses an array of date/time strings and returns an array of EPOCH values.

toParse(String) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

This function parses a date/time string and returns an EPOCH value.

toParse(String) - Static method in class [gsfc.nssdc.cdf.util.Epoch16](#)

This function parses a date/time string and returns an EPOCH16 value.

toString() - Method in class [gsfc.nssdc.cdf.Attribute](#)

Gets the name of this attribute.

toString() - Method in class [gsfc.nssdc.cdf.CDF](#)

Gets the name of this CDF.

toString() - Method in class [gsfc.nssdc.cdf.Variable](#)

Gets the name of this variable.

toUTCEPOCH(long) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Convert an epoch value in TT2000 type to CDF_EPOCH type.

toUTCEPOCH16(long, double[]) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Convert an epoch value in TT2000 type to CDF_EPOCH16 type.

toUTCparts(long) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Breaks a TT2000 epoch value down into its full, UTC-based date/time component parts.

toUTCstring(Long) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of ISO 8601 style.

toUTCstring(long) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of ISO 8601 style.

toUTCstring(long[]) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Converts an iarray of epoch values in TT2000 type into readable, UTC-based date/time strings of ISO 8601 style.

toUTCstring(Long, int) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of chosen style.

toUTCstring(long, int) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Converts an epoch value in TT2000 type into a readable, UTC-based date/time string of chosen style.

toUTCstring(long[], int) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Converts an array of epoch values in TT2000 type into readable, UTC-based date/time strings of chosen style.

TRY_TO_READ_NONSTRING_DATA - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

TT2000_0_STRING_LEN - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

TT2000_1_STRING_LEN - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

TT2000_2_STRING_LEN - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

TT2000_3_STRING_LEN - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

TT2000_4_STRING_LEN - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

TT2000_CDF_MAYNEEDUPDATE - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

TT2000_TIME_ERROR - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

TT2000_USED_OUTDATED_TABLE - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

TT2000toUnixTime(long) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Converts a TT2000 value to a unix time of a double value (seconds from 1970-01-01 00:00:00 UTC).

TT2000toUnixTime(long[]) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Converts an array of TT2000 values to an array of unix time of a double value (seconds from 1970-01-01 00:00:00 UTC).

U

UNABLE_TO_PROCESS_CDF - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

UnixTimetoEpoch(double) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts a Unix time value (seconds from 1970-01-01 00:00:00 UTC) to an EPOCH time.

UnixTimetoEpoch(double[]) - Static method in class [gsfc.nssdc.cdf.util.Epoch](#)

Converts an array of Unix time values (seconds from 1970-01-01 00:00:00 UTC) to an array of EPOCH times.

UnixTimetoEpoch16(double) - Static method in class [gsfc.nssdc.cdf.util.Epoch16](#)

Converts a unix time of a double value (seconds from 1970-01-01 00:00:00 UTC) to an EPOCH16 value.

UnixTimetoTT2000(double) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Converts a Unix time of a double value (seconds from 1970-01-01 00:00:00 UTC) to a TT2000 time.

UnixTimetoTT2000(double[]) - Static method in class [gsfc.nssdc.cdf.util.CDFTT2000](#)

Converts an array of Unix time of double values (seconds from 1970-01-01 00:00:00 UTC) to an array of TT2000 times.

UNKNOWN_COMPRESSION - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

UNKNOWN_SPARSENESS - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

UNSUPPORTED_OPERATION - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

updateDataSpec(long, long) - Method in class [gsfc.nssdc.cdf.Entry](#)

Update the data specification (data type and number of elements) of the entry.

updateDataSpec(long, long) - Method in class [gsfc.nssdc.cdf.Variable](#)

Update the data specification (data type and number of elements) of the variable.

UTF16LEtoUTF8(Object) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

UTF8toCp1252(Object) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

UTF8toUTF16LE(Object) - Static method in class [gsfc.nssdc.cdf.util.CDFUtils](#)

V

- VALIDATE_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- VALIDATEFILEoff** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- VALIDATEFILEon** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- VAR_ALREADY_CLOSED** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- VAR_CLOSE_ERROR** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- VAR_CREATE_ERROR** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- VAR_DELETE_ERROR** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- VAR_EXISTS** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- VAR_NAME_TRUNC** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- VAR_OPEN_ERROR** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- VAR_READ_ERROR** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- VAR_SAVE_ERROR** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- VAR_WRITE_ERROR** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- Variable** - Class in [gsfc.nssdc.cdf](#)
 - The **Variable** class defines a CDF variable.
- VARIABLE_SCOPE** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- VARY** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- VAX_DECODING** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- VAX_ENCODING** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- verifyChecksum()** - Method in class [gsfc.nssdc.cdf.CDF](#)
 - Verifies the data integrity of the CDF file from its checksum.
- VIRTUAL_RECORD_DATA** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

Z

- zENTRY_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- zENTRY_DATA_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- zENTRY_DATASPEC_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- zENTRY_DATATYPE_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- zENTRY_EXISTENCE_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- zENTRY_NAME_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- zENTRY_NUMELEMS_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- zENTRY_NUMSTRINGS_** - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

- [zENTRY_STRINGSDATA_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [ZLIB_COMPRESS_ERROR](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [ZLIB_UNCOMPRESS_ERROR](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zMODEoff](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zMODEon1](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zMODEon2](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_ALLOCATEBLOCK_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_ALLOCATEDFROM_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_ALLOCATEDTO_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_ALLOCATERECS_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_BLOCKINGFACTOR_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_CACHESIZE_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_COMPRESSION_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_DATA_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_DATASPEC_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_DATATYPE_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_DIMCOUNTS_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_DIMINDICES_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_DIMINTERVALS_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_DIMSIZES_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_DIMVARYS_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_EXISTENCE_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_HYPERDATA_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_INITIALRECS_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_MAXallocREC_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_MAXREC_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_NAME_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_nINDEXENTRIES_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)
- [zVAR_nINDEXLEVELS_](#) - Static variable in interface [gsfc.nssdc.cdf.CDFConstants](#)

- [zVAR_nINDEXRECORDS_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_NUMAllocRECS_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_NUMBER_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_NUMDIMS_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_NUMELEMS_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_NUMRECS_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_PADVALUE_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_RECCOUNT_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_RECINTERVAL_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_RECNUMBER_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_RECORDS_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_RECORDS_RENUMBER_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_RECVAR_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_RESERVEPERCENT_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_SEQDATA_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_SEQPOS_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_SPARSEARRAYS_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVAR_SPARSERECORDS_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVARs_CACHESIZE_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVARs_MAXREC_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVARs_RECDATA_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants
- [zVARs_RECNUMBER_](#) - Static variable in interface gsfc.nssdc.cdf.CDFConstants

A B C D E F G H I L M N O P R S T U V Z

Overview	Package	Class	Tree	Deprecated	Index	Help
Prev	Next	Frames	No Frames	All Classes		

How This API Document Is Organized

This API (Application Programming Interface) document has pages corresponding to the items in the navigation bar, described as follows.

Overview

The [Overview](#) page is the front page of this API document and provides a list of all packages with a summary for each. This page can also contain an overall description of the set of packages.

Package

Each package has a page that contains a list of its classes and interfaces, with a summary for each. This page can contain six categories:

- Interfaces (*italic*)
- Classes
- Enums
- Exceptions
- Errors
- Annotation Types

Class/Interface

Each class, interface, nested class and nested interface has its own separate page. Each of these pages has three sections consisting of a class/interface description, summary tables, and detailed member descriptions:

- Class inheritance diagram
- Direct Subclasses
- All Known Subinterfaces
- All Known Implementing Classes
- Class/interface declaration
- Class/interface description
- Nested Class Summary
- Field Summary
- Constructor Summary
- Method Summary
- Field Detail
- Constructor Detail
- Method Detail

Each summary entry contains the first sentence from the detailed description for that item. The summary entries are alphabetical, while the detailed descriptions are in the order they appear in the source code. This preserves the logical groupings established by the programmer.

Annotation Type

Each annotation type has its own separate page with the following sections:

- Annotation Type declaration

- [Annotation Type description](#)
- [Required Element Summary](#)
- [Optional Element Summary](#)
- [Element Detail](#)

Enum

Each enum has its own separate page with the following sections:

- [Enum declaration](#)
- [Enum description](#)
- [Enum Constant Summary](#)
- [Enum Constant Detail](#)

Tree (Class Hierarchy)

There is a [Class Hierarchy](#) page for all packages, plus a hierarchy for each package. Each hierarchy page contains a list of classes and a list of interfaces. The classes are organized by inheritance structure starting with `java.lang.Object`. The interfaces do not inherit from `java.lang.Object`.

- When viewing the Overview page, clicking on "Tree" displays the hierarchy for all packages.
- When viewing a particular package, class or interface page, clicking "Tree" displays the hierarchy for only that package.

Deprecated API

The [Deprecated API](#) page lists all of the API that have been deprecated. A deprecated API is not recommended for use, generally due to improvements, and a replacement API is usually given. Deprecated APIs may be removed in future implementations.

Index

The [Index](#) contains an alphabetic list of all classes, interfaces, constructors, methods, and fields.

Prev/Next

These links take you to the next or previous class, interface, package, or related page.

Frames/No Frames

These links show and hide the HTML frames. All pages are available with or without frames.

All Classes

The [All Classes](#) link shows all classes and interfaces except non-static nested types.

Serialized Form

Each serializable or externalizable class has a description of its serialization fields and methods. This information is of interest to re-implementors, not to developers using the API. While there is no link in the navigation bar, you can get to this information by going to any serialized class and clicking "Serialized Form" in the "See also" section of the class description.

Constant Field Values

The [Constant Field Values](#) page lists the static final fields and their values.

This help file applies to API documentation generated using the standard doclet.

Overview	Package	Class	Tree	Deprecated	Index	Help		
Prev	Next	Frames	No Frames	All Classes				

Overview

Package

Class

Tree

Deprecated

Index

Help

Prev

Next

Frames

No Frames

All Classes

Packages

Package	Description
gsfc.nssdc.cdf	
gsfc.nssdc.cdf.util	

Overview

Package

Class

Tree

Deprecated

Index

Help

Prev

Next

Frames

No Frames

All Classes

Package gsfc.nssdc.cdf

Interface Summary	
Interface	Description
CDFConstants	This class defines the constants used by the CDF library and CDF Java APIs, and it mimics the cdf.h include file from the cdf distribution.
CDFDelegate	This class defines the method that is responsible for acting as the gateway between the CDF Java code and the CDF library.
CDFObject	CDFObject provides the base interface for all CDF objects.

Class Summary	
Class	Description
Attribute	This class contains the methods that are associated with either global or variable attributes.
CDF	The CDF class is the main class used to interact with a CDF file.
CDFData	This class acts as the glue between the Java code and the Java Native Interface (JNI) code.
CDFNativeLibrary	This class implements the method that act as the gateway between the CDF Java APIs and the CDF library.
CDFTools	CDFTools.java Created: Tue Nov 24 16:14:50 1998
Entry	This class describes a CDF global or variable attribute entry.
Variable	The Variable class defines a CDF variable.

Exception Summary	
Exception	Description
CDFException	This class defines the informational, warning, and error messages that can arise from CDF operations.

Package gsfc.nssdc.cdf.util

Class Summary	
Class	Description
CDFTT2000	This class contains the handy utility routines (methods) called by the CDF applications to handle epoch data of CDF's CDF_TIME_TT2000 data type.
CDFUtils	This class contains the handy utility routines (methods) called by the core CDF Java APIs.
Epoch	This class contains the handy utility routines (methods) called by the CDF applications to handle epoch data of CDF's CDF_EPOCH data type.
Epoch16	This class contains the handy utility routines (methods) called by the CDF applications to handle epoch data of CDF's CDF_EPOCH16 data type.
EpochNative	The Epoch class is a Java wrapper to the CDF epoch handling routines.

Hierarchy For Package gsfc.nssdc.cdf

Package Hierarchies:
[All Packages](#)

Class Hierarchy

- java.lang.Object
 - gsfc.nssdc.cdf.**Attribute** (implements gsfc.nssdc.cdf.CDFConstants, gsfc.nssdc.cdf.CDFObject)
 - gsfc.nssdc.cdf.**CDF** (implements gsfc.nssdc.cdf.CDFConstants, gsfc.nssdc.cdf.CDFObject)
 - gsfc.nssdc.cdf.**CDFData** (implements gsfc.nssdc.cdf.CDFConstants, gsfc.nssdc.cdf.CDFObject)
 - gsfc.nssdc.cdf.**CDFNativeLibrary** (implements gsfc.nssdc.cdf.CDFDelegate)
 - gsfc.nssdc.cdf.**CDFTools** (implements gsfc.nssdc.cdf.CDFConstants)
 - gsfc.nssdc.cdf.**Entry** (implements gsfc.nssdc.cdf.CDFConstants, gsfc.nssdc.cdf.CDFObject)
 - java.lang.Throwable (implements java.io.Serializable)
 - java.lang.Exception
 - gsfc.nssdc.cdf.**CDFException** (implements gsfc.nssdc.cdf.CDFConstants)
 - gsfc.nssdc.cdf.**Variable** (implements gsfc.nssdc.cdf.CDFConstants, gsfc.nssdc.cdf.CDFObject)

Interface Hierarchy

- gsfc.nssdc.cdf.**CDFConstants**
- gsfc.nssdc.cdf.**CDFDelegate**
- gsfc.nssdc.cdf.**CDFObject**

All Classes				
-------------	--	--	--	--

- Attribute
- CDF
- CDFConstants*
- CDFData
- CDFDelegate*
- CDFException
- CDFNativeLibrary
- CDFObject*
- CDFTools
- CDFTT2000
- CDFUtils
- Entry
- Epoch
- Epoch16
- EpochNative
- Variable

Constant Field Values

Contents

gsfc.nssdc.*

gsfc.nssdc.*

gsfc.nssdc.cdf.CDFConstants			
Modifier and Type		Constant Field	Value
public static final long		AHUFF_COMPRESSION	3L
public static final long		ALPHAOSF1_DECODING	13L
public static final long		ALPHAOSF1_ENCODING	13L
public static final long		ALPHAVMSd_DECODING	14L
public static final long		ALPHAVMSd_ENCODING	14L
public static final long		ALPHAVMSg_DECODING	15L
public static final long		ALPHAVMSg_ENCODING	15L
public static final long		ALPHAVMSi_DECODING	16L
public static final long		ALPHAVMSi_ENCODING	16L
public static final long		ARM_BIG_DECODING	18L
public static final long		ARM_BIG_ENCODING	18L
public static final long		ARM_LITTLE_DECODING	17L
public static final long		ARM_LITTLE_ENCODING	17L
public static final long		ATTR_	85L
public static final long		ATTR_EXISTENCE_	95L
public static final long		ATTR_EXISTS	-2001L
public static final long		ATTR_MAXgENTRY_	89L
public static final long		ATTR_MAXrENTRY_	91L
public static final long		ATTR_MAXzENTRY_	93L
public static final long		ATTR_NAME_	87L
public static final long		ATTR_NAME_TRUNC	-1001L
public static final long		ATTR_NUMBER_	88L
public static final long		ATTR_NUMgENTRIES_	90L
public static final long		ATTR_NUMrENTRIES_	92L
public static final long		ATTR_NUMzENTRIES_	94L
public static final long		ATTR_SCOPE_	86L
public static final long		BACKWARD_	1010L
public static final long		BACKWARDFILEoff	0L
public static final long		BACKWARDFILEon	1L
public static final long		BAD_ALLOCATE_RECS	-2015L
public static final long		BAD_ARGUMENT	-2022L
public static final long		BAD_ATTR_NAME	-2044L
public static final long		BAD_ATTR_NUM	-2042L
public static final long		BAD_BLOCKING_FACTOR	-2031L

Constant Field Values

public static final long	BAD_CACHE_SIZE	-2063L
public static final long	BAD_CDF_EXTENSION	-2016L
public static final long	BAD_CDF_ID	-2002L
public static final long	BAD_CDF_NAME	-2049L
public static final long	BAD_CDFSTATUS	-2034L
public static final long	BAD_CHECKSUM	-2225L
public static final long	BAD_COMPRESSION_PARM	-2097L
public static final long	BAD_DATA_TYPE	-2003L
public static final long	BAD_DECODING	-2079L
public static final long	BAD_DIM_COUNT	-2039L
public static final long	BAD_DIM_INDEX	-2005L
public static final long	BAD_DIM_INTERVAL	-2040L
public static final long	BAD_DIM_SIZE	-2004L
public static final long	BAD_ENCODING	-2006L
public static final long	BAD_ENTRY_NUM	-2043L
public static final long	BAD_FNC_OR_ITEM	-2058L
public static final long	BAD_FORMAT	-2014L
public static final long	BAD_INITIAL_RECS	-2030L
public static final long	BAD_MAJORITY	-2007L
public static final long	BAD_MALLOC	-2026L
public static final long	BAD_NEGtoPOSfp0_MODE	-2081L
public static final long	BAD_NUM_DIMS	-2008L
public static final long	BAD_NUM_ELEMS	-2011L
public static final long	BAD_NUM_STRINGS	-2238L
public static final long	BAD_NUM_VARS	-2036L
public static final long	BAD_READONLY_MODE	-2073L
public static final long	BAD_REC_COUNT	-2037L
public static final long	BAD_REC_INTERVAL	-2038L
public static final long	BAD_REC_NUM	-2009L
public static final long	BAD_SCOPE	-2010L
public static final long	BAD_SCRATCH_DIR	-2111L
public static final long	BAD_SPARSEARRAYS_PARM	-2110L
public static final long	BAD_VAR_NAME	-2045L
public static final long	BAD_VAR_NUM	-2041L
public static final long	BAD_zMODE	-2072L
public static final long	BADDATE_LEAPSECOND_UPDATED	-2235L
public static final double	BeginUnixTimeEPOCH	6.21672192E13
public static final double	BeginUnixTimeEPOCH16	6.21672192E10
public static final long	BLOCKINGFACTOR_TOO_LARGE	1014L
public static final long	BLOCKINGFACTOR_TOO_SMALL	1011L
public static final long	BLOCKINGFACTOR_TOO_SMALL2	1012L
public static final long	CANNOT_ALLOCATE_RECORDS	-2103L
public static final long	CANNOT_CHANGE	-2051L
public static final long	CANNOT_COMPRESS	-2091L
public static final long	CANNOT_CONVERT_WIDECHAR	-2239L
public static final long	CANNOT_COPY	-2104L
public static final long	CANNOT_INSERT_RECORDS	-2233L
public static final long	CANNOT_SPARSEARRAYS	-2100L
public static final long	CANNOT_SPARSERECORDS	-2099L
public static final long	CDF_	1L
public static final long	CDF_ACCESS_	201L

Constant Field Values

public static final long	CDF_ATTR_NAME_LEN	64L
public static final long	CDF_ATTR_NAME_LEN256	256L
public static final long	CDF_BYTE	41L
public static final long	CDF_CACHESIZE_	117L
public static final long	CDF_CHAR	51L
public static final long	CDF_CHECKSUM_	156L
public static final long	CDF_CLOSE_ERROR	-2055L
public static final long	CDF_COMPRESSION_	130L
public static final long	CDF_COPYRIGHT_	7L
public static final long	CDF_COPYRIGHT_LEN	256L
public static final long	CDF_CREATE_ERROR	-2066L
public static final long	CDF_DECODING_	4L
public static final long	CDF_DELETE_ERROR	-2088L
public static final long	CDF_DOUBLE	45L
public static final long	CDF_ENCODING_	3L
public static final long	CDF_EPOCH	31L
public static final long	CDF_EPOCH16	32L
public static final long	CDF_EXISTS	-2013L
public static final long	CDF_FLOAT	44L
public static final long	CDF_FORMAT_	6L
public static final long	CDF_INCREMENT_	15L
public static final long	CDF_INFO_	129L
public static final long	CDF_INT1	1L
public static final long	CDF_INT2	2L
public static final long	CDF_INT4	4L
public static final long	CDF_INT8	8L
public static final long	CDF_INTERNAL_ERROR	-2035L
public static final long	CDF_LEAPSECONDLASTUPDATED_	159L
public static final long	CDF_MAJORITY_	5L
public static final long	CDF_MAX_DIMS	10L
public static final long	CDF_MAX_PARMS	5L
public static final long	CDF_MIN_DIMS	0L
public static final long	CDF_NAME_	2L
public static final long	CDF_NAME_TRUNC	-1002L
public static final long	CDF_NEGtoPOSfp0_MODE_	19L
public static final long	CDF_NUMATTRS_	10L
public static final long	CDF_NUMgATTRS_	11L
public static final long	CDF_NUMrVARS_	8L
public static final long	CDF_NUMvATTRS_	12L
public static final long	CDF_NUMzVARS_	9L
public static final long	CDF_OK	0L
public static final long	CDF_OPEN_ERROR	-2012L
public static final long	CDF_PATHNAME_LEN	512L
public static final long	CDF_READ_ERROR	-2074L
public static final long	CDF_READONLY_MODE_	17L
public static final long	CDF_REAL4	21L
public static final long	CDF_REAL8	22L
public static final long	CDF_RELEASE_	14L
public static final long	CDF_SAVE_ERROR	-2083L
public static final long	CDF_SCRATCHDIR_	149L
public static final long	CDF_STATUS_	16L

Constant Field Values

public static final long	CDF_STATUSTEXT_LEN	80L
public static final long	CDF_TIME_TT2000	33L
public static final long	CDF_UCHAR	52L
public static final long	CDF_UINT1	11L
public static final long	CDF_UINT2	12L
public static final long	CDF_UINT4	14L
public static final long	CDF_VAR_NAME_LEN	64L
public static final long	CDF_VAR_NAME_LEN256	256L
public static final long	CDF_VERSION_	13L
public static final long	CDF_WARN	-2000L
public static final long	CDF_WRITE_ERROR	-2075L
public static final long	CDF_zMODE_	18L
public static final long	CDFwithSTATS_	200L
public static final long	CHECKSUM_	1012L
public static final long	CHECKSUM_ERROR	-2226L
public static final long	CHECKSUM_NOT_ALLOWED	-2227L
public static final long	CLOSE_	1004L
public static final long	COLUMN_MAJOR	2L
public static final long	COMPRESS_CACHESIZE_	155L
public static final long	COMPRESSION_ERROR	-2093L
public static final long	CONFIRM_	1006L
public static final long	CORRUPTED_V2_CDF	-2028L
public static final long	CORRUPTED_V3_CDF	-2223L
public static final long	CREATE_	1001L
public static final long	CURgENTRY_EXISTENCE_	126L
public static final long	CURrENTRY_EXISTENCE_	127L
public static final long	CURzENTRY_EXISTENCE_	128L
public static final long	DATATYPE_MISMATCH	-2112L
public static final long	DATATYPE_SIZE_	125L
public static final long	DECOMPRESSION_ERROR	-2092L
public static final long	DECSTATION_DECODING	4L
public static final long	DECSTATION_ENCODING	4L
public static final byte	DEFAULT_BYTE_PADVALUE	-127
public static final char	DEFAULT_CHAR_PADVALUE	32
public static final double	DEFAULT_DOUBLE_PADVALUE	-1.0E30
public static final double	DEFAULT_EPOCH_PADVALUE	0.0
public static final double	DEFAULT_EPOCH16_PADVALUE	0.0
public static final float	DEFAULT_FLOAT_PADVALUE	-1.0000000150474662E30f
public static final byte	DEFAULT_INT1_PADVALUE	-127
public static final short	DEFAULT_INT2_PADVALUE	-32767
public static final int	DEFAULT_INT4_PADVALUE	-2147483647
public static final long	DEFAULT_INT8_PADVALUE	-9223372036854775807L
public static final float	DEFAULT_REAL4_PADVALUE	-1.0000000150474662E30f
public static final double	DEFAULT_REAL8_PADVALUE	-1.0E30
public static final long	DEFAULT_TT2000_PADVALUE	-9223372036854775807L
public static final char	DEFAULT_UCHAR_PADVALUE	32
public static final short	DEFAULT_UINT1_PADVALUE	254
public static final int	DEFAULT_UINT2_PADVALUE	65534
public static final long	DEFAULT_UINT4_PADVALUE	4294967294L
public static final long	DELETE_	1003L
public static final long	DID_NOT_COMPRESS	1002L

Constant Field Values

public static final long	EMPTY_COMPRESSED_CDF	-2096L
public static final long	END_OF_VAR	-2032L
public static final long	EPOCH_STRING_LEN	24L
public static final long	EPOCH_STRING_LEN_EXTEND	36L
public static final long	EPOCH1_STRING_LEN	16L
public static final long	EPOCH1_STRING_LEN_EXTEND	24L
public static final long	EPOCH2_STRING_LEN	14L
public static final long	EPOCH2_STRING_LEN_EXTEND	14L
public static final long	EPOCH3_STRING_LEN	24L
public static final long	EPOCH3_STRING_LEN_EXTEND	36L
public static final long	EPOCH4_STRING_LEN	23L
public static final long	EPOCH4_STRING_LEN_EXTEND	32L
public static final long	EPOCHx_FORMAT_MAX	68L
public static final long	EPOCHx_STRING_MAX	50L
public static final long	FILLED_TT2000_VALUE	-9223372036854775808L
public static final long	FORCED_PARAMETER	-1006L
public static final long	FUNCTION_NOT_SUPPORTED	-2236L
public static final long	gENTRY_	96L
public static final long	gENTRY_DATA_	101L
public static final long	gENTRY_DATASPEC_	100L
public static final long	gENTRY_DATATYPE_	98L
public static final long	gENTRY_EXISTENCE_	97L
public static final long	gENTRY_NUMELEMS_	99L
public static final long	GET_	1007L
public static final long	GETCDFCHECKSUM_	1013L
public static final long	GETCDFFILEBACKWARD_	1011L
public static final long	GETCDFVALIDATE_	1015L
public static final long	GETLEAPSECONDSENVVAR_	1016L
public static final long	GLOBAL_SCOPE	1L
public static final long	GZIP_COMPRESSION	5L
public static final long	HOST_DECODING	8L
public static final long	HOST_ENCODING	8L
public static final long	HP_DECODING	11L
public static final long	HP_ENCODING	11L
public static final long	HUFF_COMPRESSION	2L
public static final long	IA64VMSd_DECODING	20L
public static final long	IA64VMSd_ENCODING	20L
public static final long	IA64VMSg_DECODING	21L
public static final long	IA64VMSg_ENCODING	21L
public static final long	IA64VMSi_DECODING	19L
public static final long	IA64VMSi_ENCODING	19L
public static final long	IBM_PC_OVERFLOW	-2023L
public static final long	IBMPC_DECODING	6L
public static final long	IBMPC_ENCODING	6L
public static final long	IBMRS_DECODING	7L
public static final long	IBMRS_ENCODING	7L
public static final long	ILLEGAL_EPOCH_FIELD	-2224L
public static final double	ILLEGAL_EPOCH_VALUE	-1.0
public static final long	ILLEGAL_FOR_SCOPE	-2076L
public static final long	ILLEGAL_IN_zMODE	-2071L
public static final long	ILLEGAL_ON_V1_CDF	-2060L

Constant Field Values

public static final long	ILLEGAL_TT2000_VALUE	-9223372036854775805L
public static final long	IS_A_NETCDF	-2228L
public static final long	LIB_COPYRIGHT_	20L
public static final long	LIB_INCREMENT_	23L
public static final long	LIB_RELEASE_	22L
public static final long	LIB_subINCREMENT_	24L
public static final long	LIB_VERSION_	21L
public static final long	MAC_DECODING	9L
public static final long	MAC_ENCODING	9L
public static final long	MD5_CHECKSUM	1L
public static final long	MULTI_FILE	2L
public static final long	MULTI_FILE_FORMAT	1007L
public static final long	NA_FOR_VARIABLE	-1007L
public static final long	NEGATIVE_FP_ZERO	-1004L
public static final long	NEGtoPOSfp0off	0L
public static final long	NEGtoPOSfp0on	-1L
public static final long	NETWORK_DECODING	1L
public static final long	NETWORK_ENCODING	1L
public static final long	NeXT_DECODING	12L
public static final long	NeXT_ENCODING	12L
public static final long	NO_ATTR_SELECTED	-2046L
public static final long	NO_CDF_SELECTED	-2053L
public static final long	NO_CHECKSUM	0L
public static final long	NO_COMPRESSION	0L
public static final long	NO_DELETE_ACCESS	-2087L
public static final long	NO_ENTRY_SELECTED	-2047L
public static final long	NO_MORE_ACCESS	-2077L
public static final long	NO_PADVALUE_SPECIFIED	1005L
public static final long	NO_SPARSEARRAYS	0L
public static final long	NO_SPARSERECORDS	0L
public static final long	NO_STATUS_SELECTED	-2052L
public static final long	NO_SUCH_ATTR	-2017L
public static final long	NO_SUCH_CDF	-2067L
public static final long	NO_SUCH_ENTRY	-2018L
public static final long	NO_SUCH_RECORD	-2102L
public static final long	NO_SUCH_VAR	-2019L
public static final long	NO_VAR_SELECTED	-2048L
public static final long	NO_VARS_IN_CDF	1006L
public static final long	NO_WRITE_ACCESS	-2086L
public static final long	NONE_CHECKSUM	0L
public static final long	NOT_A_CDF	-2027L
public static final long	NOT_A_CDF_OR_NOT_SUPPORTED	-2113L
public static final long	NOVARY	0L
public static final long	NULL_	1000L
public static final long	OPEN_	1002L
public static final long	OPTIMAL_ENCODING_TREES	0L
public static final long	OTHER_CHECKSUM	2L
public static final long	PAD_SPARSERECORDS	1L
public static final long	PPC_DECODING	9L
public static final long	PPC_ENCODING	9L
public static final long	PRECEEDING_RECORDS_ALLOCATED	1009L

Constant Field Values

public static final long	PREV_SPARSERECORDS	2L
public static final long	PUT_	1008L
public static final long	READ_ONLY_DISTRIBUTION	-2054L
public static final long	READ_ONLY_MODE	-2070L
public static final long	READONLYoff	0L
public static final long	READONLYon	-1L
public static final long	rENTRY_	102L
public static final long	rENTRY_DATA_	108L
public static final long	rENTRY_DATASPEC_	107L
public static final long	rENTRY_DATATYPE_	105L
public static final long	rENTRY_EXISTENCE_	104L
public static final long	rENTRY_NAME_	103L
public static final long	rENTRY_NUMELEMS_	106L
public static final long	rENTRY_NUMSTRINGS_	162L
public static final long	rENTRY_STRINGSDATA_	160L
public static final long	RLE_COMPRESSION	1L
public static final long	RLE_OF_ZEROs	0L
public static final long	ROW_MAJOR	1L
public static final long	rVAR_	35L
public static final long	rVAR_ALLOCATEBLOCK_	140L
public static final long	rVAR_ALLOCATEDFROM_	143L
public static final long	rVAR_ALLOCATEDTO_	144L
public static final long	rVAR_ALLOCATERECS_	123L
public static final long	rVAR_BLOCKINGFACTOR_	51L
public static final long	rVAR_CACHESIZE_	120L
public static final long	rVAR_COMPRESSION_	137L
public static final long	rVAR_DATA_	42L
public static final long	rVAR_DATASPEC_	48L
public static final long	rVAR_DATATYPE_	37L
public static final long	rVAR_DIMVARYS_	40L
public static final long	rVAR_EXISTENCE_	54L
public static final long	rVAR_HYPERDATA_	43L
public static final long	rVAR_INITIALRECS_	50L
public static final long	rVAR_MAXallocREC_	47L
public static final long	rVAR_MAXREC_	46L
public static final long	rVAR_NAME_	36L
public static final long	rVAR_nINDEXENTRIES_	53L
public static final long	rVAR_nINDEXLEVELS_	148L
public static final long	rVAR_nINDEXRECORDS_	52L
public static final long	rVAR_NUMallocRECS_	142L
public static final long	rVAR_NUMBER_	41L
public static final long	rVAR_NUMELEMS_	38L
public static final long	rVAR_NUMRECS_	141L
public static final long	rVAR_PADVALUE_	49L
public static final long	rVAR_RECORDS_	152L
public static final long	rVAR_RECORDS_RENUMBER_	157L
public static final long	rVAR_RECVAR_	39L
public static final long	rVAR_RESERVEPERCENT_	150L
public static final long	rVAR_SEQDATA_	44L
public static final long	rVAR_SEQPOS_	45L
public static final long	rVAR_SPARSEARRAYS_	139L

Constant Field Values

public static final long	rVAR_SPARSERECORDS_	138L
public static final long	rVARs_CACHESIZE_	118L
public static final long	rVARs_DIMCOUNTS_	33L
public static final long	rVARs_DIMINDICES_	32L
public static final long	rVARs_DIMINTERVALS_	34L
public static final long	rVARs_DIMSIZES_	26L
public static final long	rVARs_MAXREC_	27L
public static final long	rVARs_NUMDIMS_	25L
public static final long	rVARs_RECCOUNT_	30L
public static final long	rVARs_RECDATA_	28L
public static final long	rVARs_RECINTERVAL_	31L
public static final long	rVARs_RECNUMBER_	29L
public static final long	SAVE_	1009L
public static final long	SCRATCH_CREATE_ERROR	-2107L
public static final long	SCRATCH_DELETE_ERROR	-2106L
public static final long	SCRATCH_READ_ERROR	-2108L
public static final long	SCRATCH_WRITE_ERROR	-2109L
public static final long	SELECT_	1005L
public static final long	SGi_DECODING	5L
public static final long	SGi_ENCODING	5L
public static final long	SINGLE_FILE	1L
public static final long	SINGLE_FILE_FORMAT	1004L
public static final long	SOME_ALREADY_ALLOCATED	1008L
public static final long	STAGE_CACHESIZE_	154L
public static final long	STATUS_TEXT_	116L
public static final long	STRING_NOT_UTF8_ENCODING	1013L
public static final long	SUN_DECODING	2L
public static final long	SUN_ENCODING	2L
public static final long	TOO_MANY_PARMS	-2101L
public static final long	TOO_MANY_VARS	-2024L
public static final long	TRY_TO_READ_NONSTRING_DATA	-2237L
public static final long	TT2000_0_STRING_LEN	30L
public static final long	TT2000_1_STRING_LEN	19L
public static final long	TT2000_2_STRING_LEN	14L
public static final long	TT2000_3_STRING_LEN	29L
public static final long	TT2000_4_STRING_LEN	30L
public static final long	TT2000_CDF_MAYNEEDUPDATE	1010L
public static final long	TT2000_TIME_ERROR	-2229L
public static final long	TT2000_USED_OUTDATED_TABLE	-2234L
public static final long	UNABLE_TO_PROCESS_CDF	-2230L
public static final long	UNKNOWN_COMPRESSION	-2090L
public static final long	UNKNOWN_SPARSENESS	-2098L
public static final long	UNSUPPORTED_OPERATION	-2082L
public static final long	VALIDATE_	1014L
public static final long	VALIDATEFILEoff	0L
public static final long	VALIDATEFILEon	-1L
public static final long	VAR_ALREADY_CLOSED	1003L
public static final long	VAR_CLOSE_ERROR	-2056L
public static final long	VAR_CREATE_ERROR	-2068L
public static final long	VAR_DELETE_ERROR	-2089L
public static final long	VAR_EXISTS	-2025L

Constant Field Values

public static final long	VAR_NAME_TRUNC	-1003L
public static final long	VAR_OPEN_ERROR	-2029L
public static final long	VAR_READ_ERROR	-2020L
public static final long	VAR_SAVE_ERROR	-2084L
public static final long	VAR_WRITE_ERROR	-2021L
public static final long	VARIABLE_SCOPE	2L
public static final long	VARY	-1L
public static final long	VAX_DECODING	3L
public static final long	VAX_ENCODING	3L
public static final long	VIRTUAL_RECORD_DATA	1001L
public static final long	zENTRY_	109L
public static final long	zENTRY_DATA_	115L
public static final long	zENTRY_DATASPEC_	114L
public static final long	zENTRY_DATATYPE_	112L
public static final long	zENTRY_EXISTENCE_	111L
public static final long	zENTRY_NAME_	110L
public static final long	zENTRY_NUMELEMS_	113L
public static final long	zENTRY_NUMSTRINGS_	163L
public static final long	zENTRY_STRINGSDATA_	161L
public static final long	ZLIB_COMPRESS_ERROR	-2231L
public static final long	ZLIB_UNCOMPRESS_ERROR	-2232L
public static final long	zMODEoff	0L
public static final long	zMODEon1	1L
public static final long	zMODEon2	2L
public static final long	zVAR_	57L
public static final long	zVAR_ALLOCATEBLOCK_	134L
public static final long	zVAR_ALLOCATEDFROM_	145L
public static final long	zVAR_ALLOCATEDTO_	146L
public static final long	zVAR_ALLOCATERECS_	124L
public static final long	zVAR_BLOCKINGFACTOR_	75L
public static final long	zVAR_CACHESIZE_	121L
public static final long	zVAR_COMPRESSION_	131L
public static final long	zVAR_DATA_	66L
public static final long	zVAR_DATASPEC_	72L
public static final long	zVAR_DATATYPE_	59L
public static final long	zVAR_DIMCOUNTS_	83L
public static final long	zVAR_DIMINDICES_	82L
public static final long	zVAR_DIMINTERVALS_	84L
public static final long	zVAR_DIMSIZES_	62L
public static final long	zVAR_DIMVARYS_	64L
public static final long	zVAR_EXISTENCE_	78L
public static final long	zVAR_HYPERDATA_	67L
public static final long	zVAR_INITIALRECS_	74L
public static final long	zVAR_MAXallocREC_	71L
public static final long	zVAR_MAXREC_	70L
public static final long	zVAR_NAME_	58L
public static final long	zVAR_nINDEXENTRIES_	77L
public static final long	zVAR_nINDEXLEVELS_	147L
public static final long	zVAR_nINDEXRECORDS_	76L
public static final long	zVAR_NUMallocRECS_	136L
public static final long	zVAR_NUMBER_	65L

Constant Field Values

public static final long	zVAR_NUMDIMS_	61L
public static final long	zVAR_NUMELEMS_	60L
public static final long	zVAR_NUMRECS_	135L
public static final long	zVAR_PADVALUE_	73L
public static final long	zVAR_RECCOUNT_	80L
public static final long	zVAR_RECINTERVAL_	81L
public static final long	zVAR_RECNUMBER_	79L
public static final long	zVAR_RECORDS_	153L
public static final long	zVAR_RECORDS_RENUMBER_	158L
public static final long	zVAR_RECVAR_	63L
public static final long	zVAR_RESERVEPERCENT_	151L
public static final long	zVAR_SEQDATA_	68L
public static final long	zVAR_SEQPOS_	69L
public static final long	zVAR_SPARSEARRAYS_	133L
public static final long	zVAR_SPASERECORDS_	132L
public static final long	zVARs_CACHESIZE_	119L
public static final long	zVARs_MAXREC_	55L
public static final long	zVARs_RECDATA_	56L
public static final long	zVARs_RECNUMBER_	122L

gsfc.nssdc.cdf.CDFTools

Modifier and Type	Constant Field	Value
public static final int	ALL_VALUES	3
public static final int	NAMED_VALUES	4
public static final int	NO_REPORTS	0
public static final int	NO_VALUES	0
public static final int	NRV_VALUES	1
public static final int	REPORT_ERRORS	1
public static final int	REPORT_INFORMATION	4
public static final int	REPORT_WARNINGS	2
public static final int	RV_VALUES	2

Overview	Package	Class	Tree	Deprecated	Index	Help			
Prev	Next	Frames	No Frames	All Classes					

Serialized Form

Package gsfc.nssdc.cdf

Class **gsfc.nssdc.cdf.CDFException** extends **java.lang.Exception** implements **Serializable**

Serialized Fields

myStatus

long myStatus

Overview	Package	Class	Tree	Deprecated	Index	Help			
Prev	Next	Frames	No Frames	All Classes					

Overview	Package	Class	Tree	Deprecated	Index	Help		
Prev	Next	Frames	No Frames	All Classes				

Hierarchy For Package gsfc.nssdc.cdf.util

Package Hierarchies:
All Packages

Class Hierarchy

- java.lang.Object
 - gsfc.nssdc.cdf.util.CDFTT2000 (implements gsfc.nssdc.cdf.CDFConstants)
 - gsfc.nssdc.cdf.util.CDFUtils (implements gsfc.nssdc.cdf.CDFConstants)
 - gsfc.nssdc.cdf.util.Epoch (implements gsfc.nssdc.cdf.CDFConstants)
 - gsfc.nssdc.cdf.util.Epoch16 (implements gsfc.nssdc.cdf.CDFConstants)
 - gsfc.nssdc.cdf.util.EpochNative

Overview	Package	Class	Tree	Deprecated	Index	Help		
Prev	Next	Frames	No Frames	All Classes				